

# Ligth Weight Magnesium Alloy Corrosion Studied by Scanning Electrochemical Microscopy


To cite this article: Janine Mauzeroll et al 2013 Meet. Abstr. MA2013-01 653

View the article online for updates and enhancements.

### You may also like

- Effect of magnesium fluoride coating on corrosion behaviour of magnesium alloy O Saliza Azlina, Mohd Shafiq Ruba'ai and D Kurriawan
- Review—Carbon Electrodes in Magnesium Sulphur Batteries: Performance Comparison of Electrodes and Future Directions Utkarsh Chadha, Preetam Bhardwaj, Sanjeevikumar Padmanaban et al.
- The 2013 Edward G. Weston Summer Research Fellowship — Summary Report: Assessment of Magnesium Alloy Corrosion Using Potentiometric Mode of Scanning Electrochemical Microscopy Philippe Dauphin Ducharme

## Measure the Electrode Expansion in the Nanometer Range. Discover the new ECD-4-nano!



- Battery Test Cell for Dilatometric Analysis (Expansion of Electrodes)
- Capacitive Displacement Sensor (Range 250 µm, Resolution ≤ 5 nm)
- Detect Thickness Changes of the Individual Electrode or the Full Cell.

www.el-cell.com +49 40 79012-734 sales@el-cell.com





### LIGTH WEIGHT MAGNESIUM ALLOY CORROSION STUDIED BY SCANNING ELECTROCHEMICAL MICROSCOPY

Dao Trinh†, Philippe Dauphin Ducharme†, Ushula Mengesha Tefashe†, Joseph R. Kish‡, Janine Mauzeroll†\*

†Laboratory for Electrochemical Reactive Imaging and Detection of Biological Systems, Department of Chemistry, McGill University, Montreal, QC, Canada, H3A 0G4

‡GM Centre for Automotive Materials and Corrosion, McMaster University, Hamilton, ON, Canada, L8S 4L7

To develop the next generation of economically viable automobiles, a great amount of effort being focused on reduction of vehicle weight. One of the most promising routes to this end is the use of magnesium, which is the lightest commercially feasible structural metal. Mg components in automobiles should have good mechanical properties and good corrosion resistivity. The latter is highly dependent on alloying elements, microstructures and contact of the alloy with more noble metallic components. The role of the alloying elements in Mg corrosion remains ambiguous because the corrosion can be influenced by solute concentration, secondary phase composition, and the distribution of secondary phase. For example, Al modifies the passive film on both the alphaand beta- phases (Mg17Al12) [1], and recent studies confirm that increased Al content improves corrosion resistance in salt sprays [2] humid vapor [3] conditions, and aerated 3.5% NaCl [4]. The higher Al content of the beta-phase makes it considerably more corrosion resistant than the alpha-phase. The simultaneous optimization of diverse casting, mechanical and corrosion properties is complex with many unresolved issues. The concentration of Al can also vary within the alpha-grains from a few % at the centre to > 10% close to the grain boundary [5], and damage accumulation mirrors this distribution being more extensive in the centre than at the periphery [6]. Clearly, control of Al distribution could have a significant influence on the corrosion. To distinguish these influences, well-designed experimental studies with controlled alloy microstructures are performed at both the sub-micron and micron levels. These experiments utilize advanced SECM and electron microscopy techniques and the results are used in corrosion simulation modeling.

#### References

- 1. G. L. Song, A. Atrens, X. Wu, Z. Bo and B. Zhang, Corros. Sci. 40, 1769(1998).
- 2. G. Ballerini, U. Bardi, R. Bignucolo and G. Ceraolo, Corros. Sci. 47, 2173(2005).
- 3. M. Jonsson and D. Persson, Corros. Sci. 52, 1077(2010).
- 4. A. Pardo, M. C. Merino, A. E. Coy, F. Viejo, R. Arrabal and S, Feliu, Electrochim. Acta 53, 7890(2008).
- 5. E. Ghali, W. Dietzel and K-U. Kainer, J. Mat. Eng and Perform. 13, 7(2004).
- 6. E. Ghali; Magnesium and Magnesium Alloys, In: Uhlig's Corrosion Handbook, Second Edition, edited by R. W. Revie, John Wiley and Sons, Inc. Chichester, U.K. 793(2000).