



HAL
open science

TOWARDS RELIABLE AND ROBUST ANAEROBIC DIGESTION

Behnam Taidi, Islam Boussaada, Dercy Mambu Luvava, Ademola Adeniji,
Sette Diop

► **To cite this version:**

Behnam Taidi, Islam Boussaada, Dercy Mambu Luvava, Ademola Adeniji, Sette Diop. TOWARDS RELIABLE AND ROBUST ANAEROBIC DIGESTION. None, Engineering Conferences International, Apr 2022, Albufeira-Algarve, Portugal. hal-04461486

HAL Id: hal-04461486

<https://hal.science/hal-04461486v1>

Submitted on 21 Nov 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

TOWARDS RELIABLE AND ROBUST ANAEROBIC DIGESTION

Behnam TAIDI, LGPM, CentraleSupélec, University of Paris Saclay
behnam.taidi@centralesupelec.fr
Islam BOUSSAADA, L2S, CentraleSupélec, University of Paris Saclay
Dercy MAMBU, L2S, CentraleSupélec, University of Paris Saclay
Ademola ADENIJI, L2S, CentraleSupélec, University of Paris Saclay
Sette DIOP, L2S, CentraleSupélec, University of Paris Saclay

Key Words: *Anaerobic digestion, Methanogenesis, Cascade fermentations, Process robustness, spent coffee*

Anaerobic digestion, employed for methane generation, is one of the sources of renewable biofuel that are cost-effective and can be energetically positive in that more energy can be produced that is used for biogas production. In the current context of the need to find and establish renewable energy sources, as well as preservation of national energetic independence, anaerobic digestion offers great potential in where large-scale farming occupies a central role in the country's economy.

On the oxidizing surface of our planet, dominated by its exposure to air containing 20.9% O₂ by volume, all carbon present in organic matter is destined to be eventually converted to CO₂. Anaerobic digestion provides a natural loop where approximately half of this carbon can be first converted to methane (CH₄) and then converted to CO₂ through combustion and generation of useful heat and energy. The end result is the same in that all the organic carbon is converted to CO₂, but not before some of the carbon is used to generate renewable energy.

Energy generation through anaerobic digestion is already adopted in many countries and it is mainly applied on dairy and pig farms and on municipal waste treatment plants. Generally, the technology works well under such conditions, but it is susceptible to changes in the nature of the feed, such as during vacation periods when the nature and volume of the domestic sewage changes, or during particularly cold spells when the mesophilic conditions required for optimal digestion are perturbed. Anaerobic digestion remains relatively fragile.

Anaerobic digestion consists of several biochemical processes: hydrolysis, acidogenesis, acetogenesis and methanogenesis. Each of these processes are performed by specific consortia of bacteria and archaea. The delicate balance of each consortium's population is one of the reasons for the fragility of the overall anaerobic digestion process. Each of the above processes has its own optimal conditions but all the processes can occur in the same bioreactor by establishing a compromising set of conditions.

This presentation outlines the work performed to study each of the processes individually in order to develop a cascade model of anaerobic digestion where each process occurs under its ideal conditions. A new and simple experimental system (Fig. 1) for the study of each of the processes separately was developed and the results used to construct a simple mathematical model (Fig. 2) that predicted the overall rate of anaerobic digestion of spent coffee.

Future work will concentrate on the assembly of a laboratory scale anaerobic digester consisting of a bioreactor for each biochemical process and a control system to pilot methane production continuously and reliably.

Fig. 1. Experimental set-up



Fig. 2. Actual and model results of anaerobic digestion of spent coffee

