

Extreme hydrological regimes of a small urban river: impact on trace element partitioning, enrichment and fluxes

Gaël Durrieu, Nicolas Layglon, Sébastien D'onofrio, Benjamin Oursel, Dario Omanović, Cédric Garnier, Stéphane Mounier

▶ To cite this version:

Gaël Durrieu, Nicolas Layglon, Sébastien D'onofrio, Benjamin Oursel, Dario Omanović, et al.. Extreme hydrological regimes of a small urban river: impact on trace element partitioning, enrichment and fluxes. Environmental Monitoring and Assessment, 2023, 195 (9), pp.1092. 10.1007/s10661-023-11622-x. hal-04477486

HAL Id: hal-04477486

https://hal.science/hal-04477486

Submitted on 26 Feb 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Extreme hydrological regimes of a small urban river: impact on trace element partitioning, 1

enrichment and fluxes 2

3

- Durrieu Gaël^{1,*}, Layglon Nicolas^{1,2}, D'Onofrio Sébastien¹, Oursel Benjamin³, Omanović Dario⁴, Garnier Cédric¹, 4
- 5 Mounier Stéphane¹

6

- 7 ¹Université de Toulon, Aix Marseille Univ., CNRS, IRD, MIO, Toulon, France
- 8 ²University of Geneva, Sciences II, 30 Quai E.-Ansermet, 1221 Geneva 4, Switzerland
- 9 ³Aix Marseille Univ., Université de Toulon, CNRS, IRD, MIO, Marseille, France
- 10 ⁴Center for Marine and Environmental Research, Ruđer Bošković Institute, P.O. Box 180, 10002 Zagreb, Croatia
- 11 *Corresponding author: gael.durrieu@univ-tln.fr
- 12 ORCID: Durrieu Gaël: 0000-0002-1917-7530; Layglon Nicolas: 0000-0001-7731-1067; Oursel Benjamin: 0000-
- 13 0002-1065-9146; Omanović Dario: 0000-0001-5961-0485; Garnier Cédric: 0000-0002-5638-6673; Mounier
- 14 Stéphane: 0000-0002-9624-0230
- 15 Email addresses: Durrieu Gaël: gael.durrieu@univ-tln.fr; Layglon Nicolas: Nicolas.Layglon@unige.ch; D'Onofrio
- 16 Sébastien: sebastien.donofrio83@gmail.com; Oursel Benjamin: benjamin.oursel@mio.osupytheas.fr; Omanović
- 17 Dario: omanovic@irb.hr; Garnier Cédric: cgarnier@univ-tln.fr; Mounier Stéphane: stephane.mounier@univ-tln.fr

18 **Abstract**

- 19 The input of trace elements from a small urban river (Las River, Toulon, France) located on the northern Mediterranean
- 20 coast was studied during both base flow and flood events. A two-year monitoring period of water flow and suspended
- 21 particulate matter (SPM) showed a typical Mediterranean hydrological regime: a strong increase in water flow and SPM
- 22 during short flood periods. During the flood event, an up to 2-fold increase in dissolved trace element (D_{TM})
- 23 concentrations and particulate trace element content in SPM (P_{TM}) was observed compared to the baseline discharge.
- 24 The enrichment factor of elements in the SPM ranges from low or moderate for Co, Ni and Cr (1.0 - 4.7) to extremely
- 25 high for Cd (157). However, the enrichment factors decrease from base flow to flood, indicating a dilution effect with a
- 26 large yield of weathering particles with higher particle size. The most significant total trace element loading occurred
- 27 during flood, ranging from 78 % for As and Ni to 91 % for Pb, while P_{TM} loading during flood ranged from 35 % for As
- 28 to 77 % for Pb. The specific dissolved fluxes during the flood are significantly higher for Pb, Cu and Zn than in the
- 29 surrounding rivers, indicating specificity in the catchment (lithology). This study shows the importance of monitoring
- 30

the transport of pollutants through small urban rivers and their potential impact on the coastal region, especially when

31 they enter small and closed bays, as a receiving pool.

32

Keywords: small river; trace metals; urban impact; Extreme event

34

35

33

Statements and Declarations

- 36 **Funding**
- 37 This study was part of the METFLUX research project funded by the French water agency "Agence de l'Eau Rhône
- 38 Méditerranée Corse" (convention n°2016-1364).

- 39 Competing Interests
- 40 The authors have no relevant financial or non-financial interests to disclose.
- 41 Data availability
- 42 The datasets generated and analysed during the current study are available from the corresponding author on reasonable
- 43 request
- 44 Author Contributions Statement
- 45 Garnier Cédric conceptualized the study and acquired the funding. Mounier Stéphane and Garnier Cédric oversaw the
- 46 project administration. Durrieu Gaël, Layglon Nicolas, D'Onofrio Sébastien, Oursel Benjamin, Omanović Dario,
- 47 Garnier Cédric and Mounier Stéphane participated in the sampling, the analyses and the revision of the original
- 48 manuscript. Durrieu Gaël, Omanović Dario and Mounier Stéphane wrote the original manuscript.
- 49 Acknowledgments
- 50 The authors wish to thank "Météo-france" for the access to data from station "la Mitre", Amonda El Houssainy for
- 51 helping create the map used and the LASEM (Laboratoire d'Analyses de Surveillance et d'Expertise de la Marine) in
- Toulon for major elements analysis. The authors also thank the PACEM-MIO platform for facilities.
- 53 This work is dedicated to our friend and colleague Cédric Garnier (1977–2018). We will always remember him with
- 54 gratefulness.

56

Introduction

57 Rivers are known to be an important transport route for pollutants from the continent to coastal areas (Viers et al., 58 2009). Overall, river runoff is the main source of metals and metalloids entering the waters of the continental shelf 59 (Olías et al., 2006; Viers et al., 2009) and therefore the transport of most contaminants depends on the runoff, resulting 60 from the precipitation regime in the river basin. The meteorological regime of the Mediterranean area is characterised 61 by long dry summers and mild winters. Long periods without rain (with accumulation of contaminants on the surfaces 62 of the catchment areas) are very often interrupted by short but intense rainfalls (Bernal et al. 2013; Cowling et al., 2005; 63 Miller, 1983) during which urban runoff, erosion and sediment resuspension occur. Consequently, water quality is 64 known to be affected by elevated trace metal concentrations (Cobelo-García et al., 2004; Nicolau et al., 2012; Oursel et 65 al., 2014). Another characteristic of flash flooding in Mediterranean regions is that it brings with it a considerable 66 amount of suspended matter of natural or anthropogenic origin, which serves as a vector for trace metals, (Dumas et al., 67 2015; Meybeck, 2001; Pont et al., 2002). This particular system requires an adapted sampling protocol to take into 68 account the actual pollutant load. The large fluctuations in precipitation lead to extreme variations in runoff and thus in 69 the fluxes of chemical elements. As a result, high-frequency sampling is required during flood events (intraday 70 frequency), while regular sampling (weekly or monthly) is sufficient during baseflow. Furthermore, understanding the 71 relationships between catchment characteristics (bedrock and lithology), anthropogenic activities (land use in the 72 catchment) and river flow (dam discharges and precipitation) is crucial for developing spatial models for trace metals in 73 a temperate continental shelf such as the Toulon Bay (France) (González-Ortegón et al., 2019). Moreover, small rivers 74 play an important role in the coastal zone of the Mediterranean because of their number (Nicolau et al., 2012; Roussiez 75 et al., 2011). Therefore, it is particularly important to ensure a good assessment of metal fluxes in urbanised coastal 76 areas, as they contribute significantly to the total amount of trace metals in the environment. Furthermore, when inputs 77 occur in a semi-enclosed bay, metal inputs can lead to a contamination gradient due to low tides and low water

78 turnover. In Toulon Bay (France), for example, there is a strong gradient of metal contamination in the sediments 79 (Tessier et al., 2011) for which it was found to affects benthic prokaryotic diversity (Misson et al., 2016) and has 80 implications for the quality of mussels farmed in the bay (Dang et al., 2015). Sediment resuspension has been shown to 81 influence the chemical and biological quality of Toulon Bay (Layglon et al., 2020). In the same bay, a high gradient of 82 dissolved trace metals in the water column was found to impact bacterioplanktonic and phytoplanktonic communities 83 (Coclet et al., 2018, 2019, 2020; Layglon et al., 2020). This gradient could be also due to the river input like the Las 84 river which is first rural and then becomes more urbanized along its crossing (Dufresne 2014). Since the watershed is 85 not much industrialized and the municipalities crossed fairly well cleaned up the quality of the river water should be 86 good even though not much information are available concerning this river. That's why, until now, it is unclear what is 87 the most important driver in bay contamination: river inputs, sediment resuspension, aerosol or river inputs.

The annual fluxes of contaminants to the coastal region by rivers are commonly estimated based on average level of contaminants concentration and average river discharge. However, the dynamics of the fluxes, i.e. base flow vs. flood events, was not always considered due to the logistical problems. Hence, the Las River (Toulon, France) was used as a model of a small Mediterranean urban river characterised by extreme hydrological regimes due to the episodic heavy rain events. This work aimed to (i) Characterise the inputs of trace metals during base flow and flood events, to (ii)estimate the contribution of these inputs to the bay.

Materials and methods

95 Site description

88

89

90

91

92

93

94

96 The Las River is an 8 km long urban river located in south-eastern France near the city of Toulon on the north-western 97 coast of the Mediterranean Sea. Its catchment is located in a predominantly calcareous area (Baudement et al., 2017). In 98 the upper part it is mainly composed of forest, small agricultural zones and two stone quarries and in the lower part it is 99 urbanised. The area of the catchment is estimated at 60 km², but due to the karst type, water from another aguifer can 100 enter in the watershed (Dufresne, 2014; Lamarque, 2014). It starts at an altitude of 100 m after the Dardennes dam 101 (43°10'29.23" N; 5°55'49.13" E) which is used for drinking water supply, but also causes karst flash floods 102 downstream in the urban area (Baudement et al., 2017). The bed of the river consists in coarse gravel and crushed stone 103 (Dufresne et al. 2020). In the middle course, the Las River is channelised with concrete and covered over a length of 104 about 2 km. The river flows into the sea in the little bay of Toulon (43°6'58.11" N; 5°53'27.81" E) within a military 105 zone. This little bay is a semi-enclosed bay of about 9.1 km² characterized by an average depth of 10 m and separated 106 from the large bay by a dyke.

The rainfall regime of the region is Mediterranean and is subject to high (inter)annual variability. For example, precipitation in Toulon averaged 670 mm in 2013-2018, with a minimum of 270 mm in 2017 and a maximum of 1120 mm in 2014 (Météo France, La Mitre station), and most rain occurred from October to April.


Sampling

- To consider the most important part of the river, the sampling point (43°7'22.44" N; 5°53'44.20" E) is located 900 m
- before the confluence with the sea (Fig. 1). To our knowledge, there are no further water inflows after this point.
- 114 The sampling strategy consisted in sampling during base flow and flood events, using the passive and manual sampling
- of suspended particulate matter and water. Sensus Ultra (ReefNet Inc.) loggers were used to monitor the water column

110

pressure (depth) and temperature (at 10 min intervals) in the period from March 2017 to March 2019, while a multi parameters probe (600-OMS-V2, YSI) was additionally used to monitor turbidity, conductivity, depth and temperature in the period from January 2018 to March 2019.

Before sampling, all FEP (Fluoro Ethylene Propylene) and HDPE (High Density Polyethylene) sampling bottles (Nalgene) were cleaned with 10 % v/v HNO3 (Fisher scientific, Analytical Reagent grade), rinsed 3 times with Milli-Q water (resistivity 18.2 M Ω ; Milli-Q Direct 8, Millipore) and filled with Milli-Q water acidified with 0.1 % HCl (Carl Roth, Rotipuran supra) until sampling. Glass bottles (Wheaton 24 mL) and a glass filtration system were cleaned with 10 % v/v HCl (Fisher scientific 37 %, Analytical Reagent grade), rinsed 3 times with Milli-Q water before being combusted for 6 h at 450 °C. Glass fibre filters (Whatman GFF, 0.7 μ m) were combusted for 6 h at 450 °C, placed in an oven (60 °C) until constant weight was measured.






Figure 1. The Las River catchment area (green) and sampling station (red point). LiB= little Bay, LaB = Large Bay

The strategy of sampling needed to combine a long-term monitoring of the river during the base flow and punctual sampling of flood events. For that purpose, during base flow samples were taken every month to cover the seasonal and temporal variability. The detail sampling of the major flood event monitored on 10/10/2018 is described below.

Sampling during the base flow

In total, 24 monthly sampling campaigns were conducted under base flow conditions from 20/2/2017 to 20/2/2019. For each campaign, 4 L of water was taken directly in the stream (after rinsing the sampling bottle 3 times with the stream water) for dissolved and particulate fraction analysis. In addition, using two deployed loggers and a YSI probe, the main physico-chemical parameters (temperature, specific conductivity, redox, pH, chlorophyll-a), were punctually measured each time using the Hydrolab DS5 multi-probe.

Sampling during the flood event

The strong rainy event (94 mm rain in 24 h, Météo France, La Mitre) occurred on 10/10/2018 was selected as a representative flood event. Samples were collected in a period from 11 h UTC to 24 h UTC. A precleaned HDPE bucket with a rope was used to collect river water from the bridge (43°7'22.44" N; 5°53'44.20" E). An integrative sampling strategy was used: depending on river discharge, estimated by water height, every 10 min during 1 h or every 20 min during 2 h, an aliquot of (1) 150 mL of bulk water was pooled in a 1 L HDPE bottle for further analysis of particulate material and (2) a 60 mL of sample was filtered using a 0.2 µm cellulose acetate (CA) syringe filter (Minisart,

Sartorius) and pooled in a 0.5 L FEP bottle for analysis of dissolved trace elements. In this way, a total of 11 composite samples of (1) bulk (unfiltered) water and (2) filtered water were collected during the whole flood event.

149

150

151

152

153

154

155

156

157

158

159

160

161

Time-Integrated Suspended Particulate Matter (SPM_{TI}) sampling

A sediment trap (Phillips et al. 2000) made of a stainless-steel tube of 1 m length and 98 mm internal diameter (Fig. SI 1, in Supplementary Information) was used to continuously collect suspended particulate matter (SPM $_{TI}$). The details about the sample and principle of the work are provided by Phillips et al. (2000). In short, water entered into the sampler through a 4 mm hole facing towards the water stream. Due to the increase of the internal diameter of the tube, an internal flow of the water was suddenly slowed down, allowing settlement of the particles inside of the tube. The sediment trap is designed to collect SPM $_{TI}$ at small streams. The period of deployment was adjusted depending on meteorological conditions (from some days during flood to 1.5 month during base flow) to finally get a set of SPM $_{TI}$ corresponding to contrasted flow periods (12 samples under base flow and 5 samples under flood). The whole quantity of water and SPM $_{TI}$ in the trap was transferred in a 10 L HDPE bottle. After one day of sedimentation in a cold place, supernatant was removed and SPM $_{TI}$ was placed in a 150 mL HDPE bottle, frozen and freeze-dried thereafter.

Calculation of river flow

162 The determination of the flow is a key parameter when studying river inputs. In order to precisely determine the water 163 height of the river, two devices were used: a limnometer and a pressure sensor. The first device gives the official water 164 height certified by authorities (H_{Limn}) and the second one gives a high frequency measurement of water pressure (P_{sensor}). 165 Water pressure from the sensor was measured every 10 min and was corrected by the daily average atmospheric 166 pressure from Météo France services and transformed into water height (H_{Sensor}). By using the certified measurement, a 167 linear regression (R²=0.98, N=12) was done between H_{Limn} and H_{Sensor} and used to transform all the H_{sensor} into H_{Limn}. 168 From this extended H_{Limn} data set, the rating curve established by (Lamarque 2014) was used to obtain the high 169 frequency river discharge. This rating curve has been validated for limnometer heights between 0.35 m to 1.85 m which 170 corresponds to the heights measured during our monitoring. In accordance with previous study from (Dufresne et al. 171 2020), the threshold of 1 m³ s⁻¹ was defined as the limit between base flow and flood. Table SI 2 summarizes the flows 172 during the different sampling campaigns.

173

174

High frequency suspended particulate matter (SPM_{HF}) determination

175 Another key parameter when studying river inputs is the SPM concentration. As shown previously, this parameter is 176 highly correlated to the turbidity (Dufresne, 2014; Dufresne et al., 2020). This property is used to estimate SPM from 177 high frequency measurement of turbidity probe, calibrated by using discrete SPM measurement from GFF filtration 178 (SPM_{GF}). First, the data outliers due to sensor clogging were replaced using a specific filter described in Fig. SI 3. 179 Secondly, turbidity > 1 NTU was transformed in SPM_{HF} by using the linear relation between SPM_{GF} values and 180 corresponding turbidity measurement (R²=0.98, N=20). This concerns 25 % of the data set. Thirdly, for low turbidity, < 181 1 NTU or "nd" or data associated to flow $< 1 \text{ m}^3 \text{ s}^{-1}$, the average of all measured SPM_{GF} concentration during base flow 182 was applied (SPM_{HF} =avg(SPM_{GF}) = 1.13 +/- 0.34 mg L⁻¹). This concerns 69 % of data set. Finally, for turbidity <1 NTU or "nd" associated to a flow > 1 m³ s⁻¹, as it is not base flow measurement, a specific linear relation (R²=0.81, 183 N=16) between SPM_{GF} and flow was used to avoid underestimation of SPM_{HF} . This concerns 6 % of data set. The final 184 185 data contains N = 103,282 SPM_{HF} data between 2017 and 2019.

187

197

Filtration, treatment and preservation of samples

188 Samples for dissolved organic carbon (DOC) analysis were filtered at the laboratory using a 25 mm glass fibre filter 189 (Whatman GFF, 0.7 µm) during the base flow, whereas during the flood an in-line 0.2 µm cellulose acetate syringe 190 filter (Minisart, Sartorius) was used for on-site samples filtration. Before taking the final sample, the syringe filter was 191 rinsed several times with the ambient water (washed in this way, the blanks of DOC in Milli-Q were negligible). The 192 filtrates were collected in 24 mL pre-combusted glass tubes (Wheaton), preserved with 0.2 % HCl (Carl Roth 37 % 193 Rotipuran supra) and stored at 4 °C before analysis. The GFF filters were used to measure particulate organic carbon 194 (POC) and SPM_{GF} concentrations. Filters were dried overnight in an oven at 60 °C and thereafter stored at room 195 temperature in a closed box with a drying agent before weighting for SPMGF content. For POC analysis, the GFF filters 196 were exposed to HCl fumes during 4 h in a glass desiccator to remove inorganic carbon, and after that stored in a fume

hood during 3 h and overnight in an oven at 60 °C before analysis (Lorrain et al. 2003).

198 For analysis of dissolved trace metals (D_{TM}), samples were filtered at the laboratory by using cellulose acetate filters 199 (47 mm, 0.2 μm, Sartorius) during the base flow. Before filtration, the filters were cleaned with 100 mL of 10 % v/v 200 HNO₃ (Fisher scientific, Analytical Reagent grade), then with 1 L Milli-Q water acidified with 0.1 % HCl (Carl Roth 201 37 %, Rotipuran supra) and finally rinsed with Milli-Q water. Then, the filtrate was collected in an 8 mL HDPE bottle and preserved with 0.5 % HNO3 (Carl Roth 69 %, Rotipuran supra) for further ICP-MS measurement of D_{TM}. During 202 203 periods of flooding, samples for dissolved fractions were filtered on-site by using in-line 0.2 µm cellulose acetate 204 syringe filters (Minisart, Sartorius). In-line syringe filters were cleaned by filtering 2 x 60 mL of 0.1 % v/v HNO₃ 205 (Fisher scientific, Analytical Reagent grade), and then 2 x 60 mL of river water. After filtration in the field, the filtrate 206 was split for D_{TM} and major analysis. For analysis of particulate trace metals (P_{TM}) and SPM concentrations, water was 207 filtered at the laboratory using cellulose acetate filters (47 mm, 0.2 µm, Sartorius).

All filters from base flow and flood samples filtration were placed overnight in an oven at 60 °C and then placed 1 h in an oven at room temperature with a drying agent before weighing. Both GFF and cellulose acetate filters were used to determine SPM concentration (mg L⁻¹) in discrete samples (further denoted as SPM_{GF}).

211 Cellulose acetate filters (47 mm, $0.2 \mu m$, Sartorius) and SPM_{TI} (see section 2.3) were mineralised by microwave 212 digestion (Milestone, UltraWAVE ECR) for the determination of trace element concentrations in particulate and solid 213 samples. Filter or 100 mg of SPM_{TI} were placed in a 15 mL teflon tube with aqua regia (mixture of 7.5 mL HCl and 214 2.5 mL of HNO₃ (Carl Roth, Rotipuran supra) and mineralized (temperature range from ambient to 240 °C in 20 min 215 and hold during 20 min, while pressure ranges from 30 bar to around 70 bar). After digestion the whole volume of 216 digestate was transferred in a 30 mL HDPE bottle and diluted to a final volume of 25 mL for further ICP-MS 217 measurement of particulate trace metals (P_{TM}). The P_{TM} was then expressed in trace metal content in µg g⁻¹ of SPM 218 using SPM_{GF} or SPM_{TI} .

219

220

Analysis of parameters

221 *DOC*

DOC was determined by high temperature combustion at 720 °C using a TOC-V Analyser (Shimadzu®), calibrated using potassium hydrogen phthalate standard. The limit of quantification is 0.1 mgC L⁻¹ with a good linearity from 0.1

to 50 mgC L⁻¹. Quality control (QC) of measurements was checked every run by the determination of element concentration in "a Lake Water Reference Material" (SUPER-05, Environment and Climate Change Canada). Certified values for DOC is 1.28 mg_C L⁻¹. Obtained values for the whole data set agreed with certified values within 2 %.

227

228 POC

POC was determined using a Flash 2000 NC Soil Analyser (Thermo Scientific®). Carbon was measured by flash combustion at 930 °C in tin capsules. The limit of detection was 5 μg, and the calibration curve ranges respectively from 5 to 1100 μg. Quality control (QC) of measurements was checked by the determination of element concentration in "NC Soil" (Thermo Fisher Scientific). Certified values for POC is 2.29 % C. Obtained values for the whole data set agreed with certified values within 1 %. In the following text, POC concentration refers to mass of POC per volume of water and POC content refers to mass of POC per mass of SPM.

235

236

237

Trace elements

D_{TM} and P_{TM} (Al, As, Cd, Co, Cr, Cu, Ni, Pb and Zn) were determined by High Resolution Inductively Coupled Plasma
Mass Spectrometer (HR ICP-MS, Element 2, Thermo Finnigan, Bremen, Germany). The samples for the analyses were
prepared in pre-cleaned polypropylene tubes (Sarstedt). Freshwater samples were analysed undiluted (acidified to 2 %
v/v HNO₃, ROTIPURAN Supra, Carl Roth), whereas an appropriate dilution (5-10×) for digested SPM_{GF} or SPM_{TI}
samples was used. Indium (¹¹⁵In) was used as an internal standard. Quality control (QC) was checked by the
determination of element concentration in "River Water Reference Material for Trace Metals" (SLRS-5, National
Research Council Canada) and PACS-2 for sediment samples.

245

246

Calculation of parameters

247 Load of TM

For the dissolved fraction, the calculation of the load (DL_{TM} in g) is defined as:

$$DL_{TM} = \sum_{i=1}^{n} \left(V_i \times D_{TM,i} \times 10^{-3} \right)$$
 equation 1

where DL_{TM} is the dissolved load of a given element (g) during observation 1 to n, $D_{TM,i}$ is the dissolved concentration of a given trace metal (μ g L^{-1}) and V_i is the volume of river water (m^3) between two observations i and i+1. We distinguished two conditions for the load calculation. During the base flow (flow < of 1 m^3 s⁻¹) $D_{TM,i}$ concentration corresponds to the concentration measured from the date of sampling (observation i) until the next sampling (observation i+1). For unsampled flood events (flow > of 1 m^3 s⁻¹), $D_{TM,i}$ concentration was estimated from the relationship between DL_{TM} and Q during the flood sampling on 10^{th} October 2018. For the 8 studied elements the R^2 coefficient varied between 0.86 and 0.98, depending on the element (SI 4).

8

The particulate fraction calculation of the load (PLTM) was defined as:

 $PL_{TM} = \sum_{i=1}^{n} \left(SPM_{Mass,i} \times P_{TM,i} \times 10^{-6} \right)$ equation 2

where PL_{TM} is the particulate load of a given trace metal (g) during observation 1 to n, $P_{TM,i}$ is the content of a given trace metal during observation to i+1 ($\mu g g^{-1}$) in SPM_{TI} , $SPM_{Mass,i}$ is the mass of $SPM_{HF}(g)$ during observation i to i+1.

261

262

- Enrichment factor (EF)
- To distinguish the lithogenic from an anthropogenic origin of trace metals in particles, enrichment factors were calculated. For that purpose, aluminium is assumed as a normalizer element and the concentration of the upper continental crust (UCC) proposed by Rudnick and Gao (2014) as the lithogenic background. The enrichment factor is
- 266 calculated as follows:

$$EF_{TM,i} = \frac{\frac{P_{TM,i}}{P_{Al,i}}}{\frac{P_{TM,UCC}}{P_{Al,UCC}}}$$
 (equation 3)

where $P_{TM,i}$ is the particulate content of a given element in SPM (µg g⁻¹) at observation i, $P_{Al,i}$ the aluminium content of the considered sample at observation i, $P_{TM,UCC}$ and $P_{Al,UCC}$ the element and aluminium content (µg g⁻¹) respectively in the UCC. To compare the degree of enrichment the classification defined by Sutherland (2000) was used. EF < 2: deficiency to low enrichment; EF 2–5: moderate enrichment; EF 5–20: significant enrichment; EF 20–40: very high enrichment; EF > 40: extremely high enrichment. In the present work for an element, EF $_{TM}$ will represent the mean of EF $_{flood}$ and EF $_{base flow}$ if no distinction is given.

274

- 275 Distribution coefficient (K_D)
- To study the repartition of metals between the dissolved and the particulate fraction the distribution coefficient was calculated by the following equation:

$$K_{DTM,i} = \frac{P_{TM,i}}{D_{TM,i} \times 10^{-3}}$$
 (equation 4)

where $K_{D TM,i}$ is the distribution coefficient (L kg⁻¹), $P_{TM,i}$ is the particulate content of a given element in SPM_{GF} (µg g⁻¹), as it is a punctual measurement, $D_{TM,i}$ is the dissolved concentration of the element (µg L⁻¹) at observation *i*. For each TM, an optimised log K_D during a flood or base flow is calculated using all $P_{TM,i}$ and $D_{TM,i}$ available from measured data using Excel Solver.

- 284 Statistical analysis
- Microsoft Excel® XLSTAT add-on was used for statistical analyses. These tests were used to compare the data set for base flow versus for flood for each parameter. First, Grubbs' test was applied to remove extreme values (outliers). Then the Shapiro-Wilk test was applied to test the normality of each distribution. As all the distributions were not normally

distributed, the non-parametric test of Mann-Whitney (with a p<0.05) was applied to determine differences between the base flow and the flood data set.

Results and discussion

Main physico-chemical parameters

The average values of the main physico-chemical parameters (SPM, river flow, temperature, conductivity, dissolved oxygen and chlorophyll-a) obtained for the base flow and flood events are presented in Table SI 5, along with data from other similar water systems. A clear difference between the base flow and the flood was observed for SPM and the river flow. The average increase by a factor 34 and 20 during the flood event was evidenced for SPM GF and the flow, respectively. Compared to other Mediterranean rivers (Table SI 5), the increase of SPM is slightly higher, regardless of the watershed size, likely due to the Las River geology being composed of karstic rocks (Baudement et al., 2017). Moreover, it should be highlighted that in these two years of study the flood occurred "only" 20 % of the time, but it accounts for 69 % of the total water discharge and 78 % of the solid material yield. These results are close to ones previously reported by (Dufresne, 2014; Dufresne et al., 2020) for the period October 2012 to January 2014 (flood 30 % of the time, 85 % of the water discharge and 85 % of the solid material yield). Temperature, conductivity, dissolved oxygen and pH remain stable regardless of the water regime. Chlorophyll-a is the only parameter that increases from base flow to flood. This indicates an increase of phytoplankton abundance, however there is also a high probability that the increase is related to the measurement artefact caused by high turbidity, which was often seen when the probe touches the sediment.

Dissolved and particulate carbon concentrations

Average concentrations of organic carbon in dissolved and particulate phases are presented in Table 2. DOC concentration is in the same range of other Mediterranean rivers from the same region, with a similar, 3-fold increase during the flood over the base flow. POC concentrations are slightly smaller than other surrounding rivers mainly because of a smaller SPM concentration (Table SI 5). The POC fraction (POC/(DOC+POC)) increased from 12 % during the base flow to 47 % during the flood. Nevertheless, in terms of OC content in SPM, the values obtained in the Las River are in the same range as the Huveaune, Jarret and Eygoutier Rivers, but higher than the Rhône River. For all rivers OC content in SPM is 2-fold higher during the base flow compared to flood (Table 2). This trend is attributed to a dilution of POC by addition of mineral particles resulting from erosion processes (Oursel et al., 2014).

| | | Organic Carbon | | | |
|--------------------------|-----------------|----------------------------------|----------------------------------|----------------------|--|
| | | Dissolve d | Particulat e | Particulate content | |
| | | mg _c .L ⁻¹ | mg _c .L ⁻¹ | mg _c .g⁻¹ | |
| Las baseflow | ¤ average | 1.1 | 0.14 | 183 | |
| | ¤ sd * min - | 0.3 | 0.07 0.07 - | 82 | |
| | max | 0.7 - 4.0 | 0.47 | 40 - 360 | |
| Las flood | ¤ average | 3.3 | 2.9 | 85 | |
| | ¤ sd * min - | 2.1 | 4.3 | 41 | |
| | max | 0.8 - 6.8 | 0.1 - 14.9 | 17 - 174 | |
| Rhône river baseflow | average | 1.9 | 0.57 | 36 | |
| Rhône river flood | average | 2.8 | 7.4 | 16 | |
| Huveaune river baseflow | average | 1.3 | 1.0 | 110 | |
| Huveaune river flood | average | 4.8 | 13.8 | 69 | |
| Jarret river baseflow | average | 1.8 | 3.0 | 230 | |
| Jarret river flood | average | 6.4 | 20.9 | 91 | |
| Eygoutier river baseflow | average | 4.1 | 3.1 | 240 | |
| Eygoutier river flood | average | 17 | 39 | 150 | |

Dissolved and particulate trace metal concentrations

The average and variation range of trace metal concentrations during the base flow and flood for the Las River compared to the rivers from the same part of Mediterranean coast (Rhône, Huveaune, Jarret, and Eygoutier Rivers), and to the world average and upper continental crust are provided in Table 3 for dissolved TM and in Table SI 5 for particulate TM content.

Dissolved trace metal concentrations (D_{TM})

For most of the D_{TM} in the Las River, the values are in the same range of concentrations during the base flow and the flood, except for Cr, Co and Zn, for which the two regimes are statistically different (p < 0.05, Mann-Whitney) with an increase by a factor 2. This is also the case for Al with an increase by a factor 3. An hypothesis to explain this increase could be the presence of colloids of aluminium oxids from clays minerals weathering and their association with Cr, Co and Zn. Although concentrations of Pb between the base flow and the flood are not statistically different (due to high variability), it should be highlighted that average Pb concentrations are by factor 2 higher during the flood. Despite being an urban river, according to D_{TM} , the Las River could be characterised by a non-polluted karstic river. Indeed, all mean concentrations are below the European Quality Standards (EQS) except for Cu under flood regime (Table 3). Compared to the world's river averages, D_{TM} concentrations are higher for Zn, equivalent for Pb and lower for all other metals.

Table 3. Dissolved concentration of trace elements (in µg L⁻¹) in Las River during base flow and flood, Rhône River (Ollivier et al. 2011), Huveaune and Jarret Rivers (Oursel et al., 2013; Oursel et al., 2014), Eygoutier River (Nicolau et al., 2012), European Quality Standards (EQS), world river average (Gaillardet et al., 2003; Viers et al., 2009). For Las River, "§" refers to average and sd without extremes values, "*" refers to min-max values including extremes values.

| | Metal | Cd | Pb | Cr | Co | Ni | Cu | Zn | As | Al |
|----------------------------|---------------|-----------------------------|--------|--------|--------|--------|--------|--------|--------|-------|
| | Paramete r | Dissolved in $\mu g L^{-1}$ | | | | | | | | |
| Las base flow | § average | 0.018 | 0.09 | 0.15 | 0.03 | 0.28 | 0.89 | 2.83 | 0.24 | 4.3 |
| | § sd | 0.007 | 0.06 | 0.03 | 0.01 | 0.08 | 0.41 | 1.98 | 0.06 | 2.9 |
| | * min - | 0.010 - | 0.03 - | 0.10 - | 0.02 - | 0.15 - | 0.34 - | 0.59 - | 0.15 - | - 8.0 |
| | max | 0.046 | 0.24 | 0.36 | 0.07 | 0.48 | 1.82 | 6.90 | 0.33 | 54.0 |
| Las flood | § average | 0.017 | 0.21 | 0.25 | 0.07 | 0.26 | 1.46 | 6.37 | 0.23 | 12.6 |
| | § sd | 0.008 | 0.20 | 0.15 | 0.03 | 0.07 | 1.26 | 4.67 | 0.06 | 8.1 |
| | * min - | 0.005 - | 0.01 - | 0.10 - | 0.02 - | 0.16 - | 0.34 - | 0.45 - | 0.13 - | 2.0 - |
| | max | 0.031 | 0.64 | 0.61 | 0.12 | 0.41 | 4.53 | 16.63 | 0.33 | 26.1 |
| Rhône base flow | average | - | 0.066 | - | - | 0.763 | 2.351 | 3.595 | - | - |
| Rhône flood | average | - | 0.070 | - | - | 1.057 | 1.970 | 2.353 | - | - |
| Huveaune base flow | average | 0.008 | 0.13 | - | 0.41 | 2.52 | 1.72 | 3.40 | - | - |
| Huveaune flood | average | 0.021 | 0.31 | - | 0.24 | 1.59 | 5.02 | 17.65 | 0.74 | - |
| Jarret base flow | average | 800.0 | 0.08 | - | 0.24 | 1.70 | 1.78 | 4.77 | - | - |
| Jarret flood | average | 0.025 | 0.35 | - | 0.14 | 1.12 | 5.59 | 18.30 | 0.68 | - |
| Eygoutier base flow | average | 0.040 | 0.60 | - | - | - | 3.49 | 18.30 | - | - |
| Eygoutier flood | average | 0.006 | 1.16 | - | - | - | 3.30 | 1.31 | - | - |
| EQS | average | 0.25 | 1.2 | 3.4 | - | 4 | 1 | 7.8 | 0.83 | - |
| world average base flow | average | 0.080 | 0.08 | 0.7 | 0.15 | 0.80 | 1.48 | 0.60 | 0.62 | 32 |

Particulate trace metal content in SPM (P_{TM})

Particulate trace metal content (P_{TM}) observed in the Las River (Table SI 5) presents a small range of variation (0.4-fold for Cd and Cu to 1.8-fold for Co and 2.5-fold for Al) between the base flow and the flood. Nevertheless, for Cd, Cr, Co, Ni, Cu, As and Al the two periods are statistically different (p < 0.05, Mann-Whitney). For Cd and Cu, this difference consists of a decrease by a factor 2.5 of content during the flood, whereas it corresponds to a relative increase for Cr, Co, Ni, As and Al. Thus, the particles brought to the sea by the river during a flood are richer in Cr, Co, Ni, Zn and As, increasing the net mass contribution. This contribution could be associated with the average urban particle signature taking into account these five elements (Kaonga et al. 2021).

For any of the considered metals, no regularity could be extracted for the base flow and the flood events, between different rivers and the world averages. A short description of P_{TM} tendencies is provided in Table SI 6.

Lastly, it stands that all metal contents in SPM are above the UCC average whatever the period except Co. Moreover Cd, Cu, Zn and Pb are over or in the range of the world's river average content. So an enrichment factor of these elements in Las River SPM calculation will give more information concerning possible anthropogenic inputs.

Enrichment Factor (EF)

Average enrichment factors for measured elements for the base flow, the flood event and for SPM collected by discrete (SPM_{GF}) and time integrative (SPM_{TI}) sampling are presented in Fig. 2. Among the eight studied elements Co showed the lowest EF (EF < 2) indicating the absence of the anthropogenic contribution, while the highest EF was obtained for Cd (EF > 150; for SPM_{GF}). Therefore, high EF of Cd indicates a potential strong anthropogenic influence or a different composition of the weathered rocks/soils compared to UCC composition. Assuming that the carbonate background of

the watershed is composed mainly of limestone and dolomite (Durozoy et al., 1974; El Houssainy, 2020), there is high probability that dolomites are enriched in Cd, as it was already found for other karstic carbonate regions (Cuculić et al., 2009; Vukosav et al., 2014). Enrichment factors for all metals are higher in samples collected during the base flow. This trend has already been observed in other rivers (Benoit et al., 1994; Miller et al., 2003). This indicates that during flood the particles are less enriched than during the base flow. This could be linked to the weathering of more crustal material containing less metals (Cobelo-García & Prego, 2004; Ollivier et al., 2011). This is supported by an increase of Al content during flood (Table SI 6) and the statistical test of difference (Mann-Whitney test) conducted between the average EF of SPM_{GF}, indeed for all TM a statistical difference is observed between flood and base flow regime (p < 0.05) except for As.




Figure 2. Average Enrichment Factors (EF) of measured elements relative to Al content and UCC composition (Rudnick & Gao, 2014). EF is plotted in log scale during baseflow as a function of EF in log scale during flood for punctual SPM_{GF} particles (blue) and integrated SPM_{TI} (orange). Dotted line represents equivalent distribution. Colour scale of the EF legend is described on the left and corresponds to the colour of the axes. Error bars represent one standard deviation.

EF observed for the Las River are higher than those observed in the Rhône River (Ollivier et al., 2011) due to an higher urban surface in Las River watershed (about 30% for Las River against 3.8% for Rhône River). In the Rhône River only Pb, Cd and Zn were considered as enriched (EF higher than 3) whereas Cu, Ni, Co and Cr were around 1.5. Using average data from Table SI 6, enrichment factors were calculated for trace metals in Las, Huveaune, Jarret, Eygoutier and Rhône Rivers during base flow and flood and compared to the average world river SPM (Table SI 7). For Cd, Pb,

- 395 Cu, Zn and As in Huveaune River and Cd, Cu and Zn in Jarret River we observed a very high enrichment factor and an
- 396 extremely high enrichment of Pb in the Jarret River which is the most urbanised watershed (about 50%). In general,
- 397 during floods EF is less important in the Las River than in the Huveaune and Jarret, but higher than in Rhône River
- 398 which is the less urbanised catchment.
- 399 Fig. 2 also points out the differences between SPM_{GF} and SPM_{TI}. For all metals, the EFs during the flood were higher for
- 400 particles collected using time-integrated passive sampler (SPM_{TI}) than for grab samples (SPM_{GF}). Nevertheless, this
- 401 difference is only significant for Co, Ni and Zn (Mann-Whitney, p<0.05). This difference was attributed to the
- 402 difference of sampling method and possible variability in the SPM composition (Lučić et al., 2019, 2021). This could
- also be related to the particles size, as in average the lower grain size with the higher specific surface is collected using
- 404 integrative sampler. During base flow, mean EF are similar whatever the way particles were collected, for all metals
- 405 except Cd, Cr and Co.

407

Partitioning between particulate and dissolved fraction

- 408 The partitioning of trace metals based on the calculation of the distribution coefficient (K_D) was studied to estimate
- 409 whether the composition of particles is changing upon the different flow regimes. The percentages of particulate
- 410 fractions as a function of SPM_{GF}, along with the theoretical lines representing the different distribution coefficients are
- 411 plotted in Fig. 3 and Fig. SI 8.
- 412 From a general point of view, elements can be grouped depending on their different $\log K_D$. Arsenic presents a $\log K_D$
- 413 around 4.6 (Fig. 3-A), Zn, Cu, Ni, Co, and Cd have a $\log K_D$ around 5 (Fig. 3-B, example of Cu), Cr around 5.5 (Fig. 3-
- 414 C) and Pb around 6 (Fig. 3-D).
- 415 The optimised $log K_D$ are similar for the flood and the base flow for Cr, Co and Zn but different for Cd, Cu, As, Ni and
- 416 Pb. This indicates different interaction properties of particles with respect to these trace metals. Cd and Cu have a
- 417 higher K_D during the base flow than during the flood, whereas it is the opposite for Pb, As and Ni (Fig. 3 and Fig. SI 7).
- 418 Cobelo-García et al. (2004) described a negative relation between K_D of trace metals and SPM concentrations explained
- 419 by an organic rich SPM predominant during base flow and a detrital SPM, poor in metals and increasing with flow.
- 420 (Ollivier et al. 2011) also presented this relation with a negative trend for some metals (Ni and Cu) and not significant
- 421 for Zn and Pb. This negative trend could also be related to the effect of the particle concentration on the trace metal
- 422 partition between the water and particles, named "particle concentration effect" as discussed by (Benoit & Rozan
- 423 1999), with a various of causes. In our case, a negative trend is observed for Cd, Cu and Zn.
- 424 The optimised logK_D for Cu, Pb, Cd and Zn are consistent with literature (Cobelo-García et al., 2004; Deycard et al.,
- 425 2014; Miller et al., 2003; Ollivier et al., 2011; Oursel et al., 2014). Copper is known to have a great affinity for organic
- 426 matter. POC content being higher during base flow in the Las River but also in other rivers (Table 2), this could explain
- 427 the higher $\log K_D$ of Cu during base flow compared to flood (Fig. 3-B).
- 428 The optimised $log K_D$ for Co are consistent with the values from (Miller et al., 2003) under base flow (5.0) but slightly
- higher than those observed during the flood compared to the Huveaune and Jarret rivers (Oursel et al., 2014).
- 430 Concerning Ni and Cr, the $log K_D$ are significantly higher than the one observed in previous works and seem not to be
- influenced by the hydrologic regime (Miller et al., 2003; Oursel et al., 2014).

Finally, $\log K_D$ for As is the lowest in this study and it is consistent with value of Oursel et al. (2014) in Huveaune and Jarret rivers (3.9) and of Miller et al. (2003) in Chesterville Branch (4.4).

From Fig. 3 it can be noted that the percentage of particulate metal increases with increasing SPM concentration following the optimised $log K_D$ of each metal. So, according to the optimised $log K_D$ calculated under flood, particulate metals become prevailing over the dissolved ones at SPM concentration of above 20, 15, 3, 1 mg L⁻¹, for As, Cu, Cr and Pb, respectively. It is therefore clear that during the flood Cr and Pb load is dominated by the particulate fraction.






Figure 3. Selected Particulate TM concentration in % as a function of SPM_{GF} concentration (mg L⁻¹) in log scale. Empty square represents base flow data and black disc represents flood. Black lines represent theoretical lines for $\log K_D$, blue line represents optimised $\log K_D$ during flood and orange line represents optimised $\log K_D$ during base flow. The Quadrant B for Cu is representative of Zn, Ni, Co, and Cd patterns.

Trace metal fluxes

Fluxes of trace metals are calculated for two hydrological annual periods: March 2017 to March 2018 (period 1) and March 2018 to March 2019 (period 2), presenting different meteorological conditions (Table 4). The rainfall for the second period (785 mm) was twice the former one (356 mm). As a results, the volume of water and the SPM load delivered by the Las River due to floods are different during the two periods. Between periods 1 and 2, the water and SPM load are 6 and 4 times higher, respectively (Table 4). On the contrary under baseflow conditions, the volume of water is quite similar during the two annual periods, while the SPM load is 3 times higher during the period 2 compared

to the period 1 (Table 4). The values of SPM and flow are consistent with those found by Dufresne et al. (2020) for a year in 2013 (SPM: 707 t y^{-1} and flow: $58 \text{ Mm}^3 \text{ y}^{-1}$).

Table 4. Hydrological conditions during the two studied periods.

| | 3/2017-3/2018 | 8 (period 1) | 3/2018-3/2019 (period 2) | | |
|---|---------------|--------------|--------------------------|-------|--|
| | Base flow | Flood | Base flow | Flood | |
| volume (×10 ⁶ m ³) | 8.1 | 4.9 | 7.9 | 30 | |
| SPM ($\times 10^6$ g) | 15 | 185 | 54 | 777 | |
| Rain (mm) | | 356 | | 785 | |

The annual load of each studied TM for the two separate periods are represented in Fig. 4, distinguishing base flow and flood on separate histograms and indicating on each histogram the proportion of particulate and dissolved load. For period 1 (3/17 to 3/18), the flood inputs are dominant and represents from 50 % to 87 %, for As to Pb, respectively. It seems consistent because As is predominantly delivered in a dissolved form irrespective of the hydrologic regime and Pb is predominantly delivered under particulate form for any hydrologic regime. During period 2 (3/18 to 3/19), the flood inputs are also dominant representing from 87 % to 92 %, from As to Pb, respectively.

Taking into account the mean of the 2 years of the study, during the base flow period, Cd, Co, Ni, Cu, Zn and As are predominantly loaded under dissolved form (from 70 % for Ni to 93 % for As). Only Pb and Cr are predominantly delivered in particulate form with only 21 and 46 % under dissolved form respectively. These results are in accordance with the K_D and the lower concentration of SPM under base flow regime. During flood, Cd, Pb, Cr and Ni prevailed under particulate form (respectively 62, 77, 65 and 62 %), Co and Zn are equally distributed (respectively 50 and 52 %) and lastly Cu and As prevailed in dissolved form (respectively 38 and 35 %). For Pb, Cr and As these findings are consistent with the optimised $log K_D$ determined. For metals like Cu ($log K_D$ around 5) the correlation between K_D and percentage in particulate form is probably subjected to large uncertainty hiding the theoretical trend.





Figure 4. Annual TM load in kg y⁻¹ during two periods March 2017 to March 2018 (P1) and March 2018 to March 2019 (P2) for selected TM (As, Cu, Cr and Pb). For each period load is separated into flood and baseflow. On flood (F) histogram dark grey represents particulate load and wavy plot represents dissolved load. On the base flow (BF) histogram grey represents particulate load and white represents dissolved load. Errors bars represent 5 % of the value for dissolved fraction and 7 % of the value for particulate fraction. Value (in %) above each histogram refers to the particulate % in the histogram.






Figure 5. Dissolved and particulate specific flux (in g y⁻¹ km⁻²) for Cd, Pb, Co, Ni, Cu, Zn, As, Cr in Las River (this study) and other small and large Mediterranean rivers during base flow and flood (Nicolau et al., 2012; Ollivier et al., 2011; Oursel et al., 2013). Empty forms represent base flow data (BF) and full forms represent flood (F).

The specific fluxes, meaning annual load divided by the watershed surface (Nicolau et al., 2012; Ollivier et al., 2011), allowed us to compare rivers of different watersheds. Contrasting patterns were obtained for dissolved metals under base flow (Fig.5). Specific cadmium flux in the Las River is equivalent to Jarret River (both are urban rivers), but it is significantly higher than the flux of the Eygoutier River (less urban river and less calcareous area than Las River). For Pb all specific fluxes are in the same range, highlighting nodifference in terms of sources of contamination between these catchments. For Co, Ni and As, the Las River is less contaminated than other surrounding watersheds. In the Las River, Cu and Zn fluxes are relatively equal to those found in the Eygoutier and Huveaune Rivers, but clearly lower than in the Jarret and Rhone Rivers. During flood comparison with the Rhone River changes. Contamination by Pb, Cu and Zn became predominant in the Las River whereas for Ni and As, the Rhône River is predominant (Fig. 5).

For all particulate metals under the base flow specific fluxes are in the same range of values as for the Eygoutier and Huveaune Rivers, but significantly lower than in the Jarret and Rhône Rivers (Fig. 5). A comparison with the Rhône River during the flood indicates a greater load of trace metals per km² related to the 10 times higher specific SPM flux

of the Rhône River (Table SI 7). So, an extrapolation of our results to other Mediterranean rivers should be conducted with care as, the SPM can play an important role.

Contribution to the bay

From these particulate and dissolved fluxes, an estimation of contribution of the Las River trace metal inputs is calculated. These values are compared to the stock of trace metals in the upper (0-5 cm) sediment estimated in the little Bay of Toulon Bay (Tessier et al., 2011) for the particulate fraction. For the dissolved fraction these values are compared to an estimation stock of dissolved trace metals in the little bay, from concentrations measured in 2017 in surface (unpublished data) as described by Coclet et al., 2018 and extrapolated to the whole volume. As a result, the annual particulate contribution of the Las River is less than 0.2 % for Cu, Pb, Zn (Table SI 9), so Las River is not the main contributor to the sediment contamination in the little bay. The annual dissolved contribution of the Las River varies among trace metals. For Cd, Pb, Cr, Ni, Cu and Zn it is between 21 and 48 %, around 4 % for As and 115 % for Co (Table SI 9). In these conditions the contribution of the Las River appears as not negligeable, compared to the water column stock.

Conclusions

This work highlights the importance of sampling strategy for small river studies. First, high-frequency monitoring of flow and turbidity as a proxy of suspended particulate matter is necessary to correctly account for these two key parameters. For chemical measurements monthly sampling during base flow was sufficient to obtain a correct annual load. However, it was important to consider flood differently than base flow (focus on flood). For floods, a relation between flux and flow can be used that allows extrapolation to unsampled flood events. The use of time-integrated SPM sampler allowed periodic collection of representative particles.

The results point out that for small Mediterranean rivers the flood represents the main regime for trace metal load (from 78 % for As to 91 % for Pb) even if it occurs only 20 % of the time. Moreover, the impact of the flood was mainly dependent on the SPM flux and on the flow intensity. Indeed, a 2-fold increase in precipitation leads to an increase in volume and SPM discharge by a factor of 4 to 6 and consequently to a corresponding increase in TM load depending on its main affinity for dissolved fractions (e.g. As increase for the same volume increase) or particulate fractions (e.g. Pb increase for the same SPM increase). It was also found that the yield of As, Cu, Co, Zn, Cd and Ni during base flow was mainly in the dissolved phase and for Pb in the particulate phase. During flood, the yield of As was mainly in the dissolved phase, while the yield of Cd, Ni, Cr and Pb was in the particulate phase. A decrease in the enrichment factor for all trace metals was observed from base flow to flood probably due to more neutral particles coming from the watershed erosion. Compared to other watersheds, we conclude that the specific dissolved fluxes for some metals could be higher in small rivers, but for the specific particulate fluxes the importance of SPM concentrations should be considered. Extrapolation of results from one catchment to a larger zone should therefore be considered with caution. In terms of contribution to the small bay, particulate trace metals annual yield is low compared to the high contamination of the sediment while dissolved trace metals annual input represents, for Cd, Pb, Cr, Ni, Cu and Zn 20 to 50 % of the dissolved stock.

References

589 udement, C., Arfib, B., Mazzilli, N., Jouves, J., Lamarque, T., & Guglielmi, Y. (2017). Groundwater management of a highly dynamic karst by assessing baseflow and quickflow with a rainfall-discharge model (Dardennes

- 541 springs, SE France). Bulletin de la Société géologique de France, 188(6), 40.
- 542 https://doi.org/10.1051/bsgf/2017203
- 5&cnoit, G., Oktay-Marshall, S. D., Cantu, A., Hood, E. M., Coleman, C. H., Corapcioglu, M. O., & Santschi, P. H.
- 544 (1994). Partitioning of Cu, Pb, Ag, Zn, Fe, Al, and Mn between filter-retained particles, colloids, and solution
- 545 in six Texas estuaries. Marine Chemistry, 45(4), 307–336. https://doi.org/10.1016/0304-4203(94)90076-0
- 586 noit, Gaboury, & Rozan, T. F. (1999). The influence of size distribution on the particle concentration effect and
- trace metal partitioning in rivers. Geochimica et Cosmochimica Acta, 63(1), 113-127.
- 548 https://doi.org/10.1016/S0016-7037(98)00276-2
- 58ernal, S., von Schiller, D., Sabater, F., & Martí, E. (2013, November). Hydrological extremes modulate nutrient
- 550 dynamics in mediterranean climate streams across different spatial scales. Hydrobiologia.
- 551 https://doi.org/10.1007/s10750-012-1246-2
- 552 belo-García, A., & Prego, R. (2004). Influence of point sources on trace metal contamination and distribution in
- a semi-enclosed industrial embayment: the Ferrol Ria (NW Spain). Estuarine, Coastal and Shelf Science,
- 554 60(4), 695-703. https://doi.org/10.1016/J.ECSS.2004.03.008
- 555 belo-García, A., Prego, R., & Labandeira, A. (2004). Land inputs of trace metals, major elements, particulate
- organic carbon and suspended solids to an industrial coastal bay of the NE Atlantic. Water Research, 38(7),
- 557 1753-1764. https://doi.org/10.1016/j.watres.2003.12.038
- 550 clet, C., Garnier, C., Delpy, F., Jamet, D., Durrieu, G., Le Poupon, C., et al. (2018). Trace metal contamination as
- 559 a toxic and structuring factor impacting ultraphytoplankton communities in a multicontaminated
- 560 Mediterranean coastal area. *Progress in Oceanography*, 163, 196–213.
- 561 https://doi.org/10.1016/j.pocean.2017.06.006
- 562clet, C., Garnier, C., Durrieu, G., D'Onofrio, S., Layglon, N., Briand, J. F., & Misson, B. (2020). Impacts of copper
- and lead exposure on prokaryotic communities from contaminated contrasted coastal seawaters: The
- influence of previous metal exposure. FEMS Microbiology Ecology, 96(6).
- 565 https://doi.org/10.1093/femsec/fiaa048
- 566clet, C., Garnier, C., Durrieu, G., Omanović, D., D'Onofrio, S., Le Poupon, C., et al. (2019). Changes in
- 567 Bacterioplankton Communities Resulting From Direct and Indirect Interactions With Trace Metal Gradients
- in an Urbanized Marine Coastal Area. Frontiers in Microbiology, 10(FEB), 257.
- 569 https://doi.org/10.3389/fmicb.2019.00257
- 5700 wling, R. M., Ojeda, F., Lamont, B. B., Rundel, P. W., & Lechmere-Oertel, R. (2005). Rainfall reliability, a
- 571 neglected factor in explaining convergence and divergence of plant traits in fire-prone mediterranean-
- 572 climate ecosystems. Global Ecology and Biogeography, 14(6), 509-519. https://doi.org/10.1111/J.1466-
- 573 822X.2005.00166.X
- 5724 culić, V., Cukrov, N., Kwokal, Ž., & Mlakar, M. (2009). Natural and anthropogenic sources of Hg, Cd, Pb, Cu and
- 575 In in seawater and sediment of Mljet National Park, Croatia. Estuarine, Coastal and Shelf Science, 81(3),
- 576 311-320. https://doi.org/10.1016/j.ecss.2008.11.006
- 570 Ang, D. H., Schäfer, J., Brach-Papa, C., Lenoble, V., Durrieu, G., Dutruch, L., et al. (2015). Evidencing the Impact
- of Coastal Contaminated Sediments on Mussels Through Pb Stable Isotopes Composition. Environmental
- 579 Science and Technology, 49(19), 11438–11448. https://doi.org/10.1021/acs.est.5b01893
- 580eycard, V. N., Schäfer, J., Blanc, G., Coynel, A., Petit, J. C. J., Lanceleur, L., et al. (2014). Contributions and
- 581 potential impacts of seven priority substances (As, Cd, Cu, Cr, Ni, Pb, and Zn) to a major European Estuary
- 582 (Gironde Estuary, France) from urban wastewater. Marine Chemistry, 167, 123-134.
- 583 https://doi.org/10.1016/j.marchem.2014.05.005

- 58Aufresne, C. (2014). Compréhension et analyse des processus hydro-sédimentaires de la Baie de Toulon. : Apport 585 à la modélisation de la dispersion des radionucléides. Ph. D. Université de toulon.
- 58% fresne, C., Arfib, B., Ducros, L., Duffa, C., Giner, F., & Rey, V. (2020). Karst and urban flood-induced solid
- 587 discharges in Mediterranean coastal rivers: The case study of Las River (SE France). Journal of Hydrology,
- 588 590. https://doi.org/10.1016/j.jhydrol.2020.125194
- 589umas, C., Ludwig, W., Aubert, D., Eyrolle, F., Raimbault, P., Gueneugues, A., & Sotin, C. (2015). Riverine transfer
- of anthropogenic and natural trace metals to the Gulf of Lions (NW Mediterranean Sea). Applied
- 591 Geochemistry, 58, 14-25. https://doi.org/10.1016/J.APGEOCHEM.2015.02.017
- 5 Durozoy, G., Gouvernet, C., & Jonquet, P. (1974). Ministère de l'industrie, Bureau de Recherches Géologiques et
- 593 Minières, Service géologique national, Notice explicative Echelle: 1/50000 Service géologique régional
- 594 Provence-Corse.
- 55 Houssainy, A. (2020). Apports et géochimie sédimentaire des éléments traces métalliques dans deux zones
- 596 côtières méditerranéennes urbanisées : Beyrouth (Liban) et Toulon (France). Université de Toulon.
- 5 % ang, T. H., & Chen, W. H. (2021). Dissolved and particulate nitrogen species partitioning and distribution in the
- 598 Danshuei River estuary, northern Taiwan. Marine Pollution Bulletin, 164.
- 599 https://doi.org/10.1016/j.marpolbul.2021.111981
- 600aillardet, J., Viers, J., & Dupré, B. (2003). Trace Elements in River Waters. In Treatise on Geochemistry (Vol. 5-9,
- 601 pp. 225–272). Elsevier. https://doi.org/10.1016/B0-08-043751-6/05165-3
- 6@alloway, J. N., Aber, J. D., Erisman, J. W., Seitzinger, S. P., Howarth, R. W., Cowling, E. B., & Cosby, B. J. (2003).
- 603 The Nitrogen Cascade. BioScience, 53(4), 341–356.
- 6026 bnzález-Ortegón, E., Laiz, I., Sánchez-Quiles, D., Cobelo-Garcia, A., & Tovar-Sánchez, A. (2019). Trace metal
- 605 characterization and fluxes from the Guadiana, Tinto-Odiel and Guadalquivir estuaries to the Gulf of Cadiz.
- 606 Science of the Total Environment, 650, 2454-2466. https://doi.org/10.1016/j.scitotenv.2018.09.290
- 60amarque, T. (2014). Établissement d'une courbe de tarage des débits du cours d'eau du Las réalisée d'août à 608 décembre 2013.
- 609yglon, N., Misson, B., Durrieu, G., Coclet, C., D'Onofrio, S., Dang, D. H., et al. (2020). Long-term monitoring
- 610 emphasizes impacts of the dredging on dissolved Cu and Pb contamination along with ultraplankton
- 611 distribution and structure in Toulon Bay (NW Mediterranean Sea, France). Marine Pollution Bulletin, 156.
- 612 https://doi.org/10.1016/j.marpolbul.2020.111196
- 618 rrain, A., Savoye, N., Chauvaud, L., Paulet, Y. M., & Naulet, N. (2003). Decarbonation and preservation method
- 614 for the analysis of organic C and N contents and stable isotope ratios of low-carbonated suspended
- 615 particulate material. Analytica Chimica Acta, 491(2), 125-133. https://doi.org/10.1016/S0003-
- 616 2670(03)00815-8
- 61 vicić, M., Jurina, I., Ščančar, J., Mikac, N., & Vdović, N. (2019). Sedimentological and geochemical
- characterization of river suspended particulate matter (SPM) sampled by time-integrated mass flux sampler
- 619 (TIMS) in the Sava River (Croatia). Journal of Soils and Sediments, 19(2), 989–1004.
- 620 https://doi.org/10.1007/s11368-018-2104-2
- 62 ωčić, M., Mikac, N., Bačić, N., & Vdović, N. (2021). Appraisal of geochemical composition and hydrodynamic
- sorting of the river suspended material: Application of time-integrated suspended sediment sampler in a
- 623 medium-sized river (the Sava River catchment). Journal of Hydrology, 597, 125768.
- 624 https://doi.org/10.1016/J.JHYDROL.2020.125768

- 625 eybeck, M. (2001). River sediment transport and quality: From space and time variability to management.
- 626 Houille Blanche, (6-7), 34-43. https://doi.org/10.1051/lhb/2001067
- 62Miller, P. C. (1983). Canopy Structure of Mediterranean-Type Shrubs in Relation to Heat and Moisture, 133-166.
- 628 https://doi.org/10.1007/978-3-642-68935-2_8
- 629iller, C. V., Foster, G. D., & Majedi, B. F. (2003). Baseflow and stormflow metal fluxes from two small
- 630 agricultural catchments in the Coastal Plain of the Chesapeake Bay Basin, United States. Applied
- 631 Geochemistry, 18(4), 483-501. https://doi.org/10.1016/S0883-2927(02)00103-8
- 632isson, B., Garnier, C., Lauga, B., Dang, D. H., Ghiglione, J. F., Mullot, J. U., et al. (2016). Chemical multi-
- 633 contamination drives benthic prokaryotic diversity in the anthropized Toulon Bay. Science of the Total
- 634 Environment, 556, 319-329. https://doi.org/10.1016/j.scitotenv.2016.02.038
- 636 colau, R., Lucas, Y., Merdy, P., & Raynaud, M. (2012). Base flow and stormwater net fluxes of carbon and trace
- 636 metals to the Mediterranean sea by an urbanized small river. Water Research, 46(20), 6625–6637.
- 637 https://doi.org/10.1016/j.watres.2012.01.031
- 638 colau, Rudy. (2005). Caractérisation et quantification des transferts dus aux petites rivières côtières
- 639 méditerranéennes. Université de Toulon.
- 640grinc, N., Markovics, R., Kanduč, T., Walter, L. M., & Hamilton, S. K. (2008). Sources and transport of carbon and
- 641 nitrogen in the River Sava watershed, a major tributary of the River Danube. Applied Geochemistry, 23(12),
- 642 3685-3698. https://doi.org/10.1016/J.APGEOCHEM.2008.09.003
- 6421ías, M., Cánovas, C. R., Nieto, J. M., & Sarmiento, A. M. (2006). Evaluation of the dissolved contaminant load
- 644 transported by the Tinto and Odiel rivers (South West Spain). Applied Geochemistry, 21(10), 1733–1749.
- 645 https://doi.org/10.1016/J.APGEOCHEM.2006.05.009
- 64 divier, P., Radakovitch, O., & Hamelin, B. (2011). Major and trace element partition and fluxes in the Rhône
- 647 River. Chemical Geology, 285(1-4), 15-31. https://doi.org/10.1016/j.chemgeo.2011.02.011
- 648ursel, B., Garnier, C., Durrieu, G., Mounier, S., Omanović, D., & Lucas, Y. (2013). Dynamics and fates of trace
- 649 metals chronically input in a Mediterranean coastal zone impacted by a large urban area. Marine Pollution
- 650 Bulletin, 69(1-2), 137-149. https://doi.org/10.1016/j.marpolbul.2013.01.023
- 6 Dursel, B., Garnier, C., Pairaud, I., Omanović, D., Durrieu, G., Syakti, A. D., et al. (2014). Behaviour and fate of
- 652 urban particles in coastal waters: Settling rate, size distribution and metals contamination characterization.
- 653 Estuarine, Coastal and Shelf Science, 138, 14–26. https://doi.org/10.1016/j.ecss.2013.12.002
- 65Aursel, B., Garnier, C., Zebracki, M., Durrieu, G., Pairaud, I., Omanović, D., et al. (2014). Flood inputs in a
- 655 mediterranean coastal zone impacted by a large urban area: Dynamic and fate of trace metals. Marine
- 656 Chemistry, 167, 44–56. https://doi.org/10.1016/j.marchem.2014.08.005
- 65 telet, E., Luck, J. M., Ben Othman, D., Negrel, P., & Aquilina, L. (1998). Geochemistry and water dynamics of a
- 658 medium-sized watershed: the Hérault, southern France: 1. Organisation of the different water reservoirs as
- constrained by Sr isotopes, major, and trace elements. Chemical Geology, 150(1-2), 63-83.
- 660 https://doi.org/10.1016/S0009-2541(98)00053-9
- 66hillips, J. M., Russell, M. A., & Walling, D. E. (2000). Time-integrated sampling of fluvial suspended sediment: a
- simple methodology for small catchments. Hydrological processes, 14, 2589-2602.
- 663nt, D., Simonnet, J. P., & Walter, A. V. (2002). Medium-term Changes in Suspended Sediment Delivery to the
- Ocean: Consequences of Catchment Heterogeneity and River Management (Rhône River, France).
- 665 Estuarine, Coastal and Shelf Science, 54(1), 1-18. https://doi.org/10.1006/ECSS.2001.0829

- 666tot, C., Féraud, G., Schärer, U., Barats, A., Durrieu, G., Le Poupon, C., et al. (2012). Groundwater and river
- 667 baseline quality using major, trace elements, organic carbon and Sr-Pb-O isotopes in a Mediterranean
- catchment: The case of the Lower Var Valley (south-eastern France). Journal of Hydrology, 472-473, 126-
- 669 147. https://doi.org/10.1016/j.jhydrol.2012.09.023
- 6 Roussiez, V., Ludwig, W., Radakovitch, O., Probst, J. L., Monaco, A., Charrière, B., & Buscail, R. (2011). Fate of
- 671 metals in coastal sediments of a Mediterranean flood-dominated system: An approach based on total and
- labile fractions. Estuarine, Coastal and Shelf Science, 92(3), 486-495.
- 673 https://doi.org/10.1016/j.ecss.2011.02.009
- 6 R4 dnick, R. L., & Gao, S. (2014). Composition of the Continental Crust. In Treatise on Geochemistry: Second
- 675 Edition (Vol. 4, pp. 1–51). Elsevier Inc. https://doi.org/10.1016/B978-0-08-095975-7.00301-6
- 636 mpere, R., Charrière, B., Van Wambeke, F., & Cauwet, G. (2000). Carbon inputs of the Rhône River to the
- 677 Mediterranean Sea: Biogeochemical implications Carbon inputs of the Rhône River to the Mediterranean
- 678 Sea: Biogeochemical implications. Global Biogeochemical Cycles, 14(2), 669-681.
- 679 https://doi.org/10.1029/1999GB900069ï
- 680 therland, R. A. (2000). Bed sediment-associated trace metals in an urban stream, Oahu, Hawaii. *Environmental Geology* 2000 39:6, 39(6), 611–627. https://doi.org/10.1007/S002540050473
- 682 ssier, E., Garnier, C., Mullot, J. U., Lenoble, V., Arnaud, M., Raynaud, M., & Mounier, S. (2011). Study of the
- 683 spatial and historical distribution of sediment inorganic contamination in the Toulon bay (France). Marine
- 684 Pollution Bulletin, 62(10), 2075-2086. https://doi.org/10.1016/J.MARPOLBUL.2011.07.022
- 686ers, J., Dupré, B., & Gaillardet, J. (2009). Chemical composition of suspended sediments in World Rivers: New
- insights from a new database. Science of the Total Environment, 407(2), 853–868.
- 687 https://doi.org/10.1016/j.scitotenv.2008.09.053
- 688 kosav, P., Mlakar, M., Cukrov, N., Kwokal, Ž., Pižeta, I., Pavlus, N., et al. (2014). Heavy metal contents in water,
- sediment and fish in a karst aquatic ecosystem of the Plitvice Lakes National Park (Croatia). Environmental
- 690 Science and Pollution Research, 21(5), 3826-3839. https://doi.org/10.1007/s11356-013-2377-3
- 691
- 692
- 693