



HAL
open science

Hydro-chemical characterization and spatial distribution of groundwater quality in a watershed in Antananarivo Madagascar

Nelly Ghislaine Rakoto, Wilson Adolphe Rajerison, Alphonse
Rafenomanantsoa, Gérard Sarazin

► **To cite this version:**

Nelly Ghislaine Rakoto, Wilson Adolphe Rajerison, Alphonse Rafenomanantsoa, Gérard Sarazin. Hydro-chemical characterization and spatial distribution of groundwater quality in a watershed in Antananarivo Madagascar. 2024. hal-04492768

HAL Id: hal-04492768

<https://hal.science/hal-04492768>

Preprint submitted on 6 Mar 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Title: Hydro-chemical characterization and spatial distribution of groundwater quality in a watershed in Antananarivo Madagascar

Titre : Caractérisation hydrochimique et distribution spatiale de la qualité des eaux souterraines d'un bassin versant localisé à Antananarivo Madagascar

Authors : ^{1,2}Nelly Ghislaine RAKOTO, ²Wilson Adolphe RAJERISON, ²Alphonse RAFENOMANANTSOA, ³Gérard SARAZIN

¹Laboratoire de Chimie de l'Environnement, Mention Procédés et Écologie Industrielle, Domaine Sciences et Technologies, Université d'Antananarivo Madagascar

²Ecole Doctorale Valorisation des Ressources Naturelles Renouvelables (VRNR) – Domaine Sciences et Technologies – Université d'Antananarivo Madagascar

³Equipe biogéochimie environnementale – Université Paris-Diderot & Institut de Physique du Globe de Paris (IPGP) - 1 rue de Jussieu 75005 Paris. France

*Corresponding author: rakotonelly@yahoo.fr or nelly.rakoto@univ-antananarivo.mg

ABSTRACT:

Groundwater exploitation contributes to achieving sustainable development goal 6: access to safe and affordable drinking water for all. This study aims to determine hydro-chemical facies, groundwater quality, and its spatial distribution in the Antananarivo watershed. Various parameters including pH, Electrical Conductivity (EC), Turbidity, major cations (Ca^{2+} , Mg^{2+} , and K^{+}), and major anions (SO_4^{2-} , Cl^{-} , and HCO_3^{-}) were measured to estimate the Water Quality Index (WQI). Spatial analysis was conducted using the Inverse Distance Weighted (IDW) method in QGIS. Principal Component Analysis (PCA) of Pearson correlation was used to analyse the relationships between variables. Approximately 75% of groundwater samples, mainly from lithosol areas, were found to be suitable for drinking purposes based on the established WQI. However, less than 25% of wells located in ferralitic and hydro-morphic mineral soils, primarily in lower altitude areas, were deemed unsuitable for human consumption. The aquifers in the watershed were characterized by three hydro-chemical facies: Calcium – Chloride (44 wells), Calcium – Magnesium – Chloride (6 wells), and Calcium – Magnesium – Bicarbonate (2 wells), with Chloride and Calcium dominating.

Keywords: *Groundwater, hydrochemistry, Water Quality Index (WQI), spatial interpolation, Watershed*

RESUME

L'exploitation des eaux souterraines contribue à la réalisation de l'objectif de développement durable n°6 : accès à l'eau potable et abordable pour tous. L'étude vise à déterminer le faciès hydrochimique, la qualité des eaux souterraines et leur répartition spatiale dans le bassin versant d'Antananarivo. Divers paramètres, notamment

le pH, la conductivité électrique (CE), la turbidité, les cations majeurs (Ca^{2+} , Mg^{2+} et K^+) et les anions majeurs (SO_4^{2-} , Cl^- et HCO_3^-) ont été mesurés pour estimer l'indice de qualité de l'eau (WQI). L'analyse spatiale a été réalisée à l'aide de la méthode Inverse Distance Weighted (IDW) dans QGIS. L'analyse en composantes principales (ACP) de la corrélation de Pearson a été utilisée pour analyser les relations entre les variables. Selon l'IQE établi, environ 75 % des échantillons d'eaux souterraines, principalement provenant de zones de lithosol, se sont révélés propres à la consommation. Cependant, moins de 25 % des puits situés dans des sols ferrallitiques et hydro-morphes minéraux, principalement dans les zones de basse altitude, ont été jugés impropres à la consommation humaine. Les aquifères du bassin versant sont caractérisés par trois faciès hydrochimiques : Calcium – Chlorure (44 puits), Calcium – Magnésium – Chlorure (6 puits) et Calcium – Magnésium – Bicarbonate (2 puits), à dominante Chlorure et Calcium.

Mots clés : Eaux souterraines, hydrochimie, Indice de la Qualité des Eaux, Interpolation spatiale, Bassin versant

1. INTRODUCTION

Sustainable Development Goal 6 (SDG 6) focuses on ensuring availability and sustainable management of water and sanitation for all. It aims to achieve universal and equitable access to safe and affordable drinking water for everyone, as well as adequate and equitable sanitation and hygiene for all, by 2030 (The United Nations World Water Development Report 2022). It is an unevenly distributed renewable natural resource and accounts for almost half of the drinking water in the world.

In 2016, only 23% of the population had access to safe drinking water in Madagascar; Within the agglomeration of Antananarivo, capital city, 71.88% of the population had access to drinking water which was calculated based on various infrastructures such as private connections, public standpipes of JIRAMA (the National Company of Electricity and Water in Madagascar), boreholes, and wells with human-powered pumps (MAHTP & JICA, 2019). Despite the efforts of JIRAMA to provide water connections, the coverage is still not complete, there are areas within the agglomeration where access to drinking water is lacking. The low coverage of urban water infrastructure and the limited service provided by JIRAMA significantly impact the quantity, quality and reliability of water provision. Only 33 % of population in the Urban Commune of Antananarivo have access to private water connection (Ognard, Taglioni 2019).

Aquifers are porous and permeable geological formations that act as natural reservoirs of water. They are supplied by natural recharge processes, such as rainfall, and are used by the urban dwellers for various activities.

19 Aquifers are pumped for human activities, including domestic use and small-scale private or community irriga-
20 tion. Some residents of Antananarivo rely on groundwater from aquifers for drinking water. City residents prefer
21 this source over the water provided by JIRAMA because the latter is thought to be contaminated, non-potable
22 and potentially pose health harm. Groundwater from aquifers is believed to be protected from microorganisms.
23 During the infiltration of water into the aquifer, the soil and rocks act as natural filters, removing or reducing the
24 presence of harmful microorganisms.

25 Protecting and conserving this resource entails managing both its quantity and quality. Natural phenomena and
26 anthropogenic activities can impact groundwater quality. The nature of the chemical facies is influenced by fac-
27 tors such as evaporation rates, precipitation, weathering of primary or secondary minerals through water-rock
28 interaction, and soil quality above the aquifer (Salim et al. 2020). The acid hydrolysis of rocks is significant in
29 mineralizing water, enriching it with nutritive salts, affecting the solubility of Mn^{2+} and Fe^{2+} , and making Al species
30 available, primarily through kaolinite and/or gibbsite dissolution (Ahoussi et al. 2013, Aka et al. 2013). Weathering
31 of feldspars increases the concentration of Na^+ , Ca^{2+} , and K^+ in groundwater; Groundwater interacts with vegeta-
32 tion, atmospheric CO_2 , and soil microorganisms, enriching it with HCO_3^- and increasing water alkalinity (Saravanan
33 et al. 2015). Environmental conditions such as high temperature, low rainfall, and high evaporation can lead to
34 increased dissolved salt content in groundwater and decreased recharge rates (Ahmad et al. 2020).

35 Groundwater deterioration is a significant environmental concern influenced by various human activities such as
36 urbanization, agricultural development, use of fertilizers, overexploitation, and strong demographic pressure
37 which produce high quantities of solid and liquid wastes. These activities lead to both pollution and depletion of
38 groundwater resources (Ahmad et al. 2020). Nitrate, sulphate, and chloride pollution through sewers, organic
39 waste spreaded on the ground, and use of nitrogenous fertilizers can originate from agricultural practices, indus-
40 trial processes, and domestic activities (Aka et al. 2013, Zheng et al. 2017); rain water and irrigation carry pollu-
41 tants through the soil layers by infiltration, so that they can leach into groundwater (Chen et al. 2023).

42 The current study focuses on analyzing the physicochemical properties of groundwater to understand the influ-
43 ences of natural and human activities. By conducting geochemical analyses using the Piper diagram, the study
44 aims to determine hydrochemical facies and elucidate the presence of various ions and salts. The spatial distri-
45 bution of the Water Quality Index (WQI) within these hydro chemical facies is examined to provide valuable in-
46 sights for aquifer management (Ahoussi et al. 2013).

47 2. MATERIAL AND METHODS

48 2.1. Description of study area

49
50 The watershed covers 21 fokontany (smallest political subdivision in Madagascar) in Antananarivo, with a total
51 area of 4,16 km². It was delineated from ASF ALOS PALSAR – Digital Elevation Map (Figure 1) using hydrological
52 processing tool in GRASS-GIS. It lies between latitudes -18,9472306°S; -18,9193111°S and longitudes
53 47,5225889°E; 47,5438889°E. The highest elevation, approximately 1 433 m, is observed in the fokontany of
54 Manjakamiadana where the queen’s palace is located. Sewerage and storm water are collected in the lowland of
55 the watershed, reach the outlet (47, 52900844°E, -18, 94124730°S) and discharging into Ikopa River in An-
56 drondrakely Saropody. The majority of the city’s inhabitants get their water supply from standpipes rarely from
57 wells. Groundwater are mainly used for domestic and permaculture watering activities.

58 Antananarivo has a tropical climate characterised by a dry and cold winter from May to September, a rainy and
59 warm summer from October to April. The mean annual temperature is 18°C, with a maximum of 26°C in Novem-
60 ber and a minimum 10°C in July. The annual rainfall ranges from 1,000 mm to 1,600 mm per year.

61 Figure 3 depicts three soil types in the study area: ferralitic (FS), mineral hydromorphic (HM) and lithosoil (LS)
62 (Bourgeat 1968). FS are characterised by their iron and aluminium content, low exchange capacity, low base con-
63 tent, low pH and red colour. HM or low humus and gley soils, form in poorly drained areas, with permanent deep
64 waterlogging and fairly significant fine alluvium. The organic horizon is more compact than in the previous types
65 and is generally no more than 20 to 30 cm thick. Organic matter levels are frequently in the order of 4 to 5% and
66 less than 10%. HM with pseudo gley are acid with variable granulometry, low saturation rate with few mineral
67 reserves. Unprocessed mineral soils named lithosols (LS) may not occupy large areas in the valleys of ancient
68 massifs. These soils are normally micaceous, with an acid reaction, rather poor in mineral elements.




Figure 1: Watershed localization in Antananarivo Madagascar

69
70
71




Figure 2: Elevation and stream order characteristics of the watershed

72




Figure 3: Soil types characteristic of the watershed

73

2.2. Water quality analysis

74

75

76

77

78

79

80

Water samples were collected from 52 wells of Antananarivo watershed during June 2023, beginning of dry and cold season (Figure 3, table 1). They were georeferenced using kinematic GPS. The water from these wells is used for various purposes including domestic activities, drinking, and agricultural activities. Rinsed PolyEthylene Terphthalate bottles of one litre were used for collecting samples. The samples were kept at a temperature below 4°C during transportation and conservation to maintain their integrity before analysis.

Soil type	Number of wells for sampling
Ferralitic soil (FS)	19
Lithosol (LS)	9
Mineral Hydromorphe (HM)	24

81

Table 1: Number of wells per soil types

82

83

The pH and Electrical Conductivity (EC) were measured in-situ, at the same time as geographical data collection, using portable analyzers pH-meter Greisinger instruments and Conductimeter HANNA. Turbidity was measured

84 using a turbidimeter HANNA. The bicarbonate (HCO_3^-) was analysed by Gran titration method using HCl ($0,1 \text{ mol.l}^{-1}$).
85 1). The Hardness or TH (an indication of concentration of Ca^{2+} and Mg^{2+} dissolved in water), calcium (Ca^{2+}) and
86 magnesium (Mg^{2+}) were measured by EDTA – Complexation and the potassium (K^+) by HANNA photometer. The
87 procedure of determination of sulphate (SO_4^{2-}) amount in water involve its precipitation by barium chloride, fol-
88 lowed by stabilization with TWEEN 20 solution. The homogeneous suspensions were measured with a spectro-
89 photometer at 650 nm. The chloride was measured by volumetric method based on Mohr method using silver
90 nitrate (Ag NO_3) and potassium chromate (K_2CrO_4).

91 Descriptive statistic using excel tool such as boxplot was employed for data statistical analysis. Major cations (K^+ ,
92 Mg^{2+} , Ca^{2+}) and major anions (HCO_3^- , SO_4^{2-} , Cl^-) were plotted on Piper diagram used to visualize and describe the
93 groundwater quality.

94 Water Quality Index (WQI) is a numerical single value used to evaluate the overall quality of water based on
95 various parameters. The WQI is particularly useful in assessing groundwater quality for different purposes such
96 as drinking, irrigation, or industrial use (Chidiac et al. 2023). WQI is used to assess groundwater quality status,
97 taking into account water quality parameters. Determining WQI consists of three main steps:

98 **Step 1: Weighting:** Ten parameters such as pH, EC, Turbidity, hardness (TH), Ca^{2+} , Mg^{2+} , K^+ , SO_4^{2-} , Cl^- and HCO_3^-
99 were considered, and relative weights are assigned to each parameter which can be calculated as:

100
$$Wi = \frac{wi}{\sum_{i=1}^n wi}$$

101 Wi : Relative weight for each parameter

102 wi : weight assigned for each parameter

103 n : number of parameters selected

104 **Step 2: calculating rating scale**

105 In general, water quality parameters have different units. This step aims to transform all parameters into common
106 scale. The rating scale values Qi depend on the permissible limits from Malagasy drinking water standard and can
107 be calculated by the following equation:

108
$$Qi = \frac{Ci - Co}{Si - Co} \times 100$$

109 Qi : Rating scale value

110 Ci : parameter value

111 Co : Ideal value of the parameter ($Co = 0$) except for pH ($Co = 7$)

112 Si: Standard value

113 Step 3: Aggregation and Producing WQI

114 The final step is calculating sub-index Sli by multiplying the rating scale values with weights. Then, the WQI
115 value can be determined by aggregating Sli values.

$$116 \quad Sli = Wi * Qi$$

$$117 \quad WQI = \sum_{i=1}^n Sli$$

118 Si: sub-index parameters

119 Qi: Rating scale value based on amount of i^{th} parameter

120 n: number of the parameter

121 The water quality status depends on WQI values and provided on table 2

122 **Table 2: water quality status (Siriwardhana et al. 2023)**

WQI	Water Quality Status	Possible use		
		Drinking	Agricultural	Industrial
0 - 25	Excellent	Suitable	Suitable	Suitable
25 - 50	Good	Suitable	Suitable	Suitable
50 - 75	Poor	Not suitable	Suitable	Suitable
75 - 100	Very poor	Not suitable	Suitable	Not suitable
Above 100	Not suitable for drinking or fish culture	Proper treatment required		

123

124 Principal Component Analysis (PCA) was performed by using Pearson Correlation Method providing insight into
125 the relationship between pairs of water quality parameters. Pearson correlation coefficient ranges between -1
126 and +1. Coefficient equal to zero means no linear correlation between the two variables, negative value next to -
127 1 and positive value next to 1 means respectively negative and positive correlation between the two variables.

128 2.3. Hydrochemical properties analysis

129

130 Hydrochemical properties of groundwater are related to groundwater resident time, lithology and human activ-
131 ities can indeed reflect the composition of the rocks through which the water has flowed. The Piper diagram is a
132 graphical method used in hydrogeochemistry to analyze and classify the chemical composition of water based on
133 the concentrations of major cations (such as calcium, magnesium, sodium, and potassium) and major anions
134 (such as bicarbonate, sulphate, and chloride). Piper diagram is useful in understanding groundwater quality, iden-
135 tifying sources of contamination, and studying water-rock interactions. It presents the variation type of facies in
136 groundwater chemistry. This ternary diagram is composed by two triangles corresponding with dominant cations
137 and anions and one diamond which illustrate the facies types.

138 2.4. Spatial analysis

139 Spatial distribution maps of the water quality index were created using the Inverse Distance Weighted (IDW)
140 method. It is an effective tools for spatial interpolation of groundwater quality and predicts the value of a variable
141 at an unsampled point by an average weight of the observed variables (Ram et al. 2021). The weighting is a
142 function of the distance between the observation point and the forecast point so that the closer points have more
143 influence.
144

145 3. RESULTS AND DISCUSSION

146 3.1. Physico-chemical characteristics of groundwater

147
148 The pH of all studied water samples were slightly acidic. More than 75 % of water from lithosoil have circumneu-
149 tral pH. The remaining 25 % of samples under mineral hydromorphic soil and under ferralitic soil are more acidic.
150 The lower pH values are attributed to CO₂ carried by precipitation which recharges groundwater through infiltra-
151 tion. The dissolution of this entity produce carbonic acid and decrease pH value (Huang, Ma 2019, Miller 1987).
152 High acidity might be associated to organic acid issued from decomposition of vegetation (Zakaria et al. 2015);
153 when vegetation decomposes through biologic and microbiologic activity, organic acids such as humic acid, fulvic
154 acid, and tannic acid can be released into the surrounding environment.

155 The EC indicates mineralization degree of water. A significant variation of these parameter is observed for samples
156 under the same soil type: between 330 $\mu\text{S.cm}^{-1}$ and 1670 $\mu\text{S.cm}^{-1}$ for samples under mineral hydromorphic soil,
157 between 250 $\mu\text{S.cm}^{-1}$ and 960 $\mu\text{S.cm}^{-1}$ for samples under ferralitic soil and between 470 $\mu\text{S.cm}^{-1}$ to 1050 $\mu\text{S.cm}^{-1}$
158 for samples under lithosoil. EC values respect the standard (3000 $\mu\text{S.cm}^{-1}$) for drinking water recommended by


159 Environmental Ministry in Madagascar. Highly mineralized water contains high amount of Cl^- and SO_4^{2-} as for sam-
160 ples under hydromorphic soil ($1670 \mu\text{S}\cdot\text{cm}^{-1}$) (**Figure 4**). This could origin from anthropogenic activities such as
161 agricultural, commercial and domestic which make water unsuitable for human consumption. Atmospheric dep-
162 osition contribute also in increasing the amount of Cl^- in groundwater and a weakly acid water could increase
163 Ca^{2+} and Mg^{2+} concentrations by dissolving mainly carbonate minerals; These two processes rise groundwater EC
164 (Huang, Ma 2019).

165 Turbidity measures the clarity of water, the majority of groundwater samples are characterized by low turbidity,
166 less than 5 NTU (Nephelometric Turbidity Unit), limit value required for drinking water by Environmental Ministry
167 Malagasy (*NORME DE POTABILITE MALAGASY 2004*). Thus, turbid water was found on some wells under ferralitic
168 soil, it might be caused by silt, inorganic matter such as clay, organic matter like decaying plant material, dissolved
169 organic compounds, and microscopic organisms such as algae or bacteria.


170 Only one sample from well under hydromorphic soil contain an excess of Mg^{2+} . All the amount of the other ions
171 in each sample respect standard values of drinking water ($\text{Ca}^{2+} = 200 \text{ mg/l}$, $\text{Mg}^{2+} = 50 \text{ mg/l}$, $\text{Cl}^- = 250 \text{ mg/l}$ and
172 $\text{SO}_4^{2-} = 250 \text{ mg/l}$) (**Figure 5**). A correlation coefficient greater than 0.5 implies a significant degree of positive
173 correlation. EC presents a good correlation with Cl^- , K^+ , Mg^{2+} , Ca^{2+} , which suggests that mineralization is mainly
174 coming from these elements. A correlation coefficient of 0.5 between the prevalence of SO_4^{2-} and Ca^{2+} , of 0,53
175 between potassium (K^+) and chloride (Cl^-), of 0,63 between Ca^{2+} and Cl^- , of 0,48 between Mg^{2+} and Cl^- suggest a
176 moderate positive correlation (**Table 3**). This could indeed indicate that some of the sulphate ions in solution may
177 have originated from the dissolution of minerals such as $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ (gypsum), where Ca^{2+} and SO_4^{2-} ions are
178 released into solution during weathering processes (**Gura, Aguro 2007**); and the presence of Ca^{2+} and Cl^- ions in
179 solution could be coming from weathering of minerals containing calcium sulfate ($\text{CaSO}_4 \cdot 1/2\text{H}_2\text{O}$) and calcium
180 chloride (CaCl_2). Anthropogenic activities such as agricultural practices, industrial processes, and urbanization can
181 introduce magnesium and chloride ions into the environment. These ions can be transported through various
182 pathways, including streams, where they may infiltrate into groundwater or be carried further downstream. No
183 relationship was found between HCO_3^- and all other ions, it indicates that carbonates did not influence the pres-
184 ence of these ions in groundwater.

185


186



187



188



189

190

Figure 4: Box plot of indicators of: (a) acidity (pH), (b) conductivity (EC) and (c) turbidity (HM: Hydromorphic mineral, FS Ferralitic Soil, LS: Lithosoil)




Figure 5: Box plot for the major ions (HM: Hydromorphic mineral, FS Ferralitic Soil, LS: Lithosoil)

191
192
193
194

	<i>pH</i>	<i>CE</i>	<i>Turbidity</i>	HCO_3^-	<i>TH</i>	Ca^{2+}	Mg^{2+}	SO_4^{2-}	<i>Cl</i>	K^+
<i>pH</i>	1									
<i>CE</i>	-0.09	1.00								
<i>Turbidity</i>	0.11	-0.12	1.00							
HCO_3^-	0.52	0.27	0.48	1.00						
<i>TH</i>	0.11	0.72	-0.02	0.11	1.00					
Ca^{2+}	0.29	0.68	0.06	0.23	0.93	1.00				
Mg^{2+}	-0.12	0.65	-0.11	-0.04	0.90	0.67	1.00			
SO_4^{2-}	0.35	0.48	-0.04	0.24	0.44	0.54	0.24	1.00		
<i>Cl</i>	0.08	0.83	0.07	0.39	0.61	0.63	0.48	0.47	1.00	
K^+	0.10	0.69	-0.06	0.35	0.39	0.47	0.23	0.69	0.53	1.00

195

196


Table 3: Pearson Correlation between physico-chemical parameters

197

3.2. Spatial distribution of water quality


198

199 The WQI was used to aggregate diverse parameters and their dimension into a single spatial map (figure 7). More
 200 than 75% of groundwater samples analyzed have a WQI ranging between 9.0 and 50. These samples were pre-
 201 dominantly found under lithosoil (Figure 6). They are classified as exhibiting good to excellent quality and are
 202 suitable for drinking, irrigation and industrial uses. Less than 25% from wells under ferralitic and hydromorphic
 203 soils have WQI range between 50 and 75, they are not suitable for drinking use. They are mainly located in low
 204 altitude.



205
 206
 207

Figure 6: Box plot of WQI (HM: Hydromorphic mineral, FS Ferralitic Soil, LS: Lithosoil)



208
 209

Figure 7: Spatial distribution of the water quality

210 3.3. Hydro chemical facies

211

212 Piper diagram shows three facies hydro-chemical types (**Figure 8**) with domination of Chloride for the anions and

213 Calcium or no domination for the cations:

214 • Calcium – Chloride facies (type 1) for 44 samples of groundwater: Calcium-Chloride in groundwater oc-
215 curs rarely, in continental groundwater systems. Chloride ions in groundwater of this type may originate
216 from atmospheric deposition. These ions reach the groundwater through precipitation infiltration re-
217 charge. This ion is commonly used as tracers in water cycle and are helpful in estimating water recharge
218 processes. (Huang, Ma 2019).




219 • Calcium-Magnesium-Chloride facies (type 2) for six samples of groundwater: it is characterized by water
220 with high amount of Calcium and Magnesium ($Mg^{2+} > Ca^{2+}$). These ions originate from complex rocks rich
221 in calco-magnesian minerals such as scapolites, pyrites, and mica that are also rich in chlorides (Zakaria
222 et al. 2015).

223 • Calcium – Magnesium – Bicarbonate facies (type 5) for two samples of groundwater under ferralitic soil:
224 Infiltrating atmospheric precipitation and the dissolution of silicate minerals within the ferralitic soil con-
225 tribute to the recharge of the aquifers. This process involves water percolating through the soil and rock
226 layers, increasing dissolved ions along the way. As the groundwater interacts with the surrounding soil
227 and rock formations, ions exchange occurs. This process involves the replacement of certain ions in the
228 water with others present in the soil or rock minerals. In this case, the transition from a Ca-Mg-Cl facies
229 to a Ca-Mg- HCO_3^- facies suggests that chloride ions (Cl^-) are being replaced by bicarbonate ions (HCO_3^-)
230 through ion exchange reactions. (Nur, Ishaku, Yusuf 2012)

231 For Ca-Cl, Ca-Mg-Cl and Ca – Mg – HCO_3^- facies, major cations Ca^{2+} and Mg^{2+} into the water from various geological
232 sources, particularly carbonates and clay minerals such as kaolinite, smectites, and illites. When water interacts
233 with these minerals, either through weathering or dissolution processes, the cations present in the minerals,
234 including Ca^{2+} and Mg^{2+} , can be released into solution, affecting the composition of the water (Huang, Ma 2019).

235 Silicate minerals, which are abundant in the Earth's crust, can weather and dissolve when exposed to weak car-
236 bonic acid, a product of the dissolution of carbon dioxide (CO_2) in rainwater. This process is known as carbonation
237 or carbonic acid weathering. As silicate minerals weather, they release various ions, including silica SiO_3^{2-} calcium
238 (Ca^{2+}), magnesium (Mg^{2+}), and other elements into the water. Serpentine and wollastonite, two silicate minerals,

239 release these ions by mineral carbonation which can be describe by reactions 1 and 2. These ions can then be
 240 transported by groundwater, increasing the concentration of dissolved silica and other elements in the ground-
 241 water (Nur, Ishaku, Yusuf 2012).



247
 248 **Figure 8: Groundwater facies**

249 **Diamond:** 1: Ca-Cl type; 2 : Ca-Mg-Cl (Mixed) type; 3: Ca-K-HCO₃⁻(Mixed) type; 4 : K – HCO₃⁻ type ; 5: Ca – Mg –
 250 HCO₃⁻ type; 6: K– Cl type;

251 **Two triangles:** Cations and anions dominant: 7: Sulphate; 8 and 12: no dominant type; 9: Bicarbonate; 10: Chlo-
 252 chloride; 11: Magnesium; 13: Calcium; 14: Potassium

253 4. CONCLUSION

254
 255 This study highlights the groundwater quality within a specific watershed, focusing on various parameters includ-
 256 ing pH, electrical conductivity (EC), turbidity, major anions (SO₄²⁻, Cl⁻, HCO₃⁻), major cations (Ca²⁺, Mg²⁺, K⁺), pH,
 257 and the Water Quality Index (WQI).

258 The findings indicate that most of the groundwater from wells under lithosoil meets good quality standards suit-
259 able for drinking purposes, constituting 75% of the sampled wells. However, a portion of wells (less than 25%)
260 under ferralitic and mineral hydromorphic soils are deemed suitable only for agricultural use but not potable.
261 Additionally, wells located at lower altitudes are more susceptible to pollution, rendering them unsuitable for
262 drinking.

263 The study identifies three facies types within the watershed: Calcium-Chloride (Ca-Cl) facies, Calcium-Magne-
264 sium-Chloride (Ca-Mg-Cl) facies, and Calcium-Magnesium-Bicarbonate (Ca-Mg-HCO₃⁻) facies, with chloride and
265 calcium predominating.

266 Future research will focus on understanding the impact of climatic parameters on groundwater quality in the
267 studied area, indicating a commitment to further investigation and potential mitigation strategies to address any
268 identified issues.

Acknowledgements:

The authors are grateful to:

- SAFE – M project (Soutenir l'Apprentissage et les Formations sur l'eau à Madagascar/ Supporting WASH formations in Madagascar) for providing equipment and reagents for water analysis and wells localisation.
- The students in Master 1 (first promotion/2023) in Chemistry and Eco-Industrial Synergie and Tics (Professional training) and students in Master 2 in Environmental Chemistry (academic formation) - Processes and Industrial Ecology Department – Sciences and Technologies Domain – University of Antananarivo – Madagascar

References:

1. Ahmad A.Y., Al-Ghouti M.A., Khraisheh M., Zouari N. (2020). Hydrogeochemical characterization and quality evaluation of groundwater suitability for domestic and agricultural uses in the state of Qatar. *Groundwater for Sustainable Development*. Vol. 11, n° August, pp. 100467. DOI 10.1016/j.gsd.2020.100467. Disponible à l'adresse : <https://doi.org/10.1016/j.gsd.2020.100467>
2. Ahoussi K.E., Koffi Y.B., Kouassi A.M., Soro G., Biemi J. (2013). Étude hydrochimique et microbiologique des eaux de source de l'ouest montagneux de la Côte d'Ivoire : Cas du village de Mangouin-Yrongouin (sous-préfecture de Biankouman). *Journal of Applied Biosciences*. Vol. 63, n° 1, pp. 4703. <http://dx.doi.org/10.4314/jab.v63i1.87245>
3. Aka N., Bamba S.B., Soro G., Soro N. (2013). Étude hydrochimique et microbiologique des nappes d'altérites sous climat tropical humide : cas du département d'abengourou (sud-est de la côte d'Ivoire). *Larhyss Journal*. N° 16, 31-52.
4. Bourgeat F. (1968). Carte pédologique. *Office de Recherche Scientifique et Technique Outre-Mer (centre Antananarivo)*. 1968. 110.
5. Chen J., Yan B., Xu T., Xia F. (2023). Hydrochemical evolution characteristics and mechanism of groundwater funnel areas under artificial governance in Hengshui City, North China. *Ecological Indicators*. 148(110059), 1-18. <https://doi.org/10.1016/j.ecolind.2023.110059>

6. Chidiac S., EL- Najjar P., Ouaini N., EL-Rayess Y., EL-Azzi D. (2023). *A comprehensive review of water quality indices (WQIs): history, models, attempts and perspectives*. Springer Netherlands. ISBN 0123456789. <https://doi.org/10.1007/s11157-023-09650-7>
7. Gura H.O., Aguro M.H. (2007). Reaction Characteristics of CaSO_4 / $\text{CaSO}_4 \cdot 1/2\text{H}_2\text{O}$ Reversible Reaction. 40 (13), 1252-1256.
8. Huang T., Ma B. (2019). The origin of major ions of groundwater in a loess aquifer. *Water (Switzerland)*. 11 (12) 1-14. <http://dx.doi.org/10.3390/w11122464>
9. Miller C.T. (1987). Groundwater Quality. Madagascar. *Journal of the Water Pollution Control Federation*. 59 (6), 513-531. <http://dx.doi.org/10.2175/106143012x13407275695599>
10. MINISTÈRE DE L'AMÉNAGEMENT DU TERRITOIRE DE L'HABITAT ET DES TRAVAUX PUBLICS (MATHTP), Agence Japonaise de Coopération Internationale (JICA), 2019. Plan D ' Urbanisme Directeur De L ' Agglomeration D ' Antananarivo. p.111.
11. NORME DE POTABILITE MALAGASY (2004).
12. Nur A., Ishaku J.M., Yusuf S. N. (2012). Groundwater Flow Patterns and Hydrochemical Facies Distribution Using Geographical Information System (GIS) in Damaturu, Northeast Nigeria. *International Journal of Geosciences*. 03 (05), 1096-1106. <http://dx.doi.org/10.4236/ijg.2012.35111>
13. Ognard C., Taglioni F. (2019). *Ressource en eau et fabrique du risque sanitaire au prisme de l'analyse de la vulnérabilité dans la capitale malgache*. ISBN 9791030005783. Ressource en eau et fabrique du risque sanitaire au prisme de l'analyse de la vulnérabilité dans la capitale malgache Carole Ognard, François Taglioni To cite this version: Carole Ognard, François Taglioni. Ressource en eau et fabrique du risque sanitaire au prisme de l'analyse de la vulnérabilité dans la capitale malgache. Les Cahiers d'Outre-Mer. Revue de géo-graphie de Bordeaux, Presses universitaires de Bordeaux.
14. Ram A., Tiwari S. K., Pandey H. K., Chaurasia A. K., Singh S., Singh Y. V. (2021). Groundwater quality assessment using water quality index (WQI) under GIS framework. *Applied Water Science* [en ligne]. 2021. 11 (2), p.20. <https://doi.org/10.1007/s13201-021-01376-7>

15. Salim M., Tarawneh M., Janardhana M.R., Muzamil M. (2020). HydroResearch Hydrochemical processes and groundwater quality assessment in North eastern region of Jordan valley , Jordan. *HydroResearch* [en ligne]. 2 (2019), 129-145. <https://doi.org/10.1016/j.hydres.2020.02.001>
16. Saravanan K., Srinivasamoorthy K., Prakash R., Gopinath S., Suma C.S. (2015). An Evaluation of Hydrogeochemistry of Groundwater in Upper Vellar Sub – Basin Using Mineral Stability and Solute Transport Modelling. *Aquatic Procedia*. 4, 1119-1125. <http://dx.doi.org/10.1016/j.aqpro.2015.02.142>
17. Siriwardhana K.D., Jayaneththi D.I., Herath R.D., Makumbura R.K., Jayasinghe H., Gunathilake M.B., Azamathulla H.M., Tota-Maharaj K., Rathnayake U. (2023). A Simplified Equation for Calculating the Water Quality Index (WQI), Kalu River, Sri Lanka. *Sustainability (Switzerland)*. 15(15). <http://dx.doi.org/10.3390/su151512012>
18. THE UNITED NATIONS WORLD WATER DEVELOPMENT REPORT (2022). *380721Eng.Pdf*. Paris. ISBN 9789231005077.
19. Zakaria M.G., Taupin J. D., Ranaivoarisoa A., Robison L.R. (2015). Caractérisation géochimique et bactériologique des nappes d'une région à climat tropical sec au centre Sud de Madagascar. *Hydrological Sciences Journal*. 60 (4), 746-759. <http://dx.doi.org/10.1080/02626667.2014.932052>
20. Zheng Q., Ma T., Wang Y., Yan Y., Liu L. (2017). Hydrochemical Characteristics and Quality Assessment of Shallow Groundwater in Xincai River Basin, Northern China. *Procedia Earth and Planetary Science* [en ligne]. 17, 368-371. <http://dx.doi.org/10.1016/j.proeps.2016.12.093>