

Deciphering TrFE Fingerprints in P(VDF-TrFE) by Raman Spectroscopy: Defect Quantification and Morphotropic Phase Boundary

Pedro Resende, Jean-David Isasa, Georges Hadziioannou, Guillaume Fleury

▶ To cite this version:

Pedro Resende, Jean-David Isasa, Georges Hadziioannou, Guillaume Fleury. Deciphering TrFE Fingerprints in P(VDF-TrFE) by Raman Spectroscopy: Defect Quantification and Morphotropic Phase Boundary. Macromolecules, 2023, 56 (23), pp.9673-9684. 10.1021/acs.macromol.3c01700 . hal-04493852

HAL Id: hal-04493852 https://hal.science/hal-04493852v1

Submitted on 7 Mar 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

- 1 Deciphering TrFE Fingerprints in P(VDF-TrFE) by Raman
- 2 Spectroscopy: Defect Quantification and Morphotropic Phase
- 3 Boundary
- 4 Pedro M. Resende*, Jean-David Isasa, Georges Hadziioannou, Guillaume Fleury
- 5 Univ. Bordeaux, CNRS, Bordeaux INP, LCPO, UMR 5629, F-33600, Pessac, France
- 6 Keywords: Raman Spectroscopy, P(VDF-TrFE), Chain Conformation, Ferroelectric, Relaxor.



8 ABSTRACT:

9 The electroactive behavior of PVDF-based polymers is tightly related to the macromolecular 10 sequence, chain conformation, and crystallinity. Although β -PVDF is the most attractive phase for applications in organic electronics, PVDF tends to crystallize into other thermodynamically 11 more stable phases. Copolymerization of VDF and TrFE addressed this issue, and has resulted 12 in high ferroelectric content co-polymers. Later on, the insertion of CFE/CTFE units into the 13 P(VDF-TrFE) architecture yielded ter-polymers with relaxor-ferroelectric properties, 14 especially attractive in energy storage and electrocaloric applications. The investigation of the 15 corresponding electroactive phases in these polymers relied mainly on FT-IR and X-ray 16 diffraction techniques, demanding an extensive combination of material characterization and 17 analysis to detect the majority phases and predict material behavior. In this work, we 18 demonstrate a facile and non-invasive approach to assess the relative ratio of defects in TrFE-19

segments through a detailed analysis of the polymer Raman spectra. By varying the content of
TrFE in P(VDF-TrFE) samples, a detailed assignation of the TrFE unit modes (1347 and 1366
cm⁻¹) contribution to the polymer Raman spectra was established which was further validated
by FT-IR, X-ray diffraction, calorimetry, and dielectric spectroscopy measurements. Based on
our findings, we further propose a defect quantification ratio that can be used to predict chain
conformation and electroactive behavior.

26

27 INTRODUCTION

Poly(vinylidene fluoride)-based (PVDF) polymers have attractive ferrotronic properties, 28 resulting in numerous applications in organic electronics: sensors and transducers (from piezo-29 30 and pyroelectricity); FETs for non-volatile memories (from ferroelectricity); energy harvesting from motion and temperature (piezo- and pyroelectricity, and electrocalorics); capacitors for 31 energy storage (from relaxor-ferroelectric); and cooling applications (from electrocalorics).¹⁻¹¹ 32 The ferrotronic properties (ferro-, piezo-, pyro-electric and electrocaloric) of these materials 33 are tightly related to their chain structure, and there are numerous reports investigating how 34 these properties evolve as a function of processing and material composition. 35

PVDF is a polymorph that can crystallize into three main distinct phases: α (*tgtg*'), β (all-*trans*), 36 and γ (*tttgtttg'*) phases. The α phase is paraelectric (PE) due to the anti-parallel orientation of 37 adjacent chains (symmetric with respect to the *b* axis), having a net zero dipolar moment. In 38 the β phase, adjacent chains are aligned parallel to each other, creating a non-zero dipolar 39 moment along the *b* axis, at the origin of the ferroelectric (FE) behavior. The all-*trans* chain 40 conformation maximizes the dipolar moment, as all the dipolar moments are aligned in the 41 same direction. Finally, in the γ phase the polymer presents a non-zero dipolar moment, but 42 43 much weaker than in the previous case. Additional phases are mentioned in the literature, which 44 correspond to variants of the α and γ phases. These phases present the same crystalline structures, but differ in the parallel or anti-parallel orientation of adjacent chains. PVDF 45 predominantly crystallizes into the non-polar α phase requiring additional processing to obtain 46 47 β phase. Different approaches have been demonstrated to successfully produce high β phase content, such as thermal annealing, material poling, film stretching, blending, or co-48 polymerization.¹²⁻¹⁶ The last led to the development of co-polymers based on VDF and 49 trifluoroethylene (TrFE) units, that readily crystallize into the β phase. Further research resulted 50 in the observation of relaxor-ferroelectric (RFE) properties in electron-irradiated P(VDF-51 52 TrFE), explained by the local disruption of FE domains that softened FE hysteresis and lowered the remnant field.^{17, 18} This is especially attractive for energy storage applications, providing a 53 54 narrow material hysteresis with lower dielectric losses. RFE behavior was then obtained with P(VDF-TrFE) based ter-polymers by the addition of chlorofuoroethylene (CFE) or 55 chlorotrifluoroethylene (CTFE) units.^{12, 19-22} The presence of CFE or CTFE units disrupted the 56 long all-trans chain segments due to the high steric hindrance of the Cl atoms yielding a RFE 57 58 material. The FE nano-domain model was used to explain the observed RFE behavior in these materials, proposing that the introduction of bulky units, such as CFE and CTFE, greatly 59 disrupted local material ordering (as in electron-irradiated P(VDF-TrFE)), producing small FE 60 domains that softened material hysteresis. However, this interpretation was unable to fully 61 explain the appearance of RFE behavior in P(VDF-TrFE) co-polymers with high TrFE content. 62 63 Liu and co-workers investigated this system and reported on the presence of a morphotropic phase boundary (MPB) around 50% TrFE molar content, where a competition between the all-64 trans and a 3/1 helix conformation takes place.²³⁻²⁵ Their results showed chain tacticity played 65 a very important role on the polymer FE behavior, and that chain chirality was responsible for 66 the formation of "disordered" helix conformations that lead to RFE behavior. 67

68 Accordingly, the study of the polymer structure and chain conformation for these systems is of prime importance in order to decipher their functional behaviors. It has been performed mainly 69 by FT-IR and Raman spectroscopies, and X-ray diffraction techniques. FT-IR studies analyzed 70 71 the vibration spectra for a variety of PVDF-based polymers, attempting to decipher the origin of the different modes both experimentally and through simulation. It was in these works, prior 72 to the 1980s, that researchers managed to detect and differentiate the three commonly observed 73 phases (α , β , and γ). This was especially difficult given the large number of predicted modes 74 for the γ phase, in many cases overlapping with α and β modes. Raman spectroscopy analysis 75 76 of these polymers became more frequent between the 1980s and the 2000s, offering an easy, non-invasive, and non-destructive approach to study polymer structure and chain conformation 77 78 under different conditions (such as temperature, stress, or material polarization). Several works 79 investigated structural changes in PVDF and P(VDF-TrFE) with respect to monomer content and temperature. These studies gave important insight into the evolution of the spectra with 80 increasing TrFE content, showing increases in β phase content with increases in TrFE 81 proportion as well as the appearance of TrFE-unit specific modes.^{15, 26-36} Nevertheless, the 82 determination of the polymorphism in PVDF-based polymers has mainly relied on FT-IR 83 spectroscopy combined with X-ray diffraction in the past 20 years. This is particularly true for 84 reports on the FE and RFE properties of PVDF-based ter-polymers. In these systems, it was 85 demonstrated that the introduction of bulky TrFE, CTFE, or CFE units gradually increased the 86 87 crystalline lamellae interplanar distance, along with the gradual appearance of tg defects to the detriment of the all-trans conformation. Despite this, the determination of the FE behavior of 88 these materials has relied on an extensive collection of characterization techniques (FT-IR, X-89 ray diffraction, calorimetry, dielectric spectroscopy, or ferroelectric hysteresis), many of which 90 requiring specific sample preparation that may impact material performance in comparison to 91 92 real case uses.

93 Raman spectroscopy offers a facile and non-invasive approach to probe local polymer chain 94 conformation and chain orientation under a wide range of parameters (temperature, excitation wavelength, or wavenumber range), requiring little to no sample preparation. These aspects 95 96 make it extremely attractive as a quick and easy-to-implement technique to determine polymer functional behavior, with the possibility to integrate into production line quality control at large 97 scale device fabrication.³⁷ In this work, we utilize Raman spectroscopy to study the evolution 98 in chain conformation of solution-cast P(VDF-TrFE) co-polymers as a function of the TrFE 99 100 molar content. Raman spectral data are then put into perspective with those from other 101 characterization techniques, including FT-IR spectroscopy, X-ray diffraction (WAXS), calorimetry (DSC), and dielectric spectroscopy (DE), providing a full picture of the underlying 102 103 chain transformations and consolidating our results. Based on this analysis, we propose a band 104 assignment for the TrFE contributions to the Raman spectra, as well as a defect quantification and chain conformation prediction based on the proposed assignment. These results intend to 105 show the versatility of Raman spectroscopy in the analysis of these ferrotronic materials, 106 107 potentially predicting their behavior from a straightforward spectral fit and analysis, and expanding this analysis to other PVDF-based co- and ter-polymers. 108

109

110 MATERIALS AND METHODS

Materials. The P(VDF-TrFE) co-polymers used in this study were kindly supplied by
Piezotech. According to the manufacturer, the four different co-polymers have a TrFE molar
content of 20 %, 25 %, 30 %, and 50 %. Additional information is provided in the Supporting
Information (SI). Triethyl phosphate (TEP) was purchased from Sigma-Aldrich.

Polymer Thin Films. Polymer films were made by drop-casting from 15 wt.% solutions in
TEP. The solutions were poured onto previously cleaned glass substrates followed by a drying

process of 2 hours 20 min, on a hot plate at 90 °C and atmospheric pressure. Before casting, the solutions were stirred for at least 48h at room temperature. The produced films were detached from the glass substrates through immersion in deionized water, wetting the glass and separating the thin films without deformation or stretching.

Raman Spectroscopy. Raman spectra were recorded with an XploRa spectrometer (Horiba 121 Instruments) coupled with an Olympus microscope, with a linearly polarized laser (Nd:YAG, 122 $\lambda = 532$ nm), at a magnification of 50 × (sampling diameter of 10 to 15 µm). No modifications 123 from the laser intensity were observed. The spectra were recorded at ambient conditions after 124 instrument calibration with a Si sample. The spectra were obtained for ranges between 200 and 125 1600 cm⁻¹. Data treatment included spectral peak detection from 2nd derivative, with derivative 126 2nd order Savitsky-Golay smoothing; spectral resizing for multiple sample comparison through 127 standard normal variate analysis; and background removal through fitting of 2nd or 4th order 128 polynomials. Peak fitting was performed with Origin and Fityk software using Gaussian and 129 Voigt profiles. 130

FT-IR Spectroscopy. Spectra were recorded with a Nicolet iS5, with an ATR module iD7 (diamond-crystal window, diameter of 1.8 mm), between 4000 to 400 cm⁻¹. Software in-built ATR spectral correction was used. No sample modifications were observed from the pressure exerted by the sample holder screw. Data analysis was focused on the 1600 to 400 cm⁻¹ range, following the same peak detection procedure used in the Raman spectra analysis.

136 **X-ray Diffraction.** The crystalline structure was analyzed with a wide-angle X-ray scattering 137 (WAXS) system, Xeuss 2.0 from XENOCS, under vacuum and ambient temperature, with a 138 sample-to-detector distance of 151 mm, and $\lambda = 1.54$ Å (Cu K α). The diffraction pattern was 139 collecting with a DECTRIS PILATUS-300k detector, for a *q* range of 0.1 to 3.1 Å⁻¹ (1.4° to 46°), followed by azimuthal integration. Data analysis was made with Fityk (software), using
Voigt profiles. Additional information on peak fitting is provided in SI.

142 **Calorimetry.** Calorimetric analysis was performed with a Differential Scanning Calorimetry 143 (DSC) system (Mettler Toledo DSC 1, with intra-cooler, and N_2 flux). The thermograms were 144 recorded for a maximum temperature range of -50 to 200 °C, at a heating rate of 10 °C min⁻¹. 145 A total of three curves were recorded, corresponding to the first heating, first cooling, and 146 second heating. Only the first heating curves were considered in this analysis, and related to 147 results obtained from the remaining characterization. The melting and Curie transition 148 temperatures were estimated from the minima of the recorded endotherms.

Dielectric Spectroscopy. Broadband dielectric spectroscopy of metal-polymer-metal devices was performed with a Solartron 1260 A impedance analyzer equipped with a Linkam LTS 350 temperature-control system. The measurements were performed with an AC signal of 1 V, at a frequency of 10 Hz, for a maximum temperature range between -60 to 50 °C. The glass transition temperature of the samples was estimated from the loss maximum for the measurements performed at 10 Hz. The device preparation procedure for the dielectric spectroscopy measurements is available in SI.

156

157 RESULTS AND DISCUSSION

Films were prepared through solution casting from four different P(VDF-TrFE) with TrFE molar content ranging from 20 to 50 %. All films were dried for 2 h and 20 min at 90 °C under atmospheric pressure. All the used co-polymers present similar molecular weights around 2×10^5 kg mol⁻¹ (as determined by SEC – see SI), which we expect to have a negligible influence on property variability between co-polymers when compared to changes induced by TrFE molar content. To decipher the evolution of the chain conformation and crystalline structure as 164 a function of the TrFE content, Raman and FT-IR spectroscopies were combined with X-ray scattering, calorimetry, and dielectric spectroscopy. This analysis intends primarily to extract 165 valuable information from the Raman spectra, by providing detailed vibration band labelling 166 167 and relating the changes observed to the structure with respect to the TrFE content. In the literature, the chain conformation analysis has been predominantly made with FT-IR 168 spectroscopy, with only a handful of works providing in-depth discussions of Raman spectra.^{15,} 169 ^{26-36, 38-53} Several of these works have performed crystalline band labelling based on theoretical 170 spectral simulations. Simulations of Raman and FT-IR spectra identify the lattice modes of an 171 172 ideal crystal, calculating the contribution of an infinite crystal lattice. This scenario disregards tg-defect formation or the presence of head-to-head chain defects. For this reason, these spectra 173 174 have shown significant shifts from experimental values (that have been independently 175 reproduced in different works), but have nonetheless aided in the assignment of the experimentally detected bands. In the particular case of P(VDF-TrFE) co-polymers, the nature 176 of the detectable TrFE bands is seldom debated, disregarding potential valuable information 177 178 on the characterization of the material. Indeed, these changes could then be further related with the polymer structural data, drawing relationships between these different techniques. 179



180

Figure 1. Raman spectra with band assignment, height, and Raman shift (position). a) Raman 181 spectra with band assignment for the different TrFE molar content from 200 to 1500 cm⁻¹. The 182 dashed arrows indicate the direction of increase in band intensity. The bands marked b1 to b4 183 correspond to bands with no clear assignment. b) Band modes for the range of 750 to 925 cm⁻ 184 ¹, highlighting the multiple mode contributions to the observed 800, 845, and 880 cm⁻¹ bands. 185 c) Raman band height with band assignment for a selection of bands: 800, 845, 880, 1348, and 186 1430 cm⁻¹. d) Raman band positions as a function of the TrFE content for the same bands as 187 shown in c). 188

190 Raman Spectroscopy. The Raman spectra of the different P(VDF-TrFE) films were recorded 191 in the range 200 to 1600 cm⁻¹. This covers most of the modes for PVDF-based polymers. Figure 192 1 shows the obtained spectra, with the respective band assignment (with type, molecular group, 193 and phases), and extracted band height and position for a selection of crystalline bands. 194 Crystalline band assignment followed several seminal works on Raman and FT-IR

spectroscopy of PVDF homopolymer and P(VDF-TrFE) co-polymers.^{36, 38-53} In the literature, 195 bands are typically assigned to specific phases (such as α , β , and γ phases of PVDF), which 196 can lead to misinterpretations. Analysis should focus on the chain conformations associated to 197 198 the observed modes, in this case, the all-*trans, tttg*, and *tg* conformations that are found in the different phases of PVDF-based polymers. Indeed, some bands arising from vibrational modes 199 200 of *tt*-segments will present overlapping contributions from two distinct phases (in this case, β and γ) and a clear phase attribution cannot be performed. This was addressed by Cai *et al.* as 201 they discussed band assignment and phase determination from FT-IR analysis of PVDF 202 homopolymer through a simple diagram relying on the detection of phase-specific modes.⁴³ A 203 conformation-oriented analysis can provide important information on chain structure with 204 205 different parameters.

The Raman spectra shown in Figure 1a can be divided into five regions: 1) 200 and 750 cm⁻¹. 206 2) 750 and 900 cm⁻¹, 3) 900 up to 1300 cm⁻¹, 4) 1320 and 1380 cm⁻¹, and 5) above 1380 cm⁻¹. 207 The range between 200 and 750 cm⁻¹ (zone 1) covers several torsion (τ), wagging (w), and 208 rocking (ρ) CF₂ modes, with several CF₂ bending (δ) modes after 500 cm⁻¹. The modes at 268, 209 478, and 512 cm⁻¹ have been associated to all-*trans* segments and constitute a good evidence 210 for the presence of "all-trans-phase" in these PVDF-based co-polymers. The band at 512 cm⁻¹ 211 often contains an additional contribution at 514 cm⁻¹ associated to *tt*-segments in γ -PVDF, and 212 has been observed in several previous works.^{41-43, 46} A general increase in all-trans specific 213 214 modes can be seen with increasing TrFE molar content. However, several *tg*-associated modes are still present for all spectra, suggesting the presence of tg defects for all TrFE contents. A 215 *tttg* (γ) mode at 310 cm⁻¹ is observed to increase with TrFE, though no other phase-specific 216 217 modes are detected in this range. Additional bands are also present, especially for 50% TrFE, labelled as b1, b2, and b3, which do not correspond to any reported band in PVDF-based 218

219 materials. We can speculate that these bands may be associated to tg-containing segments, such 220 as *tttg* or t>3g, as their intensity increases with TrFE content.

The zone 2 between 750 and 900 cm⁻¹ is associated to CH₂ τ and ρ modes (VDF modes), CF₂ 221 stretching (v) modes, and some CC v modes (associated to VDF). These bands are typically 222 used in the analysis of PVDF phases in Raman and FT-IR studies. A close-up of this region is 223 shown in Figure 1b. The overlapping modes give rise to three main peaks around 800, 845, and 224 880 cm⁻¹. The peak around 800 cm⁻¹ has contributions from the α and γ , corresponding to tg 225 and *tttg*-segments respectively; the 845 cm⁻¹ peak contains largely contributions from all-*trans* 226 227 segments under the form of a $CF_2 v$ mode, but several early works point to the presence of additional *tttg*-segment modes, around 833 to 843 cm⁻¹ (839 cm⁻¹ in FT-IR). More recent 228 simulation works showed these *tttg*-modes are expected to have much lower intensity than the 229 all-*trans* specific mode at around 845 cm⁻¹, even for a pure γ sample (for which the band at 811 230 cm⁻¹ appears prominently in the spectra).⁴⁴ Lastly, the 880 peak presents multiple VDF-specific 231 contributions from different modes related to different chain segments (at 874, 876, and 884 232 cm⁻¹). This band is observed to decrease with TrFE content. The most intense peak occurs at 233 around 845 cm⁻¹ (v CF₂) and is associated to β -phase crystallites. As TrFE content increases, 234 the 800 band shifts towards 811 cm⁻¹, which corresponds to a *tttg*-specific mode (ρ CH₂). The 235 main 845 band increases its intensity while also shifting towards higher wavenumbers (increase 236 237 in all-trans segments).

The zone 3 spans from around 900 up to 1300 cm⁻¹, comprising several CC and CF₂ v modes. This region presents high intensity bands in FT-IR spectroscopy, used to estimate chain defects and phase in several PVDF-based co- and ter-polymers. Despite the weaker response in Raman spectroscopy, a few overlapping bands can still be identified around 1060 to 1070 cm⁻¹ (from *tg* and *tt* segments); and around 1280 to 1290 cm⁻¹ (all-*trans* and *tg* segments, respectively). The band at 1280 cm⁻¹ is a good indication of the presence of β-phase crystallites (*t* > 4) in 244 PVDF-based materials, often mentioned in FT-IR analysis. Immediately after, zone 4 (1320 to 1380 cm⁻¹) contains modes associated to the TrFE units (around 1347 and 1366 cm⁻¹). This 245 assignment has not always been reported in the literature, with works disregarding these bands, 246 247 performing wrong mode attribution, or acknowledging its relationship with TrFE without further exploration.^{15, 26-36} The neglect is in part due to the low intensity of these bands for low 248 TrFE contents. So far there has not been an exploration of the type of vibration, the associate 249 chain segments, or their relationship with the material behavior or crystallinity, despite reports 250 during the 1980s and 1990s on the synthesis of P(VDF-TrFE) and polytrifluoroethylene 251 (PTrFE) and their IR and Raman spectra.^{15, 26-32} An increase in mode intensity is clearly 252 observed with TrFE molar content. Finally, zone 5 comprises the modes above 1380 cm⁻¹, 253 which include several VDF specific CH₂ δ modes. In particular, around 1430 cm⁻¹, three modes 254 can be found at approximately 1427 (not shown), 1430, and 1434 cm⁻¹, corresponding to *tttg*, 255 tgtg, and all-trans segments. For the considered experimental conditions and TrFE molar 256 compositions, a decrease in these bands is observed with TrFE content. 257

The variation in band intensity and band position is plotted in Figure 1c-d, for the bands located 258 at ca. 800, 845, 880, 1348, and 1430 cm⁻¹, corresponding to: the 796 + 811 cm⁻¹ group (tg τ 259 and *tttg* ρ , CH₂); the 843 + 845 cm⁻¹ group (*tttg* + all-*trans*, CF₂ v); the CC v modes (VDF, all 260 conformations); one of the observed TrFE unit modes; and the 1430 + 1434 cm⁻¹ group (tg and 261 all-*trans*, $CH_2 \delta$), respectively. Several observations can be made from such a representation. 262 Firstly, the 845 cm⁻¹ band is most intense for a TrFE content of 20 %, after which it gradually 263 weakens, consistent with previous reports on the favorable formation of β-phase crystalline 264 domains in P(VDF-TrFE).^{54, 55} Secondly, the 800 cm⁻¹ band increases (especially for 50 % 265 266 TrFE), pointing to an increase in tg or tttg conformations in VDF-segments and agreeing with other low intensity tg and tttg modes (tttg specific mode at 310 cm⁻¹) observed in the spectra. 267 Lastly, the VDF-specific 880 cm⁻¹ band shows a decrease with TrFE, in accordance with the 268

gradual replacement of the VDF units by TrFE. It is interesting to note that the TrFE band at
1348 cm⁻¹ increases in intensity, but not linearly. The opposite is observed with the VDF band
at 1430 cm⁻¹, which decreases with the TrFE content.

272 The shifts in band position, shown in Figure 1d, also proved instructive. These shifts are most significant in the case of the 800 cm⁻¹ band, which rises from 808 to 813 cm⁻¹ (consistent with 273 an increase in *tttg* segments); and the 845 cm⁻¹ band, which initially lies at 843 cm⁻¹ and shifts 274 to around 852 cm⁻¹. The observed band position shifts (towards higher energy) can be 275 associated to stress, changing the molecular environment. This behavior will be further 276 discussed in the next sections (*vide infra*). Finally, the 1430 cm⁻¹ band initially appears around 277 1434 cm⁻¹, shifting towards 1431 cm⁻¹. As no α -specific modes are clearly observed for a TrFE 278 content of 50%, we can assert that this shift towards 1430 cm⁻¹ is due to the observed decrease 279 280 in band intensity combined to the slow increase in *tttg* modes (in this case, a small overshadowed contribution from the band at 1427 cm⁻¹ that shifts the convoluted peak towards 281 low wavenumbers). 282

In summary, the prepared samples are primarily composed of long all-*trans* segments, and should be expected to present high β -phase content (thus a more ferroelectric behavior). Nevertheless, the gradual appearance of defects with TrFE content is clear (especially *tttg*segments) marked by band position shifts, the persistence of low intensity bands from *tg*segments (but the absence of α -specific modes), and the appearance of the 310 cm⁻¹ band (*tttg*specific).



Figure 2. FT-IR spectra, and band height and shift as a function of TrFE content. a) FT-IR spectra for samples with different TrFE molar content, with respective band labeling and phase assignment. Multiple phases can be associated to the same band. b) Band height for a selection of β -specific (840, 1170, and 1280 cm⁻¹), γ (1116 cm⁻¹), and VDF modes (880 and 1400 cm⁻¹) with TrFE content. c) Band shifts for the same bands shown in b).

289

FT-IR Spectroscopy. Complementary FT-IR characterization was performed in order to relate 296 the experimental observations between the two techniques. The FT-IR spectra are plotted in 297 Figure 2a, with the assignation of several bands to their associated phases and type of vibration. 298 Several β-specific modes are present for all compositions (470, 506, 840, 1172, 1280, and 1430 299 cm⁻¹). The range 900-1300 cm⁻¹ (zone 3 in Raman) is particularly more active in FT-IR and 300 provides additional information. A gradual increase in a γ -related mode is observed around 301 1116 cm⁻¹ (arising from *tttg*-segments), as well as other shared modes from *tt* and *tg* segments. 302 An additional band can also be seen around 1097 cm⁻¹ (marked with "?"), the origin of which 303 is unclear, as previous works have not reported the presence of any band at this location. 304 305 Considering its location, it is likely that this mode arises from *tttg* or *tg* segments, as a gradual increase in these modes is observed with increasing TrFE content. The same band was also 306

307 detected in the Raman spectra, labelled as b4 (see Figure 1a), albeit with a much lower intensity. The 1343 cm⁻¹ TrFE band is also visible, although it increases only slightly with the 308 TrFE molar content. The 1364 cm⁻¹ TrFE band is overshadowed by the 1400 cm⁻¹ band, which 309 is more active in FT-IR. This shows that Raman spectroscopy is a more suitable technique to 310 analyze changes in this spectral region linked to the TrFE bands. Peak height and position are 311 plotted in Figure 2b and 2c. The same tendencies as those retrieved in Raman spectroscopy are 312 also observed, with maxima in β -specific modes (840, 1170, and 1280 cm⁻¹) occurring for TrFE 313 contents of 20 %. The VDF-specific 880, 1400, and 1430 cm⁻¹ (the latter less active in FT-IR) 314 decrease with TrFE, in line with the Raman spectra. Several band shifts are detected, with β-315 specific modes shifting towards high wavenumbers. The 1400 cm⁻¹ band presents a shift 316 towards low energy (as the 1430 cm⁻¹ bands in Raman). The presence of these two bands in 317 Raman and FT-IR (with different activity) and arising from different conformations of the VDF 318 units demonstrate that despite the high content of β -phase, there are still several VDF chain 319 segments presenting *tttg* and *tg* conformations in-between long all-*trans* segments. These *tg*-320 321 defects may arise from within the crystalline domains but also from the crystalline-toamorphous boundaries where a certain degree of long range ordering may still exist (oriented 322 amorphous fractions).^{56, 57} The FT-IR spectra agrees very well with the tendencies observed 323 from the Raman spectra. In particular, FT-IR analysis confirmed the increase of defective 324 conformations with TrFE molar content (such as *tttg* and *tg* segments), such as the case of the 325 bands at 1072 and 1116 cm⁻¹. 326



327

Figure 3. X-ray diffraction patterns, calorimetry, and dielectric spectroscopy. a) Diffraction 328 patterns for the considered samples, with peak labelling. b) Peak position, in q, extracted from 329 the pattern fitting functions in a). c) Crystallinity and main peak ratio calculated from the 330 331 crystalline peak area. d) DSC thermograms, showing the shift in melting temperature (blue arrow) and Curie transition temperature (red arrow). The areas of the endotherms are also 332 shown. e) Permittivity loss factor, tan δ , at 10 Hz, as a function of temperature, showing a shift 333 of the glass transition temperature (dashed black arrow) towards higher temperatures. f) Plot 334 of the transition temperatures $(T_{glass}^{10 Hz}, T_{Curie}, \text{ and } T_{melt})$ estimated from the DSC and DE data 335 shown in d) and e), respectively. g) Plot of the fusion enthalpy (solid-liquid, ΔH_f), Curie 336 transition enthalpy (solid-solid, ΔH_c), and their sum, obtained from endotherm integration from 337 d). The values for 20% TrFE were extrapolated from an endotherm deconvolution (see SI, 338 Figure 2S). 339

341 **X-ray Structural Analysis.** The structure of the P(VDF-TrFE) films was assessed with wide-342 angle X-ray scattering (WAXS). The azimuthally integrated diffraction patterns and the 343 respective fittings (see SI for additional information) are shown in Figure 3a. Several 344 diffraction peaks were identified for all compositions: the ferroelectric (FE) β phase with 345 pseudo-hexagonal/orthorhombic unit cell (20 to 30 % TrFE); the defective ferroelectric (DFE) phase (all co-polymers); and the relaxor-ferroelectric (RFE) phase for 50 % TrFE. For the 20 346 to 30 % TrFE, the main detected phase corresponded to the FE β phase, with the most intense 347 reflection associated to the (200)/(110) peak around 1.42 Å⁻¹. It was already reported that DFE 348 phases can arise in PVDF co- and ter-polymers with TrFE and low amounts of CFE or CTFE 349 due to the increase in the interplanar distance and the incorporation of tg defects along the 350 polymer chain, disrupting long-range ferroelectric ordering.^{58, 59} The increase in chain defect 351 occurrence (from the increase of TrFE, CFE, or CTFE) has been linked to the eventual 352 transformation of this DFE phase into a relaxor-ferroelectric (RFE) phase.⁵⁸ This is the case 353 for the sample with 50 % TrFE content, which presents two diffraction peaks associated to a 354 RFE and a DFE phase (at 1.32 and 1.36 Å⁻¹, respectively), with the disappearance of the FE β 355 356 phase. The presence of a RFE phase for 50% TrFE is consistent with previous reports on the presence of a morphotropic phase boundary around this TrFE proportion, leading to a 357 competition between FE/DFE and RFE phases, after which the RFE becomes the dominant 358 phase.^{23-25,60} In addition, no crystalline bands were detected in Raman or FT-IR that correspond 359 to a PE phase (α -specific, *tgtg*'), which further corroborates that the detected diffraction peaks 360 correspond to a RFE and DFE phases. The extracted peak positions (in q) from the fitted data 361 are plotted in Figure 3b for the FE, DFE, and RFE. The positions decrease in q (i.e., an increase 362 in the interplanar distance) due to the incorporation of TrFE units inside the crystalline 363 lamellae. The potential incorporation of tg defects inside the crystalline lamellae is also 364 expected to play an important role in the increase of the interplanar distance for high TrFE 365 contents, as backed up by the Raman and FT-IR spectra. The absence of crystalline diffraction 366 peaks at high q (above 2.4 Å⁻¹) for a 50 % TrFE content suggests a significant disruption in 367 long range chain ordering. The diffraction planes associated to these reflections [(001) and 368 (201)] contain a *c*-axis component (chain axis), and their absence may point to a disruption on 369

chain ordering from the appearance of *tg* segments. This observation is consistent with recent
 interpretations on the origin of relaxor behavior in the PVDF family of co- and ter-polymers.²³⁻
 ²⁵ These works highlight the formation of a disordered 3/1 helix structure due to the chirality
 of the TrFE (or CTFE) monomer, disrupting structural and ferroelectric long-range ordering.

The crystallinity (χ_c) was estimated from the diffraction patterns (ratio of crystalline peak area 374 to total pattern area). The values are plotted in Figure 3c, with χ_c increasing up to 38 % for a 375 30 % TrFE content, decreasing to around 30 % for 50 % TrFE. A recent work by María et al. 376 reported on the crystallization kinetics of molten bulk P(VDF-TrFE) co-polymers, showing 377 that the inclusion of TrFE inside the PVDF-crystals increased nucleation rate and density.⁶¹ 378 This work deals with solution cast and dried thin films, in which solvent-polymer interaction 379 is expected to have an important contribution. In the considered conditions, high TrFE content 380 381 appears to promote higher crystallinity. The observed decrease for a TrFE content of 50 % could be explained by the absence of high q diffraction peaks, reducing χ_c . This may not entail 382 a decrease in sample crystallinity, but rather a disruption in chain long-range ordering 383 (particularly along the *c*-axis). In fact, if we calculate the main peak ratio considering only the 384 contributions between 1.0 to 1.6 $Å^{-1}$ (also shown in Figure 3c), we observe that it increases 385 386 constantly with the TrFE content due to the decrease of the amorphous halo around 1.2 to 1.3 Å⁻¹. 387

388

Calorimetry and Dielectric Spectroscopy. Calorimetry is often used to estimate χ_c in these polymer systems. However, the variation of the enthalpy of fusion (ΔH_f^0) with TrFE in P(VDF-TrFE) is not established, with several works utilizing reported values with variations of 5 to 10 % from the experimentally used proportions. ΔH_f^0 of 93 and 67 J g⁻¹ have been reported for PVDF and PTrFE homopolymers, respectively, with more recent works reporting values around 40 J g⁻¹ for P(VDF-TrFE) with 20 % TrFE.⁶²⁻⁶⁵ These values show ΔH_f^0 in P(VDF-TrFE) co-polymer systems has a non-linear response, and an extrapolation is not sufficient to properly estimate χ_c for a large array of molar fractions.

397 Nonetheless, calorimetry provides important information on transition temperatures. DSC was performed and the resulting endotherms plotted in Figure 3d, for the first heating scan. The 398 melting (solid-liquid transition, T_{melt}) and Curie (solid-solid transition, T_{Curie}) transition 399 temperatures present opposite tendencies, with the T_{melt} increasing with the TrFE content (blue 400 arrow), while T_{Curie} decreases (red arrow). At 20 % TrFE, T_{Curie} approaches T_{melt} resulting in 401 two overlapping endotherms. The T_{Curie} shift towards low temperature is in line with the 402 observed phases from the X-ray diffraction data, with the increase in TrFE resulting in a loss 403 404 of dipolar long-range coherence (especially for high TrFE contents). The permittivity loss 405 factor (shown in Figure 3e), tan δ , as a function of temperature (at 10 Hz) was recorded with 406 dielectric spectroscopy (DE) allowing the estimation of the glass transition temperatures $(T_{glass}^{10\,Hz})$. The maxima around -40 °C correspond to $T_{glass}^{10\,Hz}$, shifting to higher temperatures with 407 TrFE content. The estimated transition temperatures from DSC and DE $(T_{glass}^{10 Hz}, T_{Curie} \text{ and } T_{melt})$ 408 are plotted in Figure 3f, showing approximately linear tendencies with TrFE, for the considered 409 proportions. The increase in T_{melt} with TrFE content is consistent with previous early works on 410 P(VDF-TrFE) co-polymers that analyzed transition temperatures in this system. The T_{Curie} 411 412 decrease is also in agreement with the literature, stabilizing at lower temperatures for high TrFE content. This decrease signifies a shift towards a RFE phase.^{63, 66} 413

The enthalpies of fusion and Curie transition (ΔH_f and ΔH_c , respectively) are plotted in Figure 3g, along with their sum. The values for 20 % TrFE were extrapolated from the deconvolution of the endotherm by fitting with two Pearson IV functions (see SI, Figure S2). The highest values of ΔH_c are obtained for 25 % TrFE. This would suggest the largest amount of

electroactive phases is found for 25 % TrFE despite the fact that this TrFE proportion presents 418 a lower T_{Curie} , a similar χ_c , and less intense all-*trans* modes maxima (Raman and FT-IR) when 419 compared to 20 % TrFE. Another possibility to explain this discrepancy may be related to the 420 421 solid-solid phase transition enthalpy, which for 25 % TrFE may be higher than for 20 %. As far as the authors know, no systematic study has been performed on potential variations on 422 solid-solid phase transition enthalpy on these co-polymer systems. ΔH_f follows a distinct trend, 423 presenting the lowest values for 20 % TrFE (12.8 J g⁻¹, extracted from fitting), followed by 424 50 % TrFE (at 13.09 J g⁻¹), and retaining values around 15 J g⁻¹ for the remaining TrFE 425 proportions. 426

427

Deciphering the Effects of TrFE on Raman Spectra. Following the additional analysis with 428 WAXS, DSC, and DE, we can now address the band broadening and shifting observed in the 429 Raman (and FT-IR) spectra. Signal broadening is associated to loss in vibration coherence, 430 while band shifts are associated to vibration energy shifts induced by changes in molecular 431 interactions or bond compressive/tensile stresses. In the spectra in Figure 1a-b, we can see a 432 gradual broadening of the 845 cm⁻¹ band, corresponding to an all-*trans* CF₂ v mode. We can 433 quantify the degree of broadening by performing a non-linear multi-peak fitting (see SI for 434 details) for the bands located in this range (*ca*. 750 to 920 cm⁻¹) and extracting the height and 435 breadth of the 845 cm⁻¹ band. As material crystallinity and the relative amount of all-trans 436 segments directly impact the intensity of this band, we can attempt to remove these 437 contributions by calculating the ratio between peak FWHM and height. This ratio is plotted in 438 Figure 4a, where it shows a minimum for 20 % TrFE, after which it increases steadily. The 439 curve suggests that this vibration mode presents high coherence for 20 % TrFE (*i.e.*, the highest 440 all-*trans* content). The vibration coherence then decreases as the TrFE molar content increases. 441 442 The all-trans CF₂ v mode is of particular importance given the direction of the vibration with

respect to the chain backbone, *i.e.*, having a perpendicular projection to the chain, as illustrated 443 in Figure 4a. This component is also parallel to the monomer dipolar moment (μ , which is 444 perpendicular to the polymer backbone, or *c*-axis), and may serve as an indicator for dipolar 445 446 long-range ordering. This is consistent with the variation of the T_{Curie} extracted from the DSC data (Figure 3d and 3f). The highest T_{Curie} was obtained for 20 % TrFE, entailing long-range 447 dipolar ordering, after which it decreases due to a decrease in dipolar ordering from the increase 448 in inter-chain spacing (as attested by the X-ray data). It is also important to mention that phonon 449 confinement effects can also play an important role on the observed band broadening.⁶⁷ This 450 451 confinement effect originates from the gradual formation of tg-defects along all-trans segments, producing an asymmetrical band broadening. However, the complex band 452 contribution in this region hinders the proper detection of a biased broadening effect. 453

454 The band shifts can be analyzed considering the effects of the TrFE units and defect incorporation into the polymer structure. Considering the diffraction peaks at high q values 455 (see Figure 3a), we can express the relative spacing variation with respect to the peak positions 456 for 20 % TrFE. This is plotted in Figure 4b, for the diffraction peaks associated to the (001), 457 (201), and (110)/(200) planes. The (001) and (201) planes containing the *a* and *c*-axis of the 458 459 unit cell present negligible relative variations, lower than 1 %; while the (110)/(200) plane increases its relative spacing, reaching almost 5 % for the DFE-phase at 50 % TrFE. As the 460 461 (201) plane includes an *a*-axis component and presents minor variations, we can conclude that 462 the unit cell expands non-uniformly in the *b*-axis, experiencing compressive stress along the *a* and *c*-axis as more TrFE units are incorporated into the polymer chain. This anisotropic unit 463 cell expansion is likely responsible for the band shift observed in both Raman and FT-IR 464 465 spectroscopy.

466



Figure 4. Band broadening, shifting, and ratios from X-ray and Raman data. a) 845 cm⁻¹ all-468 trans CF₂ v mode band broadening normalized to peak height vs. TrFE content, with illustration 469 of the vibration geometry relative to the chain c-axis and dipolar moment, μ . b) Relative unit 470 cell diffraction plane spacing variation (with respect to 20 % TrFE) for the (001), (201), and 471 (110)/(200) diffraction planes as a function of the TrFE content. An illustration of the all-trans 472 orthorhombic unit cell is also shown, seen from the direction of the c-axis. c) Relative 473 conformation content vs. TrFE molar content, calculated from the height of the 796, 811, and 474 845 cm⁻¹ fitted Raman bands. d) Evolution of the band height and area of the 1347 and 1366 475 cm⁻¹ TrFE bands, extracted from spectral fitting, and normalized to the TrFE content. An 476 477 illustration of the vibration mode is also shown. e) Band height and band area ratios for the 1347 cm⁻¹ tt and 1366 cm⁻¹ tg TrFE bands, extracted from the fitted data (Fitted H. and Fitted 478 A.) and the raw data (denoted as Raw H.), and the calculated average value (Avg. Value) from 479 all the data sets. The calculated average coincides with the fitted band height values. The β (all-480 481 *trans*) to $\alpha + \gamma (tg + tttg)$ band height ratios (in gray, left axis) are also plotted, extracted from the same fitted data utilized in c). f) Illustration of the chain conformation within the TrFE 482 segments, with decrease of the number of *tt*-segments between each *tg*-segment with increases 483 in TrFE content. The ratios I_{1347}/I_{1366} represent the band intensity [height or area, plotted in e)] 484 ratios between the bands 1347 and 1366 cm⁻¹. 485

467

487 TrFE-specific Raman Bands and Defect Quantification. The different characterization
 488 techniques reveal important information on the evolution of the chain conformation with TrFE
 489 content. We start by addressing the origin of the TrFE vibration bands, especially clear in

Raman spectroscopy. The inverse relationship between the 1347 and 1430 cm⁻¹ bands (Figure 490 1a and 1c) is a good indication of their nature. Based on well-established spectroscopic data of 491 high polymers^{28, 68} combined with the observed behavior in the recorded spectra, we are able 492 to infer the mechanism behind the evolution of the 1347 and 1366 cm⁻¹ TrFE bands. It is well-493 known that the CH₂ deformation in PVDF is shifted towards low wavenumbers in comparison 494 to polyalkenes, such as polyethylene or polypropylene, due to the presence of the F atoms that 495 reduce the vibration frequency of the δ CH₂ modes.⁶⁸ The addition of another F atom, as is the 496 case of the TrFE unit, should further shift the vibration frequency of this mode towards lower 497 energies, having a vibration dampening effect. Considering the decrease in the 1430 cm⁻¹ δ 498 CH₂ mode, we can associate the 1347 and 1366 cm⁻¹ bands as arising from CHF deformation 499 500 modes (δ CHF) in the TrFE units.

501 On the basis of this hypothesis, we can further explore the chain conformation related to these two bands by gathering evidence from the characterizations carried out. Firstly, we can use the 502 data obtained from the 845 cm⁻¹ band fitting (as discussed above; see SI, Figure S3) to infer 503 the overall relative conformation content based on the intensity of the fitted peaks for the 796, 504 811 and 845 cm⁻¹ bands. This is plotted in Figure 4c, with the highest relative all-*trans* content 505 506 obtained for TrFE contents of 20 % up to 30 %. An increase in the *tttg* conformation is then seen for 50 % TrFE, in line with the appearance of other *tttg* related bands in other zones of the 507 508 Raman and FT-IR spectra. This is also validated by the presence of the RFE phase in the Xray diffraction pattern, as well as the decrease in the magnitude of T_{Curie} and ΔH_{c} in the DSC 509 data. We can apply the same analysis to the two TrFE bands at 1347 and 1366 cm⁻¹ and perform 510 a multi-peak fitting with several Gaussian and Voigt profiles between the range of 1270 and 511 1500 cm⁻¹ (see SI, Figure S4), extracting the height and the area of these bands. As the intensity 512 is also proportional to the amount of TrFE, we should normalize the extracted data by the TrFE 513 514 molar content. The normalized peak height and area for the two bands is plotted in Figure 4d

for the considered TrFE molar contents. These two bands present approximately mirrored behaviors with similar tendencies as those observed in Figure 4c. This suggests that these two bands arise from different chain conformations, and a clear shift is detected with the variation of the TrFE molar content. Considering these observations and the overall increase in *tg* chain defects supported by the different characterization techniques, we propose that the two TrFE bands at 1347 and 1366 cm⁻¹ are associated to δ CHF modes arising from two different chain conformations, namely, a *tt* and *tg* conformation, respectively.

This band assignment opens the possibility for defect quantification in P(VDF-TrFE) co-522 523 polymers by measuring and fitting these two bands from Raman spectroscopy data. In particular, it offers a way to quantify TrFE tg defect occurrence along the polymer chain by 524 focusing on the height or area ratio of the 1347 and 1366 cm⁻¹ bands. This is shown in Figure 525 526 4e, where the 1347 and 1366 band height and area ratios are plotted from the fitted (Fitted H. and Fitted A.) and raw data (Raw H.), along with the ratio average value (Avg. Value). The 527 $\beta/(\alpha+\gamma)$ [alternatively, *tttt/(tg + tttg)*] band height ratio is also shown, obtained from the fitted 528 data (796, 811, and 845 cm⁻¹) used in the calculation of the relative conformation content 529 (Figure 4c). All the plotted data present the same tendencies with increasing TrFE content, 530 531 indicating an increase in the amount of tg defects along the polymer chain. The $\beta/(\alpha+\gamma)$ ratio presents values above the 1347/1366 ratio, suggesting the VDF segments present higher 532 533 amounts of all-*trans* sequences in relation to tg sequences. It is very important to note that the bands at 796 and 811 cm⁻¹, commonly used to estimate phase proportion in PVDF-based co-534 polymers, arise from VDF-specific segments corresponding to CH₂ vibration modes. Our 535 relative conformation estimation does not account for the mode intensity loss from the 536 537 reduction in VDF segments with TrFE content, meaning the $\beta/(\alpha+\gamma)$ ratio may be overestimated, and the VDF units may present a higher defect content than previously 538 suggested. This is also an aspect that has not been addressed in previous works, many of which 539

540 have relied on band intensity to estimate phase proportion in different processing and composition studies. Interestingly, the 1347/1366 ratio also suggests that TrFE containing 541 chain segments already present tg defects even for low TrFE content. These tg defects may be 542 incorporated into the polymer crystallites and be responsible for the increase in unit cell volume 543 along with the incorporation of TrFE units, resulting in the observed DFE phases. The larger 544 value discrepancy between the ratios calculated from fitted height and area for low TrFE 545 contents can be explained by the error associated with multi-peak fitting for low intensity bands 546 that are easily overshadowed by other more intense contributions. 547

548 Recent literature has highlighted the importance of tg defects along the polymer chain, being responsible for the appearance of RFE behavior.²³⁻²⁵ In 2020, Liu et al. reported on this effect, 549 and demonstrated how the chiral nature of the TrFE monomer leads to the formation of a 550 disordered 3/1 helix chain, with a $(tg)_3$ conformation.²⁴ Following the results discussed in this 551 article, we should expect to observe an intense vibration band around 1366 cm^{-1} for a 3/1 helix 552 structure with $(tg)_3$, corresponding to the $tg \delta$ CHF, with a very small to negligible contribution 553 at 1347 cm⁻¹. This trend is indeed observed with the gradual increase of TrFE reducing the 554 contribution of the 1347 in favor of 1366 cm⁻¹, pointing to an increase in tg defects within the 555 556 TrFE segments. The ratio of these two bands may constitute a probe into the conformation of the TrFE segments, with ratios above 1 and below 1 signifying a majority of *tt*-segments or a 557 558 dominance by tg-segments, respectively. We can note from Figure 4e, that the 1347/1366 ratio 559 drops continuously, from around 2 to a value around 0.8 for 50 % TrFE. An illustration of the chain structure based on the 1347/1366 ratio (I₁₃₄₇/I₁₃₆₆) is depicted in Figure 4f, where the 560 chain conformation is represented for different contents of TrFE. The gradual increase of TrFE 561 562 decreases the length of the all-trans segments, with the ratio I1347/I1366 representing the approximate total number of *tt*-segments periodically separated by *tg* defects within the TrFE 563 segments of the polymer chain. A RFE phase is detected in this work for 50 % TrFE, for which 564

565 $I_{1347}/I_{1366} < 1$, *i.e.*, a *tg*-dominated chain structure that gradually approaches the 3/1 helix structure. From the extrapolation of the calculated data, it can be seen that $I_{1347}/I_{1366} < 1$ occurs 566 around 45 % TrFE, the same proportion where the 1347 and 1366 bands height (area) inversion 567 takes place (Figure 4d). This proportion has previously been linked to the start of the 568 morphotropic phase boundary (around 45 % to 55 % TrFE) in P(VDF-TrFE) co-polymers. As 569 a result, a quantitative relationship has been established between specific band ratios and the 570 occurrence of tg defect in PVDF-based polymers, in good agreement with recent literature on 571 the structure and FE behavior of P(VDF-TrFE) co-polymers.²³⁻²⁵ 572

573

574 CONCLUSION

575 In this work, we have analyzed the Raman spectra of P(VDF-TrFE) co-polymers for various TrFE proportions. Under the considered conditions (solution-cast, no thermal annealing), the 576 co-polymers presented β phase (all-*trans*) specific vibration modes, with an increase in 577 defective modes (tg and tttg containing modes) for higher TrFE molar content. TrFE-specific 578 modes, whose intensity increases with TrFE content, were detected at 1347 and 1366 cm⁻¹, and 579 show opposite evolution to the surrounding VDF modes at 1430 cm⁻¹. Complementary FT-IR 580 analysis confirms these observations, with the highest intensity of all-trans modes found for 581 20 % TrFE, and with several *tttg*-specific modes appearing for higher TrFE contents (at 1056 582 and 1116 cm⁻¹). X-ray diffraction showed that the majority phase corresponded to the FE β 583 phase, with traces of a minor DFE phase. For 50 % TrFE, a RFE phase was observed with DFE 584 as the majority phase. Material crystallinity for the solution-cast films increased with TrFE 585 586 content, but was observed to decrease for 50 % TrFE, suggesting enhanced nucleation for proportions around 30 %. DSC and DE showed an increase in the melting and glass 587 temperatures (T_{melt} and $T_{glass}^{10 Hz}$) and a decrease of the Curie transition temperature (T_{Curie}). 588

589 Following these results, we have proposed that the two detected TrFE bands at 1347 and 1366 cm⁻¹ are associated to δ CHF modes arising from a *tt* and *tg* conformation, respectively. 590 Monitoring of the 1347/1366 intensity ratio (I_{1347}/I_{1366}) was proposed as a potential probe into 591 592 the structure of the TrFE-segments: ratios above 1 represent a majority of *tt*-segments, while ratios below 1 represent a dominance by tg-segments. The extrapolated inversion in the 1347 593 and 1366 cm⁻¹ bands intensity also takes place for TrFE molar fractions corresponding to the 594 reported morphotropic phase boundary for P(VDF-TrFE). Accordingly, a quantitative 595 relationship has been drawn for the first time between specific band ratios and tg defect 596 597 occurrence in PVDF-based polymers. We expect this method to also be applicable to other PVDF co- and ter-polymers containing chiral monomers (like CTFE or CFE). 598

599

600 ASSOCIATED CONTENT

601 Supporting Information

602 The Supporting Information is available free of charge at.

Additional information on polymer molecular weight from SEC. Polymer thin film

604 fabrication for dielectric spectroscopy. Multi-peak non-linear fitting of the X-ray diffraction

patterns. Multi-peak non-linear fitting of the DSC endotherm for 20% TrFE. Multi-peak non-

606 linear fitting of the Raman spectra.

607 AUTHOR INFORMATION

608 Corresponding Author

609 Pedro M. Resende - Université de Bordeaux, CNRS, Bordeaux INP, LCPO, UMR 5629, F-

610 33600, Pessac, France. ORCiD: orcid.org/0000-0001-7854-2297. Email: pdecamposres@u-

611 bordeaux.fr

- Jean-David Isasa Université de Bordeaux, CNRS, Bordeaux INP, LCPO, UMR 5629, F33600, Pessac, France.
- 615 Georges Hadziioannou Université de Bordeaux, CNRS, Bordeaux INP, LCPO, UMR 5629,
- 616 F-33600, Pessac, France. ORCiD: orcid.org/0000-0002-7377-6040
- 617 Guillaume Fleury Université de Bordeaux, CNRS, Bordeaux INP, LCPO, UMR 5629, F-
- 618 33600, Pessac, France. ORCiD: orcid.org/0000-0003-0779-191X

- 620 Notes
- 621 The authors declare no conflicts of interest.
- 622
- 623 ACKNOWLEDGEMENTS
- 624 The authors acknowledge the financial support from the Industrial Chair SMILE within the
- 625 Grant Agreement No. ANR-19-CHIN-0002. The authors thank Arkema-Piezotech (France) for
- 626 providing the materials used in the study. P.M.R. would like to thank Sara Zanchi for insightful
- 627 discussions.

628 REFERENCES

- Valant, M., Electrocaloric materials for future solid-state refrigeration technologies. *Progress in Materials Science* 2012, 57 (6), 980-1009.
- 631 2. Ožbolt, M.; Kitanovski, A.; Tušek, J.; Poredoš, A., Electrocaloric refrigeration:
- 632 Thermodynamics, state of the art and future perspectives. *International Journal of Refrigeration* 2014,
 633 40, 174-188.
- 634 3. Li, Q.; Wang, Q., Ferroelectric Polymers and Their Energy-Related Applications.
- 635 *Macromolecular Chemistry and Physics* **2016**, *217* (11), 1228-1244.
- 4. Prateek; Thakur, V. K.; Gupta, R. K., Recent Progress on Ferroelectric Polymer-Based

637 Nanocomposites for High Energy Density Capacitors: Synthesis, Dielectric Properties, and Future

638 Aspects. *Chemical Reviews* **2016**, *116* (7), 4260-4317.

- 639 5. Chen, X.; Han, X.; Shen, Q.-D., PVDF-Based Ferroelectric Polymers in Modern Flexible
 640 Electronics. *Advanced Electronic Materials* 2017, *3* (5), 1600460.
- 641 6. Fähler, S., Caloric Effects in Ferroic Materials: New Concepts for Cooling. *Energy* 642 *Technology* 2018, 6 (8), 1394-1396.
- 643 7. Li, H.; Liu, F.; Fan, B.; Ai, D.; Peng, Z.; Wang, Q., Nanostructured Ferroelectric-Polymer
 644 Composites for Capacitive Energy Storage. *Small Methods* 2018, 2 (6), 1700399.
- 645 8. Cardoso, V. F.; Correia, D. M.; Ribeiro, C.; Fernandes, M. M.; Lanceros-Méndez, S.
- Fluorinated Polymers as Smart Materials for Advanced Biomedical Applications *Polymers* [Online],
 2018.
- 648 9. Zhang, C.-C.; Wang, Z.-K.; Yuan, S.; Wang, R.; Li, M.; Jimoh, M. F.; Liao, L.-S.; Yang,

Y., Polarized Ferroelectric Polymers for High-Performance Perovskite Solar Cells. *Advanced Materials* 2019, 31 (30), 1902222.

- Li, H.; Wang, R.; Han, S.-T.; Zhou, Y., Ferroelectric polymers for non-volatile memory
 devices: a review. *Polymer International* 2020, 69 (6), 533-544.
- Surmenev, R. A.; Chernozem, R. V.; Pariy, I. O.; Surmeneva, M. A., A review on piezo- and
 pyroelectric responses of flexible nano- and micropatterned polymer surfaces for biomedical sensing
 and energy harvesting applications. *Nano Energy* 2021, *79*, 105442.
- Neese, B.; Chu, B.; Lu, S.-G.; Wang, Y.; Furman, E.; Zhang, Q. M., Large Electrocaloric
 Effect in Ferroelectric Polymers Near Room Temperature. *Science* 2008, *321* (5890), 821.
- Liu, P. F.; Wang, J. L.; Meng, X. J.; Yang, J.; Dkhil, B.; Chu, J. H., Huge electrocaloric
 effect in Langmuir–Blodgett ferroelectric polymer thin films. *New Journal of Physics* 2010, *12* (2),
 023035.
- 14. Lovinger, A. J., Poly(Vinylidene Fluoride). In *Developments in Crystalline Polymers*—1,
 Bassett, D. C., Ed. Springer Netherlands: Dordrecht, 1982; pp 195-273.
- Tashiro, K.; Kobayashi, M., Structural phase transition in ferroelectric fluorine polymers: X ray diffraction and infrared/Raman spectroscopic study. *Phase Transitions* 1989, *18* (3-4), 213-246.
- Furukawa, T., Ferroelectric properties of vinylidene fluoride copolymers. *Phase Transitions* **1989**, *18* (3-4), 143-211.
- 17. Lovinger, A. J., Polymorphic transformations in ferroelectric copolymers of vinylidene
 fluoride induced by electron irradiation. *Macromolecules* 1985, *18* (5), 910-918.
- 18. Zhang, Q. M.; Bharti, V.; Zhao, X., Giant Electrostriction and Relaxor Ferroelectric Behavior
 in Electron-Irradiated Poly(vinylidene fluoride-trifluoroethylene) Copolymer. *Science* 1998, 280
 (5372), 2101-2104.
- Kavarnos, G. J.; Ting, R. Y.;
 Abdul-Sadek, G.; Belfield, K. D., High Electromechanical Responses in a Poly(vinylidene fluoride–
- 674 trifluoroethylene–chlorofluoroethylene) Terpolymer. Advanced Materials 2002, 14 (21), 1574-1577.
- Chung, T. C.; Petchsuk, A., Synthesis and Properties of Ferroelectric Fluoroterpolymers with
 Curie Transition at Ambient Temperature. *Macromolecules* 2002, *35* (20), 7678-7684.
- 677 21. Klein, R. J.; Xia, F.; Zhang, Q. M.; Bauer, F., Influence of composition on relaxor
- 678 ferroelectric and electromechanical properties of poly(vinylidene fluoride-trifluoroethylene-679 chlorofluoroethylene). *Journal of Applied Physics* **2005**, *97* (9), 094105.
- Zhu, L.; Wang, Q., Novel Ferroelectric Polymers for High Energy Density and Low Loss
 Dielectrics. *Macromolecules* 2012, 45 (7), 2937-2954.
- Liu, Y.; Aziguli, H.; Zhang, B.; Xu, W.; Lu, W.; Bernholc, J.; Wang, Q., Ferroelectric
 polymers exhibiting behaviour reminiscent of a morphotropic phase boundary. *Nature* 2018, 562
 (7725), 96-100.
- Liu, Y.; Zhang, B.; Xu, W.; Haibibu, A.; Han, Z.; Lu, W.; Bernholc, J.; Wang, Q.,
- 686 Chirality-induced relaxor properties in ferroelectric polymers. *Nature Materials* **2020**, *19* (11), 1169-687 1174.
- Liu, Y.; Chen, X.; Han, Z.; Zhou, H.; Wang, Q., Defects in poly(vinylidene fluoride)-based
 ferroelectric polymers from a molecular perspective. *Applied Physics Reviews* 2022, 9 (3), 031306.
- 690 26. Tashiro, K.; Takano, K.; Kobayashi, M.; Chatani, Y.; Tadokoro, H., Structural study on
- 691 ferroelectric phase transition of vinylidene fluoride-trifluoroethylene copolymers (III) dependence of
- transitional behavior on VDF molar content. *Ferroelectrics* **1984**, *57* (1), 297-326.

- Green, J. S.; Rabe, J. P.; Rabolt, J. F., Studies of chain conformation above the Curie point in
 a vinylidene fluoride/trifluoroethylene random copolymer. *Macromolecules* 1986, *19* (6), 1725-1728.
 Tashiro, K.; Kobayashi, M., Vibrational spectroscopic study of the ferroelectric phase
 transition in vinylidene fluoride-trifluoroethylene copolymers: 1. Temperature dependence of the
- 697 Raman spectra. *Polymer* **1988**, *29* (3), 426-436.
- Kim, K. J.; Reynolds, N. M.; Hsu, S. L., Spectroscopic analysis of the crystalline and
 amorphous phases in a vinylidene fluoride/trifluoroethylene copolymer. *Macromolecules* 1989, 22
 (12), 4395-4401.
- 701 30. Reynolds, N. M.; Kim, K. J.; Chang, C.; Hsu, S. L., Spectroscopic analysis of the electric
 702 field induced structural changes in vinylidene fluoride/trifluoroethylene copolymers. *Macromolecules*703 1989, 22 (3), 1092-1100.
- Jin Kim, K.; Reynolds, N. M.; Ling Hsu, S., Spectroscopic studies on the effect of field
 strength upon the curie transition of a VDF/TrFE copolymer. *Journal of Polymer Science Part B: Polymer Physics* 1993, 31 (11), 1555-1566.
- Xim, K. J.; Hsu, S. L., An infra-red spectroscopic study of structural reorganization of a uniaxially drawn VDF/TrFE copolymer in an electric field. *Polymer* 1994, *35* (17), 3612-3618.
- 709 33. Faria, L. O.; Moreira, R. L., Infrared spectroscopic investigation of chain conformations and
- interactions in P(VDF-TrFE)/PMMA blends. *Journal of Polymer Science Part B: Polymer Physics*2000, 38 (1), 34-40.
- 712 34. Klein, R. J.; Runt, J.; Zhang, Q. M., Influence of Crystallization Conditions on the
 713 Microstructure and Electromechanical Properties of Poly(vinylidene
- fluoride-trifluoroethylene-chlorofluoroethylene) Terpolymers. *Macromolecules* 2003, *36* (19), 7220 7226.
- 716 35. Mahdi, R. I.; Gan, W. C.; Majid, W. H. A., Hot Plate Annealing at a Low Temperature of a
- Thin Ferroelectric P(VDF-TrFE) Film with an Improved Crystalline Structure for Sensors and
 Actuators. *Sensors* 2014, *14* (10).
- 719 36. Arrigoni, A.; Brambilla, L.; Bertarelli, C.; Serra, G.; Tommasini, M.; Castiglioni, C.,
- P(VDF-TrFE) nanofibers: structure of the ferroelectric and paraelectric phases through IR and Raman
 spectroscopies. *RSC Advances* 2020, *10* (62), 37779-37796.
- 722 37. Chapron, D.; Rault, F.; Talbourdet, A.; Lemort, G.; Cochrane, C.; Bourson, P.; Devaux,
 723 E.; Campagne, C., In-situ Raman monitoring of the poly(vinylidene fluoride) crystalline structure

during a melt-spinning process. *Journal of Raman Spectroscopy* **2021**, *52* (5), 1073-1079.

- 725 38. Tashiro, K.; Kobayashi, M.; Tadokoro, H., Vibrational spectra and disorder-order transition 726 of poly(vinylidene fluoride) form III. *Macromolecules* **1981**, *14* (6), 1757-1764.
- 39. Kobayashi, M.; Tashiro, K.; Tadokoro, H., Molecular Vibrations of Three Crystal Forms of
 Poly(vinylidene fluoride). *Macromolecules* 1975, 8 (2), 158-171.
- 40. Cortili, G.; Zerbi, G., Chain conformations of polyvinylidene fluoride as derived from its
- vibrational spectrum. *Spectrochimica Acta Part A: Molecular Spectroscopy* **1967**, *23* (2), 285-299.
- 41. Gregorio, J. R.; Cestari, M., Effect of crystallization temperature on the crystalline phase
- content and morphology of poly(vinylidene fluoride). *Journal of Polymer Science Part B: Polymer Physics* 1994, 32 (5), 859-870.
- 73442.Gregorio Jr., R., Determination of the α , β , and γ crystalline phases of poly(vinylidene735fluoride) films prepared at different conditions. **2006**, *100* (4), 3272-3279.
- 736 43. Cai, X.; Lei, T.; Sun, D.; Lin, L., A critical analysis of the α , β and γ phases in
- 737 poly(vinylidene fluoride) using FTIR. *RSC Advances* **2017**, *7* (25), 15382-15389.
- 738 44. Milani, A.; Castiglioni, C.; Radice, S., Joint Experimental and Computational Investigation

of the Structural and Spectroscopic Properties of Poly(vinylidene fluoride) Polymorphs. *The Journal of Physical Chemistry B* 2015, *119* (14), 4888-4897.

- 45. Ma, W.; Zhang, J.; Chen, S.; Wang, X., β-Phase of poly(vinylidene fluoride) formation in
- poly(vinylidene fluoride)/poly(methyl methacrylate) blend from solutions. *Applied Surface Science*2008, 254 (17), 5635-5642.
- 46. Martins, P.; Lopes, A. C.; Lanceros-Mendez, S., Electroactive phases of poly(vinylidene
- fluoride): Determination, processing and applications. *Progress in Polymer Science* **2014**, *39* (4), 683-
- **746** 706.

- 747 47. Ren, J.-Y.; Ouyang, Q.-F.; Ma, G.-Q.; Li, Y.; Lei, J.; Huang, H.-D.; Jia, L.-C.; Lin, H.;
- Zhong, G.-J.; Li, Z.-M., Enhanced Dielectric and Ferroelectric Properties of Poly(vinylidene fluoride) 748 through Annealing Oriented Crystallites under High Pressure. Macromolecules 2022, 55 (6), 2014-749 750 2027.
- 48. Boccaccio, T.; Bottino, A.; Capannelli, G.; Piaggio, P., Characterization of PVDF 751
- membranes by vibrational spectroscopy. Journal of Membrane Science 2002, 210 (2), 315-329. 752
- 753 Lin, Y.; Zhang, Y.; Zhang, F.; Zhang, M.; Li, D.; Deng, G.; Guan, L.; Dong, M., Studies 49.
- 754 on the electrostatic effects of stretched PVDF films and nanofibers. *Nanoscale Research Letters* 2021, 755 16(1), 79.
- 756 50. Tashiro, K.; Yamamoto, H.; Kummara, S.; Takahama, T.; Aoyama, K.; Sekiguchi, H.;
- Iwamoto, H., High-Electric-Field-Induced Hierarchical Structure Change of Poly(vinylidene fluoride) 757 758 as Studied by the Simultaneous Time-Resolved WAXD/SAXS/FTIR Measurements and Computer
- Simulations. *Macromolecules* **2021**, *54* (5), 2334-2352. 759
- 51. 760 Thakur, A.; Dam, S.; Dey, R.; Gangavarappu, A.; Hussain, S., Temperature Raman Studies of Freestanding and Flexible Thin Films of CdS-doped PVDF. Polymer Composites 2019, 40 (7), 761
- 762 2662-2667.
- 52. Ji, Y.; Liu, J.; Jiang, Y.; Liu, Y., Analysis of Raman and infrared spectra of poly(vinylidene 763
- fluoride) irradiated by KrF excimer laser. Spectrochimica Acta Part A: Molecular and Biomolecular 764 765 Spectroscopy 2008, 70 (2), 297-300.
- 766 53. Wang, H.; Yang, X.; Zhao, Y.; Yan, C.; Wang, S.; Yang, H.; Wang, X.; Schultz, J. M., Preparation of gamma-PVDF with controlled orientation and insight into phase transformation. 767
- 768 Polymer 2017, 123, 282-289.
- 769 Aliane, A.; Benwadih, M.; Bouthinon, B.; Coppard, R.; Domingues-Dos Santos, F.; Daami, 54. 770 A., Impact of crystallization on ferro-, piezo- and pyro-electric characteristics in thin film P(VDF-TrFE). Organic Electronics 2015, 25, 92-98. 771
- 772 55.
- Zhao, C.; Hong, Y.; Chu, X.; Dong, Y.; Hu, Z.; Sun, X.; Yan, S., Enhanced Ferroelectric 773 Properties of P(VDF-TrFE) Thin Film on Single Layer Graphene Simply Adjusted by Crystallization
- 774 Condition. *Materials Today Energy* **2021**, 100678.
- Wongwirat, T.; Zhu, Z.; Rui, G.; Li, R.; Laoratanakul, P.; He, H.; Manuspiya, H.; Zhu, L., 775 56. Origins of Electrostriction in Poly(vinylidene fluoride)-Based Ferroelectric Polymers. 776
- 777 Macromolecules 2020, 53 (24), 10942-10954.
- 778 Zhu, Z.; Rui, G.; Li, R.; He, H.; Zhu, L., Enhancing Electrostrictive Actuation via Strong 57. 779 Electrostatic Repulsion among Field-Induced Nanodomains in a Relaxor Ferroelectric
- 780 Poly(vinylidene fluoride-co-trifluoroethylene-co-chlorotrifluoroethylene) Random Terpolymer. ACS 781 Applied Materials & Interfaces 2021, 13 (35), 42063–42073.
- Bargain, F.; Thuau, D.; Hadziioannou, G.; Domingues Dos Santos, F.; Tencé-Girault, S., 782 58.
- 783 Phase diagram of poly(VDF-ter-TrFE-ter-CTFE) copolymers: Relationship between crystalline 784 structure and material properties. Polymer 2021, 213, 123203.
- 785 Bargain, F.; Thuau, D.; Panine, P.; Hadziioannou, G.; Domingues Dos Santos, F.; Tencé-59.
- 786 Girault, S., Thermal behavior of poly(VDF-ter-TrFE-ter-CTFE) copolymers: Influence of CTFE 787 termonomer on the crystal-crystal transitions. Polymer 2019, 161, 64-77.
- 788 Hafner, J.; Benaglia, S.; Richheimer, F.; Teuschel, M.; Maier, F. J.; Werner, A.; Wood, S.; 60. Platz, D.; Schneider, M.; Hradil, K.; Castro, F. A.; Garcia, R.; Schmid, U., Multi-scale
- 789 790 characterisation of a ferroelectric polymer reveals the emergence of a morphological phase transition 791 driven by temperature. Nature Communications 2021, 12 (1), 152.
- 792 María, N.; Le Goupil, F.; Cavallo, D.; Maiz, J.; Müller, A. J., Effect of the TrFE Content on 61.
- 793 the Crystallization and SSA Thermal Fractionation of P(VDF-co-TrFE) Copolymers. International Journal of Molecular Sciences 2022, 23 (18), 10365. 794
- 795 Yagi, T., Heat of Fusion and Crystallization Kinetics of Poly(trifluoroethylene). Polymer 62. Journal 1980, 12 (1), 9-15. 796
- Koga, K.; Ohigashi, H., Piezoelectricity and related properties of vinylidene fluoride and 797 63. 798 trifluoroethylene copolymers. Journal of Applied Physics 1986, 59 (6), 2142-2150.
- 799 Meng, N.; Zhu, X.; Mao, R.; Reece, M. J.; Bilotti, E., Nanoscale interfacial electroactivity 64.
- in PVDF/PVDF-TrFE blended films with enhanced dielectric and ferroelectric properties. Journal of 800 801 Materials Chemistry C 2017, 5 (13), 3296-3305.

- 802 65. Kim, K.; Lee, S.; Nam, J.-S.; Joo, M.; Mikladal, B.; Zhang, Q.; Kauppinen, E. I.; Jeon, I.;
- An, S., Highly Transparent and Mechanically Robust Energy-harvestable Piezocomposite with
- 804 Embedded 1D P(VDF-TrFE) Nanofibers and Single-walled Carbon Nanotubes. 2023, *33* (14),
 805 2213374.
- 806 66. Ohigashi, H.; Koga, K., Ferroelectric Copolymers of Vinylidenefluoride and
- 807 Trifluoroethylene with a Large Electromechanical Coupling Factor. Japanese Journal of Applied
- 808 *Physics* **1982,** *21* (8A), L455.
- 809 67. Osswald, S.; Mochalin, V. N.; Havel, M.; Yushin, G.; Gogotsi, Y., Phonon confinement
- effects in the Raman spectrum of nanodiamond. *Physical Review B* **2009**, *80* (7), 075419.
- 811 68. Lin-Vien, D.; Colthup, N. B.; Fateley, W. G.; Grasselli, J. G., CHAPTER 3 -
- 812 Halocompounds. In *The Handbook of Infrared and Raman Characteristic Frequencies of Organic*
- 813 Molecules, Lin-Vien, D.; Colthup, N. B.; Fateley, W. G.; Grasselli, J. G., Eds. Academic Press: San
- 814 Diego, 1991; pp 29-44.