Behavior in cooling-induced oxide scale spallation of original and modified Cantor's HEA alloys oxidized at high temperature

Nassima Chenikha, Corentin Gay, Pauline Spaeter, Lionel Aranda, Patrice Berthod

Institut Jean Lamour / Université de Lorraine



About the Presenter

Patrice BERTHOD – Institut Jean Lamour, Univ. Lorraine, Nancy, FRANCE

Associate Professor in Materials Chemistry

CV highlights and research interests:

- Mech. Eng. Ecole Centrale de Lille, PhD Mater. Sci., Habil. Chemistry
- Foundry, metallurgy, corrosion, microstructures and properties of superalloys at high temperature

"Surface & Interface: Chemical Reactivity of Materials" research group

Work achieved without funding sources

No conflict of interest

Email: patrice.berthod@univ-lorraine.fr



Outlines

- Introduction
- Short reminder about the synthesis route, and the obtained chemical compositions and microstructures
- Oxide scale spallation during post-isothermal oxidation cooling
 - Oxidized samples observed by the naked eye
 - Exploitation of the cooling parts of the thermogravimetry curves
 - Cross-sectional observations
- Conclusions
- Outlooks





Introduction

- High Entropy Alloys; equimolar CoNiFeMnCr composition: Cantor Alloy
- Adding MC carbides \rightarrow increase in mechanical resistance at H.T.
- Isothermal oxidation behavior at 1000°C and 1100°C (shown today, at 2:20 PM)
 - Mass gain kinetic: parabolic but ...
 - Very fast for the Cantor alloys and its {+MC} derivatives
 - Slowed down if \downarrow Mn to 10 at.% and \uparrow Cr to 30 at.% *(but still worse than Ni–30 wt.%Cr)*
- More or less protection by the external multi-constituted oxide scale
- THIS WORK: how does this complex scale behave if temperature varies?
- \rightarrow first answers available in the cooling parts of the thermogravimetry curves




Reminder about the synthesis route

Targeted chemical compositions:

Common parts: Co-Ni-Fe-Mn-Cr (20 at.% each) or CoNiFe-10at.%Mn- 30at.%Cr

- No more elements
- or + 0.25C-3.8Ta (wt.%)
- or + 0.25C-3.7Hf (wt.%)
- Technical details:
- 40g of mix of pure elements (>99.9%)
- High frequency induction furnace, 300 millibars pure Argon
- Melting in the water-cooled copper crucible (5kV, 110kHz)
- 10' of homogenization in the liquid state (≈1700°C), solidification and cooling











Reminder of the alloys characteristics



- Obtained chemical compositions: close to the targeted ones
- Dendritic matrix and eutectic carbides (and some pre-eutectic HfC)



Oxide scale spallation behavior Oxidized samples observed by the naked eye




Cooling at -5 K min⁻¹ from 1000°C

- Reminder of the mass gain isothermally achieved:
- \approx 1.6 mg / cm² for Mn0.5Cr1.5, 2.4 mg / cm² (+TaC), 4.3 mg / cm² (+HfC)
- No evident oxide scale loss, except along the edges and corners




Oxide scale spallation behavior Oxidized samples observed by the naked eye



Cooling at -5 K min⁻¹ from 1100°C

- Reminder of the mass gain isothermally achieved:
- \approx 3.1 mg / cm² for Mn0.5Cr1.5, 4.7 mg / cm² (+TaC), 6.4 mg / cm² (+HfC)
- Little oxide scale loss in all cases (+TaC: slightly better behavior?)






Mass variations for the carbide-free alloy (compared to the Mn1Cr1 alloys)

- From 1000°C: spallation only for the equimolar alloy
- From 1100°C: oxide scales spalled off for both alloys






Mass variations for the TaC-containing alloy (compared to the Mn1Cr1TaC alloy)

- From 1000°C: spallation only for the Mn1Cr1TaC alloy
- From 1100°C: spallation in both cases, but much important for Mn1Cr1TaC






Mass variations for the HfC-containing alloy (compared to the Mn1Cr1HfC alloy)

- From 1000°C: (very important) spallation only for the Mn1Cr1HfC alloy
- From 1100°C: spallation in both cases, but much important for Mn1Cr1HfC






Two criteria for analyzing scale spallation: 1/temperature of spallation start

- For the Mn1Cr1 alloys spallation started sooner when carbides were present in alloy
- For the Mn1Cr1 alloys again, spallation started after a same decrease in temperature
- Very resistant against scale spallation after 50h at 1000°C the Mn0.5Cr1.5 alloys behave more or less as the Mn1Cr1 alloys after 50h at 1100°C






Two criteria for analyzing scale spallation: 2/total mass loss during cooling


- For all alloys mass loss is more important for cooling from 1100°C than from 1000°C
- For the Mn1Cr1 alloys much more mass was lost when carbides were present in alloy



Oxide scale spallation behavior

Cross-sectional observations where oxides were still here





- Many shear rupture of the scales at cooling (and maybe also by handling even done carefully)
- Disappearance of TaC in a depth increasing with temperature for a given duration
- Internal oxidation of HfC more extended inwards for 1100°C than for 1000°C



Conclusions / Outlooks

- \downarrow Mn and \uparrow Cr indisputably improve the resistance against scale spallation
- Difference probably due to scales not as thick as for Mn1Cr1 alloys
- But obvious lack of mechanical resistance of these multi-constituted scales
- Mn:

 isothermal oxidation, takes part to scales more than Cr, thus a double
 deleterious effect on the scales which still exists even if %Mn is lowered

\rightarrow Remove all Mn from Cantor's alloy derivatives destined to T \geq 1000°C

 \rightarrow Testing new alloys as here and also for much faster and repeated coolings





https://planetofhotels.com/guide/sites/default/files/styles/node__blog_post__bp_banner/public/live_banner/ORLANDO-2.jpg

(corresponding TMS2024 proceeding: pp. 1194–1204)



TMS 2024 153RD ANNUAL MEETING & EXHIBITION www.tms.org/TMS2024 • #TMSAnnualMeeting

