



A numerical scheme accurate at low Mach number based on space velocity enrichment

Jonathan Jung, Vincent Perrier

► To cite this version:

Jonathan Jung, Vincent Perrier. A numerical scheme accurate at low Mach number based on space velocity enrichment. 36ème séminaire CEA/SMAI-GAMNI de mécanique des fluides numérique, Jan 2024, Paris, France. hal-04503360

HAL Id: hal-04503360

<https://hal.science/hal-04503360>

Submitted on 13 Mar 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

A numerical scheme accurate at low Mach number based on space velocity enrichment

Jonathan Jung, Vincent Perrier

LMAP & Inria CAGIRE team, UPPA, Pau, France

Model

Compressible barotropic Euler equations:

$$\begin{cases} \partial_t \rho + \operatorname{div}_{\mathbf{x}}(\rho \mathbf{u}) = 0 \\ \partial_t(\rho \mathbf{u}) + \operatorname{div}_{\mathbf{x}}(\rho \mathbf{u} \otimes \mathbf{u}) + \nabla_{\mathbf{x}} p = 0 \end{cases} \quad \text{where } \rho \mapsto p(\rho) \text{ is a convex function}$$

Properties:

- System of conservative laws : $\partial_t \mathbf{W} + \operatorname{div}_{\mathbf{x}} \mathbf{f}(\mathbf{W}) = 0$.
- Hyperbolic system of conservation laws with 3 different eigenvalues $\lambda_1 = \mathbf{u} \cdot \mathbf{n} - c$ (acoustic), $\lambda_2 = \mathbf{u} \cdot \mathbf{n}$ (material), $\lambda_3 = \mathbf{u} \cdot \mathbf{n} + c$ (acoustic) where $c = \sqrt{p'(\rho)}$ is the sound speed.

Motivation

Numerical scheme able to compute accurately

- low Mach number flows ($M = \|\mathbf{u}\|/c \ll 1$),
- acoustic waves.

Collocated finite volume scheme

$$\int_{\Omega_i} \partial_t \mathbf{W} + \operatorname{div}_{\mathbf{x}} \mathbf{f}(\mathbf{W}) = 0 \Rightarrow |\Omega_i| \frac{d}{dt} \mathbf{W}_i + \sum_{\Gamma_{ij} \subset \partial \Omega_i} |\Gamma_{ij}| \underbrace{F(\mathbf{W}_i, \mathbf{W}_j, \mathbf{n}_{ij})}_{\text{numerical flux}} = 0.$$

Numerical flux: Rusanov or Roe

$$F(\mathbf{W}_i, \mathbf{W}_j, \mathbf{n}_{ij}) = \frac{\mathbf{f}(\mathbf{W}_i) + \mathbf{f}(\mathbf{W}_j)}{2} \cdot \mathbf{n}_{ij} - \star \Delta \rho - \star \Delta(\rho \mathbf{u}).$$

Two time scales asymptotic analysis

Scaling variables: x_0, ρ_0, u_0

$$\tilde{\rho} = \frac{\rho}{\rho_0}, \quad \tilde{p} = \frac{p}{p(\rho_0)}, \quad \tilde{\mathbf{u}} = \frac{\mathbf{u}}{u_0}, \quad \tilde{\mathbf{x}} = \frac{\mathbf{x}}{x_0}, \quad \tilde{t} = \frac{t}{x_0/u_0}, \quad \tau = \frac{t}{x_0/c_0} = \frac{\tilde{t}}{u_0/c_0} = \frac{\tilde{t}}{M}.$$

Dimensionless system:

$$\begin{cases} \partial_{\tilde{t}} \tilde{\rho} + \frac{1}{M} \partial_{\tau} \tilde{\rho} + \operatorname{div}_{\tilde{\mathbf{x}}}(\tilde{\rho} \tilde{\mathbf{u}}) = 0, \\ \partial_{\tilde{t}}(\tilde{\rho} \tilde{\mathbf{u}}) + \frac{1}{M} \partial_{\tau}(\tilde{\rho} \tilde{\mathbf{u}}) + \operatorname{div}_{\tilde{\mathbf{x}}}(\tilde{\rho} \tilde{\mathbf{u}} \otimes \tilde{\mathbf{u}}) + \frac{1}{\gamma M^2} \nabla_{\tilde{\mathbf{x}}} \tilde{p} = 0. \end{cases}$$

Develop each variable as power of M :

$$\tilde{\psi}(\tilde{\mathbf{x}}, \tilde{t}, \tau, M) = \tilde{\psi}^{(0)}(\tilde{\mathbf{x}}, \tilde{t}, \tau) + M \tilde{\psi}^{(1)}(\tilde{\mathbf{x}}, \tilde{t}, \tau) + M^2 \tilde{\psi}^{(2)}(\tilde{\mathbf{x}}, \tilde{t}, \tau) + \mathcal{O}(M^3).$$

Continuous case: $(\tilde{p}^{(1)}/\gamma, (\tilde{\rho} \tilde{\mathbf{u}})^{(0)}) = (\bar{p}, \bar{\mathbf{u}}) = \mathbf{U}$ satisfies a first order wave system

$$\begin{cases} \partial_{\tau} \bar{p} + \bar{c}_0^2 \operatorname{div}_{\tilde{\mathbf{x}}} \bar{\mathbf{u}} = 0, \\ \partial_{\tau} \bar{\mathbf{u}} + \nabla_{\tilde{\mathbf{x}}} \bar{p} = 0, \end{cases} \quad \text{where } \tau = \tilde{t}/M \xrightarrow[M \rightarrow 0]{} +\infty.$$

Discrete case: Rusanov and Roe schemes are asymptotically consistent with a wave system discretization

$$\partial_{\tau} \mathbf{U}_i + \frac{1}{|\tilde{\Omega}_i|} \sum_{\Gamma_{ij} \subset \partial \Omega_i} |\tilde{\Gamma}_{ij}| \left[A(\mathbf{n}_{ij}) \frac{\mathbf{U}_i + \mathbf{U}_j}{2} + D(\mathbf{n}_{ij})(\mathbf{U}_i - \mathbf{U}_j) \right] = 0,$$

$$\text{with } A(\mathbf{n}) = \begin{bmatrix} 0 & \bar{c}_0^2 \mathbf{n}^T \\ 1 & 0 \end{bmatrix}, \quad D^{\text{Rusanov/Godunov}}(\mathbf{n}) = \frac{\bar{c}_0}{2} \begin{bmatrix} 1 & 0 \\ 0 & \mathbf{I}/\mathbf{n}^T \end{bmatrix}.$$

Low Mach number limit/long time wave [1, 2]

Euler system

Well-prepared initial/boundary condition

$$\begin{cases} 0 = \tilde{p}_0^{(0)} = \tilde{p}_0^{(1)} = \tilde{p}_b^{(0)} = \tilde{p}_b^{(1)}, \\ 0 = \operatorname{div}_{\tilde{\mathbf{x}}}(\tilde{\rho} \tilde{\mathbf{u}})_0^{(0)} = \int_{\partial \Omega} (\tilde{\rho} \tilde{\mathbf{u}})_b^{(0)} \cdot \mathbf{n}. \end{cases}$$

Low Mach number limit

$$\begin{cases} \tilde{p} = \bar{p}^\infty + \mathcal{O}(M^2), \\ \tilde{\rho} \tilde{\mathbf{u}} = \bar{\mathbf{u}}^\infty + \mathcal{O}(M). \end{cases}$$

Wave system

Initial/boundary condition

$$\begin{cases} 0 = \bar{p}_0 = \bar{p}_b, \\ 0 = \operatorname{div}_{\tilde{\mathbf{x}}} \bar{\mathbf{u}}_0 = \int_{\partial \Omega} \bar{\mathbf{u}}_b \cdot \mathbf{n}. \end{cases}$$

Long time limit

$$\begin{cases} \bar{p}^\infty = 0, \\ \operatorname{div}_{\tilde{\mathbf{x}}} \bar{\mathbf{u}}^\infty = 0. \end{cases}$$

Wave structure

$$\partial_{\tau} (\operatorname{curl}_{\tilde{\mathbf{x}}} \bar{\mathbf{u}}) = 0$$

Hodge-Helmholtz decomposition: $\bar{\mathbf{u}} = \bar{\mathbf{u}}^\varphi + \bar{\mathbf{u}}^\Psi$ where $\begin{cases} \operatorname{curl}_{\tilde{\mathbf{x}}} \bar{\mathbf{u}}^\varphi = 0, \\ \operatorname{div}_{\tilde{\mathbf{x}}} \bar{\mathbf{u}}^\Psi = 0. \end{cases}$
Preserving a curl \leftrightarrow preserving $\bar{\mathbf{u}}^\Psi$.

Triangular mesh [3]

Discrete Hodge-Helmholtz decomposition: $d\mathbb{P}_0(\Omega) \ni \bar{\mathbf{u}}_h = \bar{\mathbf{u}}_h^\varphi + \bar{\mathbf{u}}_h^\Psi$ where

$$\bullet \bar{\mathbf{u}}_h^\varphi = \nabla_{\mathbf{x}} \varphi \text{ with } \varphi \in \mathbb{C}\mathbb{R}(\Omega), \quad \bullet \bar{\mathbf{u}}_h^\Psi = \nabla_{\mathbf{x}}^\perp \Psi \text{ with } \Psi \in \mathbb{P}_1(\Omega).$$

Structure preserved on wave system with Godunov' numerical flux:

- Periodic domain: $(\nabla_{\tilde{\mathbf{x}}}^\perp)^* \bar{\mathbf{u}}_h$ is preserved over time,
- Bounded domain: $(\bar{p}_b, \bar{\mathbf{u}}_h^\Psi(\bar{\mathbf{u}}_0))$ is preserved over time and the relative entropy is decreasing.

Quadrangular mesh: velocity enrichment

$$\nabla_{\mathbf{x}}^\perp \mathbb{Q}_1, \nabla_{\mathbf{x}} \mathbb{R} \mathbb{A} \mathbb{T} u \subset d\mathbb{S}_0 := \operatorname{span} \left(\begin{pmatrix} 1 \\ 0 \end{pmatrix}, \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \begin{pmatrix} x - 1/2 \\ -y + 1/2 \end{pmatrix} \right)$$

Discrete Hodge-Helmholtz decomposition: $d\mathbb{S}_0(\Omega) \ni \bar{\mathbf{u}}_h = \bar{\mathbf{u}}_h^\varphi + \bar{\mathbf{u}}_h^\Psi$ where



$$\bullet \bar{\mathbf{u}}_h^\varphi = \nabla_{\mathbf{x}} \varphi \text{ with } \varphi \in \mathbb{R} \mathbb{A} \mathbb{T} u(\Omega), \quad \bullet \bar{\mathbf{u}}_h^\Psi = \nabla_{\mathbf{x}}^\perp \Psi \text{ with } \Psi \in \mathbb{Q}_1(\Omega).$$

Structure preserved on wave system with Godunov' numerical flux:

- Periodic domain: $(\nabla_{\tilde{\mathbf{x}}}^\perp)^* \bar{\mathbf{u}}_h$ is preserved over time,
- Bounded domain: $(\bar{p}_b, \bar{\mathbf{u}}_h^\Psi(\bar{\mathbf{u}}_0))$ is preserved over time and the relative entropy is decreasing.

Numerical results on quadrangular mesh



Wave system: preservation of the adjoint curl



Euler cylinder scattering:

$$\begin{cases} \rho_b = 1 \\ \mathbf{u}_b^x = M \times c_b \\ \mathbf{u}_b^y = 0 \end{cases} \Rightarrow$$

$$\tilde{p} - \tilde{p}_b^{(0)} \stackrel{?}{=} \mathcal{O}(M^2)$$



Conclusion

- Low Mach accuracy is equivalent to curl preserving for wave system.
- Triangular mesh+Godunov flux is curl preserving.
- Quadrangular+Godunov+change velocity basis is curl preserving.

References

- [1] S Schochet. Fast singular limits of hyperbolic pdes. *Journal of differential equations*, 114(2):476–512, 1994.
- [2] J. Jung and V. Perrier. Steady low mach number flows: identification of the spurious mode and filtering method. *Journal of Computational Physics*, 468:111462, 2022.
- [3] S. Dellacherie, P. Omnes, and F. Rieper. The influence of cell geometry on the Godunov scheme applied to the linear wave equation. *Journal of Computational Physics*, 229(14):5315–5338, 2010.