

# Tuning Co-Cu-Al catalysts and their reaction conditions on the CO2 hydrogenation reaction to higher alcohols under mild conditions

Vitor Duarte Lage, Anthony Le Valant, Nicolas Bion, Fabio Souza Toniolo

# ▶ To cite this version:

Vitor Duarte Lage, Anthony Le Valant, Nicolas Bion, Fabio Souza Toniolo. Tuning Co-Cu-Al catalysts and their reaction conditions on the CO2 hydrogenation reaction to higher alcohols under mild conditions. Chemical Engineering Science, 2023, 281, pp.119208. 10.1016/j.ces.2023.119208 . hal-04503677

# HAL Id: hal-04503677 https://hal.science/hal-04503677v1

Submitted on 23 Oct 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## 1 Tuning Co-Cu-Al catalysts and their reaction conditions on the CO<sub>2</sub>

- 2 hydrogenation reaction to higher alcohols under mild conditions.
  - 3

4

#### Vitor Duarte Lage<sup>a</sup>, Anthony Le Valant<sup>b</sup>, Nicolas Bion<sup>b</sup>, Fabio Souza Toniolo<sup>a</sup>

<sup>a</sup> Chemical Engineering Program – PEQ/COPPE – Universidade Federal do Rio de Janeiro, Cidade
Universitária, Rio de Janeiro CEP 21941-972, RJ, Brazil

- <sup>b</sup> Institut de Chimie des Milieux et Matériaux de Poitiers (IC2MP)/Université de Poitiers CNRS,
  Poitiers, France
- 9

### 10 Abstract

11 The catalytic conversion of  $CO_2$  and  $H_2$  into valuable chemicals is a promising alternative to the recent energy and environmental challenges. However, designing an earth-abundant catalyst 12 capable of actively and selectively converting CO<sub>2</sub> into desirable products is yet a challenge. Herein, 13 we report on a facile K-Co-Cu-Al catalyst prepared by a coprecipitation method for CO<sub>2</sub> 14 hydrogenation to higher alcohols (HAs). We investigated different Co:Cu ratios, reduction 15 temperatures, and reaction conditions (temperature, space velocity, and H<sub>2</sub>/CO<sub>2</sub> ratio) to tune it, 16 enhancing the selectivity and yield of higher alcohols. Co1.8Cu0.9AIOx (1 wt% K), reduced at 400 °C, 17 exhibits a high HAs selectivity of 44.8% (20.8% for ethanol) and space-time yield of 18 19 5.54 mmol·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> (3.08 mmol·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> of ethanol), under mild conditions (250 °C, 30 bar, H<sub>2</sub>/CO<sub>2</sub> ratio of 1.5, and 14200 mL g<sub>cat</sub><sup>-1</sup>·h<sup>-1</sup>), which represents one of the best performances among related 20 studies, especially among Co-based catalysts. 21

22

Keywords: CO<sub>2</sub> hydrogenation; Ethanol production; CO<sub>2</sub> conversion; Co-based catalyst; Cu-based
 catalyst; Bimetallic catalyst.

25

#### 27 Graphical Abstract



28

#### 29 **1. Introduction**

One of the most significant current scientific challenges is reducing the atmospheric 30 concentration of CO<sub>2</sub>, an anthropogenic greenhouse gas responsible for global warming. To address 31 32 this challenge three main strategies can be employed: (i) reducing emissions; (ii) capturing and storing; and (iii) utilizing or transforming CO<sub>2</sub>. In that sense, the CO<sub>2</sub> hydrogenation reaction emerges 33 as a promising alternative to both capture and transform this anthropogenic gas, as CO<sub>2</sub>, captured 34 from industrial effluents, can serve as a C1 building block to produce value-added products and 35 feedstock [1,2]. However, the CO<sub>2</sub> hydrogenation reaction can yield various possible products, 36 37 including CO, CH<sub>4</sub>, C<sub>2+</sub> hydrocarbons (HCs), methanol, and higher alcohols (HAs or C<sub>2+</sub>OH), each with its advantages, disadvantages, and academic challenges [3-6]. 38

Among these products, higher alcohols, particularly ethanol, have garnered significant research and industrial attention due to their versatile applications as fuel, solvents, chemical precursors, and cleaning agents. They also offer higher energy density, sustainability, and reduced environmental impact compared to alternative substances [3,5–8]. Nonetheless, tailoring the catalysts, and optimizing the process condition are key challenges in this field [4,5].

For the synthesis of HAs via CO<sub>2</sub> hydrogenation, various catalysts have been reported [9– 16], but certain trends have been identified, including Rh-based, Cu-based, Co-based [5,6,8], Pdbased [5], and Mo-based [6,8] catalysts. Among these, Co- and Cu-based catalysts stand out as non-noble metal catalysts [11], offering relative cost advantages. Co-based catalysts exhibit higher CO<sub>2</sub> conversion [5,6,8], but methane is typically the predominant product formed [11], particularly in their metallic form (Co<sup>0</sup>). However, recent studies have demonstrated that modifying Co-based catalysts through alloy formation or interaction with some oxide supports can reduce their ability to break the C-O bond, favoring HAs formation [5,8]. These modified Co-based catalysts (CoAlO<sub>x</sub>, Na-Co/SiO<sub>2</sub>, Pt/Co<sub>3</sub>O<sub>4</sub>, LaCoGaO<sub>3</sub>, CoNiAlO<sub>x</sub>) have been studied in both continuous and batch reactions for HAs synthesis, exhibiting CO<sub>2</sub> conversion ranging from 5-67%, selectivity to HAs from 0.05-92%, and space-time yield (STY) from 0.01-2.16 mmol·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> [8].

55 Cu has emerged as a promising metal for Co-based alloys [14,17], as it promotes COinsertion [18] and inhibits C-O bond cleavage [8,19]. Additionally, alkali metals have been 56 57 investigated as promoters to enhance basicity by donating electrons to Co sites. Amidst, Na, and K have been extensively studied for HAs synthesis, as they have been reported to reduce CH4 58 formation, increase CO<sub>2</sub> conversion, and tune HAs selectivity [5,6,11,20,21]. However, excess Na 59 (>5 wt%) can inhibit CO insertion, increasing CO selectivity [8]. For K, a wide range of weight content 60 (0.1-17.6 wt%) has been explored, with optimal composition falling between 0.5 to 4.6 wt% 61 62 [11,12,20–23].

Regarding the reaction conditions, determining the optimal temperature, H<sub>2</sub>/CO<sub>2</sub> ratio, and 63 64 space velocity, among other parameters, is detrimental to improving the HAs synthesis. Temperature 65 plays a dual role, favoring CO<sub>2</sub> conversion with its increase but hindering HAs formation [5,24]. Similarly, increasing the H<sub>2</sub>/CO<sub>2</sub> ratio also favors conversion, but excess H<sub>2</sub> can further hydrogenate 66 67 the reaction intermediate of ethanol, while decreasing it can favor methanol synthesis routes [5,25]. 68 Adjusting the space velocity (SV) is also vital. Increasing SV results in lower conversion, whereas 69 lower velocities can favor some reaction pathways over others, leading to undesired products [5,9,26]. In summary, optimizing these conditions is necessary to strike a balance between 70 71 conversion and product selectivity, thereby increasing the yield of the desired product [5]. Most Co-72 based catalysts exhibit optimal performance in the temperature range of 140-250 °C with space 73 velocity between 3000-6000 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> [6]. However, the effect of the H<sub>2</sub>/CO<sub>2</sub> ratio has not been 74 widely explored.

To address the need for improving CO<sub>2</sub> conversion and inhibiting the formation of undesired products, mainly methane, we propose investigating CoCu catalysts. In this study, we prepared a series of Co<sub>(2.8-n)</sub>Cu<sub>n</sub>AlO<sub>x</sub> catalysts derived from layered-double hydroxides (LDH), carefully tailored to retain 1 wt% of K. LDHs have garnered attention as promising precursors for heterogeneous catalysts due to their thermal stability and the possibility of modifying the characteristics of the resulting material such as surface area, particle size, electronic state and distribution of metal species [14,27,28]. Moreover, LDH-derived catalysts can easily be synthesized on a large scale via coprecipitation and have shown promising results in CO<sub>2</sub> hydrogenation to ethanol [11,14,24,29].

Herein, we aim to explore different Co:Cu ratios, reduction temperatures, and reaction conditions (temperature, space velocity, and  $H_2/CO_2$  ratio) to investigate their effects on  $CO_2$ conversion, product selectivity, and yield. By fine-tuning the catalyst design and optimizing the reaction conditions, we aspire to overcome the thermodynamic and kinetic limitations associated with CO2 hydrogenation and enhance the efficiency and viability of higher alcohol synthesis.

#### 88 2. Experimental

#### 89 2.1 Catalyst Preparation

90 The Co<sub>(2.8-n)</sub>Cu<sub>n</sub>AlO<sub>x</sub> samples were derived from the calcination of LDH clays, which were prepared by a modified coprecipitation method [30,31]. The alkaline solution was formed by 2 M 91 92 NaOH (Sigma-Aldrich,  $\geq$ 98%) and 0.5 M Na<sub>2</sub>CO<sub>3</sub> (Sigma-Aldrich,  $\geq$ 99.5%). The precursor solution (1 M) was prepared by dissolving Co(NO<sub>3</sub>)<sub>2</sub>·6H<sub>2</sub>O (Sigma-Aldrich,  $\geq$ 98%), Cu(NO<sub>3</sub>)<sub>2</sub>·2.5H<sub>2</sub>O (Sigma-93 94 Aldrich,  $\geq 98\%$ ), and Al(NO<sub>3</sub>)<sub>3</sub>·9H<sub>2</sub>O (Sigma-Aldrich,  $\geq 98\%$ ), in deionized water, with the desired Co:Cu:Al molar ratio. The chosen M:Al ratio (M: active metals, i.e., Co and Cu) was 2.8, based on 95 other works reporting similar materials [30-34]. The selected molar ratios of Co and Cu, expressed 96 97 by the Co/(Co+Cu), were 0, 0.5, 0.66, and 1.

Both the precursor and alkaline solutions were added drop-wise to a recipient under agitation, maintaining pH 10 by regulating the flow of the alkaline solution. After adding the precursor solution, the resulting solution was aged overnight, filtered, and washed thoroughly in deionized water to remove excess sodium [30,31]. The resulting filtered cake was suspended in a  $K_2CO_3$  with concentration adjusted to obtain approximately 1 wt% K in the catalyst [34,35]. Finally, the resulting sludge was filtered and calcined in a muffle furnace in static air at 500 °C for 3 h [34,36].

#### 104 2.2 Characterization

The metal content in each prepared sample was determined by ICP-OES (Inductively Coupled Plasma Optical Emission Spectrometry) on a Perkin Elmer Optima 2000DV spectrometer. Prior to analysis, the samples underwent acid digestion, i.e., dissolved in an HNO<sub>3</sub>/HCl acidic mixture (1:3 ratio) and heated by microwave. The solution was then injected into the plasma as an aerosol generated by a nebulizer.

110 The identification of the crystalline phases and crystallographic properties of the prepared 111 samples were analyzed via X-ray diffraction (XRD) collected on a Rigaku Miniflex diffractometer 112 (30 kV, and 15 mA) with an X-ray tube Cu target (CuK $\alpha$ ,  $\lambda$ =1,5418 Å). The diffractograms were 113 collected with Bragg angles ranging from 10° to 80°, using a continuous scan mode with a step size 114 of 0.05° and a collection time of 1 s per step.

The textural properties such as surface area ( $A_{BET}$ ), pore volume ( $V_{pore}$ ), and pore diameter ( $d_{pore}$ ) of the calcined catalysts were determined by N<sub>2</sub> physisorption using a Micromeritics Tristar instrument and calculated according to the method of Brunauer, Emmet and Teller (BET). The samples were degassed at 200 °C overnight before the N<sub>2</sub> physisorption analysis.

The reduction profile of the catalysts was analyzed in temperature-programmed reduction (TPR) experiments employing a Micromeritics Autochem II 2920 apparatus equipped with a thermal conductivity detector (TCD). The samples were pretreated at 200 °C with an Ar flow (30 mL·min<sup>-1</sup>) for 1 h. Subsequently, the TPR experiments were carried out with approximately 125 mg of catalyst in a 10% H<sub>2</sub>/Ar flow (30 mL·min<sup>-1</sup>) from 30 to 1000 °C (5 °C·min<sup>-1</sup>) using a programmable temperature controller. The reduction degree was then calculated by dividing the real H<sub>2</sub>-intake by the theoretical H<sub>2</sub>-intake, which, was determined based on the ICP-OES results.

The basicity profile of the catalysts was analyzed in  $CO_2$  temperature-programmed desorption ( $CO_2$ -TPD) experiments in a multipurpose testing unit equipped with an online quadrupole mass detector QUADSTAR 422 (QMS 200, BALZERS). For that, the sample (100 mg) was placed into a quartz tube reactor, which was heated (10 °C·min<sup>-1</sup>) to the desired temperatures (250, 400, and 500 °C) under pure H<sub>2</sub> flow (60 mL·min<sup>-1</sup>) for 30 min, and then cooled to room temperature in ultra-high purity He flow (60 mL·min<sup>-1</sup>). After pretreatment, the CO<sub>2</sub> adsorption stage was conducted by passing pure CO<sub>2</sub> (30 mL·min<sup>-1</sup>) for 30 min and then flushing the reaction with He (60 mL·min<sup>-1</sup>) for 60 min. The TPD was performed by heating (20 °C·min<sup>-1</sup>) the sample to 800 °C. The effluent gases were monitored by an online mass detector (m/z = 2, 4, 28, 30, 32, 44, and 46).

135 2.3 Catalytic Test

The CO<sub>2</sub> hydrogenation catalytic tests for the Co<sub>(2.8-n)</sub>Cu<sub>n</sub>AlO<sub>x</sub> samples were executed in a continuous fixed-bed stainless steel reactor. The sample (300 mg, 0.160-0.100 mm sieved fraction) was placed between two layers of SiC (0.125 mm), enough to ensure an 8 cm height reaction bed and to maintain the fluid dynamic conditions between different samples. Prior to the reaction, the samples underwent *in situ* reduction at four different temperatures (250, 300, 400, and 500 °C) for 30 min (heating ramp: 5 °C.min<sup>-1</sup>) under pure H<sub>2</sub> flow (30 ml·min<sup>-1</sup>).

142 The initial tests were conducted at 250 °C and 30 bar in an  $H_2/CO_2/N_2$  flow (ratio: 3/1/0.25) with gas-hourly space velocity (GHSV) set to 14200 mL·g<sub>cat</sub>-1·h<sup>-1</sup> for 24 h. Subsequently, different 143 H<sub>2</sub>/CO<sub>2</sub> ratio (H<sub>2</sub>/CO<sub>2</sub>/N<sub>2</sub> ratio: 3/2/0.25), GHSV (10625 mL.g<sub>cat</sub><sup>-1</sup>.h<sup>-1</sup>) and temperatures (200, 250 and 144 145 300 °C) were explored. The outlet products were analyzed online (each 36 min) in an Agilent 7890A gas chromatograph (GC). The gas products (CO, CO<sub>2</sub>, H<sub>2</sub>, and N<sub>2</sub>) were detected by a TCD detector. 146 147 Hydrocarbons and condensable liquid products were analyzed by an FID detector. The catalytic performance was expressed by CO<sub>2</sub> conversion (X<sub>CO2</sub>), C-based product selectivity (S<sub>i</sub>), and the 148 149 product space-time yield (STY<sub>i</sub>), calculated by the equation as follows:

$$X_{CO_2} = \frac{[CO_2]_{in} - [CO_2]_{out}}{[CO_2]_{in}} \times 100\%$$
(1)

$$S_i = \frac{n_i \times C_i}{\sum (n_i \times C_i)} \times 100\%$$
<sup>(2)</sup>

$$STY_i = \frac{F_{CO_2,in} \times X_{CO_2} \times S_i}{m_{cat}}$$
(3)

where  $[CO_2]_{in}$  and  $[CO_2]_{out}$ , respectively, are the molar concentration of  $CO_2$  in the inlet and outlet flow; Ci refers the concentration of products (CO, CH<sub>4</sub>, C<sub>x</sub>H<sub>n</sub>, CH<sub>3</sub>OH, C<sub>2</sub>H<sub>5</sub>OH, C<sub>3</sub>H<sub>7</sub>OH, among others) in the outlet flow; n<sub>i</sub> represents the number of carbon atoms for product C<sub>i</sub>; F<sub>CO2,in</sub> stands for the flow rate of CO<sub>2</sub>; and m<sub>cat</sub> is the mass of catalyst.

#### 154 **3. Results and Discussion**

#### 155 3.1 Physical-Chemical Properties

The metallic weight content (wt%) obtained for the samples on the ICP-OES analysis, the 156 calculated molar ratio between Co:Cu:Al, and their textural properties, are summarized in Table 1. 157 Henceforth the catalysts are referred to as Cu<sub>2.6</sub>AlO<sub>x</sub>, Co<sub>1.3</sub>Cu<sub>1.3</sub>AlO<sub>x</sub>, Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub>, and Co<sub>2.6</sub>AlO<sub>x</sub>, 158 according to their Co:Cu:Al ratios. We verified that the Co/(Co+Cu) ratios agreed with expected 159 nominal values and that obtaining an M-AI ratio close to 2.8 was possible, as desired. The samples 160 did not present any detectable amounts of Na, confirming that the treatment with K<sub>2</sub>CO<sub>3</sub> solution was 161 162 efficiently removed the excess Na. The K content for Cu<sub>2.6</sub>AlO<sub>x</sub>, Co<sub>1.3</sub>Cu<sub>1.3</sub>AlO<sub>x</sub>, Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub>, and Co<sub>2.6</sub>AIO<sub>x</sub> was 0.8, 0.7, 0.8 and 0.9 wt%, respectively, close to the expected 1 wt%. 163

164

**Table 1.** Content of Co, Cu, Al, and K (determined by ICP-OES ), Surface area (A<sub>BET</sub>), pore volume
 (V<sub>pore</sub>), and pore diameter (d<sub>pore</sub>) of the prepared catalysts after calcination at 500 °C.

Catalyst	Meta	allic cor	ntent (v	vt%)	Co:Cu:Al	$A_{BET}$	Vpore	dpore
Catalyst	AI	Со	Cu	К	Ratio	(m <sup>2</sup> ·g <sup>-1</sup> )	(cm <sup>3.</sup> g <sup>-1</sup> )	(nm)
Cu2.6AlOx	9.3	0.0	57.5	0.8	0:2.6:1	56	0.18	9
Co1.3Cu1.3AlOx	9.3	27.3	29.3	0.7	1.3:1.3:1	85	0.44	19
Co1.8Cu0.9AlOx	9.0	34.9	18.7	0.8	1.8:0.9:1	69	0.37	18
Co2.6AIOx	9.1	52.2	0.0	0.9	2.6:0:1	78	0.35	13

167

Regarding the N<sub>2</sub> physisorption isotherms for Cu<sub>2.6</sub>AlO<sub>x</sub> (blue), Co<sub>1.3</sub>Cu<sub>1.3</sub>AlO<sub>x</sub> (light purple), Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> (dark purple), and Co<sub>2.6</sub>AlO<sub>x</sub> (red) are shown in **Figure 1**. Based on the N<sub>2</sub> physisorption analysis, the calculated BET surface area for Cu<sub>2.6</sub>AlO<sub>x</sub>, Co<sub>1.3</sub>Cu<sub>1.3</sub>AlO<sub>x</sub>, Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub>, and Co<sub>2.6</sub>AlO<sub>x</sub>. was 56, 85, 69, and 78 m<sup>2</sup>·g<sup>-1</sup>, in that order. The values agree with the expected area (50-150 m<sup>2</sup>·g<sup>-1</sup>) for mixed oxides prepared by the modified coprecipitation method [30,36]. Moreover, the hysteresis at high relative pressure (**Figure 1**) indicates the formation of a mesoporous material

- 174 [37], which is consistent with similar previously reported materials [27,32,37–39] and with the values
- 175 of pore diameter (**Table 1**).



Figure 1. Nitrogen adsorption isotherms of for  $Cu_{2.6}AIO_x$  (blue),  $Co_{1.3}Cu_{1.3}AIO_x$  (light purple), Co<sub>1.8</sub>Cu<sub>0.9</sub>AIO<sub>x</sub> (dark purple), and Co<sub>2.6</sub>AIO<sub>x</sub> (red).

179

Powder XRD patterns for the samples calcined at 500 °C are presented in Figure 2. For 180 181  $Cu_{2.6}AlO_x$  (blue), a CuO (tenorite, PDF#48-1548) phase was identified. It is also possible to infer the presence of small and poorly defined peaks that could be attributed to CuAl<sub>2</sub>O<sub>4</sub> spinel (PDF#44-182 0106). For Co<sub>2.6</sub>AlO<sub>x</sub> (red), the Co<sub>3</sub>O<sub>4</sub> (PDF#43-1003) and the Co<sub>2</sub>AlO<sub>4</sub> inverse spinel (PDF#38-183 0814) phases were compatible with the XRD pattern. It is also possible to infer the presence of 184 185 CoAl<sub>2</sub>O<sub>4</sub> spinel (PDF#44-0106), as it presents the same position of diffraction lines only slightly 186 shifted to a lower angle. From the XRD patterns, it is difficult to distinguish  $Co_3O_4$  from spinel-like structures, as their lattice parameters are very similar [39]. As for Co<sub>1.3</sub>Cu<sub>1.3</sub>AlO<sub>x</sub> (light purple) and 187 Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> (dark purple), the presence of a mix of CuO, Co<sub>3</sub>O<sub>4</sub>, and the Co-Al spinel-like 188 189 structures is the likely case. It is also reported on Co-Cu mixed oxides, such as Co<sub>2.2</sub>Cu<sub>0.8</sub>O<sub>4</sub> (PDF#36-1189), Co<sub>2.05</sub>Cu<sub>0.95</sub>O<sub>4</sub> (PDF#36-1189), and Co<sub>2.84</sub>Cu<sub>0.15</sub>O<sub>4</sub> (PDF#36-1189), to display the 190 same diffraction pattern as Co<sub>3</sub>O<sub>4</sub>, with a slight shift in angle due to the small difference in Co and 191 192 Cu cationic radii, which implies that, through XRD, it is difficult to determine whether the pattern

193 corresponds to Co<sub>3</sub>O<sub>4</sub> or a Co-Cu spinel [32,40]. Recent works reported similar materials containing



a mixture of different phases and spinel structures [31–33,37,39].

195

Figure 2.  $Cu_{2.6}AlO_x$  (blue),  $Co_{1.3}Cu_{1.3}AlO_x$  (light purple),  $Co_{1.8}Cu_{0.9}AlO_x$  (dark purple), and  $Co_{2.6}AlO_x$ (red) XRD patterns (CuK $\alpha$ ,  $\lambda$ =1,5418 Å).

198

199 The reduction profiles of the samples calcined at 500 °C were obtained using H<sub>2</sub>-TPR and are presented in Figure 3. For Cu<sub>2.6</sub>AlO<sub>x</sub> (blue), we observed a single reduction region around 200 200 and 300 °C, marking the reduction of Cu<sup>2+</sup> to Cu<sup>0</sup> [41]. Similar reduction profiles for Cu-Al catalysts 201 derived from LDHs are reported in the literature [38,42–44]. For Co<sub>2.6</sub>AlO<sub>x</sub> (red), we can ascribe at 202 least three distinct reduction regions: a peak at 250 °C, a broad region from 350 to 450 °C, and a 203 204 broad peak around 700 °C. The first peak and region are commonly attributed to the reduction of Co<sup>3+</sup> to Co<sup>2+</sup>, and the reduction of Co<sup>2+</sup> to Co<sup>0</sup>, whereas reduction peaks above 450 °C were 205 previously attributed to the reduction of spinel-like structures [27,35,45]. Furthermore, Co-Al 206 catalysts derived from LDHs have been reported with two distinct reduction regions, one around 250-207 450 °C, attributed to the reduction of Co<sup>3+</sup> to Co<sup>2+</sup>, and other one around 550-700 °C, assigned to 208 the reduction of  $Co^{2+}$  to  $Co^{0}$  [24,45–48]. For  $Co_{1,3}Cu_{1,3}AIO_x$  (light purple) and  $Co_{1,8}Cu_{0,9}AIO_x$  (dark 209 purple), we observed two distinct regions: one from 200 to 400 °C, which could be attributed to, first, 210 the reduction of Cu<sup>2+</sup> to Cu<sup>0</sup>, along with the reduction of Co<sup>3+</sup> to Co<sup>2+</sup> [31,32,37].; and a second broad 211

region above 400 °C, ascribed to the two-step reduction of bulk  $Co^{3+}$  to  $Co^{0}$ , the reduction of  $Co^{2+}$  to Co<sup>0</sup>, and the reduction of spinel-like structures [31,37]. It is worth mentioning that adding Cu to the Co-Al structure significantly reduced its reduction temperature. Moreover, when compared, Co<sub>1.3</sub>Cu<sub>1.3</sub>AlO<sub>x</sub> and Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub>, the reduction profile of Co<sub>1.3</sub>Cu<sub>1.3</sub>AlO<sub>x</sub> is slightly shifted to a lower temperature. This shift to lower reduction temperatures of Co-containing catalysts can be explained by hydrogen spillover from Cu metallic particles [31,32,37,49,50].

218



219

Figure 3.  $H_2$  TPR profile of  $Cu_{2.6}AIO_x$  (blue),  $Co_{1.3}Cu_{1.3}AIO_x$  (dark purple),  $Co_{1.8}Cu_{0.9}AIO_x$  (dark purple), and  $Co_{2.6}AIO_x$  (red) under 10%  $H_2$  flow (30 mL.min<sup>-1</sup>).

222

Based on the TPR analysis and elemental analysis of Co and Cu, we calculated the degree 223 of reduction of the samples. It is expressed as the experimental  $H_2$  consumption (based on the peak 224 225 area of the TPR profiles) divided by the theoretical  $H_2$  consumption (based on the nominal molar content of Co and Cu in the samples, considering all Co as Co<sub>3</sub>O<sub>4</sub>, and all Cu as CuO) in percentage. 226 227 That information is summarized in **Table 2**. The degree of reduction ranged from 88% to 99% with the increase in Cu content in the samples. In other words, the measured H<sub>2</sub> consumption was lower 228 229 than the expected  $H_2$  consumption, which could mean that not all Co is present as  $Co_3O_4$ , mostly 230 likely due to spinel-like structures.

233	Table 2. Calculated experimental and theoretical H <sub>2</sub> consumption, and degree of reduction based
234	on the 10% $H_2$ -TPR profiles of the catalysts.

Catalyst	Experimental H2 consumption (mmol·g <sup>-1</sup> )	Theoretical H2 consumption (mmol·g <sup>-1</sup> )	Degree of Reduction (%)
Cu <sub>2.6</sub> AIO <sub>x</sub>	8.97	9.05	99
Co1.3Cu1.3AlOx	9.62	10.79	89
Co1.8Cu0.9AlOx	9.70	10.84	89
Co2.6AIOx	10.44	11.81	88

236 Information regarding surface basicity, an essential aspect of CO<sub>2</sub> hydrogenation catalysts, was assessed through CO<sub>2</sub>-TPD experiments for the catalysts and is shown in Figure 4. All samples 237 reduced at 250 °C (Figure 4a) displayed a sharp peak around 110 °C and a sinusoidal pattern from 238 239 150 to 350 °C due to the re-adsorption of CO<sub>2</sub>[51–54] Co<sub>1.3</sub>Cu<sub>1.3</sub>AlO<sub>x</sub> and Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> also 240 displayed a broader peak around 250 and 300 °C. That broad peak at intermediate temperature became prominent when Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> was reduced at 400 °C, but it disappeared when it was 241 reduced at 500 °C (Figure 4c). Contrastingly, Co<sub>2.6</sub>AlO<sub>x</sub>, after reduction at 500 °C, displayed a sharp 242 at 200 °C and a tail indicating CO<sub>2</sub> desorption up until 700 °C (Figure 4b). It is worth mentioning that 243 244 CO2-TPD experiments were carried out at different reduction temperatures for Co2.6AIOx and 245 Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub>, as these samples were tested in such conditions in the CO<sub>2</sub> hydrogenation reaction 246 (section 3.2.2).

247

231





Figure 4. CO<sub>2</sub>-TPD curves for the catalysts reduced at 250  $^{\circ}$ C (a), and for Co<sub>2.6</sub>AlO<sub>x</sub> (b), Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> (c), after different reduction temperatures.

According to the literature, it is possible to divide the CO2-TPD profile into three regions 251 according to the strength of the adsorption site. Below 200 °C, the desorption is ascribed to weakly 252 adsorbed CO<sub>2</sub> [15–17,55–57]. This region can be assigned to Bronsted basicity sites, i.e., surface 253 254 hydroxyl (-OH) [15,58–60]. The second desorption region, from 200 to 500 °C, is attributed to 255 moderately adsorbed CO<sub>2</sub> [15,16,55,60] and associated with Lewis basicity, ergo oxygen sites [59], more specifically metal-oxygen pairs (M-O) [60]. It is reported that these moderate basic sites 256 contribute to ethanol formation [25] and the activity of catalysts on the CO<sub>2</sub> hydrogenation reaction 257 258 at that range of temperature [15]. The last region, above 500 °C, is attributed to strong basic sites [17,55], also associated with Lewis basicity [59], more specifically to low coordination oxygen atoms 259 [60]. Strong CO<sub>2</sub> adsorption sites are reported to favor CO<sub>2</sub> methanation [61] and, in the case of Co-260 based catalysts, are associated with Co<sup>0</sup> species [17]. 261

Therefore, it is possible to infer that combining Co and Cu led to an increase in CO<sub>2</sub> 262 adsorption, which becomes evident when comparing the calculated CO<sub>2</sub> uptake from the 263 264 monometallic catalysts,  $Cu_{2.6}AIO_x$  and  $Co_{2.6}AIO_x$ , to the bimetallic catalysts,  $Co_{1.3}Cu_{1.3}AIO_x$  and  $Co_{1.8}Cu_{0.9}AIO_x$ , which is summarized in **Table 3**.  $Co_{1.3}Cu_{1.3}AIO_x$  and  $Co_{1.8}Cu_{0.9}AIO_x$  (Figure 4a) also 265 displayed a desorption peak at the moderate basicity region (250 °C), attributed to CO<sub>2</sub> 266 hydrogenation activity. Furthermore, the moderate basicity peak on the TPD profile of  $Co_{1.8}Cu_{0.9}AIO_x$ 267 268 increased when the sample was reduced at 400 °C (Figure 4c), leading to nearly double CO2 uptake. Upon reducing Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> at 500 °C, the CO<sub>2</sub> uptake was cut to half, and the peak at 269

270 250 °C disappeared. The CO<sub>2</sub> uptake of Co<sub>2.6</sub>AlO<sub>x</sub> increased with the increase in the reduction 271 temperature. At 500 °C, all three desorption regions were identified: two sharp peaks for weakly and 272 moderately adsorbed CO<sub>2</sub>; and a broad region from 500 to 700 °C, attributed to strongly adsorbed 273 CO<sub>2</sub>. The effect of reduction temperature on Co<sub>2.6</sub>AlO<sub>x</sub> and Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> activity was further 274 discussed along with the catalytic tests (section 3.2.2).

275

276

**Table 3**. Calculated CO<sub>2</sub> uptake based on the CO<sub>2</sub>-TPD results for the samples.

Catalyst	Reduction Temperature (ºC)	CO2 uptake (µmol·g <sup>-1</sup> )
Cu <sub>2.6</sub> AlO <sub>x</sub>	250	10.1
Co1.3Cu1.3AlOx	250	57.2
Co1.8Cu0.9AlOx	250	43.4
	400	84.5
	500	42.9
Co2.6AIOx	250	17.8
	400	31.1
	500	55.5

277

### 278 3.2 Tuning Catalytic Performance

We initially tested the catalysts, namely  $Cu_{2.6}AIO_x$ ,  $Cu_{1.3}Co_{1.3}AIO_x$ ,  $Cu_{1.8}Co_{0.9}AIO_x$ , and Co<sub>2.6</sub>AIO<sub>x</sub>, in the CO<sub>2</sub> hydrogenation reaction at 30 bar, 250 °C, H<sub>2</sub>/CO<sub>2</sub> ratio of 3, gas-hourly space velocity (GHSV) of 14200 mL·g<sub>cat</sub><sup>-1</sup>·h<sup>-1</sup>. Henceforth, the products are coded as CH<sub>4</sub> (methane), CO (carbon monoxide), C<sub>2-5</sub> alkanes and alkenes (HCs), methanol, ethanol, and C<sub>3+</sub>OH (propanol, isopropanol, and other C<sub>3+</sub> oxygenates).

We evaluated their CO<sub>2</sub> conversion, product selectivity (HCs and oxygenates, CO, and CH<sub>4</sub>), HCs and oxygenates (methanol, ethanol, and C<sub>3+</sub>OH) distribution, and space-time yield (STY). For the first test, each sample was reduced at the reaction temperature (250 °C) in pure hydrogen. Later, we evaluated the effect of changing this temperature of reduction and some reaction parameters. All the results expressed below are summarized in **Table S1** and **Table S2**.

289 3.2.1 Effect of Co-Cu Ratio

The effect of combining Co and Cu was evidenced by the increase in  $CO_2$  conversion and selectivity towards products of interest. For that, the molar ratios between cobalt and copper in the catalysts can be expressed by the Co/(Co+Cu) ratio. The Co/(Co+Cu) ratios for the samples  $Cu_{2.6}AIO_x$ ,  $Cu_{1.3}Co_{1.3}AIO_x$ ,  $Co_{1.8}Cu_{0.9}AIO_x$ , and  $Co_{2.6}AIO_x$  are, respectively, 0, 0.5, 0.66, and 1. The changes in  $CO_2$  conversion and selectivity towards the different products are expressed in **Figure 5**.

295

296



297

Figure 5. Effect of Co/(Co+Cu) ratio on the selectivity and CO<sub>2</sub> conversion (a), HCs and oxygenates distribution (b), and the STY of products of interest (c) (250 °C, 30 bar, H<sub>2</sub>/CO<sub>2</sub> = 3, GHSV = 14200 mL· $g_{cat}^{-1}$ ·h<sup>-1</sup>).

303 It is possible to observe an increase in CO<sub>2</sub> conversion and selectivity towards products of 304 interest, i.e., hydrocarbons and oxygenates (red), when combining cobalt and copper (Figure 5a). Both mixed Co-Cu catalysts, Cu<sub>1.3</sub>Co<sub>1.3</sub>AlO<sub>x</sub> and Cu<sub>1.8</sub>Co<sub>0.9</sub>AlO<sub>x</sub>, displayed CO<sub>2</sub> conversion above 305 306 10%, whereas the values of conversion for the single metal catalysts,  $Cu_{2.6}AIO_x$  and  $Cu_{2.6}AIO_x$ , were 307 below 10%. When comparing the HCs and oxygenates distribution (Figure 5b), Cu<sub>2.6</sub>AlO<sub>x</sub> displayed 308 100% selectivity towards methanol, whereas Cu<sub>1.3</sub>Co<sub>1.3</sub>AlO<sub>x</sub>, Cu<sub>1.8</sub>Co<sub>0.9</sub>AlO<sub>x</sub>, and Co<sub>2.6</sub>AlO<sub>x</sub> produced 309 HCs (gray), ethanol (light red),  $C_{3+}OH$  (dark red) and methanol (blue). One can infer that combining Co and Cu increases the yield of higher alcohols and hydrocarbons, implying that the Co-Cu 310 combination favors chain growth. Moreover, Cu<sub>1.8</sub>Co<sub>0.9</sub>AlO<sub>x</sub>, with the Co/(Co+Cu) ratio of 0.66, led to 311 312 the lowest selectivity towards undesired products, i.e., CH<sub>4</sub> (green) and CO (purple), and the higher yield of both ethanol and  $C_{3+}OH$ , namely 0.71 and 0.43 mmol.h<sup>-1</sup>.g<sup>-1</sup> (**Figure 5c**). This synergic effect 313 between Co and Cu has been previously reported for improving HAs selectivity from syngas 314 315 [18,31,62,63] and CO<sub>2</sub> hydrogenation [14,19,55]. Subramanian et al. [62], for instance, observed that 316 mixed CoCu particles were more selective towards HAs than CoCu core-shell particles, inferring that both Co and Cu sites must be present on the surface. Sun et al. [18] concluded that each metal 317 played a role in the synthesis of HAs (Cu, activation of surface CO\*; and Co, hydrogenation, and 318 chain growth). Moreover, through DFT data and experimental results, Liu et al. [20] observed that 319 320 there is an ideal Co/(Co+Cu) ratio to maintain optimum CO\* surface coverage to produce ethanol. Both Liu et al. [19] and Wang et al. [55] observed the best ethanol selectivity and STY at Co/(Co+Cu) 321 322 ratios of 0.5 and 0.66.

323 Considering these results,  $Cu_{1.8}Co_{0.9}AIO_x$  displayed the highest STY of HAs and the second-324 highest CO<sub>2</sub> conversion of all four catalysts; hence we decided to investigate the effect of reduction 325 temperature on this sample. Additionally, we decided to compare the results of  $Cu_{2.6}AIO_x$  and 326  $Co_{2.6}AIO_x$  to highlight the Co-Cu catalyst.

#### 327 3.2.2 Effect of Reduction Temperature

First, we evaluated the influence of the reduction temperature (pure H<sub>2</sub>, 30 ml.min<sup>-1</sup>) on the activity of the catalysts. Based on the TPR results and the literature [38,42-44], Cu<sub>2.6</sub>AlO<sub>x</sub> was not 330 tested with different reduction temperatures, since 250 °C is sufficient for the reduction and activation of copper. Moreover, the effect of reduction temperatures on Co<sub>2.6</sub>AlO<sub>x</sub> catalytic performance on the 331 332 CO<sub>2</sub> hydrogenation to higher alcohols is displayed in Figure 6. The increase in the reduction temperature led to an increase in CO<sub>2</sub> conversion for Co<sub>2.6</sub>AlO<sub>x</sub>, with a decrease in CH<sub>4</sub> selectivity 333 until 400 °C (Figure 6a). Reducing Co<sub>2.6</sub>AlO<sub>x</sub> at 500 °C led to a noticeable increase in CO<sub>2</sub> 334 conversion with the consequent increase in CH<sub>4</sub> selectivity. The HCs and oxygenates distribution did 335 not change from 400 to 500 °C (Figure 6b). The yield of HAs and HCs was hindered by the reduction 336 at 500 °C (Figure 6c). 337

338



339

Figure 6. Effect of the reduction temperature on the selectivity and CO<sub>2</sub> conversion (a), HCs and oxygenates distribution (b), and the STY of products of interest (c) of Co<sub>2.6</sub>AlO<sub>x</sub> (250 °C, 30 bar,

344

$$H_2/CO_2 = 3$$
, GHSV = 14200 mL·g<sub>cat</sub>-1·h<sup>-1</sup>).

345

As previously discussed in the TPR analysis, at temperatures above 400 °C, the reduction procedure likely leads to the reduction of bulk Co and spinel-like structures [27,31,35]. Excess Co<sup>0</sup> and larger metallic particles can favor methanation reaction [1,2], justifying the increase in CO<sub>2</sub> conversion and CH<sub>4</sub> selectivity. Furthermore, in the CO<sub>2</sub>-TPD analyses, the profile of Co<sub>2.6</sub>AlO<sub>x</sub> reduced at 500 °C displayed remarkable desorption up until 700 °C, marking strong basicity sites, which promotes methanation [61].

Furthermore, the same reduction temperatures were tested on  $Co_{1.8}Cu_{0.9}AIO_x$ , and its catalytic performance is presented in **Figure 7**.

354

355

....

356

357

358



Figure 7. Effect of the reduction temperature on the selectivity and CO<sub>2</sub> conversion (a), HCs and
 oxygenates distribution (b), and the STY of products of interest (c) of Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> (250 °C,

364 30 bar, 
$$H_2/CO_2 = 3$$
, GHSV = 14200 mL·g<sub>cat</sub>-1·h<sup>-1</sup>).

365

Similar to  $Co_{2.6}AIO_x$ , increasing the reduction temperature led to a decrease in CH<sub>4</sub> selectivity for  $Co_{1.8}Cu_{0.9}AIO_x$  and an increase in  $CO_2$  conversion up to 400 °C. Contrastingly, reducing  $Co_{1.8}Cu_{0.9}AIO_x$  at 500 °C led to a decrease in  $CO_2$  conversion (**Figure 7a**) without a significant change in the distribution of HCs and oxygenates (**Figure 7b**). The highest STY of HAs was for the sample reduced at 400 °C, namely 1.55 and 1.35 mmol.h<sup>-1</sup>.g<sup>-1</sup>, in that order, for ethanol and C<sub>3+</sub>OH, which represents an increase of approximately 2 and 3 times, respectively, in yield of both HAs (**Figure 7c**). It is likely that above 400 °C, the reduction increases the Co<sup>0</sup>/Co<sup> $\delta$ +</sup> ratio on the surface; as a result, hindering the catalyst activity [24,64,65]. As reported, an optimum Co<sup>0</sup>/Co<sup> $\delta$ +</sup> ratio is necessary to tune a cobalt-based catalyst activity and selectivity in the CO<sub>2</sub> hydrogenation reaction [8,24,55,66]. Furthermore, these catalytic test results reflect the CO<sub>2</sub>-TPD profile for the different reduction temperatures of Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> (**Figure 4**). Reducing at 500 °C reduced by half the calculated CO<sub>2</sub> uptake and led to the disappearance of the peak attributed to moderate basicity and associated with ethanol selectivity [25] and CO<sub>2</sub> hydrogenation activity [15].

379 A comparison between  $Cu_{2,6}AIO_x$ ,  $Co_{1,8}Cu_{0,9}AIO_x$ , and  $Co_{2,6}AIO_x$  catalytic tests results is shown in **Figure 8**, each catalyst after its best-tested pretreatment, i.e.,  $Co_{2.6}AIO_x$  and  $Co_{1.8}Cu_{0.9}AIO_x$ 380 reduced at 400 °C, and Cu<sub>2.6</sub>AlO<sub>x</sub> reduced at 250 °C. Comparatively, the CO<sub>2</sub> conversions for 381 382 Cu<sub>2.6</sub>AIO<sub>x</sub>, Co<sub>1.8</sub>Cu<sub>0.9</sub>AIO<sub>x</sub>, and Co<sub>2.6</sub>AIO<sub>x</sub> at the optimal reduction temperature were 8.8%, 17.2%, and 9.8%, in that order (Figure 8a). Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> reduced at 400 °C converted nearly twice as 383 much CO<sub>2</sub> as the other two compared catalysts. Moreover, mixing Co-Cu increased the HAs 384 385 selectivity (28.5%) and hydrocarbons (31.3%). Regarding the yield of products of interest 386 (**Figure 8b**), Cu<sub>2.6</sub>AlO<sub>x</sub> reduced at 250 °C produced only methanol, circa 2.78 mmol.h<sup>-1</sup>.g<sub>cat</sub><sup>-1</sup>, while the Co-containing catalysts also yielded HAs ( $C_{2-3}$ ), HCs ( $C_{2-5}$ ). The yield of HAs and HCs, for 387 Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> reduced at 400 °C, were approximately 2.90 and 3.00 mmol.h<sup>-1</sup>.g<sub>cat</sub><sup>-1</sup>, respectively. In 388 that sense, Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> yielded as much HAs as Cu<sub>2.6</sub>AlO<sub>x</sub> yielded methanol. Henceforth, we 389 390 evaluated the effect of reaction conditions of Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> reduced at 400 °C.



Figure 8. Comparison of the selectivity and CO<sub>2</sub> conversion (a), and the STY of products of interest (b) of the catalysts after the best reduction pretreatment: Cu<sub>2.6</sub>AlO<sub>x</sub> (250 °C), Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> (400 °C), and Co<sub>2.6</sub>AlO<sub>x</sub> (400 °C), on the CO<sub>2</sub> hydrogenation reaction (250 °C, 30 bar, H<sub>2</sub>/CO<sub>2</sub> = 3, GHSV = 14200 mL·g<sub>cat</sub><sup>-1</sup>·h<sup>-1</sup>).

392

# 398 3.2.3 Effect of the Reaction Temperature

We evaluated the influence of the reaction temperature, 50 °C above and below the previously used temperature (250 °C), on the activity of  $Co_{1.8}Cu_{0.9}AIO_x$  catalytic performance on the CO<sub>2</sub> hydrogenation to HAs, which is displayed in **Figure 9**.



404

Figure 9. Effect of the reaction temperature on the selectivity and CO<sub>2</sub> conversion (a), HCs and oxygenates distribution (b), and the yield of products of interest (c) of Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> reduced at  $400 \ ^{\circ}C$  (30 bar, H<sub>2</sub>/CO<sub>2</sub> = 3, GHSV = 14200 mL·g<sub>cat</sub><sup>-1</sup>·h<sup>-1</sup>).

408

Increasing the reaction temperature from 200 to 300 °C increased CO<sub>2</sub> conversion, from 7.1% at 200 °C to 30.1% at 300 °C (**Figure 9a**). However, the highest STY for the products of interest (HCs and oxygenates) was at 250 °C. The increase in reaction temperature to 300 °C led to CO formation. Moreover, the increase in reaction temperature from 250 to 300 °C promoted the production of hydrocarbons (**Figure 9b**). Decreasing it from 250 to 200 °C caused an increase in ethanol selectivity and a decrease in HCs selectivity. In short, even though the increase in reaction temperature promoted the CO<sub>2</sub> conversion, the yield of higher alcohols was hindered at 300 °C (**Figure 9b**). Overall, the yield of ethanol and C<sub>3+</sub>OH was higher at 250 °C.

417 The increase in reaction temperature leads to an increase in  $CO_2$  conversion, which can be accompanied by an increase in the yield of higher alcohols [64,67]even when HAs selectivity is 418 hindered by the increase in temperature [24], here evidenced when reaction temperature increased 419 from 200 to 250 °C. However, the increase in the reaction temperature can also favor the production 420 of side products, such as CO [20], hydrocarbons [68], and methanol [65,69]. As reviewed by Zeng 421 422 et al. [6], most of the recently reported Co-based catalysts operate well from 140 to 250 °C, whereas the temperature for Mo-based, Rh-based, and Cu-based catalysts ranges from 200-340 °C, 240-423 270 °C, and 300-350 °C, respectively. 424

425 3.2.4 Effect of the Space Velocity

We tested the effect of space velocity on  $Co_{1.8}Cu_{0.9}AIO_x$  catalytic performance, by decreasing the gas-hourly space velocity (GHSV) of the reaction system from 14200 to 10625 mL.h<sup>-1</sup>.g<sub>cat</sub><sup>-1</sup>, and the results are shown in **Figure 10**.





Figure 10. Effect of the space velocity on the selectivity and  $CO_2$  conversion (a), HCs and oxygenates distribution (b), and the yield of products of interest (c) of  $Co_{1.8}Cu_{0.9}AIO_x$  reduced at 433  $400 \,^{\circ}C$  (250  $^{\circ}C$ , 30 bar,  $H_2/CO_2 = 3$ ).

As explained by Si et al. [9], higher space velocity hinders CO insertion, which has slow 434 reaction rate than the C-C coupling and hydrogenation reactions; hence lowering the space velocity 435 could benefit the HAs selectivity. On the other hand, lowering too much the space velocity could lead 436 to a decrease in STY. Overall, this decrease in space velocity was beneficial to the yield of HAs and 437 led to an increase in CO<sub>2</sub> conversion from 17.1% to 24.4%, an increase of roughly 40% (**Figure 10a**). 438 439 This change also inhibited the production of methane. Moreover, aside from reduced methanol selectivity, the HCs and oxygenates distribution remained roughly the same (Figure 10b). This 440 decrease in space velocity promoted the formation of HAs, namely, the yield of ethanol and C<sub>3+</sub>OH 441 442 increased approximately 1.5 times each (Figure 10c). Xu et al. [10] also observed an increase in 443 CO<sub>2</sub> conversion and a decrease in CO selectivity with the decrease in space velocity, implying that increasing the contact time promotes CO conversion to HAs and HCs. Noteworthy, Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> 444 did not yield any CO at the space velocity tests. 445

446 3.2.5 Effect of the  $H_2/CO_2$  ratio

447 Next, we also evaluated the effect of changing the  $H_2/CO_2$  ratio from 3 (3:1), as commonly 448 used in most of the recently reported literature [6,9–16], to 1.5 (3:2) on the activity of  $Co_{1.8}Cu_{0.9}AlO_x$ 449 catalytic performance on the  $CO_2$  hydrogenation to HAs, which can be seen on **Figure 11**.

450

451



Figure 11. Effect of the  $H_2/CO_2$  ratio on the selectivity and  $CO_2$  conversion (a), HCs and oxygenates distribution (b), and the yield of products of interest (c) of  $Co_{1.8}Cu_{0.9}AIO_x$  reduced at  $400 \ ^{\circ}C$  (250  $^{\circ}C$ , 30 bar, GHSV: 14200 mL·g<sub>cat</sub>-<sup>1</sup>·h<sup>-1</sup>).

453

458 Reducing the H<sub>2</sub>/CO<sub>2</sub> ratio from 3 (3:1) to 1.5 (3:2), we observed a reduction in the nominal value of CO<sub>2</sub> conversion from 17.1% to 12.2%, respectively (Figure 11a). However, decreasing the 459  $H_2/CO_2$  ratio implies reducing the amount of  $H_2$  and increasing the amount of  $CO_2$ ; therefore, at an 460  $H_2/CO_2$  ratio of 3:2, more  $CO_2$  was fed to the reactor, namely 60%, more than at  $H_2/CO_2$  ratio of 3:1. 461 Hence, reducing the  $H_2/CO_2$  ratio from 3 (3:1) to 1.5 (3:2) led to an increase in the amount of  $CO_2$ 462 converted, in terms of moles of CO<sub>2</sub> converted per hour at the same space velocity, here evaluated 463 for both tests with different H<sub>2</sub>/CO<sub>2</sub> ratio. Methane production is also inhibited, decreasing CH<sub>4</sub> 464 selectivity from 39.5% to 22.5%. This reduction in the H<sub>2</sub>/CO<sub>2</sub> ratio also promoted the selectivity 465 466 towards HAs, namely ethanol, and  $C_{3+}OH$  composed approximately 58% of the HCs and oxygenates distribution at  $H_2/CO_2$  ratio of 3:2, compared to 47.1% at  $H_2/CO_2$  ratio of 3:1 (Figure 11b). 467 Furthermore, this represents an increase of about 2 and 1.8 times, respectively, to the STY of ethanol 468 and C<sub>3+</sub>OH, whereas the yield of HCs increased by roughly 1.2 times. It is reported that the increase 469 470 in H<sub>2</sub>/CO<sub>2</sub> ratio leads to a decrease in HAs selectivity [25].



The 24 h stability profiles of Co<sub>1.8</sub>Cu<sub>0.9</sub>AIO<sub>x</sub> reduced at 400 °C are displayed in Figure 12, at 472 the initial conditions (250 °C, 30 bar,  $H_2/CO_2 = 3$ , GHSV = 14200 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>), after reducing in 473 space velocity (GHSV = 10625 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>) (**Figure 12b**), and after changing  $H_2/CO_2$  ratio to 1.5 474 (Figure 12c). In all conditions, the carbon balance (C-balance) reaches 95-102% after the first 3 h 475 476 of reaction, probably due to reactor wash-out after opening. Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub>, at the initial conditions (Figure 12a), achieves stability after 12 h of reaction. Meanwhile, at GHSV of 10625 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> 477 (Figure 12b), this period was stretched in 3 h. On the other hand, reducing the  $H_2/CO_2$  ratio from 3 478 to 1.5 (Figure 12c) leads to the reactional system reaching stability right after the reactor wash-out. 479 Moreover, after reaching stability, the CO<sub>2</sub> conversion and HAs selectivitydid not change during the 480 24 h test at that condition, i.e.,  $Co_{1.8}Cu_{0.9}AIO_x$  did not deactivate. Considering the stability test and 481 yield of products of interest, the H<sub>2</sub>/CO<sub>2</sub> ratio change rendered the best catalytic performance for 482 483  $Co_{1.8}Cu_{0.9}AlO_x$ .

484



Figure 12. 24 h-TOS of  $Co_{1.8}Cu_{0.9}AlO_x$  reduced at 400 °C at 250 °C and 30 bar after (a) initial conditions (H<sub>2</sub>/CO<sub>2</sub> = 3, GHSV = 14200 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>); (b) decreasing GSHV to 10625 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> (H<sub>2</sub>/CO<sub>2</sub> = 3); and (c) changing H<sub>2</sub>/CO<sub>2</sub> ratio to 1.5 (GHSV = 14200 mL·g<sub>cat</sub><sup>-1</sup>·h<sup>-1</sup>).

489

491 Finally, the changes in CO<sub>2</sub> conversion, product selectivity, and STY of each of the tuning steps towards improving Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> catalytic performance are presented in Figure 13. We also 492 493 compared our best results with the current CO<sub>2</sub> hydrogenation literature, summarized in Table 4. In short, there is a progressive decrease in the selectivity of undesired products with each step 494 (Figure 13a). Co<sub>1.8</sub>Cu<sub>0.9</sub>AIO<sub>x</sub> reduced at 250 °C (reaction condition A) displays HCs and oxygenates 495 selectivity of 47.5%, later increased to 60.5% by tunning the reduction temperature to 400 °C 496 (reaction condition B). The decrease in space velocity from 14200 to 10625 mL h<sup>-1</sup> g<sub>cat</sub><sup>-1</sup> (reaction 497 condition C) leads to HCs and oxygenates selectivity of 71.6%, whereas changing the H<sub>2</sub>/CO<sub>2</sub> ratio 498 499 from 3 to 1.5 (reaction condition D) increases it to 77.5%. It is worth mentioning that very few of the reviewed works have worked with a space velocity above 6000 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> [9,13], which is usually 500 done to minimize the selectivity of undesired products, such as CH<sub>4</sub> and CO, yet we still managed 501 to achieve HCs and oxygenates selectivity above 70% working above 10000 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>. The 502 503 selectivity of Co<sub>1.8</sub>Cu<sub>0.9</sub>AIO<sub>x</sub> towards undesired products was one of the lowest in the current literature (Table 4). 504

505



**Figure 13**. Comparison of  $Co_{1.8}Cu_{0.9}AlO_x$  production selectivity and  $CO_2$  conversion (a) and STY (b), at 250 °C and 30 bar, after each change in reaction conditions: (A) reductive pretreatment at 250 °C (H<sub>2</sub>/CO<sub>2</sub> = 3, GHSV = 14200 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>); (B) reductive pretreatment at 400 °C(H<sub>2</sub>/CO<sub>2</sub> = 3, GHSV = 14200 mL.h<sup>-1</sup>.g<sub>cat</sub><sup>-1</sup>); (C) decreasing GSHV to 10625 mL.h<sup>-1</sup>.g<sub>cat</sub><sup>-1</sup> (H<sub>2</sub>/CO<sub>2</sub> = 3); and (D)

513	<b>Table 4.</b> Comparison of the catalytic performance in the current CO <sub>2</sub> hydrogenation literature.

		2			<b>STY</b> (**)						
Catalyst	 (የር)	(bar)	GHSV (*)	XCO₂ (%)		00	CLL.	HCs	ROH		Ref.
	(0)	(bui)	()	(70)	()	00	<b>CI</b> 14	$(C_{2+})$ $C_1$ $C_2$			
sp-CuNaFe	310	30	28800	32.3	3.32 <sup>f</sup>			55.0		10	[9]
CZA/K-CMZF	320	50	6000	42.3	2.24 <sup>d</sup>	13.8		67.6	1.3	17.4 <sup>d</sup>	[10]
4.6K-CMZF	320	50	6000	30.4	1.47 <sup>d</sup>	30.6		52.4	1.3	15.9 <sup>d</sup>	[11]
2.5K5Co-In <sub>2</sub> O <sub>3</sub>	380	40	2250 <sup>b</sup>	36.6	$0.73^{d}$	80.8		6.5 <sup>c</sup>	1.6 <sup>c</sup>	11.1 <sup>c, d</sup>	[12]
2K20Fe5Rh-SiO <sub>2</sub>	250	75	7000	18.4	0.79ª		46		13.8	15.9	[13]
Cu-CoGa-0.4	220	30	6000	17.8	1.35	2.3	43.5	1.9	27.5	23.8	[14]
CoGa1.0AI1.0O4/SiO2	270	30	3000	4.4	0.3	27.3		39.3	13.3	20.1	[15]
25Na-Co/SiO <sub>2</sub>	310	50	6000	53.2	1.1	3	61.8	24.3	12.9 <sup>e</sup>		[16]
Co <sub>1.8</sub> Cu <sub>0.9</sub> AlO <sub>x</sub>	250	30	10625	24.4	2.39	0	28.4	31.6	0.3	17.3	This Wor k
Co <sub>1.8</sub> Cu <sub>0.9</sub> AlO <sub>x</sub> <sup>g</sup>	250	30	14200	12.2	3.08	0	22.5	32.3	0.4	20.8	This Wor k

514 \* GHSV expressed in mL·g<sub>cat</sub>-1·h<sup>-1</sup> and H<sub>2</sub>/CO<sub>2</sub>: 3.

515 \*\* STY of ethanol expressed in mmol·g<sub>cat</sub>-1·h<sup>-1</sup>.

516

<sup>a</sup> calculated based on 18.8 mL·g<sup>-1</sup>·h<sup>-1</sup> of ethanol, STY after 6h <sup>b</sup> calculated based on provided flow (37.5 mL·min<sup>-1</sup>) and catalyst mass (1 g) 517

518 ° calculated based on HCs and oxygenates selectivity and distribution

519 <sup>d</sup> HAs (C<sub>2+</sub>OH) selectivity or STY

<sup>e</sup> Alcohol (ROH) selectivity 520

- 521 f calculated based on 153 mg·g<sub>cat</sub>-1·h-1
- 522 <sup>g</sup> H<sub>2</sub>/CO<sub>2</sub>: 3:2 (1.5).
- 523

Regarding the space-time yield of Co<sub>1.8</sub>Cu<sub>0.9</sub>AIO<sub>x</sub>, after reduction at 400 °C, reaction condition 524 B (250 °C, 30 bar, H<sub>2</sub>/CO<sub>2</sub>: 3, GHSV: 14200 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>), the yield of ethanol was 1.55 mmol·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> 525 (STY<sub>HCs</sub>: 3.00; STY<sub>C3+OH</sub>: 1.35). at these reaction conditions, the ethanol STY of  $Co_{1.8}Cu_{0.9}AIO_x$  is 526 higher or comparable to most of the current literature (Table 4). After tuning the space velocity, 527 reaction condition C (250 °C, 30 bar, H<sub>2</sub>/CO<sub>2</sub>: 3, GHSV: 10625 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>), the ethanol STY 528 reached 2.39 mmol.h<sup>-1</sup>.g<sub>cat</sub><sup>-1</sup> (STY<sub>HCs</sub>: 3.24; STY<sub>C3+OH</sub>: 2.15). Meanwhile, tuning the H<sub>2</sub>/CO<sub>2</sub> ratio, 529 reaction condition D (250 °C, 30 bar, H<sub>2</sub>/CO<sub>2</sub>: 1.5, GHSV: 14000 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>), led to an ethanol STY 530 of 3.08 mmol·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> (STY<sub>HCs</sub>: 3.54; STY<sub>C3+OH</sub>: 2.46). 531

Comparatively, Xu et al. [10] reported a tandem catalyst composed of a CuZnAI catalyst to 532

favor CO formation, and a K-CuMgZnFe catalyst to favor HAs formation reaching STY of 2.24 533

mmol.h<sup>-1</sup>.g<sub>cat</sub><sup>-1</sup> (310 °C, 50 bar, H<sub>2</sub>/CO<sub>2</sub>: 3, GHSV: 6000 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>) for higher alcohols (ethanol and 534  $C_{3+}$  oxygenates). Even though the tandem catalyst displayed elevated CO<sub>2</sub> conversion (42.3%), the 535 higher alcohol selectivity (17.4%) was lower than the one displayed by of Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> (39.7% for 536 reaction condition C and 44.8% for reaction condition D). In the end, Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> ethanol STY in 537 538 both reaction conditions was similar or higher than the higher alcohol (ethanol and  $C_{3+}$  oxygenates) 539 STY displayed by the tandem catalysts working at a much higher pressure (50 bar). Furthermore, Si et al. [9] reported a sputtering CuNaFe catalyst with high STY of alkene of 680 mg·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> and 540 ethanol of 153 mg·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> (310 °C, 30 bar, H<sub>2</sub>/CO<sub>2</sub>: 3, GHSV: 28800 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>), which converts 541 to 3.32 mmol·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup> (MM<sub>ethanol</sub>: 46.07 g·mol<sup>-1</sup>). The ethanol STY of sp-CuNaFe was similar to the 542 displayed by Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> at reaction condition D (H<sub>2</sub>/CO<sub>2</sub>: 1.5). The sp-CuNaFe catalyst operates 543 at double the GHSV of our experiments. It is also important to mention that, at reaction condition D, 544 we reduced the amount of H<sub>2</sub> used in the process, ergo diminishing its cost. Noteworthy, 545 Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub>, under certain conditions, displays one of the highest ethanol STY of the literature, to 546 the best of our knowledge. 547

548 Lastly, it is essential to acknowledge that the CO<sub>2</sub> hydrogenation reaction to ethanol and other higher alcohols (HAs) is currently rated at Technology Readiness Level (TRL) 1-2, indicating 549 that it is transitioning from pure to applied research [70]. Therefore, one should expect few reports 550 on catalysts, especially non-noble-based ones, with high selectivity to ethanol or other HAs, due to 551 552 the existing challenges in the  $CO_2$  hydrogenation process. Achieving high yields of products is challenging due to the thermodynamic stability of CO<sub>2</sub>, which often requires high temperatures, 553 pressures, excess overpotentials, or the use of catalysts with low availability and high costs [3.71]. 554 555 However, progress is being made over time as new active materials demonstrate the potential to 556 increase yield and selectivity to alcohols, making this process more feasible.

In this context, our work presents a non-noble-based catalyst that, under mild conditions, displayed conversion rates comparable to current results while showing superior selectivity and yield towards higher alcohols, particularly ethanol. This achievement represents a significant advancement in the field and offers promising potential for the synthesis of higher alcohols from CO<sub>2</sub>.

561

As we advance toward higher TRLs, it becomes crucial to consider implementation aspects,

including addressing separation and recycling steps, and their impact on the process's cost and emission reduction efficiency. These factors play a significant role in ensuring the practical viability and sustainability of the  $CO_2$  hydrogenation to higher alcohols, making it essential to explore efficient and cost-effective approaches for separation, recycling, and overall process optimization.

#### 566 **4. Conclusion**

Overall, Co-Cu-Al proves to be a performant catalyst to produce ethanol (and potential other 567 oxygenates) via the CO<sub>2</sub> hydrogenation reaction at mild reaction conditions.  $Co_{1.8}Cu_{0.9}AIO_x$ , at the 568 best-tested reaction conditions (250 °C, 30 bar,  $H_2/CO_2$ : 1.5, GHSV = 14000 mL·h<sup>-1</sup>·g<sub>cat</sub>-1), displays 569 570 very low CH<sub>4</sub> selectivity (22.5%) and very high selectivity towards products of interest (77.5), i.e., HCs and oxygenate. The space-time yields in these conditions are 3.54, 3.08, and 571 2.46 mmol·h<sup>-1</sup>· $g_{cat}$ <sup>-1</sup> for hydrocarbons (C<sub>2-5</sub>), ethanol, and C<sub>3+</sub>OH, respectively. The ethanol STY is 572 one the highest among related studies, that is, for continuous reactors. The yield of hydrocarbons 573 574 and  $C_{3+}OH$  also represents potential pathways for other utilizations of such catalysts. Finally, tuning the catalyst proves to be a viable alternative to improve the catalytic activity, as the CO<sub>2</sub> 575 hydrogenation reaction is shown to be sensitive to space velocity and  $H_2/CO_2$  ratio, among other 576 reaction conditions. The overall gain in ethanol space-time yield from the reaction condition A 577 578 (Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> reduced at 250°C – 250 °C, 30 bar, H<sub>2</sub>/CO<sub>2</sub>: 3, GHSV: 14000 mL·h<sup>-1</sup>·g<sub>cat</sub><sup>-1</sup>) to reaction 579 condition D (Co<sub>1.8</sub>Cu<sub>0.9</sub>AlO<sub>x</sub> reduced at 400°C – 250 °C, 30 bar,  $H_2/CO_2 = 1.5$ , GHSV = 14000 mL·h<sup>-1</sup>· $g_{cat}^{-1}$ ) was of 4.3-fold. In short, this work shed light on designing and tuning 580 high-efficiency Co-Cu bimetallic catalysts for converting CO<sub>2</sub> into chemicals of industrial interest. 581

#### 582 **5. Acknowledgments**

The authors would like to acknowledge CAPES (Coordenação de Aperfeiçoamento de Pessoal de Nível Superior – Brasil) – Finance Code 001 and COFECUB (Comitê Francês de Avaliação da Cooperação Universitária com o Brasil – Ph-C 912/18), European Union (ERDF) and Région Nouvelle Aquitaine for the financial support, as well as UFRJ (Universidade Federal do Rio de Janeiro), the Université de Poitiers and CNRS (Centre National de la Recherche Scientifique) for letting this research to be developed in their facilities and with the aid. The authors also would like to thank LabTecH2 (Laboratório de Tecnologia do Hidrogênio) at UFRJ for the XRD analyses.

#### 590 6. References

- 591 [1] W. Wang, S. Wang, X. Ma, J. Gong, Recent advances in catalytic hydrogenation of carbon dioxide, 592 Chem Soc Rev. 40 (2011) 3703–3727. https://doi.org/10.1039/c1cs15008a.
- W. Li, H. Wang, X. Jiang, J. Zhu, Z. Liu, X. Guo, C. Song, A short review of recent advances in CO 2
  hydrogenation to hydrocarbons over heterogeneous catalysts, RSC Adv. 8 (2018) 7651–7669.
  https://doi.org/10.1039/c7ra13546g.
- A.D.N. Kamkeng, M. Wang, J. Hu, W. Du, F. Qian, Transformation technologies for CO2 utilisation:
   Current status, challenges and future prospects, Chemical Engineering Journal. 409 (2021).
   https://doi.org/10.1016/j.cej.2020.128138.
- 599[4]W.N.R.W. Isahak, L.M. Shaker, A. Al-Amiery, Oxygenated Hydrocarbons from Catalytic Hydrogenation600of Carbon Dioxide, Catalysts. 13 (2023). https://doi.org/10.3390/catal13010115.
- 601[5]S.S. Ali, S.S. Ali, N. Tabassum, A review on CO2 hydrogenation to ethanol: Reaction mechanism and602experimental studies, J Environ Chem Eng. 10 (2022). https://doi.org/10.1016/j.jece.2021.106962.
- F. Zeng, C. Mebrahtu, X. Xi, L. Liao, J. Ren, J. Xie, H.J. Heeres, R. Palkovits, Catalysts design for higher
  alcohols synthesis by CO2 hydrogenation: Trends and future perspectives, Appl Catal B. 291 (2021).
  https://doi.org/10.1016/j.apcatb.2021.120073.
- F. He, S. Liu, W. Fu, C. Wang, C. Mebrahtu, R. Sun, F. Zeng, Thermodynamic Analysis of
  CO2Hydrogenation to Higher Alcohols (C2-4OH): Effects of Isomers and Methane, ACS Omega. (2022).
  https://doi.org/10.1021/acsomega.2c00502.
- S. Liu, Y. He, W. Fu, J. Chen, J. Ren, L. Liao, R. Sun, Z. Tang, C. Mebrahtu, F. Zeng, Hetero-site cobalt
  catalysts for higher alcohols synthesis by CO2hydrogenation: A review, Journal of CO2 Utilization. 67
  (2023). https://doi.org/10.1016/j.jcou.2022.102322.
- [9] Z. Si, L. Wang, Y. Han, J. Yu, Q. Ge, C. Zeng, J. Sun, Synthesis of Alkene and Ethanol in CO2
  Hydrogenation on a Highly Active Sputtering CuNaFe Catalyst, ACS Sustain Chem Eng. 10 (2022)
  14972–14979. https://doi.org/10.1021/acssuschemeng.2c05450.
- [10] D. Xu, H. Yang, X. Hong, G. Liu, S.C. Edman Tsang, Tandem Catalysis of Direct CO2Hydrogenation to
   Higher Alcohols, ACS Catal. 11 (2021) 8978–8984. https://doi.org/10.1021/acscatal.1c01610.
- 617 [11] D. Xu, M. Ding, X. Hong, G. Liu, Mechanistic aspects of the role of K promotion on Cu-Fe-based
  618 catalysts for higher alcohol synthesis from CO2 hydrogenation, ACS Catal. 10 (2020) 14516–14526.
  619 https://doi.org/10.1021/acscatal.0c03575.
- T. Witoon, T. Numpilai, S. Nijpanich, N. Chanlek, P. Kidkhunthod, C.K. Cheng, K.H. Ng, D.V.N. Vo, S.
   Ittisanronnachai, C. Wattanakit, M. Chareonpanich, J. Limtrakul, Enhanced CO2 hydrogenation to
   higher alcohols over K-Co promoted In2O3 catalysts, Chemical Engineering Journal. 431 (2022).
   https://doi.org/10.1016/j.cej.2021.133211.
- A. Goryachev, A. Pustovarenko, G. Shterk, N.S. Alhajri, A. Jamal, M. Albuali, L. van Koppen, I.S. Khan,
  A. Russkikh, A. Ramirez, T. Shoinkhorova, E.J.M. Hensen, J. Gascon, A Multi-Parametric Catalyst
  Screening for CO2 Hydrogenation to Ethanol, ChemCatChem. 13 (2021) 3324–3332.
  https://doi.org/10.1002/cctc.202100302.
- 628 [14] G. Zhang, G. Fan, L. Zheng, F. Li, Ga-Promoted CuCo-Based Catalysts for Efficient CO2 Hydrogenation
   629 to Ethanol: The Key Synergistic Role of Cu-CoGaOx Interfacial Sites, ACS Appl Mater Interfaces. 14
   630 (2022) 35569–35580. https://doi.org/10.1021/acsami.2c07252.
- [15] K. An, S. Zhang, H. Wang, N. Li, Z. Zhang, Y. Liu, Co0–Coδ+ active pairs tailored by Ga-Al-O spinel for
  CO2-to-ethanol synthesis, Chemical Engineering Journal. 433 (2022) 134606.
  https://doi.org/10.1016/j.cej.2022.134606.

- 634 [16] S. Zhang, Z. Wu, X. Liu, Z. Shao, L. Xia, L. Zhong, H. Wang, Y. Sun, Tuning the interaction between Na
  635 and Co2C to promote selective CO2 hydrogenation to ethanol, Appl Catal B. 293 (2021).
  636 https://doi.org/10.1016/j.apcatb.2021.120207.
- M. Wang, G. Zhang, J. Zhu, W. Li, J. Wang, K. Bian, Y. Liu, F. Ding, C. Song, X. Guo, Unraveling the
   tunable selectivity on cobalt oxide and metallic cobalt sites for CO2 hydrogenation, Chemical
   Engineering Journal. 446 (2022). https://doi.org/10.1016/j.cej.2022.137217.
- K. Sun, X. Gao, Y. Bai, M. Tan, G. Yang, Y. Tan, Synergetic catalysis of bimetallic copper-cobalt
  nanosheets for direct synthesis of ethanol and higher alcohols from syngas, Catal Sci Technol. 8 (2018)
  3936–3947. https://doi.org/10.1039/c8cy01074a.
- 643 [19] S. Liu, C. Yang, S. Zha, D. Sharapa, F. Studt, Z.J. Zhao, J. Gong, Moderate Surface Segregation Promotes
  644 Selective Ethanol Production in CO2 Hydrogenation Reaction over CoCu Catalysts, Angewandte
  645 Chemie International Edition. 61 (2022). https://doi.org/10.1002/anie.202109027.
- [20] S. Liu, H. Zhou, Q. Song, Z. Ma, Synthesis of higher alcohols from CO 2 hydrogenation over Mo–Co–K 646 647 sulfide-based catalysts, Taiwan Inst Chem 76 (2017)J Eng. 18-26. 648 https://doi.org/10.1016/j.jtice.2017.04.007.
- M. Ao, G.H. Pham, J. Sunarso, F. Li, Y. Jin, S. Liu, Effects of alkali promoters on tri-metallic Co-Ni-Cu based perovskite catalyst for higher alcohol synthesis from syngas, Catal Today. 355 (2020) 26–34.
   https://doi.org/10.1016/j.cattod.2019.06.061.
- R.A. Iloy, K. Jalama, Effect of operating temperature, pressure and potassium loading on the
  performance of silica-supported Cobalt catalyst in CO2 hydrogenation to hydrocarbon fuel, Catalysts.
  9 (2019). https://doi.org/10.3390/catal9100807.
- W. Aslam, J.N. Beltramini, L.A. Atanda, N.R. Batalha, T.U. Schülli, M. Konarova, The catalytic activity of
  KMoCo carbon spheres for higher alcohols synthesis from syngas, Appl Catal A Gen. 605 (2020)
  117803. https://doi.org/10.1016/j.apcata.2020.117803.
- L. Wang, L. Wang, J. Zhang, X. Liu, H. Wang, W. Zhang, Q. Yang, J. Ma, X. Dong, S.J. Yoo, J. Kim, X.
   Meng, F. Xiao, Selective Hydrogenation of CO2 to Ethanol over Cobalt Catalysts, Angewandte Chemie
   International Edition. 130 (2018) 6212–6216. https://doi.org/10.1002/ange.201800729.
- K. An, S. Zhang, J. Wang, Q. Liu, Z. Zhang, Y. Liu, A highly selective catalyst of Co/La4Ga2O9 for CO2
  hydrogenation to ethanol, Journal of Energy Chemistry. 56 (2021) 486–495.
  https://doi.org/10.1016/j.jechem.2020.08.045.
- [26] D. Xu, Y. Wang, M. Ding, X. Hong, G. Liu, S.C.E. Tsang, Advances in higher alcohol synthesis from CO2
   hydrogenation, Chem. 7 (2021) 849–881. https://doi.org/10.1016/j.chempr.2020.10.019.
- D. dos S. Lima, Y.R. Dias, O.W. Perez-Lopez, CO2methanation over Ni-Al and Co-Al LDH-derived 666 [27] 667 catalysts: The role of basicity, Sustain Energy Fuels. 4 (2020) 5747-5756. https://doi.org/10.1039/d0se01059f. 668
- [28] Z. Liu, X. Gao, B. Liu, W. Song, Q. Ma, T. sheng Zhao, X. Wang, J.W. Bae, X. Zhang, J. Zhang, Highly
  stable and selective layered Co-Al-O catalysts for low-temperature CO2 methanation, Appl Catal B.
  310 (2022). https://doi.org/10.1016/j.apcatb.2022.121303.
- 672 [29] L. Wang, S. He, L. Wang, Y. Lei, X. Meng, F.-S. Xiao, Cobalt–Nickel Catalysts for Selective Hydrogenation 673 ACS Catal. of Carbon Dioxide into Ethanol, 9 (2019) 11335-11340. 674 https://doi.org/10.1021/acscatal.9b04187.
- R. Benhiti, A. Ait Ichou, A. Zaghloul, R. Aziam, G. Carja, M. Zerbet, F. Sinan, M. Chiban, Synthesis,
  characterization, and comparative study of MgAl-LDHs prepared by standard coprecipitation and urea
  hydrolysis methods for phosphate removal, Environmental Science and Pollution Research. 27 (2020)
  45767–45774. https://doi.org/10.1007/s11356-020-10444-5.

- [31] C. Göbel, S. Schmidt, C. Froese, Q. Fu, Y.T. Chen, Q. Pan, M. Muhler, Structural evolution of bimetallic
  Co-Cu catalysts in CO hydrogenation to higher alcohols at high pressure, J Catal. 383 (2020) 33–41.
  https://doi.org/10.1016/j.jcat.2020.01.004.
- [32] K. Kupková, P. Topka, J. Balabánová, M. Koštejn, K. Jirátová, J.-M. Giraudon, J.-F. Lamonier, J. Maixner,
   F. Kovanda, Cobalt-Copper Oxide Catalysts for VOC Abatement: Effect of Co:Cu Ratio on Performance
   in Ethanol Oxidation, Catalysts. 13 (2023) 107. https://doi.org/10.3390/catal13010107.
- [33] K. Jirátová, F. Kovanda, J. Ludvíková, J. Balabánová, J. Klempa, Total oxidation of ethanol over layered
   double hydroxide-related mixed oxide catalysts: Effect of cation composition, Catal Today. 277 (2016)
   61–67. https://doi.org/10.1016/j.cattod.2015.10.036.
- [34] L. Obalová, K. Karásková, K. Jirátová, F. Kovanda, Effect of potassium in calcined Co-Mn-Al layered
  double hydroxide on the catalytic decomposition of N2O, Appl Catal B. 90 (2009) 132–140.
  https://doi.org/10.1016/j.apcatb.2009.03.002.
- [35] K. Karásková, K. Pacultová, K. Jirátová, D. Fridrichová, M. Koštejn, L. Obalová, K-Modified Co–Mn–Al
   Mixed Oxide—Effect of Calcination Temperature on N2O Conversion in the Presence of H2O and NOx,
   Catalysts. 10 (2020) 1134. https://doi.org/10.3390/catal10101134.
- F. Kefif, K. Ezziane, A. Bahmani, N. Bettahar, S. Mayouf, Evans Blue dye removal from contaminated water on calcined and uncalcined Cu-Al-CO3 layered double hydroxide materials prepared by coprecipitation, Bulletin of Materials Science. 42 (2019). https://doi.org/10.1007/s12034-018-1694 z.
- [37] T.P. Sulmonetti, B. Hu, S. Lee, P.K. Agrawal, C.W. Jones, Reduced Cu-Co-Al Mixed Metal Oxides for the
   Ring-Opening of Furfuryl Alcohol to Produce Renewable Diols, ACS Sustain Chem Eng. 5 (2017) 8959–
   8969. https://doi.org/10.1021/acssuschemeng.7b01769.
- [38] C.D.O.P. Teixeira, S.D.S. Montani, L.A. Palacio, F.M.Z. Zotin, The effect of preparation methods on the
   thermal and chemical reducibility of Cu in Cu-Al oxides, Dalton Transactions. 47 (2018) 10989–11001.
   https://doi.org/10.1039/c8dt01150h.
- [39] C. Wan, X. Wei, G. Cai, D. Li, Y. Zhan, Y. Xiao, L. Jiang, Hydrotalcite-derived aluminum-doped cobalt
   oxides for catalytic benzene combustion: Effect of calcination atmosphere, Molecular Catalysis. 520
   (2022). https://doi.org/10.1016/j.mcat.2022.112160.
- [40] C. Chen, L. Liu, Y. Li, W. Li, L. Zhou, Y. Lan, Y. Li, Insight into heterogeneous catalytic degradation of sulfamethazine by peroxymonosulfate activated with CuCo2O4 derived from bimetallic oxalate, Chemical Engineering Journal. 384 (2020) 123257. https://doi.org/10.1016/j.cej.2019.123257.
- Y. Wei, S. Li, J. Jing, M. Yang, C. Jiang, W. Chu, Synthesis of Cu–Co Catalysts for Methanol
   Decomposition to Hydrogen Production via Deposition–Precipitation with Urea Method, Catal Letters.
   149 (2019) 2671–2682. https://doi.org/10.1007/s10562-019-02731-9.
- [42] W. Kim, K.K. Mohaideen, D.J. Seo, W.L. Yoon, Methanol-steam reforming reaction over Cu-Al-based
  catalysts derived from layered double hydroxides, Int J Hydrogen Energy. 42 (2017) 2081–2087.
  https://doi.org/10.1016/j.ijhydene.2016.11.014.
- [43] H.R. Prakruthi, B.M. Chandrashekara, J.P. Jai, Y.S. Bhat, Hydrogenation efficiency of highly porous Cu Al oxides derived from dealuminated LDH in the conversion of furfural to furfuryl alcohol, Journal of
   Industrial and Engineering Chemistry. 62 (2018) 96–105. https://doi.org/10.1016/j.jiec.2017.12.048.
- [44] C.L.O. Corrêa, Y.E. Licea, L.A. Palacio, F.M.Z. Zotin, Effect of composition and thermal treatment in catalysts derived from Cu-Al hydrotalcites-like compounds in the NO reduction by CO, Catal Today.
   289 (2017) 133–142. https://doi.org/10.1016/j.cattod.2016.08.023.
- [45] Q. Zhao, Y. Ge, K. Fu, N. Ji, C. Song, Q. Liu, Oxidation of acetone over Co-based catalysts derived from
   hierarchical layer hydrotalcite: Influence of Co/Al molar ratios and calcination temperatures,
   Chemosphere. 204 (2018) 257–266. https://doi.org/10.1016/j.chemosphere.2018.03.198.

- R. Ramos, A. Grigoropoulos, N. Perret, M. Zanella, A.P. Katsoulidis, T.D. Manning, J.B. Claridge, M.J.
   Rosseinsky, Selective conversion of 5-hydroxymethylfurfural to cyclopentanone derivatives over Cu Al2O3 and Co-Al2O3 catalysts in water, Green Chemistry. 19 (2017) 1701–1713.
   https://doi.org/10.1039/c7gc00315c.
- F. Teodorescu, A.I. Slabu, O.D. Pavel, R. Zăvoianu, A comparative study on the catalytic activity of ZnAl,
   NiAl, and CoAl mixed oxides derived from LDH obtained by mechanochemical method in the synthesis
   of 2-methylpyrazine, Catal Commun. 133 (2020). https://doi.org/10.1016/j.catcom.2019.105829.
- 732 N. Aider, F. Touahra, F. Bali, B. Djebarri, D. Lerari, K. Bachari, D. Halliche, Improvement of catalytic [48] stability and carbon resistance in the process of CO2 reforming of methane by CoAl and CoFe 733 734 hydrotalcite-derived catalysts, Int J Hydrogen Energy. 43 (2018) 8256-8266. 735 https://doi.org/10.1016/j.ijhydene.2018.03.118.
- R. Berenguer, C. Quijada, A. la Rosa-Toro, E. Morallón, Electro-oxidation of cyanide on active and nonactive anodes: Designing the electrocatalytic response of cobalt spinels, Sep Purif Technol. 208 (2019)
  42–50. https://doi.org/10.1016/j.seppur.2018.05.024.
- P. Paknahad, M. Askari, M. Ghorbanzadeh, Characterization of nanocrystalline CuCo2O4 spinel
   prepared by sol-gel technique applicable to the SOFC interconnect coating, Applied Physics A. 119
   (2015) 727-734. https://doi.org/10.1007/s00339-015-9021-7.
- [51] B. Kreitz, G.D. Wehinger, C.F. Goldsmith, T. Turek, Microkinetic Modeling of the CO2Desorption from
   Supported Multifaceted Ni Catalysts, Journal of Physical Chemistry C. 125 (2021) 2984–3000.
   https://doi.org/10.1021/acs.jpcc.0c09985.
- 745 [52] J.A. Delgado, J.L. Sotelo, J.M. Gómez, P. Gómez, Estimation of Adsorption Parameters from 746 Temperature-Programmed Desorption Thermograms: Application to the Adsorption of Carbon 747 Dioxide onto Alumina, Adsorption Science & Technology. (2007) 113-128. 25 748 https://doi.org/10.1260/026361707782398146.
- J.A. Delgado, J.M. Gómez, Estimation of adsorption parameters from temperature-programed desorption thermograms: Application to the adsorption of carbon dioxide onto Na-and H-mordenite,
   Langmuir. 21 (2005) 9555–9561. https://doi.org/10.1021/la050966u.
- M. Xu, E. Iglesia, Readsorption and Adsorption-Assisted Desorption of CO2 on Basic Solids, J Phys
   Chem B. 102 (1998) 961–966. https://doi.org/10.1021/jp972200b.
- [55] Z. Wang, C. Yang, X. Li, X. Song, C. Pei, Z.J. Zhao, J. Gong, The role of CO2 dissociation in CO2
   hydrogenation to ethanol on CoCu/silica catalysts, Nano Res. (2022). https://doi.org/10.1007/s12274 022-5092-x.
- Z. Shi, H. Yang, P. Gao, X. Li, L. Zhong, H. Wang, H. Liu, W. Wei, Y. Sun, Direct conversion of CO2 to
  long-chain hydrocarbon fuels over K-promoted CoCu/TiO2 catalysts, Catal Today. 311 (2018) 65–73.
  https://doi.org/10.1016/j.cattod.2017.09.053.
- T.H. Nguyen, H.B. Kim, E.D. Park, CO and CO2 Methanation over CeO2-Supported Cobalt Catalysts,
   Catalysts. 12 (2022). https://doi.org/10.3390/catal12020212.
- 762 [58] O. Tursunov, L. Kustov, Z. Tilyabaev, Methanol synthesis from the catalytic hydrogenation of CO2 over
   763 CuO–ZnO supported on aluminum and silicon oxides, J Taiwan Inst Chem Eng. 78 (2017) 416–422.
   764 https://doi.org/10.1016/j.jtice.2017.06.049.
- 765 [59] H. Ronduda, M. Zybert, W. Patkowski, A. Ostrowski, P. Jodłowski, D. Szymański, L. Kępiński, W. Raróg-Pilecka, A high performance barium-promoted cobalt catalyst supported on magnesium-lanthanum 766 767 mixed oxide for ammonia synthesis, RSC Adv. 11 (2021) 14218-14228. https://doi.org/10.1039/d1ra01584b. 768
- 769 [60] C. Liu, X. Guo, Q. Guo, D. Mao, J. Yu, G. Lu, Methanol synthesis from CO2 hydrogenation over copper
  770 catalysts supported on MgO-modified TiO2, J Mol Catal A Chem. 425 (2016) 86–93.
  771 https://doi.org/10.1016/j.molcata.2016.09.032.

- T.A. Le, M.S. Kim, S.H. Lee, E.D. Park, CO and CO2 Methanation Over Supported Cobalt Catalysts, Top
   Catal. 60 (2017) 714–720. https://doi.org/10.1007/s11244-017-0788-y.
- N.D. Subramanian, G. Balaji, C.S.S.R. Kumar, J.J. Spivey, Development of cobalt-copper nanoparticles
  as catalysts for higher alcohol synthesis from syngas, Catal Today. 147 (2009) 100–106.
  https://doi.org/10.1016/j.cattod.2009.02.027.
- K. Sun, Z. Liu, S. Song, W. Liu, P. Wang, T. Zhang, Y. Xue, Y. Wang, Y. Tan, Effect of Hydroxyl Groups on CuCoMg Nanosheets for Ethanol and Higher Alcohol Synthesis from Syngas, Ind Eng Chem Res. 60 (2021) 2388–2399. https://doi.org/10.1021/acs.iecr.0c05204.
- [64] S. Bai, Q. Shao, P. Wang, Q. Dai, X. Wang, X. Huang, Highly Active and Selective Hydrogenation of CO
  2 to Ethanol by Ordered Pd Cu Nanoparticles, (2017) 23–26. https://doi.org/10.1021/jacs.7b03101.
- [65] J. Zheng, K. An, J. Wang, J. Li, Y. Liu, Direct synthesis of ethanol via CO2 hydrogenation over the Co/La Ga-O composite oxide catalyst, Journal of Fuel Chemistry and Technology. 47 (2019) 697–708.
   https://doi.org/10.1016/S1872-5813(19)30031-3.
- 785 [66] K. Zhao, M. Calizzi, E. Moioli, M. Li, A. Borsay, L. Lombardo, R. Mutschler, W. Luo, A. Züttel, Unraveling 786 and optimizing the metal-metal oxide synergistic effect in a highly active Cox(CoO)1-x catalyst for CO2 787 Chemistry. 241-250. hydrogenation, Journal of Energy 53 (2020) 788 https://doi.org/10.1016/j.jechem.2020.05.025.
- [67] Z. He, Q. Qian, Z. Zhang, Q. Meng, H. Zhou, Z. Jiang, B. Han, Synthesis of higher alcohols from CO2 hydrogenationovera PtRu/Fe2O3 catalyst under supercritical condition, Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences.Trans.R.Soc.A. 373 (2015) 1–10. https://doi.org/http://dx.doi.org/10.1098/rsta.2015.0006.
- [68] B. Liu, B. Ouyang, Y. Zhang, K. Lv, Q. Li, Y. Ding, J. Li, Effects of mesoporous structure and Pt promoter
  on the activity of Co-based catalysts in low-temperature CO2 hydrogenation for higher alcohol
  synthesis, J Catal. 366 (2018) 91–97. https://doi.org/10.1016/j.jcat.2018.07.019.
- [69] Z. He, Q. Qian, J. Ma, Q. Meng, H. Zhou, J. Song, Z. Liu, B. Han, Water-Enhanced Synthesis of Higher
   Alcohols from CO2 Hydrogenation over a Pt/Co3O4 Catalyst under Milder Conditions, Angewandte
   Chemie International Edition. 55 (2016) 737–741. https://doi.org/10.1002/anie.201507585.
- R. Chauvy, N. Meunier, D. Thomas, G. De Weireld, Selecting emerging CO2 utilization products for
  short- to mid-term deployment, Appl Energy. 236 (2019) 662–680.
  https://doi.org/10.1016/j.apenergy.2018.11.096.
- 802 [71] Y. He, S. Liu, W. Fu, J. Chen, Y. Zhai, X. Bi, J. Ren, R. Sun, Z. Tang, C. Mebrahtu, F. Zeng, Assessing the 803 efficiency of CO2 hydrogenation for emission reduction: Simulating ethanol synthesis process as a 804 Research case study, Chemical Engineering and Design. 195 (2023) 106-115. 805 https://doi.org/10.1016/j.cherd.2023.05.043.
- 806
- 807

#### 809 7. Appendix A (Supplementary Material)

Table S1. Reaction data for all presented catalysts and reaction conditions. All catalytic tests were 810 811 conducted at 30 bar.

	<b>-</b> a	<b>-</b> a	_		V		Selectivity (%)						Yield (mmol.g <sub>cat</sub> -1.h-1)				
Catalyst			R b		Xco2	~~~	<u>сп</u>	HCs		ROH		HCs		ROH			
	$(\mathbf{C})$	(0)		()	(70)	CU	СП4	(C <sub>2-5</sub> )	<b>C</b> <sub>1</sub>	<b>C</b> <sub>2</sub>	<b>C</b> <sub>3+</sub>	(C <sub>2-5</sub> )	<b>C</b> <sub>1</sub>	<b>C</b> <sub>2</sub>	<b>C</b> <sub>3+</sub>		
Cu <sub>2.6</sub> AIO <sub>x</sub>	250	250	3:1	14200	8.8	78.8	0	0	21	0	0	0	2.78	0	0		
Co <sub>1.3</sub> Cu <sub>1.3</sub> AlO <sub>x</sub>	250	250	3:1	14200	14.6	0	68.9	19.6	1.6	5.4	4.5	1.77	0.34	0.59	0.32		
$Co_{1.8}Cu_{0.9}AIO_x$	250	250	3:1	14200	11.3	0	52.5	31.0	0.4	8.4	7.7	2.12	0.07	0.71	0.43		
Co <sub>2.6</sub> AIO <sub>x</sub>	250	250	3:1	14200	5.3	0	59	18.8	7.2	6.7	8.3	0.63	0.56	0.26	0.21		
Co <sub>2.6</sub> AIO <sub>x</sub>	300	250	3:1	14200	6.9	0	53.4	28.9	2.0	6.3	9.4	1.11	0.2	0.32	0.33		
Co <sub>2.6</sub> AIO <sub>x</sub>	400	250	3:1	14200	9.8	0	44.1	35.4	0.3	10.6	9.6	2.03	0.04	0.77	0.46		
Co <sub>2.6</sub> AIO <sub>x</sub>	500	250	3:1	14200	51.8	0	90.1	5.6	0.0	2.1	2.2	1.74	0	0.79	0.57		
$Co_{1.8}Cu_{0.9}AlO_x$	300	250	3:1	14200	12.6	0	45.1	30.5	0.7	10.6	13.1	2.18	0.13	0.97	0.79		
$Co_{1.8}Cu_{0.9}AlO_x$	400	250	3:1	14200	17.1	0	39.5	31.3	0.7	12.0	16.5	3	0.18	1.55	1.35		
$Co_{1.8}Cu_{0.9}AlO_x$	500	250	3:1	14200	12.0	0	47.8	34.9	0.6	8.6	8.1	2.35	0.11	0.78	0.51		
$Co_{1.8}Cu_{0.9}AlO_x$	400	200	3:1	14200	7.1	0	53.4	21.8	0.4	12.3	12.1	0.95	0.04	0.65	0.43		
$Co_{1.8}Cu_{0.9}AIO_x$	400	300	3:1	14200	30.1	9.4	45	31.2	3.4	4.1	6.9	4.84	1.52	0.91	1.03		
Co <sub>2.6</sub> AIO <sub>x</sub>	400	200	3:1	14200	3.0	0	49	19.3	2.3	16.5	12.9	0.34	0.1	0.37	0.19		
Co <sub>2.6</sub> AIO <sub>x</sub>	400	300	3:1	14200	19.5	14.2	40.6	28.7	5.1	5.5	5.9	3.25	1.49	0.81	0.6		
$Co_{1.8}Cu_{0.9}AIO_x$	400	250	3:1	10625	24.4	0	28.4	31.6	0.3	17.3	22.4	3.24	0.08	2.39	2.15		
Co <sub>1.8</sub> Cu <sub>0.9</sub> AlO <sub>x</sub>	400	250	3:2	14200	12.2	0	22.5	32.3	0.4	20.8	24.0	3.54	0.12	3.08	2.46		

 $^{\rm a}$  T\_R: reduction temperature; and T: reaction temperature.

812 813 814 <sup>b</sup> R: H<sub>2</sub>/CO<sub>2</sub> ratio.

<sup>c</sup> GHSV expressed in mL.g<sub>cat</sub><sup>-1</sup>.h<sup>-1</sup>.

815

816 Table S2. Hydrocarbons yield distribution for all presented catalysts and reaction conditions. All catalytic tests were conducted at 30 bar. 817

Catalyst	T <sub>R</sub> a	Ta	R	GHSV	X <sub>CO2</sub>	HCs Yield (mmol.g <sub>cat</sub> <sup>-1</sup> .h <sup>-1</sup> ) <sup>d</sup>								
Catalyst	(°C)	(°C)	b	(c)	(%)	C2=	C2	C3=	C3	C4=	C4	C5=	C5	
Cu <sub>2.6</sub> AlO <sub>x</sub>	250	250	3:1	14200	8.8	0	0	0	0	0	0	0	0	
$Co_{1.3}Cu_{1.3}AIO_x$	250	250	3:1	14200	14.6	0.00	1.06	0.01	0.70	0	0	0	0	
$Co_{1.8}Cu_{0.9}AIO_x$	250	250	3:1	14200	11.3	0.02	1.14	0.21	0.76	0	0	0	0	
Co <sub>2.6</sub> AIO <sub>x</sub>	250	250	3:1	14200	5.3	0	0.42	0	0.21	0	0	0	0	
Co <sub>2.6</sub> AIO <sub>x</sub>	300	250	3:1	14200	6.9	0.1	0.43	0.27	0.18	0.07	0.02	0.01	0.03	
Co <sub>2.6</sub> AIO <sub>x</sub>	400	250	3:1	14200	9.8	0	1.02	0.21	0.72	0.04	0.04	0	0	
Co <sub>2.6</sub> AIO <sub>x</sub>	500	250	3:1	14200	51.8	0.03	1.06	0.15	0.37	0.06	0.02	0.02	0.03	
Co <sub>1.8</sub> Cu <sub>0.9</sub> AlO <sub>x</sub>	300	250	3:1	14200	12.6	0.03	1.09	0.31	0.64	0.07	0.04	0	0	
$Co_{1.8}Cu_{0.9}AlO_x$	400	250	3:1	14200	17.1	0.13	1.3	0.56	0.73	0.19	0.07	0.01	0.01	
$Co_{1.8}Cu_{0.9}AlO_x$	500	250	3:1	14200	12.0	0.12	1	0.36	0.63	0.09	0.1	0.02	0.03	
Co <sub>1.8</sub> Cu <sub>0.9</sub> AlO <sub>x</sub>	400	200	3:1	14200	7.1	0.03	0.51	0.04	0.33	0.01	0.03	0	0	
Co <sub>1.8</sub> Cu <sub>0.9</sub> AlO <sub>x</sub>	400	300	3:1	14200	30.1	0.45	1.68	0.95	0.91	0.33	0.28	0.06	0.18	
Co <sub>2.6</sub> AIO <sub>x</sub>	400	200	3:1	14200	3.0	0	0.17	0	0.15	0	0.02	0	0	
Co <sub>2.6</sub> AIO <sub>x</sub>	400	300	3:1	14200	19.5	0.52	1.19	0.36	0.89	0.15	0.12	0.01	0.01	
Co <sub>1.8</sub> Cu <sub>0.9</sub> AlO <sub>x</sub>	400	250	3:1	10625	24.4	0.17	1.16	0.83	0.59	0.25	0.17	0.03	0.04	
Co <sub>1.8</sub> Cu <sub>0.9</sub> AlO <sub>x</sub>	400	250	3:2	14200	12.2	0.29	1.29	0.85	0.63	0.29	0.09	0.04	0.06	

 $^{\rm a}$  T\_R: reduction temperature; and T: reaction temperature.

<sup>b</sup> R: H<sub>2</sub>/CO<sub>2</sub> ratio.

<sup>c</sup> GHSV expressed in mL.g<sub>cat</sub><sup>-1</sup>.h<sup>-1</sup>.
 <sup>d</sup> HCs are separated by the number of carbons and whether they are paraffins (C2, C3) or olefins (C2=, C3=).