

Collisions against obstacles while skiing: Typology of victims and impact conditions

Marine Dorsemaine, M. Llari, S. Riveill, J.-D. Laporte, C. Jacot, C. Masson,

P.-J. Arnoux

To cite this version:

Marine Dorsemaine, M. Llari, S. Riveill, J.-D. Laporte, C. Jacot, et al.. Collisions against obstacles while skiing: Typology of victims and impact conditions. Science & Sports, 2023, 38 (8), pp.807-817. 10.1016/j.scispo.2022.07.010. hal-04532792

HAL Id: hal-04532792 <https://hal.science/hal-04532792v1>

Submitted on 4 Apr 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

COLLISIONS AGAINST OBSTACLES WHILE SKIING: WHICH USERS FOR WHICH IMPACT CONDITIONS?

COLLISIONS CONTRE OBSTACLES EN SKI ALPIN : PROFILS ET CONDITIONS D'IMPACT

ABSTRACT

 Objective: despite their potential severity, collisions against obstacles on alpine ski slopes remain poorly described and a better understanding of these accidents is required to improve the protection of users on the slopes. Therefore, this study aimed to characterize the impact conditions applied to the human body during collisions against obstacles by coupling multibody simulations while skiing with an epidemiological analysis to model representative scenarios. **Equipment and methods:** in France, between 2014 and 2019, 201805 snow sports accidents led to ski patrol interventions and/or ski resort doctors' consultations. The 3393 collisions against obstacles included in these accidents were analyzed (population, injuries, accident conditions). Based on this characterization, 1080 multibody simulations of collisions against obstacles were performed. They included various skier speed and size, slope angle, obstacle type and distance at impact to better understand loading conditions applied to the human body. **Results**: victims of collisions against obstacles were frequently skiers, young people, wore a helmet and head/neck and trunk were injured in up to 46% of the accidents. The numerical simulations confirmed head protection as a priority, due to the high frequency of head impacts (68%), especially as the first impact location (47%), associated with high normal impact speeds 46 (30 \pm 15 km/h). Trunk impacts (63% of the accidents) also appeared at risk. Moreover, the initial speed and the distance to the obstacle are two key factors influencing impact severity and should be considered in the slopes' layout. Thus, this work provided an original epidemiological characterization of victims of collisions against obstacles and of their injuries. The large database of numerical simulations identifies the impact conditions of representative accidents. These data and impact conditions are key elements for the evaluation and design of safety mattress, for standards revision, for slopes' layout, for the reconstruction of a specific collision against obstacle and for the evaluation of the potential severity of such accidents.

RÉSUMÉ

 Objectif : malgré leur sévérité potentielle, les collisions contre obstacles survenant sur les domaines skiables alpins demeurent peu étudiées et une meilleure compréhension de ces accidents est requise afin d'améliorer la protection des usagers fréquentant les domaines skiables. Ainsi, cette étude vise à caractériser les conditions d'impact subies par le corps humain lors de collisions contre obstacles en associant des simulations multi-corps avec une analyse épidémiologique permettant de modéliser des scénarios d'accidents représentatifs. **Matériels et méthodes :** en France entre 2014 et 2019, 201805 accidents de sports d'hiver ont mené à une intervention des pisteurs-secouristes et/ou à une consultation dans un cabinet médical en station. Les 3393 collisions contre obstacles inclues dans ces accidents ont été analysés (population, blessures, conditions d'accident). Puis 1080 simulations multi-corps de collisions contre obstacles ont été réalisées à partir de cette caractérisation épidémiologique. Elles comprenaient différentes vitesses et morphologies de skieurs, pentes de piste, types et distances jusqu'à l'obstacle afin de mieux comprendre les conditions d'impact appliquées au corps humain. **Résultats :** les victimes des collisions contre obstacles étaient souvent des skieurs, des personnes jeunes, qui portent un casque et jusqu'à 46% des accidents ont induit des blessures aux régions tête/cou et torse. Les simulations numériques ont confirmé la nécessité de cibler la protection de la tête, de par la forte fréquence des impacts de la tête (68%), en particulier en 74 première région d'impact (47%), et des vitesses d'impact normales élevées (30 \pm 15 km/h). Les impacts du torse (63% des accidents) sont également à risque. De plus, la vitesse initiale du skieur et la distance avant l'obstacle sont deux paramètres influençant la gravité de l'impact et devraient être pris en compte dans l'aménagement des pistes. Ainsi, cette étude apporte une caractérisation épidémiologique des victimes des collisions contre obstacles et de leurs blessures. La grande base de données de simulations numériques a également permis d'identifier les conditions d'impacts d'accidents représentatifs. Ces données et conditions d'impact sont essentielles pour l'évaluation et la conception des matelas de protection, pour la révision des normes, pour l'aménagement des pistes, pour la reconstruction d'un accident précis et pour l'évaluation de la gravité potentielle de ces accidents.

KEYWORDS: snow sport; biomechanics; epidemiology; computer simulation; safety

MOTS CLÉS : sport d'hiver ; biomécanique ; épidémiologie ; simulation numérique ; sécurité

1. Introduction

 Collisions against obstacles (CO) represent around 1% of ski patrol interventions on French ski slopes [1] and 4.5% of the accidents on ski slopes in the USA [2]. However, they are a major safety issue on ski slopes as they can lead to severe traumatic brain injuries(TBI) [3], and deaths on ski slopes (from 35% to more than 70% according to Ruedl et al. [4] and Shealy et al. [5]). Despite this potential severity, CO are poorly described. CO were mostly mentioned as accident type but the analyses were not focused on them. Dedicated studies on CO were conducted more than 30 years ago [6,7] and snow sports activities have evolved a lot since, through equipment, population and behavior on ski slopes. Most of the more recent studies either focused on global epidemiological analysis [2] or specific accident severity (such as deaths on slopes [4,5]), or specific injury location (like head injuries [3]). Head impact conditions and the risk evaluation of head injury were focused for various scenarios of CO while skiing through human multibody simulations [8]. Nevertheless, impact conditions on other body segments during these CO remain unknown.

 Nowadays, in regards to injury severity up to fatal accidents observed on ski slopes, CO prevention is becoming a key point for ski resorts. It is also illustrated by numerous safety equipment placed in skiing areas on or close to obstacles to protect users from a collision against them and by many questions rising about the efficiency of such devices. The performances of safety equipment dedicated to CO protection are addressed through existing regulation standards (NF S52-105 French standard for safety mattresses [9]). The safety performances of these devices were also investigated by some studies [10,11]. However, there is little data available on CO (impact speed, impact location and injuries caused), the consistency between normative impact conditions and the reality of impacts on ski slopes is asked.

 Hence the main research question who thrust this work was about the need to get a better comprehension of CO. Therefore, this study aimed at providing a description of the impacts of collisions against obstacles in snow sports by combining epidemiological data investigations and numerical simulations to investigate the most relevant accident scenarios. The final objective of this work was to provide a relevant description of the impact conditions (velocity and location) applied to the human body during a CO.

-
-

2. Materials and methods

2.1. Epidemiological analysis

 Medical and ski patrol networks are powerful tools to provide robust data for an epidemiological analysis of accidents on ski slopes. In France, three entities deal with snow sport accidents: the doctors in ski resort medical offices [12], the ski patrollers [1] and the doctors in hospitals in the valleys. None of these groups sees the entire injured population: the most severe accidents leading to a direct transfer to the hospital are seen by ski patrollers and hospital doctors but not by ski resort doctors. The less severe accidents, where the users (skiers or snowboarders) go by themselves to the medical centers are only seen by ski resort doctors. And for other accidents, users are brought to ski resort medical offices by ski patrollers (around 40% of the medical office consultations [12]).

 Thus, to provide a complete comprehension of CO, the analysis was based on two databases: 1) the one of the *Association des Médecins de Montagne* (database-Mdm) and 2) the one of the *Système National d'Observation de la Sécurité en Montagne* (SNOSM) (database-Snosm). The *Association des Médecins de Montagne* is a 29 years old network of doctors located in 14 French ski resorts which gathers epidemiological information on snow sports. The *SNOSM* collects ski patroller accident reports from 60 ski resorts in French mountains. The two networks publish annual syntheses on snow sport epidemiology [1,12] and scientific publications were based on the database-Mdm [13,14]. This double approach allowed an exhaustive analysis of snow sport accidents as firstly, the two networks formed one of the largest databases on snow sports accidents in the world with more than 200 000 accidents between 2015 and 2019 (88 451 among the database-Mdm and 113 354 among the database- Snosm) for an incidence of 2.68 accidents per 1 000 skier days in 2019 based on the database- Mdm [12]. Secondly, this double analysis included all accidents requiring an immediate treatment, through medical consultation or ski patrol rescue. Thus, it brought an exhaustive analysis on the injured population on our slopes.

 The analysis was conducted on skiing and snowboarding accidents occurring on French ski areas from the winter seasons 2014-2015 to 2018-2019 and restricted to accidents with a well- defined accident type (CO, collisions against another user or non-collisions). Accident different than CO were only used to compute the occurrence of CO among snow sports accidents. 88 451 and 113 354 accidents from the database-Mdm and the database-Snosm were analyzed. Among them, CO were identified by the variable "Collision with = obstacle" for the database-Mdm and by the information included in three free-text fields related to accident type, accident cause and collision type for the database-Snosm. Two groups were considered: CO from the database- Mdm (n=2 570) and CO from the database-Snosm (n=823). Age, gender, type of sport practiced and injury location were investigated for all accidents. For injury location, five anatomical regions were considered: *head/neck* (including head, neck and cervical spine), *trunk* (thorax, abdomen, pelvis/hip, and spine), *upper limbs* (arm, elbow, forearm, wrist, hand, thumb, shoulder and clavicle), *knee* and *lower limbs* (thigh, leg, ankle and foot). Multiple injuries were counted once and recorded according to their anatomical region if they occurred on the same one or as *multiple* if they occurred on two or more anatomical regions (except for the combination of a knee injury and a lower limb injury, which was only recorded as lower limb injury). The database-Snosm also provided additional information on the location of the accident. Moreover, information on the self-estimated level (SEL) of the user, the use of a helmet or back protector and the type of injury, wasincluded in the database-Mdm. The analysis focused on describing the victims of CO, the location of CO and the injuries induced to then numerically model representative accident scenarios.

2.2. Model description

 An existing multibody human model, previously developed for pedestrian accident analysis and adapted for snow sports accidents [8], was used to model CO on Madymo 7.5 (Tass International, Helmond, Netherlands) (Figure 1). Based on the epidemiological analysis, only CO occurring while skiing were modelled and various CO scenarios were investigated with a design of experiment (DOE, Figure 1a). For that, three morphologies of a male skier were investigated: a $5th$ percentile, a $50th$ percentile and a $95th$ percentile (described, along with their equipment, by Bailly et al. [8]), with an initial skier speed of 30 km/h, 45 km/h and 60 km/h, 179 corresponding to the mean speed \pm standard deviation on ski slopes [15]. The slope angle was adapted to represent three slopes: very easy, easy and medium slopes, with respective angles of 6°, 11° and 16.5° [16]. We assumed that the ski slope was covered in hard snow (using previously calibrated snow properties [17], friction coefficient of 0.3 against the skier and 0.09 against the skis). In cases of TBI induced by a CO, 31% of the CO were characterized by a direct collision between the user and the obstacle, but in 69% of CO, the user fell prior to the obstacle and the fall was followed by a CO [3]. Therefore, these two scenarios were modelled: 1) direct collision and 2) collision after a fall. The fall was generated by the impact of skis against a snow mound, located either 5 m or 10 m before the obstacle. The position of the snow mound in relation to the skiers was also varied for each skier's position to simulate different fall kinematics. Two skier positions were modelled: either facing the slope or with a 45° orientation (Figure 1a). Three cylindrical obstacles (with diameters of 20 cm, 40 cm and 90 cm) and a flat obstacle were modelled. The obstacle was considered as rigid. The full factorial DOE was conducted with HyperStudy 2017 (Altair, Troy, Michigan, USA), leading to 1080 simulations.

 Figure 1. a) Multibody model and parameters of the design of experiment, b) definition of the 197 normal (n) and tangential (t_1 and t_2) directions in case of a flat obstacle and c) in case of a cylindrical obstacle

2.3. Variables of interest and analysis

 The objective of the DOE was to define the impact conditions (contact areas and impact velocities) of the human body against the obstacle during the CO. Therefore, contacts between body segments (head, neck, torso, abdomen, pelvis, shoulders, left and right arms, forearms, hands, thighs, legs and ski boots) and the obstacle were investigated. Special attention was paid to the first impact between the skier and the obstacle. Impact speeds were investigated through normal, tangential and resultant speeds expressed in the obstacle coordinate system. The normal

 direction (n) of the obstacle was obvious for the flat obstacle (Figure 1b), but this direction needed to be computed for cylindrical obstacles given the obstacle position and the position of the center of mass of the body segment prior to the impact (Figure 1c). Therefore, the normal 210 direction was unique for each body segment and was not aligned with the slope (Y_{slope}) nor the skier's initial velocity. Tangential speeds were expressed in the plane normal to the impact 212 direction (formed by vectors t_1 and t_2 on Figure 1b and 1c).

213

214 Epidemiological and numerical results were post-processed with Matlab 2013a (MathWorks, 215 Natick, Massachusetts, USA) and R (R Core Team (2015), Vienna, Austria).

216

217 **3. Results**

218 **3.1. Epidemiological analysis**

 From 2014-2015 to 2018-2019, 88 451 and 113 354 alpine snow sport accidents were recorded respectively in the database-Mdm and database-Snosm, considering all accidents types and severities. Among them, 2 570 (2.9%) and 823 (0.7%) were identified as CO in these two databases (Table 1). Victims were mostly young (mean age < 30 years old), experienced, skiers (>85%), wore helmets (70%) but no back protectors (87%), and males were slightly more represented than females. Moreover, the majority of patients went to medical offices without ski patrol rescue (65%). CO mostly occurred on slopes (77%), particularly on easy (35%), medium (20%) and very easy slopes (13%).

227

228 **Table 1.** Characterization of victims and injuries induced by CO among the databases

229 *SD: Standard Deviation, MTL: Musculo-Tendinous Lesion*

230 All body regions were affected by CO but more than 40% of the accidents led to head or trunk

231 injuries (two regions being associated with neurological or hemorrhagic issues). 9% of the CO

232 of the database-Snosm caused injuries to more than one anatomical region. Among all injuries,

 contusions were the most frequent (35%), followed by fractures (20%), lacerations (18%) and sprains (18%).

3.2. Multibody analysis

 Among the 1 080 simulations, 170 did not induce a collision between the skier and the obstacle because the skier's fall stopped before impacting the obstacle. These scenarios were characterized by far obstacles and low initial skier speeds (respectively 147 and 152 simulations with an obstacle at 10 m and an initial speed of 30 km/h including 129 simulations with both a far obstacle and a low initial speed).

243 For the other 910 simulations, 8 ± 4 body regions (out of 18 possible) impacted the obstacle (Figure 2a). All body areas were targeted by these impacts, though no impact occurred to the neck. In 93% (respectively in 37%) of accidents, at least one impact occurred between the obstacle and the head or (respectively and) the trunk (Figure 2b). Finally, the head was the first body region to impact the obstacle in 47% of accidents, followed by ski boots (17%) and hands (15%). Without distinction of the impact order, the head remained the body region impacting the obstacle the most, before the pelvis, shoulders and thighs.

 Figure 2. a) Number of body segments impacted, b) number of simulations (normalized by the total number of simulations: 910) leading to at least one impact between the obstacle and the body region

256 Considering all impacts between the skier and the obstacle, normal speeds $(25.3 \pm 15.7 \text{ km/h})$ 257 were higher than tangential speeds $(14.4 \pm 10.6 \text{ km/h})$ (Figure 3a and Figure 3b). Normal speeds 258 were higher for the head $(30.0 \pm 14.8 \text{ km/h})$ and the hands, followed by the lower limbs, abdomen and pelvis (Figure 3a), whereas higher tangential speeds were recorded for ski boots, hands and thighs than for the rest of the body (Figure 3b). Finally, the lower limbs, hands and head were the body regions impacting the obstacle with the highest resultant speeds (Figure 3c). For head impacts, some tangential speeds were very high compared to the rest of the speed distribution and appeared as outliers (7.6% of the head tangential speeds). These high values were mostly caused by the downward motion of the head during the fall (Figure 3d) or by the sliding motion of the head against the obstacle (Figure 3e).

-
-

 Figure 3. Distribution of a) normal impact speeds, b) tangential impact speeds, c) resultant impact speeds, d) case of tangential speed induced by the downward motion of the head and e) case of a sliding motion of the head compared to the obstacle

 Head and trunk impacts were focused on Figure 4 by considering all impacts on their subareas. The top of the head was the head area impacting the obstacle the most, with a high normal speed. Anterior (respectively posterior) head impacts were less frequent but associated with high normal and resultant (respectively tangential) speeds. Most of trunk impacts occurred on anterior and lateral areas though the higher impact speeds were recorded on posterior areas.

 Figure 4. a) impact frequencies of head and trunk according to areas of interests and including multiple impacts, and b) head, c) torso, d) abdomen and e) pelvis impact speeds according to the areas of interest.

 The type of obstacle, type of slope and the skier's size had little influence on impact velocities (Figure 5a, b and c) whereas the initial speed and the distance of the obstacle strongly affected normal, tangential and resultant impact speeds (Figure 5d and e). First, skiers travelling at 30 287 km/h, 45 km/h and 60 km/h respectively impacted the obstacle at resultant speeds of 18.2 ± 9.1 288 km/h, 25.1 ± 12.7 km/h and 38.7 ± 16.8 km/h, which corresponded on average to 61%, 56% 289 and 65% of their initial speed. Second, the fall of the skier (when the obstacle was placed at 5 m or 10 m) induced a strong reduction of the impact speeds, compared to direct collisions (distance of 0 m). As these two factors also had a strong influence on the absence of impact between the skier and the obstacle, their interaction was investigated in Figure 5f. For high initial speeds, a higher proportion of the initial speed was kept at impact (62% and 57% on average for 5 m and 10 m at 60 km/h) than for low initial speeds (respectively 38% and 25% at 30 km/h, Figure 5f). This interaction was absent for direct collisions (0 m) for which body segments impacted the obstacle on average at 77% of the initial skier speed.

 Figure 5. Speed distribution of all impacts according to a) the shape of the obstacle (a cylinder with a diameter of 1: 20 cm ; 2: 40 cm ; 3: 90 cm ; and 4: a flat obstacle), b) the slope, c) the skier's size, d) the initial skier speed, e) the distance of the obstacle (direct collision (0 m) or collision after a fall (5 m or 10 m)) and f) distribution of the resultant impact ratio (resultant impact speed normalized by the initial speed) according to initial speed and obstacle distance

4. Discussion

 The objective of this article was to describe the impact conditions of CO on ski slopes in terms of impact speed and injury location. The originality and reliability of this work come from the combination of exhaustive epidemiological data and a large number of numerical simulations in order to investigate various possible CO.

4.1. Epidemiological analysis

 This epidemiological analysis of CO aimed at providing an exhaustive representation of these accidents through the double analysis of both ski patroller and ski resort doctor databases. This double investigation was particularly interesting as it includes all accident severities requiring an immediate intervention from the mild accident to the life-threatening one helicoptered

 towards hospital. Moreover, this analysis identified collisions against obstacles among two large databases, regrouping more than 200 000 accidents. This favors the study of a representative population of CO and a powerful analysis. The interest of analyzing both ski patrol rescues and medical consultations is highlighted by the low rate of ski patrol rescue among CO victims from the database-Mdm (around one third). This element also underlines the heterogeneity of the severity of these accidents: though CO can be severe and lethal, most of CO victims were able to go to the medical center by themselves, without ski patrol rescue. The double analysis also brought complementary information on these accidents which participates to this exhaustive analysis. The database-Snosm covered all aspects of the accidents (victims, injuries, accident location and rescue services) while the database-Mdm brought detailed information on victims and their injuries. The two databases provided consistent information (young age of the victims, majority of skiers, and high occurrence of injuries to the head/neck or the trunk) which reinforces the reliability of this analysis. This exhaustive analysis was associated with some redundancy as CO victims rescued by ski patrol and brought to medical offices were included in the two databases.

 This description of CO on French ski slopes was consistent with previous studies, concerning the frequency of CO (0.7-2.9% vs 4.5% of ski patrol interventions in the USA [2]) but also the injury locations. Indeed, head/neck and trunk were frequently injured, as previously observed by Lystad [7] (around 26% of head and 23% of trunk injuries), which highlighted the potential severity of CO, as the most life-threatening injuries occurred in these areas of the body. Injuries were similar to Lystad's study (who observed around 57% of contusions, 27% of fractures, 7% of lacerations and 4% of sprains) [7] but with more lacerations (18%) and sprains (18%) and fewer contusions (35%) and fractures (20%). Besides, the occurrence of TBI among CO victims (3%) might be underestimated compared to the 10% observed by Bailly et al. [13], probably due to the inclusion of skull fractures and concussions in the TBI group of this latter study. This analysis of numerous CO (3 393 CO over 201 805 accidents on ski slopes), combined with a consistency between the two databases and with previous studies provided a solid basis for numerical CO modelling. In particular, this description highlighted the need to focus on alpine skiing CO, on medium or easier slopes, inducing head or trunk injuries. These elements should be targeted by evolutions on CO protection.

4.2. Numerical modelling

 The CO description (population at risk, accident location) of the epidemiological analysis was used to investigate the impact conditions of CO by modelling various accidents scenarios. To represent the variability of obstacles found on or close to ski slopes, four obstacles were modelled: a post, a tree, a lift tower and a wall. This study aimed at defining impact conditions against obstacles to then improve the preventive measures taken against these accidents (including through safety devices). Thus, protection devices were not modelled, and the obstacles were assumed to be rigid bodies, given the high difference in stiffness between the human body and a tree or a lift tower. Little information was available on the CO kinematics and on the possible fall prior to the obstacle, so we chose to model various accident scenarios through different fall initiations (through the combination of the skier orientation and the position of the snow mound). Some scenarios remain to be investigated, such as CO after or during a jump or CO after a short fall (less than 5 m). We wished to weight the DOE according to the accident frequencies to bring the analysis closer to the accident reality but it was not possible due to the lack of information on the obstacle type and distance, the skier's size or the accident's kinematics. All impact speeds were analyzed independently of the impact order, as the first impact did not ultimately have the most severe consequences (for example, a hand impact followed by a head impact). These impact speeds were defined in the coordinate system of the obstacle, to characterize the impact conditions applied to protection devices. Therefore, the normal direction was not aligned with the initial speed, leading to potential high tangential impact speeds. Higher normal speeds compared to tangential speeds were a severity factor, as higher energies were dissipated against the rigid obstacle than in case of sliding. However, the obstacle was numerically placed on the skier's way to ensure the modelling of the collision, which represented worst-case situations and may have induced an overestimation of the normal speed contribution. Still, this numerical analysis brought the first description of impact areas and impact speeds of CO based on representative accident conditions. Furthermore, the numerous simulations constitute a large database on CO than can be useful for prevention measures and accident reconstructions.

4.3. Impact conditions

 This study highlighted the need to protect head impact during a CO. Indeed, this body region, at risk of life-threatening injuries, frequently impacted the obstacle (68% of the accidents) and especially in first position (47%). This high impact frequency was linked to the kinematics of the skier, with either a forward fall or the initial position of the skier in case of direct collisions. This induced high impact speeds, high energy dissipations on the head and therefore high injury risks. These head impact speeds were consistent with a previous study [8], though higher tangential velocities were previously obtained, probably due to different modelling choices (distance, orientation and type of obstacle and approach angle of the skier). Besides, most of head impacts occurred on the top, the lateral or the posterior areas of the head, areas that are protected by a helmet (wore in 70% of CO, based on the epidemiological analysis). This might reduce the severity of the impact. However, high normal impact speeds were recorded on the anterior area of the head which is not protected by the helmet and thus, at risk of face injuries. Trunk impacts also need to be protected due to their impact frequency (63% of the accidents) combined with the life-threatening risks associated with this body region. These results are also consistent with the high frequency of head and trunk injuries observed in the epidemiological analysis. Most of impacts occurred in the antero-lateral trunk and thus, were at risk of hemorrhagic injuries whereas the less frequent but more violent posterior impacts were more likely to cause neurologic injuries. Further analyses are required to investigate the injury risks of such accidents. The impact speeds of hands and ski boots against the obstacle were also high. However, their masses and inertias were low and offset compared to the mass distribution of the whole body. Thus, hand or boot impacts were more likely to deflect the skier during the collision than to stop it, contrary to trunk impacts. Besides, hand and foot impacts are not at risk of life-threatening injuries, therefore the protection of head and trunk impacts should be the primary concern of CO safety devices.

4.4. Standards' evolution

 These new elements on CO impact conditions provide inputs for mattress testing conditions. In keeping with the French standard, mattresses are tested with impacts at 9.3 and 19.5 km/h [9] 406 which corresponded to the $18th$ and $41th$ percentiles of all the normal impact speeds obtained while considering representative initial skier speeds. Therefore, the standards should include impact tests at higher impact speeds. Besides, the two impacting masses of this standard are small (diameter inferior to 20 cm). This does not represent the reality of CO as 1) large body regions (such as the trunk) were identified as primary concern and 2) numerous body segments impacted the obstacle during an accident, which led to high contact surfaces. Based on the epidemiological and numerical analyses, we recommend including both head-like and trunk- like impacts in safety mattress evaluations, which also allow to evaluate protection devices in two conditions: 1) small and piercing impacts and 2) large impact surface conditions.

4.5. Obstacles' environment

 The initial impact speed combined with the distance of the obstacle are two major factors associated with CO injury risks as they influenced 1) the absence of impact between the skier and the obstacle but also 2) the impact speed (consistently with a previously study [8]). Direct collisions between users and obstacles should be avoided as less energy is dissipated prior to the impact with the obstacle, increasing impact speeds and accident severity. The lower speed dissipation for high initial skier speed may be associated with the chosen obstacle distances. However, a high initial speed remains a strong injury risk factor. These elements could influence the environment around obstacles on slopes, by either moving obstacles away from the slopes when possible, or through slow-down barriers placed prior to the obstacles, to decrease initial skier velocity and therefore the impact velocity. Contrary to Bailly et al. [8] for head impacts, the slope angulation did not induce high variations of normal impact speeds, 428 probably due to the larger slope variations previously modelled $(0^{\circ}, 20^{\circ}$ and $40^{\circ})$.

4.6. Limitations

 Considering the epidemiological analysis, the presence of a protection device on the obstacle was not mentioned in the two databases, which could influence the injuries induced. As the analysis focused on accidents requiring an immediate treatment, it did not include the mild accidents where the victim was neither rescued by ski patrol nor went to a medical center on the ski resort but consulted a doctor outside the resort. The comparison of the epidemiological results was also limited by the few studies targeting these accidents. Currently, no experimental data of skiing accidents can be used to validate the skier numerical model. However, this model was previously validated for snowboarding, pedestrian, cyclist and motorcycle accidents [17– 19] and used for skiing falls, CO and collisions with another user [8]. Moreover, muscle activity was not modelled but the contribution of this activity was estimated to be small considering the short impact duration. Besides, given the proportions of females and young people among CO victims, additional simulations should be performed to represent the whole population injured by CO. The influence of snow properties was not investigated and only a worst-case scenario (hard snow) was modelled. Finally, a direct comparison between the epidemiological and the numerical analyses was not possible due to missing information on the accident kinematics and on the obstacle (protection, distance, type).

5. Conclusion

 By combining accident data analysis and multibody simulations, this work provides an original methodology to investigate a large panel of potential accident conditions.

 Through a unique database of 3 393 accident scenarios from more than 60 ski resorts in France and 1 080 numerical simulations performed, it was possible to get the first characterization of CO since the 1990s. This characterization should be very useful to improve the safety of skiers: the category of CO victims (mostly young people, skiers, with some experience) gives relevant indications for future public awareness campaigns; with more than 40% of injuries located on head and trunk, the efficiency of safety mattresses in regards to trauma severity should be a major concern.

 At last, from simulations and main impact conditions (velocities …), it becomes possible to provide characteristics for an exhaustive evaluation of safety mattress efficiency and then promote further evolutions for existing safety standards.

6. Practical applications

 First, the current analysis brings quantitative information on the potential severity of CO injuries, based on the kinematics of the accidents. These knowledges are essential for ski resorts to adapt their prevention measures but also to define the rescue services required for an accident. Secondly, the existing French standard for safety mattresses shows limited representation of CO impact conditions. Mountain professionals are in favor of the evolution of this non-adapted standard. This standard should evolve to target head and trunk impact protection, with representative impact velocities. The results of this study brought important information for safety mattress companies, by identifying impact conditions of safety mattress. These knowledges can therefore be used to evaluate safety mattress performances but also to develop more efficient mattresses and afford a better protection for the tomorrow's mattress. Finally, this study brings a methodological tool to reconstruct a CO for a legal expertise. In this context, the results of the DOE can participate to the reconstruction by identifying the potential accident scenario and the influence of initial parameters.

ACKNOWLEDGMENTS

 We would like to thank the medical teams and the ski patrol members who contributed to build the databases.

REFERENCES

- [1] Système National d'Observation de la Sécurité en Montagne. Dossier 2019 de l'accidentologie des domaines skiables du réseau des préfectures des départements "de montagne". Saison 2018-2019 2019.
- [2] Shealy J, Ettlinger C, Scher I, Johnson R. 2010/2011 NSAA 10-Year Interval Injury Study 2014. https://doi.org/10.1520/STP158220140002.
- [3] Bailly N, Afquir S, Laporte J-D, Melot A, Savary D, Seigneuret E, et al. Analysis of Injury Mechanisms in Head Injuries in Skiers and Snowboarders. Med Sci Sports Exerc 2017;49:1–10. https://doi.org/10.1249/MSS.0000000000001078.
- [4] Ruedl G, Bilek H, Ebner H, Gabl K, Kopp M, Burtscher M. Fatalities on Austrian ski slopes during a 5-year period. Wilderness Environ Med 2011;22:326–8. https://doi.org/10.1016/j.wem.2011.06.008.
- [5] Shealy J, Johnson R, Ettlinger C. On Piste Fatalities in Recreational Snow Sports in the U.S. In: Johnson R, Shealy J, Yamagishi T, editors. Skiing Trauma and Safety: Sixteenth Volume, West Conshohocken, PA: ASTM International; 2006, p. 27–34. https://doi.org/10.1520/STP39643S.
- [6] Jenkins R, Johnson RJ, Pope MH. Collision Injuries in Downhill Skiing. In: Johnson R, Mote C, editors. Skiing Trauma And Safety: Fifth International Symposium, West Conshohocken, PA: ASTM International; 1985, p. 358–66. https://doi.org/10.1520/STP46651S.
- [7] Lystad H. Collision Injuries in Alpine Skiing. In: Johnson R, Mote C, Binet M-H, editors. Skiing Trauma and Safety: Seventh International Symposium, West Conshohocken, PA: ASTM International; 1989, p. 69–74. https://doi.org/10.1520/STP19455S.
- [8] Bailly N, Llari M, Donnadieu T, Masson C, Arnoux P-J. Numerical Reconstruction of Traumatic Brain Injury in Skiing and Snowboarding. Med Sci Sports Exerc 2018;50:2322–9. https://doi.org/10.1249/MSS.0000000000001701.
- [9] AFNOR. NF S52-105 Pistes de ski Fabrication des matelas pour dispositif de protection 2003.
- [10] Scher IS, Stepan L, Shealy JE, Hoover RW. Examining Ski Area Padding for Head and Neck Injury Mitigation. Journal of Science and Medicine in Sport 2020. https://doi.org/10.1016/j.jsams.2020.04.019.
- [11] Dorsemaine M, Bailly N, Riveill S, Faucheur T, Perretier C, Masson C, et al. About some factors influencing safety mattress performances in head impact collisions: A pilot study. 516 Journal of Science and Medicine in Sport 2021;0. https://doi.org/10.1016/j.jsams.2021.02.015.
- [12] Médecins de Montagne. Dossier de presse 2020 de l'accidentologie des sports d'hiver saison 2018-2019 2020.
- [13] Bailly N, Laporte J-D, Afquir S, Masson C, Donnadieu T, Delay J-B, et al. Effect of Helmet Use on Traumatic Brain Injuries and Other Head Injuries in Alpine Sport. Wilderness Environ Med 2018;29:151–8. https://doi.org/10.1016/j.wem.2017.11.007.
- [14] Laporte J-D, Bajolle L, Lamy D, Delay J-B. Winter Sports Injuries in France over Two Decades. In: Johnson R, Shealy J, Greenwald R, Scher I, editors. Skiing Trauma and Safety: 19th Volume, West Conshohocken, PA: ASTM International; 2012, p. 201–15. https://doi.org/10.1520/STP20120055.
- [15] Bailly N, Abouchiche S, Masson C, Donnadieu T, Arnoux P-J. Recorded Speed on Alpine Slopes: How to Interpret Skier's Perception of Their Speed? In: Scher IS, Greenwald RM, Petrone N, editors. Snow Sports Trauma and Safety, Springer International Publishing; 2017, p. 163–74.
- [16] Domaines Skiables de France. Pisteur-Secouriste 1er degré. Support pédagogique à l'usage des candidats à l'examen BREVET NATIONAL PISTEUR-SECOURISTE 1er DEGRÉ. 2018.
- [17] Bailly N, Llari M, Donnadieu T, Masson C, Arnoux PJ. Head impact in a snowboarding accident. Scand J Med Sci Sports 2017;27:964–74. https://doi.org/10.1111/sms.12699.
- [18] Serre T, Masson C, Perrin C, Chalandon S, Llari M, Py M, et al. Real accidents involving vulnerable road users: in-depth investigation, numerical simulation and experimental reconstitution with PMHS. Int J Crashworthiness 2007;12:227–34. https://doi.org/10.1080/13588260701441050.
- [19] Serre T, Masson C, Perrin C, Martin J-L, Moskal A, Llari M. The motorcyclist impact against a light vehicle: epidemiological, accidentological and biomechanic analysis. Accid Anal Prev 2012;49:223–8. https://doi.org/10.1016/j.aap.2012.08.013.
-

FIGURES CAPTIONS

All figures are 2-column fitting images.