



HAL
open science

Non-parametric trend analysis of condition monitoring indicators

Adrien Marsick, Hugo Andre, Ilyes Khelf, Quentin Leclere, Jérôme Antoni

► **To cite this version:**

Adrien Marsick, Hugo Andre, Ilyes Khelf, Quentin Leclere, Jérôme Antoni. Non-parametric trend analysis of condition monitoring indicators. Wind Energy Science Conference 2023, May 2023, Glasgow-University of Strathclyde, United Kingdom. hal-04533312

HAL Id: hal-04533312

<https://hal.science/hal-04533312>

Submitted on 4 Apr 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

WESC
25th May 2023



Adrien MARSICK

Non-parametric trend analysis of condition monitoring indicators

A. Marsick^{1,2}, H. Andre³, I. Khelf², Q. Leclere¹, J. Antoni¹



Context on condition-based maintenance




Monitoring workflow

Physical signals


Health indicators

Alarms



- Compromise between early replacement and catastrophic failure
- Fleet scale surveillance
- Usual monitoring
 - Statistical threshold
 - Learnt from “healthy” state


Challenges



- Small increasing trends & Outliers
- Multiple episodes (Degradation process)

Need of trend analysis and segmentation

Qualitative analysis of trend




Benefits of studying trend

Fault gravity information

Indicator fusion

Input for machine learning


What is a trend ?



A trend is a consecutive **sequence of episodes** in which the beginning and end time instants are uniquely determined to manifest a time of **qualitative state change**


Tasks

1. Segment episodes
2. Characterise




Rank-based statistics

How to detect a trend without assumption on the distribution of the data?



Test the tidiness of the data!



Pair test If $x_i < x_j$, does

$y_j > y_i$?


Concordant pair

$y_j < y_i$?


Discordant pair



Pair to pair comparison



Rank Matrix



A view on two rank tests


Stationarity: Mann-Kendall test

- Sum of the rank matrix
- Stationarity given by concordance / discordance of pairs
- Statistical confidence

Concordant



Discordant




Equal pairs on average

Non parametric, independent of amplitude, robust to outliers

Change-point: Pettitt test

- Blocks of concordance
- Gives the most probable change-point
- Statistical confidence




Sum of rectangle


Maximum at transition

Segmentation algorithm

Sliding window with Pettitt change point test



- Output: list of transition dates
- Labelling of segments & transition




Algorithm



Segment $\rightarrow [0; 0.1]$ $i = 1$ $d = 0.1$ Change point \rightarrow NO	Segment $\rightarrow [0; 0.2]$ $i = 2$ $d = 0.1$ Change point \rightarrow NO	Segment $\rightarrow [0; 0.3]$ $i = 3$ $d = 0.1$ Change point \rightarrow YES $I_{start} = 0.25$
---	---	--

Segmentation algorithm

Sliding window with Pettitt change point test





- Output: list of transition dates
- Labelling of segments & transition



A rank-based evaluation of the slope

Non-parametric dynamic → Slope to Noise Ratio

- For an increasing trend, more points are needed for small hidden trends
- Latency = number of points needed to reject the stationarity hypothesis







Non-parametric measure of Slope to Noise Ratio

Example vibration-based indicator




Damaged bearing

Condition indicator





- Robust segmentation
- Qualitative characterisation of episodes
- Information on latency

Multi-indicators monitoring



Decreasing median
Increasing median





Maintenance operation



Similar dynamic
Rise in diagnostic confidence

Multi-indicators monitoring

Multiple indicators analysis



Zoom
Early trend detection

Conclusion

- ⇒ Need for a **qualitative trend analysis** tool
- ⇒ **Rank-based** statistics offers a **non-parametric** framework
- ⇒ **A segmentation and characterisation** method has been proposed



Gains of the method:



- simplified language, robust to outliers
- multi indicator analysis
- added information for maintenance decision



- **Input** for large study of **historical defects**
- **Not limited to** vibration-based indicators series
- **Room for improvement** : selection of hyperparameters, online implementation




Thank You


- [1] A.N. Pettitt, A Non-Parametric Approach to the Change-Point Problem, *Journal of the Royal Statistical Society. Series C (Applied Statistics)*. 28 (1979) 126–135. <https://doi.org/10.2307/2346729>.
- [2] H.B. Mann, Nonparametric Tests Against Trend, *Econometrica*. 13 (1945) 245–259. <https://doi.org/10.2307/1907187>.



Tunable parameters



Length of the segment d
Significance confidence $1 - \alpha$



$$k(n) = \sum_{i=1}^n \sum_{i=n+1}^N \text{sgn}(t_i - t_j) \text{sgn}(x_i - x_j). \quad (6)$$

The Pettitt statistic $k(n)$ is maximised for the most probable change point T , that is





$$K = \max_{1 \leq n \leq N} (|k(n)|), \quad (7)$$

$$T = \arg \max_{1 \leq n \leq N} (|k(n)|). \quad (8)$$

Most importantly, using the well-defined properties of stationary series, Pettitt proposed a significance test for the rejection of H_0 where the p-value for rejection is approximated by

$$p \approx 2 \exp\left(-\frac{6K^2}{n^3 + n^2}\right), \quad (9)$$

Tunable parameters



Mann Kendall

$$S = \sum_{k=1}^{n-1} \sum_{j=k+1}^n \text{sgn}(y_j - y_k)$$

Avec $\tau = \frac{S}{S_{\text{total number of pairs}}} = \frac{2S}{n(n-1)}$



Variance of the sum is

$$\sigma_S^2 = \frac{n(n-1)(2n+5)}{18}$$



With null mathematical expectation

Deviation from gaussian



Increasing



Stationary



Decreasing



Statistically more +1 pairs


Statistically equal +/-1 pairs

Statistically more -1 pairs


The issue of increasing trends

- Pettitt test : detection of change in median

Linear increase + noise




Linear increase + step



How to differentiate the two ?

The issue of increasing trends

- Pettitt test : detection of change in median






Criteria on rank correlation

Global surveillance and industrial application

Segmentation on multiple indicators

Multiple indicators analysis




Non significant episodes

High latency


Context on condition-based maintenance

Threshold on the amplitude



- Canonical trend (stationary, initiation, catastrophic increase)
- Usual monitoring
 - Statistical threshold
 - Learnt from “healthy” state

Challenges



- Outliers and unknown noise distribution
- Hidden trends
- Different episodes
- Versatile shapes



Need