

Describing carbons

Marc Monthioux

▶ To cite this version:

Carbon Trends, 2024, 14, pp.100325.

HAL Id: hal-04537141 https://hal.science/hal-04537141

Submitted on 8 Apr 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Contents lists available at ScienceDirect

Carbon Trends

journal homepage: www.elsevier.com/locate/cartre

Describing carbons

Marc Monthioux

Centre d'Elaboration des Matériaux et d'Etudes Structurales (CEMES), UPR-8011 CNRS, Université Toulouse 3, Toulouse 31400, France

ARTICLE INFO

Keywords: Terminology Descriptor Carbon materials Allotropes Graphene Texture Nanotexture Structure Carbonisation Graphitisation Nanotubes Carbon fibres Carbon black

ABSTRACT

Carbon materials are unique materials for their diversity, owing to three possible hybridisation states (*sp*, *sp*², *sp*³), their ability to switch from one phase to another upon various external stresses (thermal, mechanical, pressure...), and the tolerance of graphene (*sp*²C) to defects of many kinds. This makes their description difficult, due to the lack of standardised vocabulary and misuses or ignorance of the existing ones. A common language is needed so that every word has the same meaning to everyone and that carbon scientists understand each other as accurately as possible. This paper aims to clarify the basic terminology to be used on this matter, by reminding some important definitions or terms, *e.g.* allotrope, polymorphism, molecular form, crystallite, graphitic, graphene, graphene layer, graphenic, graphitisation, graphitisation treatment..., based on authoritative publications when available. In addition, as *sp*²C-based carbon materials exhibit the largest variability, a four-term description scheme (namely: morphology, texture, nanotexture, structure) is proposed and argued, which is believed to be sufficient (and necessary) to describe any kind of carbons, but molecular forms. Applying the recommendations proposed is expected to bring more consistency, clarity, and understandability to the forthcoming literature dealing with carbon materials.

1. Introduction

Carbon and humankind share a millennium-long common history. However, at a time where science was barely born, identifying some natural phases as carbon or, even more, discriminating between carbon phases was a job left to alchemists, that is to say, identification criteria were based on experiments where empiricism disputed with magics. The poor accuracy of the identification criteria mostly based on visual observations and biased interpretations had made that graphite was confused with lead for a long while, making it named "plumbago" (from latin "plumbum"). Then chemistry came to help, and plumbago was identified as actually being carbon, though as tardily as in 1779, thanks to C. W. Scheele. It was then proposed to be named "graphite" instead of plumbago 10 years later by A. G. Werner, to refer to its main application at that time, as pencil... lead. It was the same for diamond, even once proposed to be made of water (by L.-B. Guyton de Morveau [1]), until the joint efforts of chemists such as A. L. Lavoisier and L.-B. Guyton de Morveau in France and S. Tennant in UK finally acknowledged diamond to be pure carbon, in mid-18th Century. Then, the question regarding what could make diamond and graphite so different from each other raised up. Mineralogy came to the rescue, and the serious description of phases started, based on external, eye-visible aspects such as morphology, brightness, colour, and geometry measurement (angle

between faces, and symmetries). But the methodology was lacking the appropriate tools, and was unfortunately mostly limited to the macroscopic scale. It was not so much different, though, that the methodology which was used in Antiquity by Plato to propose some relationship between 5 different geometrical solid forms (that he could find in minerals) and the elemental components (namely: fire, air, water, earth, and universe). But progress was made, and A. Bravais (in 1848, books say) was able to propose his famous system of 32 symmetry classes dispatched into 7 different main crystal systems. But at that time, it was more an intuition, which appeared to be right and is still valid today, than a demonstration. This limitation has made materials to be tentatively discriminated by their properties, as an indirect characterisation of structure differences, since the identification of the atomic configurations was lacking. This was the approach based on which Berzelius proposed the term "allotropy" in 1841 [2] to discriminate between the different phases made of a single type of atoms but exhibiting different properties and multi-atom phases (compounds) of similar compositions. In the latter case, the term "polymorphs" was preferred in case the discrimination was based on physical behaviour, or "isomers" in case the discrimination was based on chemical behaviour [3,4]. As the terminology was depending on which property was considered, confusion and debates kept going on until the principle of X-ray diffraction (XRD) was discovered, understood, and exploited by the cumulated work

https://doi.org/10.1016/j.cartre.2024.100325

Received 31 August 2023; Received in revised form 20 January 2024; Accepted 21 January 2024 Available online 22 January 2024

2667-0569/© 2024 The Author(s). Published by Elsevier Ltd. This is an open access article under the CC BY license (http://creativecommons.org/licenses/by/4.0/).







E-mail address: marc.monthioux@cemes.fr.

performed by W. Röntgen, then M. von Laue, then W. H. and W. L. Bragg in the early 20th century [5]. From this moment, discriminating between phases was able to be made through the positions of their constituting atoms.

Since then, the problem of discriminating between phases from their crystallographic structures instead of properties was solved, but it was not sufficient for carbon. Carbon is the only element of the Mendeleev Table able of a tremendous versatility regarding its solid forms thanks to (*i*) a choice of three electronic structures (sp, sp^2 , sp^3); (*ii*) the possibility to exist as molecular forms as well as allotropic crystals; (*iii*) the existence of metastable forms which allow carbon to exist either as two-dimensional crystals or three-dimensional crystals while being able to adopt all the intermediate structural compositions; (*iv*) and most of all, the extraordinary flexibility and adaptability of the graphene sheet which allows building an infinity of possible graphene arrangements, the same way a paper sheet has in the art of origami.

Obviously, then, XRD is not enough to describe a carbon material accurately. This means that giving a specific name to each of the carbon crystal structures identified so far (graphite, diamond, lonsdaleite...) thanks to XRD is not enough, a more comprehensive terminology is needed to describe whatever makes a carbon material different from another. And this is where confusion and misunderstanding take place. Because of the lack of standardised nomenclature, or the ignorance of those which exist [6,7], words such as allotrope, phase, structure, microstructure, microtexture, graphitic, amorphous, graphite and so on are largely misused in scientific papers dealing with carbon materials or used with different meanings. Even worse, they may be used willingly as words which the meaning is fuzzy enough to cover various aspects and features of the materials studied within the same paper, precisely because there is no normalised vocabulary available.

A contemporary French scientist and philosopher, Etienne Klein, once said: "Si on dit mal les choses, on risque de mal les penser" ("With saying things wrong, comes the risk of thinking them wrong"). This paper is here to focus on this problem, and aims to introduce a simple semantic guide to carbon scientists so that each of them may speak the same language and understand each other with no ambiguity, not by introducing new words, but by giving each of them a unique meaning and a unique, not-overlapping lexical field. Consequently, this paper does not intend to describe all kinds of carbon materials (they are too many for this). Excellent textbooks and monographs doing this can be found in the literature [8–12]. However, reading such textbooks evidences the lack of consistency regarding the terminology and vocabulary used, and reading them while keeping in mind the definitions and descriptors proposed here is advised.

2. What is a carbon allotrope?

Because carbon **phases** are made of a single type of atom, the term "**allotropes**" is the one to use for them, preferably to "**polymorphs**". However, since the advent of XRD methods, Berzelius's definition may be revised and completed, say upgraded, and carbon **allotropes** are actually those which discriminate by their atomic configurations, no longer by their difference in properties, in particular because the latter might not be discriminating enough. For instance, no significant difference in properties experimentally measured discriminates two crystallised forms of sp^3 carbon such as diamond and lonsdaleite (although calculations predicted the latter being 58 % harder than the former [13]), but they clearly discriminate by their crystallographic systems, cubic and hexagonal, respectively (Fig. 1).

Therefore, a modern and more accurate definition of **allotropy** (yet already 60 years old) is "the phenomenon of the existence of an element in a crystalline solid state in at least two distinct forms that differ from each other by the spatial arrangement of their atoms", as stated by Addison [15]. Attention has to be paid, though, that the diffraction patterns have to be obtained in powder mode, *i.e.* where the sample subjected to the incoming X-ray beam (or electron beam, eventually) is made of a




Fig. 1. X-ray diffractogram (Cu radiation) of the diamond and lonsdaleite **structures**. The specimen is a polycrystalline material in which diamond-lonsdaleite polytypes developed, obtained by a high pressure, high temperature treatment of **graphite** (reprinted from Ref. [14] by permission of Elsevier).

sufficient amount of randomly oriented **crystallites** so that no diffraction peak can be missed or altered in intensity. In other words, the orientation of the sample with respect to the direction of the incoming coherent beam should not play a role. It would be not right to designate a carbon **phase** as an **allotrope** based on a diffraction pattern which would not contain all the possible peaks merely because the carbon material would exhibit a non-isometrical **morphology** or an anisotropic **texture** (see Section 3) which makes it lying onto the sample-holder so that some atom planes cannot be under the Bragg angle. In that case, what discriminates such a carbon material from others is not **structure**-based but merely orientation-based, hence it is not an **allotrope**.

As a consequence, various carbon phases may be designated as distinct allotropes as soon as their diffractograms exhibit different diffraction peaks and/or bands at different 2θ locations. Fig. 1 already provided examples of two **allotropes** of *sp*³C-based carbon materials. Apart from many hypothetical *sp*³C **allotropes** predicted by calculation only (it is out of scope of this paper to make the list, but related references can be found in well-documented papers such as [16-18], only a few others do exist, yet more exotic, such as V-carbon, obtained from the high-pressure compression of C_{60} crystals [19]. Other $sp^{3}C$ -based allotropes may be sometimes mentioned in the literature, such as adamantane [20] and its derivatives named diamondoids [21], or a 2D material named diamane synthesised recently [22] and so-called hydrographite [23]. However, none of them is pure carbon, as they are heavily hydrogenated, and their nanosize makes the hydrogen content quite significant (for instance, H/C at. = 0.5 in diamane). Same for other 2D sp³C materials such as diamondol [24] and diamondene [25], which are presumably heavily functionalised with OH groups and other atoms, respectively. Anyway, none of them can be considered as a distinct allotrope, since their structure does not discriminate from that of genuine diamond or lonsdaleite.

Fig. 2 illustrates the best-known crystallised forms of sp^2 carbon by their calculated X-ray diffractograms [26]. The top-two diffractograms in Fig. 2 are regular three-dimensional **structures** of carbonaceous materials (meaning that the carbon atoms are displayed periodically and coherently in the three dimensions of space). The rhombohedral **structure**, which was first described in 1942 [27], has to be calculated, because it is mostly found as stacking faults in the hexagonal **structure**. As a matter of fact, experimental X-ray diffractograms of the pure rhombohedral sp^2 carbon **phase** cannot be found in the literature, because the latter is always mixed with that of **graphite** [28], or in so minor occurrence that only low-quantity-demanding methods (such as Raman spectroscopy [29]), can be used. The middle pattern in Fig. 2




Fig. 2. Calculated X-ray diffractograms (Cu radiation) of the rhombohedral structure (top), the hexagonal structure (graphite), and the turbostratic structure (bottom) of graphenic crystals [26].

corresponds to the hexagonal structure of genuine graphite. It is worth noting that it is often referred to as the "Bernal" structure (as we did in Ref. [26] ...), from the name of the author who is assumed to have first determined the related **structure** in 1924 [30]. However, giving such a kind of nickname to a structure based on his discoverer's name, or supposed to be, is dangerous because it happens that digging further into the literature may reveal some anteriority or other misunderstanding which makes the credit be definitively given to the wrong person. One example is the popular designation of "Stone-Wales defect", which turned out to be wrong and should be replaced by "Dienes defect" instead [31]). The same thing happened here, since a paper by Hull described the hexagonal structure of graphite as early as 1917 [32]. Therefore, the "Bernal structure" designation should actually be replaced by "Hull structure" from now on (or "Hull-Bernal" for the least, in order to keep a link with the previous denomination so that the unaware carbon scientists are not confused) ... until a further anteriority is revealed one day. The problem is that, once a wrong term has become popular and widespread, it is almost impossible to have it changed for the right term. Habits are hard to get rid of, and the right knowledge spreads out more slowly than mistakes. The same happened with the use and meaning of "graphene" (see below).

As a matter of simplification, it is common for long to find in the literature the **graphite structure** to be identified only based on the *002* peak position, hence the d_{002} value [33], as in the **graphitisation** index $g = (0.344 - d_{002}) / (0.344 - 0.3354)$ for instance [34]. It is right that, in principle, the lowest intergraphene distance of 0.335 nm can be reached only when the **graphene layers** involved are in 3D coherence, as in the Hull-Bernal or rhombohedral **structures**, and that, on the other hand, non-coherent stacking only allows a minimum of 0.344 nm, corresponding to the turbostratic **structure** commented further below) [35].

However, d_{002} higher than 0.344 nm are commonly obtained in immature carbons and non-graphitisable carbons [36]. On the other hand, there might be reasons (e.g., internal stresses as developed by specific formation mechanisms and specific textures such as the concentric one when involving perfect **graphenes** [37]) for which the d_{002} value may not correspond to what is expected from the structure. Therefore, the unambiguous demonstration of the graphite structure requires the existence of the 112 peak in the diffractograms (in addition to the 00l and 100 and 110 peaks), keeping in mind that the 101 peak is not reliable for this because its occurrence can be affected by the presence of stacking faults [26,35]. This has suggested to consider the I_{112}/I_{110} intensity ratio as a more appropriate alternative to quantify the graphitisation rate [38]. It is also of a much easier use than the p parameter proposed by Franklin [35], based on the shape of the 112 peak. The absolute I_{112}/I_{110} reference value to consider in this case is 1.55, as obtained from the calculated XRD (Fig. 2, middle), a value which matches the experimental one obtained for a natural graphite such as Ceylon graphite [39], which is acknowledged as one of the best standards in this regard.

The bottom diffractogram in Fig. 2 is that of the two-dimensional **structure** typical of the one that Biscoe and Warren [40] were first to designate as turbostratic (*i.e.* in which **graphene layers** are periodically piled-up while being randomly rotated). 100 % turbostratic carbon is a genuine **allotrope** indeed, since the related diffraction pattern does not exhibit all the diffraction peaks that the two others do (Fig. 2). In addition, some of the peaks (the *hk* peaks) exhibit an asymmetric band shape which witnesses the partly two-dimensional nature of the **structure** ("partly", because the occurrence of the *00l* peaks does reveal a periodicity in the *z* direction, but limited to the stacking distance). It is well-known that, depending on the chemical nature of their precursor

and their thermal history, **graphene**-based carbon materials may range within a continuum of materials in which the ultimate ones exhibit the 100 % turbostratic **structure** at one end, and the 100 % hexagonal **structure** (**graphite**) at the other end [41–43]. Only those two, in the continuum, are genuine **allotropes**. The other carbons, intermediate, are **partially graphitised** in a various extent, and then have to be considered as exhibiting defective **structures** derived from that of **graphite**, but do not make distinct **allotropes**. Similarly to $sp^{3}C$ carbons, existing $sp^{2}C$ **allotropes** other than those shown in Fig. 2 are seldom, and limited to exotic **phases** actually involving a contribution of $sp^{3}C$ such as kinds of polymeric C_{60} (one being named graphullerene) [44,45] and U-carbon [46], although the **structure** of the latter is still uncertain. Again, thanks to scientists' imagination and nowadays powerful calculation facilities, some hypothetical ones are also proposed, either based on pure $sp^{2}C$ [47], or $sp^{2}C + sp^{3}C$ combinations [48].

In a countless number of papers, including review papers dedicated to carbon material diversity (see [49–58] for instance, to cite a few), fullerenes, graphene, carbon nanotubes, and even carbon onions, are designated as carbon allotropes. This is ignoring the progress made since Berzelius's time, and the input brought by diffraction methods since then. In an attempt to clarify the situation of carbon **allotropes**, Heimann et al. [49] claimed that (i) "the term "allotropy" refers to an alteration of the equation of state of a substance" (but it is not clear where this statement came from, certainly not from Berzelius's work) and (ii) that "Addison's definition (referring to Ref. [10]) overlaps that of polymorphism" (but it does not because polymorphism is dedicated to multi-element phases whereas allotropy is dedicated to single-element phases). Heimann et al. then proposed to distinguish the various carbon phases in accordance to the type of hybridization of the valence orbitals. They ended up with a ternary phase diagram of carbon allotropes as shown in Fig. 3. Fullerenes and nanotubes, which were the focus of the carbon community at that time, are located on it, even graphenes, along with amorphous carbon, vitreous carbon, and several other phases.

Such a ternary diagram cannot be right: **graphene** (if a monolayer, which is the definition acknowledged by IUPAC [6]), fullerenes, and carbon nanotubes (if single-walled, see Section 3.3.4), are NOT carbon **allotropes**, they are carbon **molecular forms** (possibly macromolecular), as sometimes duly acknowledged yet too scarcely [53]. Unfortunately, this is a confusion that has become so viral that it has spread out

everywhere [49-52,54-58], including textbooks.

On the other hand, the periodic arrangement of **molecular forms** may generate genuine crystallographic forms. The most obvious one are **graphite** of course (hexagonal as well as rhombohedral **graphite**) and turbostratic carbon, built from **graphenes**. Fullerite, built from fullerenes [59] is another one, with three different possible **structures** (simple cubic, face-centred cubic, and hexagonal cubic [60,61]). Periodic assemblies of single-wall carbon nanotubes (SWCNTs) also exist [62], generating typical diffractograms (Fig. 4) hence corresponding to a genuine **allotrope** (once tentatively named nanotubulite [64]). All are genuine carbon **allotropes** because they generate X-ray diffractograms exhibiting specific periodicities.

Not all carbon **molecular forms** which are able to combine into periodic assemblies generate an **allotropic structure**, because they merely generate X-ray diffractograms (remember, in powder mode) which are not different from that of other **allotropes**. For instance, this is the case for so-called carbon shells or cages [65], or nano-onions [66] depending on whether they are hollow or solid. Same for multi-wall carbon nanotubes (see Section 3.3.4) and multilayer **graphenes**, the diffractograms of which do not discriminate from that of turbostratic carbon (or possibly from **graphite**, in some rare cases), hence they are merely nanoforms of carbon **phases**. Another reason for carbon **molecular forms** not to exist as genuine **allotropes** is when they cannot arrange periodically because they do not exhibit a specific and reproductible **molecular structure** (for instance, single-layer carbon nanocones [67,68], subsequently designated as carbon nanohorns [69]).

Because of the two-dimensional nature of (single-layer) **graphene**, its mechanical flexibility, and the tolerance of the sp^2 C=C bond to strain which allows replacing hexagon cycles by others (pentagon, heptagon, octagon), most of carbon **molecular forms** which do exist are usually sp^2 C-based. The most well-known are cited above (fullerenes, singlewall carbon nanotubes, **graphene**, nanohorns...) but there are so many of them that they could be dedicated an "Encyclopedia" [53]. In addition, there are a few exotic ones such as biphenylene [70], and graphynes and graphdyines which have been partly synthesised [71], although they are a mixt of sp^2 C and spC. Pure spC has some **molecular forms**, such as cyclo[18]carbon [72], in addition to the well-known linear carbyne chain, the instability of which, however, still makes its existence controversial, except if encapsulated [73]. And then, come the hypothetical ones [58]. All these **molecular forms** are not carbon **allotropes** *a priori*, unless they are able to assemble into periodic




Fig. 3. Proposition for a distribution of the carbon **allotropes** in a ternary diagram based on hybridisation state, according to Heimann et al. [49]. Reprinted by permission of Elsevier.




Fig. 4. X-ray diffractogram (Cu radiation) of an ensemble of SWCNT bundles in which all SWCNTs exhibit similar diameters (modified from Ref. [63] and obtained by courtesy of P. Launois). The diffractogram exhibits specific periodicities which make such a material a genuine **allotrope** named nanotubulite. To be compared to the diffractogram in Fig. 2-**bottom**, which corresponds – among other **graphenic** forms - to that of MWCNTs, whatever their **texture** (see below the definition used here for this term).

structures. Regarding sp^3C materials, there is no **molecular form** proposed, as far as I can tell, but possibly graphane [74] which, however, contains as many hydrogen atoms as carbon atoms, and the actual synthesis of which remains doubtful [75].

Amorphous carbons are not allotropes because (i) by definition, their X-ray diffractograms do not exhibit peaks corresponding to atom planes (unless they contain small periodic clusters, in such a case the materials are two-**phase** (the clusters + the amorphous surrounding) composites, which cannot be allotropes), except faint modulations revealing the periodicities of the contained molecules; (ii) they correspond to a continuum of composition which is having its own ternary diagram (the poles of which are the *sp*²C, *sp*³C, and H % contents [76, 77]). For this reason, **amorphous** sp³C-rich carbon materials such as "Q-carbon" [78] may be considered as phases, but not as allotropes of course. The case of "vitreous carbons" (also named glassy carbons), which can be found in Fig. 3, is the same. Glassy carbons are not amorphous, although it can be read otherwise in the literature [79]. Their name is only to refer to their macroscopic mechanical behaviour, which is brittle, similar to that of glass, and was initially a trade name, not a scientific name [6,80]. They are merely carbonaceous materials built-up with short graphene layers involved in tiny crystallites randomly oriented (actually oriented as walls of tiny - nanosized pores). The crystallite structure is turbostratic. There is a whole range of glassy carbons indeed, mostly according to their precursor and their ultimate carbonisation temperature, hence they may exhibit various crystallite sizes, but they do not discriminate from each other and from other turbostratic carbons as far as the crystallographic structure is concerned.

To summarise, attempts such as that by Heimann et al. and related ones [49,56] may have some merit, but they cannot play the role of phase diagrams of carbon allotropes because (i) not all the phases shown are allotropes (amorphous carbon is a phase but not an allotrope); and (ii) genuine allotropes having similar $sp^3/sp^2/sp$ composition are located on the same point (e.g. diamond and lonsdaleite are not discriminated, same for hexagonal and rhombohedral graphite). The description parameters used (the three hybridization states) cannot be enough to provide an identity map of the large variety of carbon forms either (allotropes or not). Reading statements (in one of the review papers previously cited) such as "all the organic life on earth is made up of allotropes of carbon" and "Carbon has basically 8 allotropes, namely, (1) diamond, (2) graphite, (3) lonsdaleite, (4) C_{60} (buckminster fullerene or bucky ball), (5) C_{540} , (6) C_{70} , (7) amorphous carbon, and (8) carbon nanotubes (CNTs; buckytube)" illustrates how far the nature of carbon allotropes can be poorly understood, and even the definition of allotropy itself. Allotropy is only a structure-based descriptor, and if allotropy could be enough to provide the identity card of crystallised forms of sp^3 -hybridised carbons, it is not able to do the same for sp^2 -hybridised carbons. As a specificity of graphene-related carbon materials, other descriptors are needed to describe them with all needed accuracy.

3. Comprehensively describing sp²C-based carbon materials

3.1. Graphene, graphenic, graphitic, graphitisable, etc

There was a time when carbon scientists were mostly chemists, hence sp^2 C-based solids were designated as polyaromatic carbons. Then came the era of carbon **molecular forms**, which started in 1985 with the disclosure of the fullerene molecule [81], then nanotubes, then **graphene**. Their **structural** simplicity (here the <u>molecular structure</u>) enabled to give coordinates to atom positions and inject them into computer models, making them objects of interest for physicists (not carbon scientists at first) to predict the properties, which appeared to be amazing. The term "**graphene**" then became generic, possibly after Novoselov et al. introduced the term "few-layer **graphene**" (FLG) in 2004, probably for the first time [82]. It was not the smartest choice

(unlike the rest of the paper), because it stated that a graphene could be made of more than one layer, in opposition to the 1995 IUPAC definition "a single carbon layer of the graphite structure" [6]. A much better option would have been to name the same material "few-graphene layer" (FGL). Same for nanotubes, by the way: geometrically speaking, a tube is a hollow cylinder with a wall, therefore, discriminating between "single-wall carbon nanotubes" and "multi-wall carbon nanotubes" (see Section 3.3.4) introduces the difficulty to name the nanotube wall (i.e. the cylinder wall) as a whole. Better terms, maybe, would have been "single-graphene carbon nanotube" and "multi-graphene carbon nanotube", respectively, the nanotube wall then being either mono-layered or multi-layered. Anyway, as discussed in Ref. [31], what is important nowadays is that everyone understands "graphene" the same way, and the same for single-wall and multi-wall carbon nanotubes. When it becomes easier to change a definition than to change everyone's understanding and habits, it means that it is about time to change the definition. This was done in 2013, when the editorial board of CARBON journal, which can be considered authoritative in such matters, proposed to admit that the term "graphene" may be both specific and generic. When specific, it designates "an isolated single-atom-thick sheet of hexagonally arranged, sp²-bonded carbon atoms", whereas "graphene layer" is for designating the same when being part of a stack contributing to build a carbon material; when generic, it designates carbon materials built from graphene layers providing it is combined with other terms as in "bilayer graphene", "few-layer graphene", "multi-layer graphene" [7]. Meanwhile, the adjective "graphenic" was introduced, along with "graphenised", and "graphenisation", which were unfortunately absent from the IUPAC nomenclature. "Unfortunately", because "graphenic" is definitely better than "polyaromatic" to qualify the broad class of carbonaceous solids built from graphene layers. The reason is that "polyaromatic" is inherited from organic chemistry, hence suggesting a saturation of the edge carbons by hydrogen atoms, which is barely the case in graphenic solids, unless they are considered at the early steps of carbonisation. Even in old work discussing about graphitisation as in Ref. [83], the lack of the term "graphenised" as an alternative to the term "graphitised" generated confusion and inappropriate definitions. While acknowledging - already in 1986 - that "the term "graphitised carbon" is widely misused and misunderstood", Knox et al. recommended to name "two-dimensional graphite" carbon materials "in which graphitic sheets are randomly oriented relative to one another", that is to say, turbostratic carbons. With such a broad coverage of the word "graphitic", all graphene-based carbons should then be said **graphitised**. It cannot be right.

Despite these crossed definitions exist since 1995 [6], and were reminded and completed in 2013 - ten years ago already [7] - many authors still use the word "graphitic" to designate any kind of carbon built with graphene layers. Others try to be more accurate, and use "graphitic" only when they see stiff graphene layers in high resolution transmission electron microscopy (HRTEM) images, and to express this way that the material organisation is improving upon annealing. Both are wrong. "Graphenic" is generally righter than "graphitic" because graphenic carbons are carbon materials built from graphene layers regardless of their size and how many are stacked in crystallites, and whatever the type of allotrope the crystallite structure corresponds to (turbostratic, graphitic, rhombohedral). As stated in Ref. [6] "graphitic carbons are all varieties of substances consisting of the element carbon in the allotropic form of graphite, irrespective of the presence of structural defects", otherwise confirmed in Ref. [7] which says "graphitic requires the existence of 3D order or layer registry, which is not directly observable by conventional TEM fringe imaging". Clear enough.

Of course, this also applies to related words such as "graphitisable" and "graphitising" which may be used only if it is known whether the carbonaceous material being discussed would actually be able to get the structure of graphite once heat-treated at the graphitisation temperature (ideally beyond 2800 °C). As already stated in the Introduction section, the language in science should be as accurate as equations, as far as possible, so that everyone understands the same thing. Unfortunately, the literature is full of examples of wrong uses of the vocabulary, thereby contributing to promoting obscurity instead of clarity.

3.2. Proposal for four independent and complementary descriptors

When describing carbon materials, the literature uses words associated with quite vague meanings such as "structure", "nanostructure", "microstructure", "crystallite", "lamellae", "particle", "flake", sometimes in the same paper, without making any attempt to clarify what the relationships between all of them are. As a specificity of carbon materials, especially graphenic, a minimum of four descriptors are needed to describe them, which are listed and defined below. This does not apply to molecular forms, which have to be described as molecules are.

In the definitions below will be used the term "**crystallite**", which has already been used several times above. Let's remind, then, that a **crystallite** is the smallest coherent volume in a crystallised ensemble, and that coherence is achieved when atoms are displayed in a periodic manner in the three dimensions of space so that they scatter a coherent wave (electrons, neutrons, X-ray photons) in specific directions. These specific directions generate the diffraction peaks in a diffractogram. A genuine **amorphous** material is able to scatter such a wave, but is not able to do it in specific directions, as an illustration of the exact difference between scattering and diffraction. Applied to **graphenic** materials, a **crystallite** is a stack of perfect **graphene layers** piled up periodically. Fig. 5 illustrates what a **crystallite** is within a crystallised ensemble of **graphene layers**, a standard configuration in carbonaceous materials with turbostratic **structure**.

The first descriptor is the morphology, because it is what is seen first. It is accessible through the naked eye, or optical microscopy, or scanning electron microscopy (SEM), depending on the dimensions of the object. "Morphology" strictly designates the shape (outer or inner) of the material: bulk, filamentous, porous, aligned (when talking about nanofilaments for instance), coiled, tubular, hollow, bamboo-like, flake, lamella, film, crumpled, folded, particle, polyhedral, facetted, etc. are morphological terms. Clearly, those terms may apply whether the material is amorphous or crystallised, whatever the crystallite size or the pore size, if any. There might be a direct relationship between a given morphology and a crystallised state, but it corresponds to particular cases. For instance, it is likely that a facetted particle reveals a crystallised nature, although diffraction should confirm it, as it is not a rule (carbon blacks will provide an example where facets occur because of the improvement of the nanotexture, not because of a structural change). Such a direct relationship may also result from a previous study having used all the needed descriptors, afterwards allowing to make such a shortcut. For instance, when considering graphene flakes, a crumpled aspect of the flake was found to indicate a turbostratic structure, whereas a folded aspect indicates a coherent stacking (i.e. crystallised according to the graphitic - or possibly rhombohedral -structure) [85].

When describing carbons, the **morphology** does not consider the orientation or even the existence of **graphene layers**.




Fig. 5. Sketch of a crystallised ensemble of **graphene layers** in a turbostratic carbon. It is made of adjacent **crystallites**, one of them being shown as the shaded part in the circled area. **Graphene layers** are not perfect, but portions of them are, within the **crystallites**. Reprinted from Ref. [84] with permission of Springer.

The second descriptor is the texture, to account for the spatial relationship between graphene stack ensembles, whenever the graphene layers are distorted (as sketched in Fig. 5) or perfect. Therefore, the texture can only be obtained by using characterisation methods able to reveal the mutual orientation of graphene layer ensembles. To achieve this, HRTEM lattice fringe mode comes immediately to mind of course, but actually seeing the graphene layers is not necessary, and low-magnification TEM dark-field imaging mode [86], or local diffraction modes may also provide the appropriate information: isotropic, anisotropic, concentric, random, fibrous, radial, aligned, alternate (the last two when talking about graphene layer ensembles), herringbone or fishbone (when talking about nanotubes), platelet (when talking about nanofibres), etc. are textural terms. The term "fibrous" is a particular case, as it implies that the textures in the longitudinal direction (the fibre axis) and in cross-section should be described independently as they are usually quite different (see Section 3.3.3).

When describing **graphenic** carbons, the **texture** does not consider whether the **graphene layers** are perfect or defective.

The third descriptor is the nanotexture, to account for the graphene quality within a crystallised ensemble, as sketched in Fig. 5. Therefore, "nanotexture" relates to the dimensions of the crystallites, which standard designations are L_a and L_c . Ultimately, with increasing carbonisation temperature, distortions within the graphene layer ensemble shown on Fig. 5 will be healed and the whole will become a single crystallite. Defective, distorted, wavy, perfect: terms related to nanotexture are few because nanotexture is mostly and accurately defined and quantified by L_a , and L_c . Fig. 5 shows other parameters, also all related to **nanotexture**, namely L_1 , L_2 , N, and β . They are all obtained from HRTEM lattice fringe imaging mode [87] and direct measurements on the fringes. L_1 is supposed to be similar to L_{α} : L_2 is the average length of the continuous yet distorted graphene layer (in that case, the same graphene layer may contribute to several crystallites); N is the number of layers in a **crystallite**; β is the average distortion angle within the graphene layer ensemble, as obtained from image analysis [88] or local diffraction [89]. L_1 , L_2 , N, and β are then complementary to L_a and L_c and then are interesting parameters in principle, but the reliability is low, considering how far the values can be fooled by (i) nanotexture alteration brought by the TEM preparation method (if based on ion-thinning), (ii) nanotexture alteration induced by the sensitivity of graphene layers to high energy electrons (when using TEM with electron beam of energy above 80 keV); (iii) superimposition effects due to the more or less aligned graphene layer stacks within the whole specimen thickness (10-100 nm in the average, hence, the lower the nanotexture quality - meaning very small crystallites - the higher the chances of error). These error sources tend presumably to minimise L_1 and L_2 values, whereas the error on N and β can occur both ways. On the other hand, because probing the material by HRTEM is very local, the values of L_1 , L_2 , N, and β can be not representative of the bulk material in case any heterogeneity is missed by the operator.

Therefore, more reliable values for L_a and L_c are obtained from XRD by applying the Scherrer law:

$$L_{hkl} = K \times \lambda / (FWHM_{hkl} \times \cos\theta)$$

 L_{hkl} is the **crystallite** dimension along the (*hkl*) planes, λ is the radiation wavelength, *FWHM*_{hkl} is the full width at half maximum of the *hkl* diffraction peak, θ is the Bragg angle. The equation is applied to the 11 (0) band/peak (preferably to the 10(0) band/peak, which is very sensitive to stacking faults [26]) to get L_a , and to the 002 peak (or 001, in case of turbostratic stacking [26]) to get L_c . However, applying the Scherrer law to *hk*(0) bands/peaks requires to give an appropriate value to *K*, a correcting factor which relates to the shape of the peak. *K* is usually taken as 0.89 for 00l peaks, the shape of which usually corresponds to a pseudo-Voigt function. For *hk* bands, K = 1.84 is commonly taken in the literature (*e.g.*, in Ref. [82]), but it remains an unsatisfactory approximation because the shape of the *hk* bands changes continuously

along their path to becoming hkO peaks and the full or partial development of the three-dimensional **structure** upon increasing annealing temperature. Correspondingly, *K* should change continuously as well (see the discussion about this in Ref. [43]). Therefore, bottom-up approaches which allow getting rid of the determination of *K*, as proposed in Refs. [26,43], should be preferred to obtain accurate L_a values.

The average value of *N* in a bulk carbon can be obtained from the *002/001* XRD peak from dividing L_c by the average intergraphene distance (obtained from the 2θ position of the *002/001* peak by using the Bragg equation: $2 d_{hkl} x \sin \theta = n x \lambda$).

 L_a (and L_c as well, in some extent, *i.e.* when L_a is large and the number

of graphene layers involved is a few only) can also be obtained by Raman spectroscopy [90,91], as a quite common method for characterising carbons. For this, specific features of the Raman spectra are related to L_a values by calibrating them on XRD results, ideally using a reference carbon series as close as possible to the carbon material to be studied. However, attention has to be paid that the values obtained from Raman and XRD are not necessarily equivalent because they do not see graphene layers the same way [92]: L_a from XRD is planarity-related, diameter meaning that it relies on the length of perfect graphene layers in the average **crystallite**. For XRD, it does not matter whether the **graphene** lavers contain in-plane defects or not (such as rings other than hexagons, or vacancies) provided those defects do not alter the planarity of the layers, nor the long-range periodic display of the atoms. On the other hand, L_a from Raman is defect-related, meaning that it relies on the occurrence of graphene edges and in-plane defects, whether the gra**phene layers** are wavy or not. In general, for very small L_a (say, few nanometres), the value differences between Raman and XRD are not distinguishable from the measurement uncertainty. For larger L_a , differences can be significant, especially in case an appropriate calibration is lacking. Therefore, when commenting about L_a values, a good habit would be to discriminate whether they are obtained from XRD or Raman by a specific notation, for instance $L_{a(XRD)}$ and $L_{a(R)}$, respectively.

> Attention has also to be paid that, although the nanotexture somehow describes the arrangements of graphene layers at nanoscale (that is why it is preferable to the term "nanostructure"), the term is not for designating the same features as **texture** when the **texture** happens to be nanosized. "Texture" (see above) is an orientation-related descriptor, whereas "nanotexture" is a perfection-related descriptor. For instance, considering an elemental particle of carbon black (see Section 3.3.2), the common concentric display of the graphene layers is a textural feature, not nanotextural, despite it is nanosized. To get rid of any doubt, let's consider the effect of annealing: for most types of carbon materials built from multi-graphene layer crystallites (hence excluding those built from individual molecular forms such as fullerenes, SWCNTs, nanohorns...), the texture remains the same whatever the annealing temperature up to 3000 °C, while the nanotexture improves (provided the graphene layers to start with are distorted, as in Fig. 5) from a low grade nanotexture to a high grade nanotexture. Therefore, using "microtexture" to designate a texture with microscale dimensions should be prohibited as well, so that not to introduce any confusion in the meaning of "nanotexture". Likewise, "microtexture" should not replace the term "nanotexture" when it happens that La may be in the micrometre range.

> When describing **graphenic** carbons, the **nanotexture** does not consider whether the **graphene layer** stacking is random (turbostratic) or coherent (**graphitic**, or rhombohedral, or a mixt of both).

Finally, the fourth descriptor is the <u>structure</u>, which strictly designates the crystallographic state only, *i.e.* the crystallographic **structure** of the **crystallites** (if any), determined by powder-mode XRD. Therefore, it is fully independent from the **crystallite** size and orientation: **allotropic**, turbostratic, **graphitic**, **partially graphitic**, Bernal (now Hull-Bernal, see Section 2), rhombohedral, **amorphous**, are **structural** terms. Of course, electron diffraction, which is more local, possibly very local, may also provide the information, but attention has to be paid to the effects of preferred orientations of the specimen with respect to the

direction of the electron probe. For instance, in local diffraction, should an electron diffraction pattern show a *112* spot, then the **graphitic** or **partially graphitic structure** is ascertained, but the absence of it does not demonstrate a turbostratic **structure**. Indeed, a preferred orientation of the specimen which does not allow any of the three (*112*) atomic plane families to be exposed to the electron beam according to the Bragg angle may always be suspected. Consistently with this definition, terms such as "**microstructure**" and "**nanostructure**" do not make any sense as any prefix to the word "**structure**" is useless, and then should be prohibited within this four-descriptor scheme.

When describing **graphenic** carbons, the **structure** does not consider the size of the **crystallites**.

It has to be emphasised that the four descriptors above describe <u>different</u> and <u>independent</u> aspects, *i.e.* switching from a descriptor to another is not generated by a change of scale, although, for instance, considering the **nanotexture** necessarily requires to look at it at the nanoscale. Overall, this four-descriptor scheme may also apply to carbon materials other than **graphene**-based, *e.g.* $sp^{3}C$ -based, however, considering descriptors 1 and 4 (**morphology** and **structure**) is usually enough in that case.

3.3. Application of the four-descriptor scheme to four examples of graphenic carbons

3.3.1. Bulk carbons being carbonised, and graphitised

In order to address common mistakes, misuses, and confusions made in the literature when describing carbonaceous materials being increasingly heat-treated, possibly up to the **graphitisation temperature** (which does not mean that the **graphitic structure** has been successfully reached [6]), the descriptors defined in Section 3.2 are here used to describe the events taking place during the carbonisation/**graphitisation** processes and their effects on the materials.

At first, let us summarise the basics of the standard carbonisation and **graphitisation** mechanisms, according to Oberlin's model and subsequent developments [41,42,93–98]:

When subjected to an increasing heat-treatment, any non-gaseous organic precursor, hence typically with a chemical composition within the C, H, O, N, S system (where O, or N, or S could be nil) starts by losing chemical elements other than carbon. This promotes polyaromatisation and then polycondensation reactions which create small graphenic entities about the size of a coronene molecule (0.7-1 nm), possibly single, otherwise stacked by 2 or 3. These small graphenic stacks are called Basic Structural Units (BSUs), because they occur in all kinds of solid organic precursors. They mark the early step of graphenisation. At some temperature (variable with the precursor), the breaking of the bonds in the material tends to make it more or less soft (in some cases very soft), allowing the BSUs to be aligned by the flow of effluents leaving the material. However, the higher the content in O (and N, and S), the higher the possibility of cross-linking functions which oppose this alignment process. At some point (400–550 °C), the material recovers a solid state irreversibly, marking the end of the so-called primary carbonisation. The regions in the material in which BSUs are about aligned are named regions of Local Molecular Orientation (LMOs), which actually make the wall of pores. The higher the O, N, S contents at about the softening temperature, the less developed the LMOs (and the smaller the pores). Therefore, LMOs are areas where the BSUs are only slightly misoriented whereas neighbouring LMOs are highly misoriented relative to each other. At this step, the BSUs are crystallites gathered as LMOs (Fig. 6).

Then, as temperature proceeds, the so-called secondary carbonisation takes place, which ends at \sim 1800–2000 °C, during which the remaining non-carbon atoms are removed, and the slight misorientations within the LMOs are progressively healed so that the alignment progresses from neighbouring BSUs to others. In other words, BSUs no longer exist, and **graphenisation** proceeds and improves (Fig. 5 may illustrate what a LMO looks like at some point of secondary




Fig. 6. Sketch of an ensemble of tiny **graphenic** entities roughly aligned, forming a LMO (or a portion of it) as it can be found at the end of primary carbonisation of an organic precursor. Some of the entities are parallel, thereby forming BSUs (two are indicated with their number *N* of constituting **graphenic** entities), others are still single. At this step, **crystallites** are limited to BSUs, and $L_{a(XRD)}$ is the average of the BSU diameters. Black dots are to represent heteroatoms (modified and reprinted from Ref. [93], by permission of Technip).

carbonisation: the BSU coalescence has started, but the healing of inplane defects has not progressed much yet). Ultimately, each single LMO finally becomes a single **crystallite** in which all the **graphene layers** are parallel (resulting in the main increase of $L_{a(XRD)}$, the starting value of which being that of the average BSU diameter, and the ultimate value of which being that of the whole LMO). Meanwhile, the misorientations between the LMO areas, which are severe, cannot be healed. Meanwhile also, the remaining heteroatom-containing crosslinkers at LMO boundaries are replaced by all-carbon defects (*e.g., sp*³C, non-6 rings...).

Finally, during a subsequent thermal treatment up to **graphitisation temperature** (~2900 °C), further solid-state rearrangements occur so that the formally turbostratic **structure** within each **crystallite** tentatively turns into the **graphitic structure**. Precursors able to generate long-range LMOs during primary carbonisation (hence, ultimately resulting in extended **crystallites**) succeed in this process, whereas precursors able to generate short-range LMOs only (hence ultimately resulting in small **crystallites** at **graphitisation temperature**) do not. All intermediate cases occur, producing more or less **partially graphitise** (arbons, also called "graphocite" [99], "poorly-ordered graphite" [100], or "semi-graphite" [101] by geologists.

These mechanisms are general and valid for all solid organic precursors (and even liquid precursors - e.g., anthracene oil - if high isostatic pressures in confined conditions are applied). Consequently, so-called glassy/vitreous carbons, previously mentioned, are not specific carbons, they are merely carbons originating from organic precursors with high O (+N, +S)/C with respect to H/C (e.g., furfurylic resin). Therefore, they are **non-graphitisable**. It is the same for natural organic precursors such as type-III kerogens (i.e., from humic origin, in other words terrestrial plants) [93]. Likewise, at the other end of the organic precursor range are industrial ones with high H/C ratios such as petroleum or coal tar pitches, or natural ones such as boghead-type coals (derived from algae) [93], which are graphitisable. All solid organic precursors roughly range in-between. When mentioning the ability of a precursor or an immature carbon to actually become graphite (or not) if heat-treated up to the graphitisation temperature, "graphitisable" and "non-graphitisable" are better terms than "graphitising" and "non-graphitising", yet the latter are commonly used in the literature. The use of the present participle should only be limited to describing carbon materials actually being thermally treated, not to express their potential in becoming graphite.

Now considering the four descriptors applied to bulk carbons (bulk carbons are of paramount importance for industrial-scale applications, *e. g.*, as constituents for anodes of any kind, or for chemicals adsorbers):

- Morphology: When considering organic precursors being carbonised, the resulting carbonaceous material has no specific morphology but porous, with an open porosity for large pores, and a tendency to close porosity for the carbonaceous materials with the smallest pores (as in glassy carbons). The related characterisation methods should have the magnification and resolution power to reveal the pore sizes, down to HRTEM for the smallest ones.
- Texture: Primary carbonisation (< 550 °C) is the step where the texture is built. Starting by being isotropic until the softening point is reached, the material then remains globally isotropic as a bulk, but becomes locally anisotropic when the LMOs are formed. Graphene layer stacks within the LMOs make the pore walls and are parallel to the pore wall surface. Additional anisotropies may also locally develop (*e.g.*, concentric, radial, so-called "Brooks & Taylor" type textures, *etc.*) depending on the precursors (*e.g.*, in some pitches, or pitch components [96,97]). Then, consistently with the definition of the descriptor, the texture will not change all along, from the end of primary carbonisation to the final graphitisation temperature, meaning that the average LMO size barely increases all along. Dark-field TEM imaging at medium range magnification is the most appropriate method to reveal LMO sizes [86].
- Nanotexture: Secondary carbonisation (~550–2000 °C) is the step where the **nanotexture** improves the most significantly, marked by the increase of L_a (and L_c , meanwhile). Graphene layers then become larger, meaning that graphenisation improves. How the **nanotexture** progresses within increasing secondary carbonisation is illustrated by Fig. 7. Although Fig. 7 illustrates the **nanotexture** by means of HRTEM images, powder-mode XRD remains the most convenient method to obtain L_a and L_c , unless local information is deliberately sought (*e.g.*, to reveal any surface anisotropy which develops at the contact to a surface, as in moulded glassy carbons).
- Structure: Graphitisation treatment step (> ~2000 °C) is where the structure is subjected to the largest changes, specifically for graphitisable carbons. This corresponds to the temperature above which the diffusion of carbon atoms in graphene crystallites becomes significant [102]. With the appropriate precursor (High H/C and low O(+N+S)/C atomic ratios, which generate large LMOs), the crystallographic structure switches from turbostratic to graphitic or partially graphitic, otherwise it remains turbostratic. More in the detail, taking the example of a graphitisable coke series, the evolution of the crystallite structure includes (i) above 1550 °C: the occurrence of graphene layers superimposed by pairs in AB positions (referring to the ABAetc. graphene laver positions in graphite) [43]; (ii) above 2000 °C: the occurrence of graphitic sequences (ABAetc. within the crystallites, yet still containing turbostratic sequences) [43]; (iii) above 2300 °C: the occurrence of stacking faults as single graphene layers in C position (in reference to the ABCAetc. graphene layer positions in the rhombohedral structure) dispersed in graphitic sequences [26]. This means that it can be said that structuration improves only if the material structure evolves from turbostratic to partially graphitised (which means a contribution of AB pairs, for the least, or more, *i.e.* the occurrence of small graphitic sequences within the crystallites) or fully graphitised (all the crystallites are made of graphene layers stacked according to the




Fig. 7. From left to right: Typical evolution of the **nanotexture** within a LMO with increasing temperature (HRTEM lattice fringe mode imaging). The interfringe distances are \sim 0.34 nm. The white circle shows up a dark contrast so-called "Bragg fringe", the occurrence of which is an indicator of local perfect **graphene** stacking and orientation with respect to the Bragg angle.

M. Monthioux

ABAetc. hexagonal sequence, possibly disturbed by stacking faults) [26,43]. In case the material remains turbostratic whatever the treatment temperature (which may happen with appropriate precursor compositions), only the **nanotexture** improves more or less upon heat-treatment.

Therefore, the carbonisation/graphitisation of organic precursors is another example of possible shortcut (referring to the aforementioned case where the structure of graphene flakes could be deduced from their morphology), since the texture of the carbonaceous materials at an immature state (primary carbonisation step), quantified by the LMO size, governs the ultimate structure at graphitisation temperature.

Attention has to be paid that what is said in this section is to describe the big picture. Carbon materials are so complex, with an infinite number of possible organic precursors, that some exceptions may always be found.

3.3.2. Carbon blacks

Alike bulk carbons at macroscale, carbon blacks are overall isotropic materials even at nanoscale (see the "Texture" paragraph below). Carbon blacks are materials based on elemental nanosized particles obtained from various thermal processes, either partially oxidative or not, starting from a variety of organic feedstock (*e.g.*, methane, oils...). They have a considerable impact on industrial-scale applications such as tyres, pigments, conductive fillers, and more. Information about their synthesis, properties, and applications can be found in textbooks such as Ref. [103].

- Morphology: the basic constituents of carbon blacks are elemental particles which, from the morphological point of view, usually exhibit the shape of more or less round nanoparticles (< ~100 nm) (Fig. 8), possibly with a hollow core. If subjected to high temperature annealing after the synthesis, The shape of elemental particles may become facetted, as a result from the improvement of the nanotexure (see below). Elemental particles can be individual (as in thermal blacks), but most often combine with each other in various ways and extent according to multi-scale arrangements so that a whole range of morphologies is obtained. They are bonded as aggregates through strong cohesive forces, and then aggregates gathered as agglomerates through weak cohesive forces (Fig. 8a). Aggregates can be more or less elongated, and more or less branched. Therefore, the term "carbon black" may designate either the elemental particles, or the aggregates, or the agglomerates.
- **Texture:** the term concerns the elemental particles only, and is almost systematically concentric (Fig. 8b and c). In spite of this, the overall **texture** can be said isotropic because, statistically speaking, all graphene orientations can be found when considering a single




Fig. 8. (a) Multiscale **morphology** of carbon blacks; reprinted from Ref. [104] with permission of Elsevier. **(b)** HRTEM image of an elemental nanoparticle of a furnace black; reprinted from Ref. [105]. **(c)** The well-known sketch of half an elemental particle proposed by Heidenreich et al. [106] showing both the hollow **morphology**, the concentric **texture**, and a common low-grade **nano-texture**, here with **crystallite** sizes 3–4 times larger than that of BSUs, but smaller sizes are quite common, as in (b); reprinted with permission of Wiley.

elemental particle, and, *a fortiori*, when considering an ensemble of them. Such a **texture** is likely to result from the carbonisation, in homogenous phase (*i.e.*, in the gas phase), of organic liquid nanodroplets containing tiny **graphenic** entities that surface tensions enforce to align parallel to the droplet surface. This mechanism was proposed long time ago [107], but recently received a strong support as the thermal cracking of methane and hydrogen was demonstrated to generate a transient, colloid-like organic liquid phase, even at temperatures far beyond 1000 °C, before it turns into solid carbon [108].

- Nanotexture: That of carbon blacks is usually of low grade (Fig. 8b and c), but it actually depends on the synthesis process, and can be improved upon thermal annealing anyway, as illustrated by Fig. 7. The ultimate improvement of the nanotexture may induce a change in the particle morphology, through faceting [96,103].
- **Structure**: The starting **structure** of carbon blacks is always turbostratic. It usually remains as such because the **crystallites** develop within the nanosized elemental particles in a volume constrained by the concentric **texture**, hence they cannot reach large L_a . This prevents the **structure** to ever become that of genuine **graphite** whatever the annealing temperature.

3.3.3. Carbon fibres

Carbon fibres [109,110] are the key components for a variety of composites devoted to highly stressful conditions of use (where the stress can be thermal or mechanical). They are interesting to consider here because they are highly anisotropic materials [111], as opposed to overall isotropic carbons as described in Sections 3.3.1 and 3.3.2. They result from the same carbonisation-graphitisation mechanisms as bulk carbons. However, they are subjected to an additional step of partial oxidation applied after spinning and before the end of primary carbonisation so that the filamentous shape is maintained while the carbonisation temperature increases. On the other hand, carbon fibres exhibit the specificity to be highly anisotropic materials due to the stretching stresses applied during the spinning process. The latter event (stretching) may improve the natural graphitisability inherited from the precursor chemical composition due to the resulting enforced alignment of the graphene layers, but the former event (partial oxidation) does not alter the graphitisability significantly, because the alignment of the graphenic entities has taken place before the oxidation step.

- Morphology: Carbon fibres are individual filaments, with diameters in the range of several micrometres (smaller for polyacrylonitrilebased (PAN-based) fibres compared to pitch-based) although commercial carbon fibres are gathered into tows of several thousand filaments during spinning. More in the detail, the cross-section of carbon fibres is not always circular. It could be bean-shaped, flattened, oval, exhibiting an open wedge... (the latter being specific to pitch precursors). The surface state (smooth, rough, irregular, striated...) may also vary.
- **Texture**: because the organic precursor (polymer or pitch) is stretched during the spinning process, the polymer-chains are aligned with respect to the fibre-axis, then generating **graphene layers** more or less aligned with respect to the fibre axis upon subsequent carbonisation. This is called a fibrous **texture**. The alignment is low for polymers with short chains, and is high for polymers with long chains (such as the ladder-polymer of PAN) or precursors containing preformed **graphene layers** along the fibre axis is an important **textural** parameter governing the properties, and can be quantified by XRD applied to a single fibre tow subjected to a nonrotated X-ray beam (*i.e.* NOT in powder-mode) and measuring the opening angle of the resulting *002/001* arc. On the other hand, the cross-sectional **texture** is independent from the longitudinal **texture**, and may appear nanoporous and random (looking like that

of glassy carbons) as it is common for PAN-based fibres (Fig. 9c and d), or concentric (Fig. 9a), or "PANAM"-type (in reference to the logo of the former airline company), or radial (Fig. 9b) as it is common for carbon fibres based on so-called anisotropic pitches.

Other **textures** may exist, including mixed ones, for instance: PANbased fibres may exhibit a ring in cross-section in which the **graphene layers** are anisotropically displayed within the overall cross-sectional isotropic **texture** [112]; carbon fibres obtained from mesophasic pitches may contain areas of isotropic **texture** visible in cross-sections as dispersed within the overall anisotropic **texture**. As opposed to the random **texture** (Fig. 9c and d), the radial **texture** (Fig. 9b) obtained for some pitch-based fibres favours the development of large **graphene layers** at long distance in both longitudinal and cross-sectional directions, allowing the material to maintain its natural **graphitisability**. Therefore, both **textures**, longitudinal and cross-sectional, are important for the properties and have to be described and quantified. In carbon fibres with fibrous **texture**, LMOs are ribbon-like.

- Nanotexture: Due to the overall fibrous texture, the dimensions of the crystallites are anisotropic as well. In particular, longitudinal and cross-sectional L_a are likely to be different, more specifically with polymer-based fibres. Longitudinal L_a can be obtained from the 11(0) band/peak during the same XRD experiments carried out to measure the 002/001-arc angular opening, but obtaining the same for cross-sectional L_a is experimentally tricky and/or time-consuming. Obtaining average L_a and L_c values by XRD on a powder of ground fibres is a quite convenient compromise for comparing the nanotextures of various fibres in first place, which could be sufficient in most of cases, specifically for carbon fibres with a similar fibrous texture.
- Structure: Because carbon fibres originate from organic precursors, their graphitisability exhibits a similar dependence on the chemical composition of the precursor as explained in Section 3.3.1. Therefore, it is no wonder that carbon fibres based on precursors such as cellulose/rayon or polyacrylonitrile (PAN) are non-graphitisable, whereas carbon fibres based on pitches can be graphitisable. This directly relates to the textural characteristics, *i.e.* that of the ribbon-like LMOs. The cross-sectional LMO dimension is in the nanometre range in PAN-based fibres, whereas it can be in the micrometre range

in pitch-based fibres (ultimately equal to the fibre radius - see Fig. 9b - assuming that the longitudinal LMO dimensions in both fibre types are alike. However, there are several examples of external stresses applied to non-graphitisable precursors which are able to enforce the graphene layers to align at long distance (hence generating larger LMOs than they naturally would), making them graphitisable: this is what may happen with natural terrestrial plantderived organic precursors subjected to oriented lithostatic pressure during diagenesis and catagenesis [113], making them able to become natural graphite whereas their starting chemical composition would forbid it; it may also happen with polyimide polymers when deposited as thin films, within which the interaction with the substrate aligns the graphenic entities parallel to it when they form during primary carbonisation [114]. Therefore, the stretching stresses developed during the spinning of fibres may help non-graphitisable precursors to acquire a partial graphitisable character. However, since acquiring the graphite structure requires largely-developed graphene layers (large LMOs), there is no way that any carbon fibre exhibiting an isotropic cross-sectional texture (as in Fig. 9c and d) can be graphitisable.

3.3.4. Carbon nanofilaments

Carbon nanofilaments also are highly anisotropic materials but are interesting to consider in addition to carbon fibres because of their nanosize. Carbon nanofilaments are emblematic of the nano-world, because they are the nanomaterials from which the craze about nanoscience really started, thanks to the seminal paper by Iijima in 1991 [115]. Combining a carbon source, a nanosized catalyst, and medium-range-temperature conditions in inert atmosphere is the most common way to produce carbon nanofilaments [116]. Such a process may produce two kinds of carbon nanofilaments, namely nanotubes and nanofibres, depending on the dimensions, geometry, and chemical composition of the catalyst nanoparticles [117]. There is no standard definition to strictly discriminate between both, hence considering logics and simplicity helps in this regard: a nanotube is a rod with a hollow core, whereas a nanofibre is a rod with a solid core... that simple (Fig. 10). There is no reason why the orientation of the graphene layers making the nanofilaments should play a role to choose between these two terms, as they both relate to morphology. On the other hand, (i) CNTs can be single-walled, i.e. the tube wall is made of a single




Fig. 9. From **(a)** to **(c)**: top: SEM images of fibre cross-sections with concentric, radial with a wedge, and isotropic **textures**, respectively; bottom: sketches of the same. (a) and (b) are pitch-based carbon fibres, (c) is a PAN-based fibre. The wedge in (b) does not exist for low carbonisation temperatures and increasingly opens as carbonisation proceeds. **(d)**: sketch of a PAN-based carbon fibre showing the fibrous, dual **texture**, *i.e.* with **graphene layers** more or less aligned along the fibre axis (anisotropic **texture**), as well as the random display of the **graphene layers** in cross-section (isotropic **texture**) forming elongated nanopores. Modified from Ref. **[42]** by permission of Taylor & Francis.




Fig. 10. HRTEM images as examples of **(a)** a multiwall carbon nanotube with the herringbone-bamboo **texture** (*hb*-MWCNT); the core is mostly hollow, with only few layers crossing perpendicularly the inner cavity. **(b)** a carbon nanofibre with the herringbone **texture** (*h*-CNF); there is no hollow core. Photo credit: L. Noé, CEMES.

graphene layer (SWCNTs); (ii) CNTs and CNFs can be multi-walled (the former being abbreviated as MWCNTs), *i.e.* the nanotube wall or the nanofibre body is made of several superimposed graphene layers or of a single graphene layer wrapped on itself. Let's also note that high-temperature catalyst-free growth of nanofilaments is also possible when starting from a sublimed graphite source, generating MWCNTs only [115,116].

Therefore, unlike SWCNTs which, as said previously, have to be considered as molecular forms, CNFs and MWCNTs are not, although they grow as individual nano-objects, because XRD of a bunch of them randomly oriented provides a diffractogram similar to the bottom one in Fig. 2. This ascertains that they do not correspond to a different allotrope, they are merely nanoforms of the turbostratic allotrope. However, there are many types of them the discrimination of which requires all four descriptors to be used, as reported in Fig. 11. Alternatively, CNTs may also be built with a single graphene layer wrapped concentrically as a scroll (forming a s-MWCNT), or a single graphene ribbon wrapped helically (forming a hw-MWCNT). In that case, strictly speaking, they may be said "multi-walled" yet made with a single graphene, thereby also generating a stacking periodicity. It is the same for CNFs, except that the scroll-type was never observed. As seen by HRTEM, the scroll texture barely discriminates from the concentric texture, and likewise, the helical wrapping texture looks like the herringbone texture. Therefore, an accurate description of nanofilament types requires more than HRTEM images (e.g. local electron diffraction, and/or grinding experiments [117]). Examples of the various morphologies and textures of CNTs and CNFs can be found in Ref. [118]. On the other hand, the fact that several graphene layers are superimposed stabilises the material, which is quite stable despite the graphene layers can be far from perfect, generating large nanotexture variations from a material to another, governed by both the chemical composition of the catalyst and the growth temperature.

It is significant that, in contrast to carbon nanofilaments built-up with several **graphene layers**, only obtaining the (*n*,*m*) helicity coordinates (by nanoprobe electron diffraction [119] or through the radial breathing modes in Raman [120]) is sufficient to fully characterise a SWCNT [121]. This is consistent with their molecular nature, as opposed to MWCNTs, which are not **molecular forms** but nanomaterials. In this picture, the peculiar case of double-wall carbon nanotubes (DWCNTs) corresponds to an ambiguity. Indeed, as SWCNTs, they usually gather into bundles and do not exhibit **nanotexture** variations (meaning that the **graphene layers** always appear straight and perfect in HRTEM longitudinal view of DWCNTs). Although I could not find an example of




Fig. 11. Description chart for carbon nanofilaments (nanofibres or nanotubes: a nanotube is hollow, a nanofibre is not) resulting from the use of the four descriptors defined in Section 3.2, in relation with the analytical methods needed (corrected and completed from Ref. [118]).

it in the literature, it is likely that bundles of DWCNTs of similar outer diameters would exhibit the same periodicity as the turbostratic **allo-trope**, added with new periodicities typical of their assembly as bundles. These features would make them a specific **allotrope**, different from both nanotubulite and MWCNTs.

4. Conclusions

A common language is needed when discussing carbon materials. At a minimum, authors should use words within the strict definitions provided in authoritative work such as Refs. [6,7]. Such definitions for words among those which are the most misused in the literature are reminded here. But this is not enough to clarify the field. Indeed, there was no methodology available to comprehensively describe carbon materials of any kind in a standardised manner so far, and this situation is responsible for confusions and misunderstandings regarding the published data. An easy protocol using four strictly independent descriptors (morphology / texture / nanotexture / structure) is proposed here in order to address this issue. It also simplifies the vocabulary to be used because words such as microtexture, microstructure, and nanostructure, the meaning of which is never clear, are no longer necessary. It is believed that the systematic use of this protocol from now on would significantly contribute to making much clearer the description and the understanding of what the carbon materials which the studies will be reported in the forthcoming literature actually are.

CRediT authorship contribution statement

Marc Monthioux: Writing – review & editing, Writing – original draft, Visualization, Validation, Resources, Methodology, Conceptualization.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Data availability

No data was used for the research described in the article.

Acknowledgments

Prof. P. Puech is thanks for fruitful comments and suggestions.

References

- C. Lehman, A la recherche de la nature du diamant: guyton de Morveau successeur de Macquer et Lavoisier. Annales De La Révolution Française n°383, Armand Colin, 2016, pp. 81–108. Paris (France).
- [2] J. Berzelius, M. Plantamour, Rapport annuel sur les progrès des sciences physiques et chimiques. Académie Royale de Stockholm, Fortin-Masson, 1841 translatorParis (France).
- [3] A. Baudrimont, Traité De Chimie Générale Et expérimentale, Avec Les Applications Aux arts, à La médecine, Et à La Pharmacie, Baillière, 1844. Paris (France).
- [4] A. Naquet, De L'allotropie Et De L'isomérie, Baillière et Fils, 1860. Paris (France).
 [5] G. Férey, Une (brève) Histoire De La Cristallographie, L'Actualité Chimique,
- 2014, pp. 29–40, 387-388-389.
 [6] E. Fitzer, K.-H. Köchling, H.P. Boehm, H. Marsh, Recommended terminology for the description of carbon as a solid, Pure Appl. Chem. 67 (1995) 473–506.
- [7] A. Bianco, H.-M. Cheng, T. Enoki, Y. Gogotsi, R.H. Hurt, N. Koratkar, T. Kyotani, M. Monthioux, C.-R. Park, J.M.D. Tascon, J. Zhang, All in the graphene family – A recommended nomenclature for two-dimensional carbon materials, Carbon 65 (2013) 1–6.
- [8] The whole physics and chemistry of carbon series (31 issues so far), initially published with Marcel Dekker, now with CRC Press, under the editorship of P. L. Walker, P. A. Thrower, and now L. Radovic.
- [9] H.O. Pierson, Handbook of Carbon, Graphite, Diamond and Fullerenes, William Andrew Publishing, Elsevier, 1994. ISBN: 0-8155-1339-9.
- [10] M. Inagaki, F. Kang, M. Toyoda, H. Konno, Advanced Materials Science and Engineering of Carbon: Fundamentals, Butterworth-Heinemann, Elsevier, 2014. ISBN: 978-0-12-407789-8.
- [11] D.D.L. Chung, Carbon Materials: Science and Applications, World Scientific, 2019. ISBN: 9813221909.
- [12] H. Jäger, W. Frohs, Industrial Carbon and Graphite Materials (Eds.), Wiley-VCH, 2021. ISBN: 978-3-527-33603-6.
- [13] Z. Pan, H. Sun, Y. Zhang, C. Chen, Harder than diamond: superior indentation strength of wurtzite BN and lonsdaleite, Phys. Rev. Lett. 102 (2009) 055503.
- [14] V.N. Denisov, B.N. Mavrin, N.R. Serebryanaya, G.A. Dubitsky, V.V. Aksenenkov, A.N. Kirichenko, N.V. Kuzmin, B.A. Kulnitskiy, I.A. Perezhogin, V.D. Blank, Firstprinciples, UV Raman, X-ray diffraction and TEM study of the structure and lattice dynamics of the diamond–lonsdaleite system, Diam. Relat. Mater. 20 (2011) 951–953.
- [15] W.E. Addison, The Allotropy of the Elements, Oldbourne Press, 1964. London.
- [16] Q. Zhu, A.R. Oganov, M. A.Salvado, P. Pertierra, A.O. Lyakhov, Denser than diamond: *ab initio* search for superdense carbon allotropes, Phys. Rev. B 83 (2011) 193410.
- [17] H.-J. Hu, C. Zhang, J. Guo, X.-Y. Ding, Q. Wang, Y.-W. Zhang, Z.G. Yu, Carbon allotropes consisting of rings and cubes, Dia. Relat. Mater. 121 (2022) 108765.
- [18] Q. Wei, H. Yuan, W. Tong, M. Zhang, Three new orthorhombic superhard metallic carbon allotropes, Dia. Relat. Mater. 121 (2022) 108731.
- [19] X. Yang, M. Yao, X. Wu, S. Liu, S. Chen, K. Yang, R. Liu, T. Cui, B. Sundqvist, B. Liu, Novel superhard sp³ carbon allotrope from cold-compressed C₆₀ peapods, Phys. Rev. Lett. 118 (2017) 245701.
- [20] C.E. Nordman, D.L. Schmitkons, Phase transition and crystal structures of adamantane, Acta Crystall. 18 (1965) 764–767.
- [21] J. Filik, J.N. Harvey, N.L. Allan, P.W. May, J.E.P. Dahl, S. Liu, R.M.K. Carlson, Raman spectroscopy of diamondoids, Spectrochim. Acta Part A 64 (2006) 681–692.
- [22] F. Piazza, K. Cruz, M. Monthioux, P. Puech, I. Gerber, Raman evidence for the successful synthesis of diamane, Carbon 169 (2020) 129–133.
- [23] V.E. Antonov, I.O. Bashkin, A.V. Bazhenov, D.M. Bulychev, V.K. Fedotov, T. N. Fursova, A.I. Kolesnikov, V.I. Kulakov, R.V. Lukashev, D.V. Matveev, M. K. Sakharov, Y.M. Shulga, Multilayer graphane synthesized under high hydrogen pressure, Carbon 100 (2016) 465–473.
- [24] A.P.M. Barboza, M.H.D. Guimaraes, D.V.P. Massote, L.C. Campos, N.M. Barbosa Neto, L.G. Cançado, R.G. Lacerda, H. Chacham, M.S.C. Mazzoni, B.R.A. Neves, Room-temperature compression induced diamondization of few-layer graphene, Adv. Mat. 23 (2011) 3014–3017.
- [25] L.G. Pimenta Martins, M.J.S. Matos, A.R. Paschoal, P.T.C. Freire, N.F. Andrade, A. L. Aguiar, J. Kong, B.R.A. Neves, A.B. de Oliveira, M.S.C. Mazzoni, A.G. Souza Filho, L.G. Cançado, Raman evidence for pressure-induced formation of diamondene, Nat. Commun. 8 (2017) 96.
- [26] P. Puech, M. Jeanningros, D. Neumeyer, M. Monthioux, Addressing the effect of stacking faults in X-ray diffractograms of graphite through atom-scale simulations, Carbon Trends 13 (2023) 100311.
- [27] H. Lipson, A.R. Stokes, The structure of graphite, Proc. R. Soc. Lond. A 181 (1942) 101–105.

- [28] G. Parthasarathy, B. Sreedhar, T.R.K. Chetty, Spectroscopic and X-ray diffraction studies on fluid deposited rhombohedral graphite from the Eastern Ghats Mobile Belt, India, Curr. Sci. 90 (2006) 995–1000.
- [29] S.L.L.M. Ramos, M.A. Pimenta, A. Champi, Multiple-excitation study of the double-resonance Raman bands in rhombohedral graphite, Carbon 179 (2021) 683–691.
- [30] J.D. Bernal, The structure of graphite, Proc. R. Soc. Lond. A 106 (1924) 749–773.
- [31] M. Monthioux, J.-M. Charlier, Giving credit where credit is due: the Stone– (Thrower)–Wales designation revisited, Carbon 75 (2014) 1–4.
- [32] A.W. Hull, A new method of X-ray crystal analysis, Phys. Rev. 10 (1917) 661–697.
 [33] A. Vlahov, XRD graphitization degrees: a review of the published data and new
- calculations, correlations, and applications, Geol. Balcan. 50 (2021) 11–35.
 [34] J. Maire, J. Méring, Le processus de la graphitation, J. Chem. Phys. 111 (1960) 803–814.
- [35] R.E. Franklin, The structure of graphitic carbons, Acta Cryst 4 (1951) 253–261.
 [36] R.E. Franklin, Crystallite growth in graphitizing and non-graphitizing carbons, Proc. Roy. Soc. Lond. A 209 (1951) 196–218.
- [37] F. Banhart, P.M. Ajayan, Carbon onions as nanoscopic pressure cells for diamond formation, Nature 382 (1996) 433–435.
- [38] V.I. Kasatochkin, A.T. Kaverov, The kinetics and mechanism of homogeneous graphitization of carbon, Dokl. Akad. Nauk SSSR 117 (1957) 837–840. In Russian.
- [39] V.L. Kuznetsov, Private communication.
- [40] J. Biscoe, B.E. Warren, An X-ray study of carbon black, J. Appl. Phys. 13 (1942) 364–371.
- [41] M. Monthioux, M. Oberlin, A. Oberlin, X. Bourrat, R. Boulet, Heavy petroleum products: microtexture and ability to graphitize, Carbon 20 (1982) 167–176.
- [42] M. Monthioux, R. Setton, P. Bernier, S. Lefrant, Structure, texture, and thermal behaviour of polyaromatic solids. Carbon Molecules and Materials, Taylor & Francis, 2002, pp. 127–177 (eds.)New York (NY, USA).
- [43] P. Puech, A. Dabrowska, N. Ratel-Ramond, G. Vignoles, M. Monthioux, New insight on carbonisation and graphitisation mechanisms as obtained from a bottom-up analytical approach of X-ray diffraction patterns, Carbon 147 (2019) 602–611.
- [44] L. Hou, X. Cui, B. Guan, S. Wang, R. Li, Y. Liu, D. Zhu, J. Zheng, Synthesis of monolayer fullerene network, Nature 606 (2022) 507–511.
- [45] E. Meirzadeh, A.M. Evans, M. Rezaee, M. Milich, C.J. Dionne, T.P. Darlington, S. T. Bao, A.K. Bartholomew, T. Handa, D.J. Rizzo, R.A. Wiscons, M. Reza, A. Zangiabadi, N. Fardian-Melamed, A.C. Crowther, P.J. Schuck, D.N. Basov, X. Zhu, A. Giri, P.E. Hopkins, P. Kim, M.L. Steigerwald, J. Yang, C. Nuckolls, X. Roy, A few laver covalent network of fullerenes, Nature 613 (2023) 71–80.
- [46] H. Fang, M. Masaki, A.B. Puthirath, J.M. Moya, G. Gao, E. Morosan, P.M. Ajayan, J. Therrien, P. Jena, Discovery of U-carbon: metallic and magnetic, ArXiv (2020) 2008–01137.
- [47] J.-T. Wang, Y. Qian, H. Weng, E. Wang, C. Chen, Three-dimensional crystalline modification of graphene in all-sp² hexagonal lattices with or without topological nodal lines, J. Phys. Chem. Lett. 10 (2019) 2515–2521.
- [48] Q. Gao, L. Ou, Z. Hu, Architecture design of novel carbon family: polyhedra as building blocks, Carbon Trends 11 (2023) 100256.
- [49] R.B. Heimann, S.E. Evssyukov, Y. Koga, Carbon allotropes: a suggested classification schemes based on valence orbital hybridization, Carbon 35 (1997) 1654–1658.
- [50] J.-B. Donnet, Les allotropes du carbone: une grande famille, Actual. Chim. 295-296 (2006) 115–118.
- [51] E.H.L. Falcao, F. Wudl, Carbon allotropes: beyond graphite and diamond, J. Chem. Technol. Biotechnol. 82 (2007) 524–531.
- [52] A. Hirsh, The era of carbon allotropes, Nat. Mater. 9 (2010) 868–870.
- [53] I. Suarez-Martinez, N. Grobert, C.P. Ewels, N. Tagmatarchis, Encyclopedia of carbon nanoforms. Advances in Carbon Nanomaterials, Pan Stanford Publishing, RC Press, 2012, pp. 1–65 (ed.)Boca Raton (FL-USA).
- [54] R.M. Hazen, R.T. Downs, A.P. Jones, L. Kah, Carbon mineralogy and crystal chemistry, Rev. Mineral. Geochem. 75 (2013) 7–46.
- [55] P.S. Karthik, A.L. Himaja, S.P. Singh, Carbon-allotropes: synthesis methods, applications and future perspectives, Carbon Lett. 15 (2014) 219–237.
- [56] M. Esser, R. Dronskowski, *Ab initio* triangle maps for new insights into the crystal wave functions of carbon allotropes, Carbon 123 (2017) 708–716.
- [57] Nayak, S.K. Tiwari, Nanocarbon Allotropes Beyond Graphene: Synthesis, Properties and Applications (eds), A. K. IOP Publishing, 2023. Bristol (UK).
 [58] E.C. Girão, A. Macmillan, V. Meunier, Classification of *sp*²-bonded carbon
- allotropes in two dimensions, Carbon 203 (2023) 611–619.
- [59] W. Krätschmer, L.D. Lamb, K. Fostiropoulos, D.R. Huffman, Solid C₆₀: a new form of carbon, Nature 347 (1990) 354–358.
- [60] P. Heiney, Structure, dynamics and ordering transition of solid C₆₀, J. Phys. Chem. Solids 53 (1992) 1333–1352.
- [61] J. Fischer, P. Heiney, Order and disorder in fullerene and fulleride solids, J. Phys. Chem. Solids 54 (1993) 1725–1757.
- [62] A. Thess, R. Lee, P. Nikolaev, H. Dai, P. Petit, J. Robert, C. Xu, Y.H. Lee, S.G. Kim, A.G. Rinzler, D.T. Colbert, G.E. Scuseria, D. Tomanek, J.E. Fischer, R.E. Smalley, Crystalline ropes of metallic carbon nanotubes, Science 273 (1996) 483–487.
- [63] E. Paineau, P.-A. Albouy, S. Rouzière, A. Orecchini, S. Rols, P. Launois, X-ray scattering determination of the structure of water during carbon nanotube filling, Nano Lett. 13 (2013) 1751–1756.
- [64] K. Suenaga, M.P. Johansson, N. Hellgren, E. Broitman, L.R. Wallenberg, C. Colliex, J.-E. Sundgren, L. Hultman, Carbon nitride nanotubulite, denselypacked and well-aligned tubular nanostructures, Chem. Phys. Lett. 300 (1999) 695–700.

M. Monthioux

- [65] Y. Saito, Nanoparticles and filled nanocapsules, Carbon 33 (1995) 979–988.
- [66] D. Ugarte, Onion-like graphitic particles, Carbon 33 (1995) 989–993.
- [67] P.J.F. Harris, High-resolution electron microscopy studies of a microporous carbon produced by arc-evaporation, J. Chem. Soc. Faraday Trans. 90 (1994) 2799–2802
- [68] J. Han, R. Jaffe, Energetics and geometry of carbon nanoconic tips, J. Chem. Phys. 108 (1998) 2817–2823.
- [69] S. Iijima, M. Yudasaka, R. Yamada, S. Bandow, K. Suenaga, F. Kokai, K. Takahashi, Nano-aggregates of single-walled graphitic carbon nano-horns, Chem. Phys. Lett. 309 (1999) 165–170.
- [70] Q. Fan, L. Yan, M.W. Tripp, O. Krejci, S. Dimosthenous, S.R. Kachel, M. Chen, A. S. Foster, E. Koert, P. Liljeroth, J.M. Gottfried, Biphenylene network: a nonbenzenoid carbon allotrope, Science 372 (2021) 852–856.
- [71] A.L. Ivanovskii, Graphynes and graphdyines, Progr. Solid State. Chem. 41 (2013) 1–19.
- [72] K. Kaiser, L.M. Scriven, F. Schulz, P. Gawel, L. Gross, H.L. Anderson, An sphybridized molecular carbon allotrope, cyclo[18]carbon, Science 365 (2019) 1299–1301.
- [73] L. Shi, P. Rohringer, K. Suenaga, Y. Niimi, J. Kotakoski, J.C. Meyer, H. Peterlik, M. Wanko, S. Cahangirov, A. Rubio, Z.J. Lapin, L. Novotny, P. Ayala, T. Pichler, Confined linear carbon chains as a route to bulk carbyne, Nat. Mater. 15 (2016) 634–640.
- [74] D.C. Elias, R.R. Nair, T.M.G. Mohiuddin, S.V. Morozov, P. Blake, M.P. Halsall, A. C. Ferrari, D.W. Boukhvalov, M.I. Katsnelson, A.K. Geim, K.S. Novoselov, Control of graphene's properties by reversible hydrogenation: evidence for graphene, Science 323 (2009) 610–613.
- [75] M. Pumera, C.H.A. Wong, Graphane and hydrogenated graphene, Chem Soc. Rev. 42 (2013) 5987–5995.
- [76] W. Jacob, W. Möller, On the structure of thin hydrocarbon films, Appl. Phys. Lett. 63 (1993) 1771–1773.
- [77] F. Piazza, M. Monthioux, P. Puech, 2D (< 10nm) sp³-C-rich carbon materials, possibly hydrogenated: a review, Carbon Trends 9 (2022) 100219.
- [78] J. Narayan, A. Bhaumik, Novel phase of carbon, ferromagnetism, and conversion into diamond, J. Appl. Phys. 118 (2015) 215303.
- [79] V. Uskokovic, A historical review of glassy carbon: synthesis, structure, properties, and applications, Carbon Trends 5 (2021) 100116.
- [80] S. Sharma, Glassy carbon: a promising material for micro-and nanomanufacturing, Materials 11 (2018) 1857.
 [81] H.W. Kroto, J.R. Heath, S.C. O'Brien, R.F. Curl, R.E. Smalley, C₆₀.
- [61] H.W. Kroto, J.K. Heath, S.C. O Brien, K.F. Curi, K.E. Sinaney, C_{60} : buckminsterfullerene, Nature 318 (1985) 162–163.
- [82] K.S. Novoselov, A.K. Geim, S.V. Morozov, D. Jiang, Y. Zhang, S.V. Dubonos, I. V. Grigorieva, A.A. Firsov, Electric field effect in atomically thin carbon films, Science 306 (2004) 666–669.
- [83] J.H. Knox, B. Kaur, G.R. Millward, Structure and performance of porous graphitic carbon in liquid chromatography, J. Chromatogr. 352 (1986) 3–25.
 [84] M. Monthioux, P. Serp, B. Caussat, E. Flahaut, M. Razafinimanana, F. Valensi,
- [84] M. Monthioux, P. Serp, B. Caussat, E. Flahaut, M. Razafinimanana, F. Valensi, C. Laurent, A. Peigney, D. Mesguish, A. Weibel, W. Bacsa, J.-M. Broto, Carbon nanotubes. Handbook of Nanotechnology, Springer Verlag, 2017, pp. 193–247.
- [85] M. Monthioux, L. Noé, M. Kobylko, Y. Wang, T. Cazares-Huerta, A. Pénicaud, Determining the structure of graphene-based flakes from their morphotype, Carbon 115 (2017) 128–133.
- [86] A. Oberlin, Application of dark-field electron microscopy to carbon study, Carbon 17 (1979) 7–20.
- [87] A. Oberlin, J. Goma, J.-N. Rouzaud, Techniques d'Etudes des structures et textures (microtextures) des matériaux carbonés, J. Chem. Phys. 81 (1984) 701–710.
- [88] P. Pré, G. Huchet, D. Jeulin, J.-N. Rouzaud, M. Sennour, A. Thorel, A new approach to characterize the nanostructure of activated carbons from mathematical morphology applied to high resolution transmission electron microscopy images, Carbon 52 (2013) 239–258.
- [89] P.I. Raynal, M. Monthioux, O. Dugne, Multi-scale quantitative analysis of carbon texture, nanotexture and structure: I. Electron diffraction-based anisotropy measurements, Carbon 66 (2014) 493–503.
- [90] L.G. Cançado, K. Takai, T. Enoki, M. Endo, Y.A. Kim, H. Mizusaki, A. Jorio, L. N. Coelho, R. Magalhães-Paniago, M.A. Pimenta, General equation for the determination of the crystallite size *L_a* of nanographite by Raman spectroscopy, Appl. Phys. Lett. 88 (2006) 163106.
- [91] P. Mallet-Ladeira, P. Puech, C. Toulouse, M. Cazayous, N. Ratel-Ramond, P. Weisbecker, G.L. Vignoles, M. Monthioux, A Raman study to obtain crystallite size of carbon materials: a better alternative to the Tuinstra–Koenig law, Carbon 80 (2014) 629–639.
- [92] P.K. Mubari, T. Beguerie, M. Monthioux, E. Weiss-Hortala, A. Nzihou, P. Puech, The X-ray, Raman and TEM signatures of cellulose-derived carbons explained, 'C' 8 (2022) 4.

- [93] A. Oberlin, J.-L. Boulmier, M. Villey, B. Durand, Electron microscopy study of kerogen microtexture. Selected criteria for determining the evolution path and evolution stage of kerogen. Kerogen, Technip, 1980, pp. 191–241 (ed.)Paris (France)Ch.7.
- [94] A. Oberlin, M. Oberlin, Graphitizability of carbonaceous materials as studied by TEM and X-ray diffraction, J. Microsc. 132 (1983) 353–363.
- [95] A. Oberlin, S. Bonnamy, X. Bourrat, M. Monthioux, J.N. Rouzaud, Electron microscopic observations on carbonization and graphitization, ACS Symp. Ser. 303 (1986) 85–98.
- [96] A. Oberlin, P.A. Thrower, High-resolution TEM studies of carbonization and graphitization. Chemistry and Physics of Carbon, Marcel Dekker, 1989, pp. 1–143 (ed.)New-York (NY, USA)vol. 22.
- [97] A. Oberlin, S. Bonnamy, K. Oshida, Landmarks for graphitization, Tanso 224 (2006) 281–298.
- [98] P. Ouzilleau, A.E. Gheribi, P. Chartrand, G. Soucy, M. Monthioux, Why some carbons may or may not graphitize? The point of view of thermodynamics, Carbon 149 (2019) 419–435.
- [99] J.M. Schopf, Definitions of peat and coal and of graphite that terminates the coal series (graphocite), J. Geol. 74 (1966) 584–592.
- [100] B. Kribek, J. Hrabal, P. Landais, J. Hladikova, The association of poorly ordered graphite, coke and bitumens in greenschist facies rocks of the ponikla group, Lugicum, Czech Republic: the result of graphitization of various types of carbonaceous matter, J. Metamorph. Geol. 12 (1994) 493–503.
- [101] B. Kwiecinska, H.I. Petersen, Graphite, semi-graphite, natural coke, and natural char classification - ICCP system, Internat. Coal Geol. 57 (2004) 99–116.
- [102] M.A. Kanter, Diffusion of carbon atoms in natural graphite crystals, Phys. Rev. 107 (1957) 655–664.
- [103] J.-B. Donnet, R.C. Bansal, M.-J. Wang, Carbon Black Science and Technology (Eds.), 2nd edition, CRC Press, 1993. ISBN 0-8247-8975-X.
- [104] A. Kausar, R. Taherian, Electrical Conductivity in Polymer-Based Composites, Elsevier, 2018. ISBN 978-0-12-812541-0.
- [105] M. Singh, R.L. Vander Wal, Nanostructure quantification of carbon blacks, C 5 (2019) 2.
- [106] R.D. Heidenreich, W.M. Hess, L.L. Ban, A test object and criteria for high resolution electron microscopy, J. Appl. Crystal. 1 (1968) 1–19.
- [107] R.O. Grisdale, The formation of black carbon, J. Appl. Phys. 24 (1953) 1082–1091.
- [108] G. Paredes, T. Ondarçuhu, M. Monthioux, F. Piazza, Unveiling the existence and role of a liquid phase in a high temperature (1400°C) pyrolytic carbon deposition process, Carbon Trends 5 (2021) 100117.
- [109] O.P. Bahl, Z. Shen, J.G. Lavin, R.A. Ross, J.-B. Donnet, T.K. Wang, J.C.M. Peng, S. Rebouillat, Manufacture of carbon fibers. Carbon Fibers, 3rd edition, Marcel Dekker, 1998, pp. 1–84 (eds.)New York (NY, USA).
- [110] A. Oberlin, S. Bonnamy, K. Lafdi, J.-B. Donnet, T.K. Wang, J.C.M. Peng, Structure and texture of carbon fibers. Carbon Fibers, 3rd edition, Marcel Dekker, 1998, pp. 85–160 (eds.)New York (NY, USA).
- [111] A. Oberlin, Microstructure et propriétés des matières carbonées, J. Microsc. Spectrosc. Electron. 7 (1982) 327–340.
- [112] M. Monthioux, O.P. Bahl, R.B. Mathur, T.L. Dhami, H.O. Dwivedi, S.P. Sharma, Controlling PAN-based carbon fibre texture via surface energetics, Carbon 38 (2000) 486–491.
- [113] M. Bonijoly, M. Oberlin, A. Oberlin, A possible mechanism for natural graphite formation, Intern. J. Coal Geol. 1 (1982) 283–312.
- [114] Y. Hishiyama, S. Yasuda, A. Yoshida, M. Inagaki, Structure and properties of highly crystallized graphite films based on polyimide Kapton, J. Mater. Sci. 23 (1988) 3272–3277.
- [115] S. Iijima, Helical microtubules of graphitic carbon, Nature 354 (1991) 56-58.
- [116] M. Monthioux, P. Serp, B. Caussat, E. Flahaut, M. Razafinimanana, F. Valensi, C. Laurent, A. peigney, D. Mesguich, A. Weibell, W. Bacsa, J.-M. Broto, B. Bhushan, Carbon nanotubes. Handbook of Nanotechnology, 4th edition, Springer, 2017, pp. 193–247 (ed.)Heidelberg (Germany).
- [117] M. Monthioux, L. Noé, L. Dussault, J.-C. Dupin, N. Latorre, T. Ubierto, E. Romeo, C. Royo, A. Monzon, C. Guimon, Texturising and structurising mechanisms of carbon nanofilaments during growth, J. Mater. Chem. 17 (2007) 4611–4618.
- [118] M. Monthioux, M. Monthioux, Introduction to carbon nanotubes. Carbon Meta-Nanotubes: Synthesis, Properties, and Applications, Wiley & Sons, 2012, pp. 7–39 (ed.)Chichester (UK).
- [119] H. Jiang, A.G. Nasibulin, D.P. Brown, E.I. Kauppinen, Unambiguous atomic structural determination of single-walled carbon nanotubes by electron diffraction, Carbon 45 (2007) 662–667.
- [120] M. Dresselhaus, G. Dresselhaus, A. Jorio, A.G. Souza Filho, M.A. Pimenta, R. Saito, Single nanotube Raman spectroscopy, Acc. Chem. Res. 35 (2002) 1070–1078.
- [121] N. Hamada, S.I. Sawada, A. Oshiyama, New one-dimensional conductors, graphite microtubules, Phys. Rev. Lett. 68 (1992) 1579–1581.

Carbon Trends 14 (2024) 100325