

Nonlinear acoustic characterization of Carrara marble degradation under thermo-hygric cycles

Marie-Laure Chavazas, Philippe Bromblet, Jérémie Berthonneau, Cédric Payan

▶ To cite this version:

Marie-Laure Chavazas, Philippe Bromblet, Jérémie Berthonneau, Cédric Payan. Nonlinear acoustic characterization of Carrara marble degradation under thermo-hygric cycles. 5th International Conference on Innovation in Art Research and Technology, Jun 2022, Paris, France. hal-04553242

HAL Id: hal-04553242

https://hal.science/hal-04553242

Submitted on 19 Apr 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.











Nonlinear acoustic characterization of Carrara marble degradation under thermo-hygric cycles

M.L. Chavazas ^{1,2}, P. Bromblet ², J. Berthonneau ², C. Payan ¹

- ¹ Aix Marseille Univ, CNRS, Centrale Marseille, LMA UMR 7031, Marseille, France
- ² Centre Interdisciplinaire de Conservation et de Restauration du Patrimoine, Marseille, France

Carrara marble is a widely used type of marble, in buildings and in sculptures, in ancient and in recent works. Yet, Carrara marble exposed to environmental conditions can develop deteriorations over time, such as bowing, cracks, expansion, reduction of mechanical strength. Previous studies [1] have shown that these degradations can result from exposure to temperature variations. Moreover, these deteriorations can be enhanced by the combination of variations of temperature and relative humidity [2].

The aim of the study is to understand and to characterize the effects of cyclic variations of temperature and relative humidity with a non-destructive method, suitable for the study of cultural heritage.

The Nonlinear Resonant Ultrasound Spectroscopy (NRUS) is chosen as it has proven to be highly sensitive to damage and to microstructural evolutions in rocks [3] and in concrete [4].





War memorial of Aubagne (P. Bromblet)

Methodology

Nonlinear Resonant Ultrasound Spectroscopy (NRUS)

- non-destructive
- contactless wave reception






Experimental set-up for NRUS tests

Study of 3 parameters


- \triangleright resonant frequency f_0
- \triangleright quality factor $Q = f_0/B$
- \succ nonlinear parameter α : $\Delta f/f_0 = \alpha \Delta \varepsilon$



NRUS curves for marble heated at 40°C


Preliminary results

Temperature variations 7000 7000 王 350 barameter 5000 5500 4500 **3**00 250 250 200 4500 4000 3500 3000 Quality 100 2500 500 600 100 Heating temperature (°Ç) Heating temperature (°C)



X-ray micro-CT scans for (a) undamaged marble and (b) marble heated at 500°C Acquisition and reconstruction by L. Sabatier (LMA)


- Loss of stiffness and increasing attenuation with increasing heating temperature
- Loss of stiffness and increasing damage with increasing relative humidity



Relative humidity variations

 $f_0 = -7,0064 \text{ RH} + 7944,2$

 $R^2 = 0.9699$



Conclusions

- > NRUS method sensitive to the effects of variations of temperature and of relative humidity
- > Degradation detectable even at low temperatures
- Links between the NRUS results and observations on the microstructure

<u>Perspectives</u>

- > Study of more temperatures between 40 and 100°C
- > Study of the effects of cyclic variations at low temperatures
- > Development of a scanning method suitable for art works and for the study of their degradation



References

- [1] Schouenborg et al., Journal of ASTM International, 2007
- [2] Koch et al., Environmental Geology, 2004
- [3] Van Den Abeele et al., J. of Geophysical Research, 2002
- [4] Payan et al., J. of the Acoustical Society of America, 2007