

# Absolute Quantum Gravimeter as a promising field sensor for volcano monitoring















# The Guadeloupe field mission

## **Objectives**

1) Identify a site to install a permanent gravity station (L&R D meter, tiltmeters, pressure gauge) at the summit

2) Retrieve and reoccupy the sites of the micro-gravimetric network with a CG5

3) Conduct absolute gravity measurements at the Volcanological and Seismological Observatory of Guadeloupe (OVSG) + Savane à Mulets with an AQG.


→ Field testing of the AQG-B01


→ Can it be operated by anyone?

4) Compare AQG and previous A10#14 measurements.










## The vagaries of the weather: a well-known but unpredictable major factor in scientific field campaigns



### **Standard weather conditions**


- <Temperature> = 24.5°C
- Relative humidity 80%

### Field mission conditions


- Heavy rainfall (up to 12 mm)
- Sustained winds (up to 40 km/h)
- Gusts reaching 70 km/h

**Packaging and transportation** Manche





Departure from Trappes (28/01/2023)






Arrival at OVSG Guadeloupe (13/02/2023)

# **Unpacking – installation – check up**







With AQG-mTools (Lion et al., in prep.)

## First startup after 3 months of shutdown

- Integrity of the units after transportation (7000 km) by air and road => OK
- Ability to install the instrument and start it up (< 45') => OK
- Instrument's capability to become operational after a long period of dormancy and in different conditions (thermalization 1 night) => OK

# First gravity measurements on the pillar at OVSG basement

From Diament et al. (2024), in press




Power supply plugs on the standard power outlet


CG5 meter

- → Sensitivity at 1 sec ≈ 60 µGal
- $\rightarrow$  Sensitivity at 1 h ≈ 1 μGal
- $\rightarrow$  Deviation between the values from AQG-B01 and A10#14 are close to the uncertainty of the meters (15  $\mu$ Gal)

The site is a good reference for the gravity monitoring of La Soufrière

# Heavy precipitation and strong winds






Campaign	Gravimeter	g value [μGal] @h_A10=71.8	cm	
18/03/2023	AQG-B01	978425878	Deviation ≈ 12-22 μGal	
26/04/2014	A10#14	978425 <mark>898</mark>		
03/06/2013	A10#14	978425 <mark>901</mark>	Time elapsed	
21/06/2011	A10#14	978425 <mark>891</mark>	≈ 10	.0 years

# Indoor: seismological pillar at OVSG


- Repeatability tests in the North direction with an agreement better than 10 μGal
- Coriolis effect: sensor head orientation's effect at low latitude
- Testing power supply mode: no difference between a standard power outlet and a generator



## **Outdoor measurements at OVSG**



- Power supply connected to the generator
- Intermittent rain every 15 minutes, followed by strong sunshine
- Regular wind (20 km/h) with gusts (up to 70 km/h)
  - → The fiber and cables are weighted and secured
  - → The AQG is protected
  - → Sensitivity ≈ 3 µGal @1h



A day of "normal" weather condition (video)



## Measurements close to the summit of the volcano


## Unfavorable weather conditions...







Utility van



→ Stability problem due to several strong gusts of wind

Decrease in g related to the observed recent heating of La Soufrière hydrothermal system?



Wind, rain, sun protection




AQG-B01



CG5


Campaign	Gravimeter	g value [μGal] @h_A10=71.8 cm
2023	AQG-B01	978281625
2019	A10#14	978281 <mark>745</mark>
2014	A10#14	978281 <mark>729</mark>
2013	A10#14	978281 <mark>921</mark>
2011	A10#14	978281 <mark>862</mark>

# AQG sensitivity under various acquisition conditions



Results from Diament et al. (2024), accepted in IEEE & IMM

# Return-back measurements at Trappes (close to Paris - France)



Shift about 10 μGal No explanation yet

## **Summarized**

- ✓ The first Absolute Quantum Gravimeter (version B) produced by Exail for field measurements
  - Is easy to operate
  - Is transportable over long distance and hard trails
  - Can measure on adverse weather conditions
  - Can make 1 point every 2 hours with few μGal sensitivity
  - Can help to survey a volcano
- ✓ Results in Diament et al. (2024), in press in IEEE & IMM, available in September 2024
- ✓ A user-friendly software, AQG-mTools, has been developed in Matlab. A forthcoming paper by Lion et al. is in prep. -> The tools will be soon openly accessible on Github (or upon request for now)
- Minor points have been addressed to Exail: better connector protection, packaging improvement for transport, a new tripod orientation mechanism, etc.
- Additional tests need to be conducted to :
  - analyze the behavior of the AQG under the influence of wind on both the fiber and the modules embedded within the utility van
  - Understand the jumps of 10 μGal