



HAL
open science

Convex lifting-based path planning for overtaking maneuver on highways

Turan Konyalıođlu, Sorin Olaru, Silviu-Iulian Niculescu, Iris Ballesteros-Tolosana, Simon Mustaki

► **To cite this version:**

Turan Konyalıođlu, Sorin Olaru, Silviu-Iulian Niculescu, Iris Ballesteros-Tolosana, Simon Mustaki. Convex lifting-based path planning for overtaking maneuver on highways. ECC 2024 - 22nd European Control Conference, Jun 2024, Stockholm, Sweden. hal-04565761

HAL Id: hal-04565761

<https://hal.science/hal-04565761v1>

Submitted on 2 May 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Convex lifting-based path planning for overtaking maneuver on highways

Turan Konyalioglu^{1,2,3}, Sorin Olaru¹, Silviu-Iulian Niculescu^{1,3}, Iris Ballesteros-Tolosana², and Simon Mustaki²

¹Université Paris-Saclay, CNRS, CentraleSupélec, Laboratoire des signaux et systèmes, France

Email: {turan.konyalioglu, sorin.olaru, silviu.niculescu}@centralesupelec.fr

²Ampere Software Technology, DEA-OCDD1, France

Email: {turan.konyalioglu, iris.ballesteros-tolosana, simon.mustaki@}renault.com

³Inria-Saclay (team "DISCO")

Abstract—This paper revisits the convex lifting method for space partition, emphasizing the generation of safe corridors in the context of navigation with obstacle avoidance guarantees. This enables the agent to navigate within the designated corridors, disregarding obstacles. The paper also emphasizes that the method can be adapted to a highway scenario, particularly in the context of overtaking maneuvers.

I. INTRODUCTION

Automated mobility, involving the use of advanced technologies for vehicles and transportation systems to operate autonomously or with minimal human intervention, aims to enhance safety, efficiency, and accessibility in transportation. The European Union (EU) has actively focused on this concept in terms of safety, applicability, and environmental benefits, with an anticipated large-scale deployment by 2030.¹ The application of self-driving cars has great potential in the pursuit of short and mid-term goals targeted at improving efficiency and safety. According to the report of the EU Commission,² facilitating these vehicles and addressing the challenges originating from highway and urban mixed traffic, it is aimed that road fatalities and serious injuries are to be reduced to zero by 2050. In this context, advanced driver assistance systems (ADAS), play a crucial role in enhancing road safety eventually by taking the driver out of the loop and this is one of the priorities of Renault.^{3 4}

A spectrum of methodologies and strategies has been investigated, specifically for autonomous highway driving. Within the automated mobility framework, [1] introduce their research on platooning of connected and automated vehicles. However, given the current lack of connectivity between vehicles and technological limitations, our research will focus on decentralized approaches. In [2], the decentralized method for merging problems in highways has been studied. [3] provides a comprehensive review of motion planning algorithms for highway driving. Notably, [4] present their solutions to overtaking maneuvers, employing multi-

objective optimization approaches. [5] deploys model predictive control (MPC) for trajectory control on clothoidal paths, while [6] integrates an obstacle avoidance solution into the problem.

The convex lifting in the path planning is a recent framework and it has been explored in [7]. This framework enables to decompose of the space in a cluttered environment and to establishment of safe navigation corridors for agents such as autonomous vehicles, robots, etc, which can utilize those corridors as kinematic constraints.

In ADAS, the path planning module relies on the perception module which is shown in Fig. 1. It detects and tracks obstacles and ensures full awareness of surrounding vehicles. These topics are of interest in control theory, computer science, and related fields. Thus, we focus on such an environment that the ego vehicle has complete information on its surroundings and target vehicles.

II. PATH PLANNING USING CONVEX LIFTING

The efficient design of corridors relies heavily on the effective utilization of space partitions.

Definition 1: Disjoint obstacles $\mathcal{P} = \bigcup_{i \in \mathcal{I}} \mathcal{P}_i$ in a subspace \mathcal{X} . The sets $\{\mathcal{X}_i\}_{i \in \mathcal{I}}$ satisfying, (i) $\mathcal{X} = \bigcup_{i \in \mathcal{I}} \mathcal{X}_i$, (ii) $\text{int}(\mathcal{X}_i) \cap \text{int}(\mathcal{X}_j) = \emptyset, (i, j) \in \mathcal{I}^2$ (iii) $\mathcal{P}_i \subset \text{int}(\mathcal{X}_i), \forall i \in \mathcal{I}$ is called a partition of \mathcal{X} induced by the obstacles \mathcal{P} .

The configuration space, denoted as $C_{\mathcal{X}}(\mathcal{P}) = \mathcal{X}/\mathcal{P}$, represents the complete set of potential poses that an agent can attain.

Definition 2: Given a polyhedral partition of a finite-dimensional space $\mathcal{X} = \bigcup_{i \in \mathcal{I}} \mathcal{X}_i$, a convex lifting is defined as a piecewise affine function $z : \mathcal{X} \rightarrow \mathbb{R}$ satisfying the following properties: $z(x) = a_i^T x + b_i$ for $x \in \mathcal{X}_i$ and $z(x) > a_j^T x + b_j, \forall x \in \text{int}(\mathcal{X}_i), (i, j) \in \mathcal{I}^2, \forall i \neq j$

The lifting can be performed optimization problem in (1).

$$\min_{a_i, b_i} J = \sum_{i=1}^{N_0} \| [a_i^T \quad b_i] \|_2^2 \quad (1a)$$

$$\text{s.t. } a_i^T v + b_i \leq M, \forall v \in \mathcal{V}(\mathcal{P}_i), \forall i \in \mathcal{I}, \quad (1b)$$

$$a_j^T v + b_j \geq a_i^T v + b_i + \epsilon, \forall v \in \mathcal{V}(\mathcal{P}_j), \forall i \neq j \quad (1c)$$

¹The European Commission (2021). Sustainable and Smart Mobility Strategy.

²Grater, A., Harrer, M., Rosenquist, M., and Steiger, E. (2022). Connected, cooperative and automated mobility roadmap.

³The European Commission (2018). Advanced driver assistance systems.

⁴This thesis fits with the objectives of Renault and the work of the first author is financially supported by the company.




Fig. 1. ADAS perception module. [8]

After obtaining the lifting function, one can compute the lifted polyhedron by calculating the epigraph.

$$\mathcal{L} = \left\{ \begin{bmatrix} x \\ y \\ z \end{bmatrix} \in \mathbb{R}^{d+1} : \begin{bmatrix} a_i^T & -1 \end{bmatrix} \begin{bmatrix} x \\ z \end{bmatrix} \leq -b_i, i \in \mathcal{I} \right\} \quad (2)$$

Then, one can obtain the space partition, by projecting them back into the space. $\mathcal{X}_i = \text{proj}(\mathcal{F}_i^{d-1}(\mathcal{L}), \mathcal{X})$ where $i \in \mathcal{I}$. The interconnected graph of paths is generated as $\Gamma(\mathcal{N}, \mathcal{E}, f)$ as a function of nodes, \mathcal{N} , edges, \mathcal{E} , and weight function, f . Then, by using any graph search algorithm a path for the agent can be found.

Definition 3: With given obstacles \mathcal{P} , a corridor between two nodes $(x_0, x_f) \in \text{int}(C_{\mathcal{X}}(\mathcal{P}))$, is defined by of two functions, $\gamma : [0, 1] \rightarrow C_{\mathcal{X}}(\mathcal{P})$ and $\rho : [0, 1] \rightarrow \mathbb{R}_{>0}$ satisfying, $\gamma(0) = x_0$ and $\gamma(1) = x_f$ where $\gamma(\theta) \oplus \mathbb{B}_{0, \rho(\theta)}^2 \subset C_{\mathcal{X}}(\mathcal{P}), \forall \theta \in [0, 1]$. Then, a corridor is defined as,

$$\Pi = \{ x \in \mathbb{R}^d : \exists \theta \in [0, 1] \text{ s.t. } x \in \gamma(\theta) \oplus \mathbb{B}_{0, \rho(\theta)}^2 \} \quad (3)$$

The corridors can be defined as a combination of convex sets as $\Pi = \bigcup_{i=1}^{N_c} \Pi_i$.

III. MPC-BASED TRAJECTORY GENERATION

Linear time-invariant dynamics of an agent is shown as,

$$x_{k+1} = Ax_k + Bu_k, \quad (4)$$

With, $x_k \in \mathbb{R}^d$ denotes the state vector, and $u_k \in \mathbb{R}^m$ is the input vector. Using a quadratic cost in MPC:

$$\mathcal{J}(N_p, \bar{x}_i, x_k, U) = \|x_{k+N_p|k} - \bar{x}_i\|_P^2 + \sum_{l=1}^{N_p-1} \|x_{k+l|k} - \bar{x}_i\|_Q^2 + \sum_{l=1}^{N_p-1} \|\Delta u_{k+l|k}\|_R^2 \quad (5)$$

where N_p is prediction horizon, \bar{x}_i is reference point such that $\bar{x}_i \in \Pi_i$, Q is state, R is control increment, and P is the terminal cost penalty matrix. The vector $U = [u_{k|k} \dots u_{k+N_p-1|k}]^T$ is the optimization argument:

$$\mathcal{T}(\Pi_i, N_p, \mathcal{X}_f, \bar{x}_i, \mathcal{X}) : \min_U \mathcal{J}(N_p, \bar{x}_i, x_k, U) \quad (6a)$$

$$\text{s.t. } x_{k+l+1|k} = Ax_{k+l|k} + Bu_{k+l|k}, \quad (6b)$$

$$u_{k+l|k} \in \mathcal{U}, \forall l = 1 : N_p - 1, \quad (6c)$$

$$x_{k+l|k} \in \Pi_i, \quad (6d)$$

$$x_{k+N_p|k} \in \mathcal{X}_f(\bar{x}_i) \quad (6e)$$

By integrating state-space dynamics (6b), input constraints (6c), and state constraints (6d) within the corridor, the MPC problem in (6) is systematically managed at each time step. During corridor transitions, ensuring the agent's trajectory aligns with controllable dynamics and terminal constraints




Fig. 2. MPC-based trajectory for overtaking maneuver.

(denoted as \mathcal{X}_f) is crucial for safe navigation. This controlled invariance set ensures the system remains safe throughout transitions and navigation along subsequent corridors. An important aspect of MPC adjustment is choosing a prediction horizon to guarantee reaching \mathcal{X}_f from any initial point in the corridor. By using the Backward Reachable Set construction, we can ascertain the necessary prediction steps for recursive feasibility.

IV. RESULTS

The method is applied in a highway scenario for overtaking. Fig. 2 displays MPC-generated trajectory for a blue ego vehicle. Parameters for convex lifting optimization are set as $\epsilon = 1.0$ and $M = 0.01$. Vehicle positions $y = 0$ and $y = 4$ denote center and objective lanes. Red target vehicles are extruded to slow lanes to block possible paths. Green tubes indicate safe corridors along MPC-generated trajectory (black line).

V. CONCLUSION

In this paper, we revisit the convex lifting framework for space partitioning and we generate obstacle-free corridors and construct an MPC-based path for the ego vehicle. Our investigation focuses on a static highway scenario. Future work will address dynamic highway environments.

REFERENCES

- [1] Marco Mirabilio, Alessio Iovine, Elena De Santis, Maria Domenica Di Benedetto, and Giordano Pola. String stability of a vehicular platoon with the use of macroscopic information. *IEEE Trans. Intell. Transp. Syst.*, 22(9):5861–5873, 2021.
- [2] Wei Xiao and Christos G. Cassandras. Decentralized optimal merging control for connected and automated vehicles with safety constraint guarantees. *Automatica*, 123:109333, 2021.
- [3] Laurene Claussmann, Marc Revilloud, Dominique Gruyer, and Sébastien Glaser. A review of motion planning for highway autonomous driving. *IEEE Trans. Intell. Transp. Syst.*, 21(5):1826–1848, 2019.
- [4] Iris Ballesteros-Tolosana, Sorin Olaru, Pedro Rodriguez-Ayerbe, Guillermo Pita-Gil, and Renaud Deborne. Collision-free trajectory planning for overtaking on highways. In *2017 IEEE 56th Annual Conference on Decision and Control (CDC)*, pages 2551–2556. IEEE, 2017.
- [5] Stefano Di Cairano, UV Kalabić, and Karl Berntorp. Vehicle tracking control on piecewise-clothoidal trajectories by MPC with guaranteed error bounds. In *2016 IEEE 55th Conference on Decision and Control (CDC)*, pages 709–714. IEEE, 2016.
- [6] Karl Berntorp. Path planning and integrated collision avoidance for autonomous vehicles. In *2017 American control conference (ACC)*, pages 4023–4028. IEEE, 2017.
- [7] Daniel Ioan, Ionela Prodan, Sorin Olaru, Florin Stoican, and Silviu-Iulian Niculescu. Navigation in cluttered environments with feasibility guarantees. *IFAC-PapersOnLine*, 53(2):5487–5492, 2020.
- [8] Alejandro Lanuza García. Vehículo autónomo y conectado: casos de uso, pronósticos de adopción y adaptación de la infraestructura, 2023.