

Electrochemical Regeneration of LiAlH4

Elijah Eric Ugaddan, Parviz Hajiyev, Thibault Charpentier, Umit Bilge Demirci

▶ To cite this version:

Elijah Eric Ugaddan, Parviz Hajiyev, Thibault Charpentier, Umit Bilge Demirci. Electrochemical Regeneration of LiAlH4. Metal-Hydrogen Systems 2024, May 2024, Saint-Malo, France. 2024. hal-04566815

HAL Id: hal-04566815 https://hal.science/hal-04566815

Submitted on 2 May 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

26-31 May 2024

Electrochemical Regeneration of LiAIH₄

E. Ugaddan^{1,3,*}, P. Hajiyev¹, T. Charpentier² and U. Demirci³

¹LITEN, CEA, Grenoble Alpes University, 38000 Grenoble, France
²NIMBE, CEA, University of Paris-Saclay,, 91191, Gif-sur-Yvette, France
³IEM, CNRS, University of Montpellier, 34090, Montpellier, France

*elijah-eric.ugaddan@cea.fr

Hydrogen, a promising clean energy vector, surpasses traditional fuels in energy content (140 MJ/kg) but faces storage challenges. Aluminum-based complex metal hydrides like LiAlH₄ offer solutions with high volumetric (>80g H₂/L) and gravimetric (>8 wt %) energy densities, along with low decomposition temperatures (<423 K). However, their synthesis involves costly organometallic reactions and high hydrogenation pressures (>1 kbar). Consequently, a significant interest is in cost-effective approaches for regenerating LiAlH₄ from its spent (hydrogen-depleted) material and H₂.

Graetz^[1] proposed its first chemical regeneration, examining dehydrogenated LiH and Al with a Ti catalyst in THF under high H₂ pressure (50 bar). Humphries^[2] explored sub-ambient regeneration (<0°C) using Me₂O and 95 bar H₂. However, their practicality is hindered by reliance on high H₂ pressure. Our research group investigates the viability of an electrochemical approach for its regeneration and potential elimination on the use of high H₂ pressure, a novel concept not previously reported in the literature..

Electrochemical properties were studied in THFbased electrolyte and Ar atmosphere at RT. Figure 1 shows a cyclic voltammogram of 1M LiAIH₄ in THF to which we identified essential reactions, including Li and AI deposition, and irreversible anodic polarization of [AIH₄-] associated with H₂ release^[3]. Applying a constant reduction potential (-3.10 V vs. hvdroaen electrode) resulted standard in dehydrogenated LiAIH₄ (Li-AI alloy formation) and demonstrating room-temperature H₂ release. electrochemical dehydrogenation with a Faradaic efficiency of 69%. We explore the effect of H₂ pressure on these electrochemical reactions using our custom electrochemical pressure cell. The next step involves regenerating the deposited Li-Al alloy under moderate H₂ pressures (<10 bar) and



Figure 1. CV of a 1M LiAlH₄ – THF solution under 7 bar of Ar with a scan rate of 20 mV/s.

applying oxidative potentials to induce [AIH₄] reformation using Pd, Pt, Ti, or Ni electrocatalysts. Reformed LiAIH₄ is quantified using ²⁷Al NMR coupled with ICP-MS. Fundamental parameters will be investigated, including its kinetics, diffusion coefficients, and regeneration mechanisms, using various electroanalytical techniques like chronoamperometry, voltammetry, rotating disk electrode, and electrochemical-impedance spectroscopy.

References

- [1] J. Graetz, J. Wegrzyn, J. Reilly, J. American Chemical Society, 130.52 (2008): 17790-17794
- [2] T. Humphries, D. Birkmire, S. McGrady, B. Hauback, C.Jenseen, J. Alloys and Cmpds, 723 (2017): 1150-1154
- [3] H. Senoh, T. Kiyobayashi, N. Kuriyama, K. Tatsumi, J. Power Sources, 164.1 (2007): 94-99