



Benefit of UHP-SPS for thermal sensitive (Al_2O_3) and thermal unstable (MgB_2) materials

Mythili Prakasam, Félix Balima, Viraphong Oudomsack, Jacques Noudem,
Alain Largeteau

► To cite this version:

Mythili Prakasam, Félix Balima, Viraphong Oudomsack, Jacques Noudem, Alain Largeteau. Benefit of UHP-SPS for thermal sensitive (Al_2O_3) and thermal unstable (MgB_2) materials. Action Nationale de Formation - ANF - CNRS : ForumHP2020 : "Innovations technologiques dans le domaine des hautes pressions pour les défis de demain", CNRS - ANF, Oct 2020, Ile d'Oléron, France. hal-04568054

HAL Id: hal-04568054

<https://hal.science/hal-04568054v1>

Submitted on 13 Jun 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Benefit of UHP-SPS for thermal sensitive (Al_2O_3) and thermal unstable (MgB_2) materials

PRAKASAM Mythili^a, BALIMA Felix^a, VIRAPHONG Oudomsack^a, NOUDEM Jacques^b, LARGETEAU Alain^a

a. CNRS, Univ. Bordeaux, ICMCB, UMR 5026, F-33600 Pessac, France

b. Normandie Univ, Ensicaen, Unicaen, CNRS, CRISMAT, Caen, 14000, France

Abstract

Influence of pressure on the mechanical properties of hard and super-hard materials are well known. Combination of high pressure and field assisted sintering yields nanostructured ceramics, stabilization of thermosensitive phases and facilitate early chemical reaction. Recently there are few reports on the possibility to combine pulsed electric power source with HP toroidal type apparatus reaching pressure up to 7.8 GPa and temperature of 1950°C. In the present work, we used our in-house built ultra-high pressure SPS (UHP-SPS) [1-4] equipment with HP Belt type apparatus that enables to reach maximum pressure of 6 GPa and temperature up to 1800°C. For its versatility for syntheses and sintering, 2 materials are studied: for highly dense MgB_2 ceramics at low temperature help by the high pressure in comparison with conventional SPS and for α - γ phase transition Al_2O_3 to occur at less severe conditions help by pulse electric current in comparison with conventional HP-HT. The advantages and the flexibilities of the developed UHP-SPS will be discussed and the results and characterization of MgB_2 and Al_2O_3 will be presented in detail.

Références bibliographiques

- [1] Prakasam M, Balima F, Cygan S, Klimczyk P, Jaworska L, Largeteau A, Chapter 9 - Ultrahigh pressure SPS (HP-SPS) as new syntheses and exploration tool in materials science, 201-218 pages in Giacomo Cao, Claude Estournès, Javier Garay, Roberto Orrù (Eds), *Spark Plasma Sintering*, Elsevier, (2019).
- [2] Balima F, Bellin F, Michau D, Viraphong O, Poulon-Quintin A, Chung U-Ch, Dourfaye A, Largeteau A, High pressure pulsed electric current activated equipment (HP-SPS) for material processing, *Materials & Design*, 139, 541-548 ((2018)).
- [3] Balima F, Largeteau A, Phase transformation of alumina induced by high pressure spark plasma sintering (HP-SPS), *Scripta Materialia*, 158, 20-23 (2019).
- [4] Largeteau A, Prakasam A, Trends in high pressure developments for new perspectives, *Solid State Sciences*, 80, 141-146 (2018).