



**HAL**  
open science

## **Influence of the $\text{LiNi}_{0.6}\text{Mn}_{0.2}\text{Co}_{0.2}\text{O}_2$ (NMC 622) layered oxide morphology on the positive electrode/electrolyte interface**

Adrien Soloy, Delphine Flahaut, Joachim Allouche, Dominique Foix, Germain Salvato Vallverdu, Erwan Dumont, Lucille Gal, François Weill, Laurence Croguennec

### ► To cite this version:

Adrien Soloy, Delphine Flahaut, Joachim Allouche, Dominique Foix, Germain Salvato Vallverdu, et al.. Influence of the  $\text{LiNi}_{0.6}\text{Mn}_{0.2}\text{Co}_{0.2}\text{O}_2$  (NMC 622) layered oxide morphology on the positive electrode/electrolyte interface. EUROMAT 2021 Conference - European Congress and Exhibition on Advanced Materials and Processes, Sep 2021, Visioconférence, Austria. hal-04569578

**HAL Id: hal-04569578**

**<https://hal.science/hal-04569578>**

Submitted on 13 May 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

**Influence of the  $\text{LiNi}_{0.6}\text{Mn}_{0.2}\text{Co}_{0.2}\text{O}_2$  (NMC 622) layered oxide morphology on the positive electrode/electrolyte interface**

Adrien Soloy<sup>1</sup>, Delphine Flahaut<sup>2,4</sup>, Joachim Allouche<sup>2,4</sup>, Dominique Foix<sup>2,4</sup>, Germain Vallverdu<sup>2,4</sup>, Erwan Dumont<sup>3</sup>, Lucille Gal<sup>3</sup>, François Weill<sup>1,4,5</sup> and Laurence Croguennec<sup>1,4,5</sup>

<sup>1</sup>CNRS, Univ. Bordeaux, Bordeaux INP, ICMCB UMR 5026, F-33600 Pessac, France

<sup>2</sup>CNRS, Université de Pau et des Pays de l'Adour, E2S UPPA, Institut des Sciences Analytiques et de Physicochimie pour l'Environnement et les Matériaux – UMR 5254, 64000 Pau, France

<sup>3</sup>SAFT, Direction de la Recherche, 33074 Bordeaux, France

<sup>4</sup>RS2E, Réseau Français sur le Stockage Electrochimique de l'Energie, FR CNRS 3459, F-80039 Amiens Cedex 1, France

<sup>5</sup>ALISTORE-ERI European Research Institute, FR CNRS 3104, F-80039 Amiens Cedex 1, France

The  $\text{LiNi}_{0.6}\text{Mn}_{0.2}\text{Co}_{0.2}\text{O}_2$  layered oxide is a very attractive positive electrode material for Li-ion batteries and possibly in a near future for all-solid-state batteries, thanks to good capacity, stability and cyclability upon long range cycling in the former. To optimize its performances in both systems, a better knowledge of its reactivity, versus liquid and solid electrolyte, is needed. The aim of this work is to tailor its morphology, particle size and shape, in order to determine their impact on the reactivity. A series of samples with crystallographic structure close to the ideal 2D layered structure (less than 5%  $\text{Ni}^{2+}$  ions into the  $\text{Li}^+$  sites) and the targeted composition were obtained by a two-step synthesis, consisting of a coprecipitation followed by a solid-state reaction. Samples with primary particle sizes from 200 nm to 2  $\mu\text{m}$  were obtained by varying the solid-state reaction temperature and atmosphere. Samples with platelet-shaped particles were obtained by using a large amount of ammonium hydroxide as template during the coprecipitation step. Two thicknesses, around 10 nm and 85 nm, were obtained by varying the thermal treatment temperature. Electrochemical tests, as well as XPS and Auger analyses were performed to characterize the electrochemical performance and surface properties of the materials. Analyses were also performed after cycling to study the electrode/electrolyte interface and compare the reactivity of the materials as a function of their morphology. These results will be discussed in details in the frame of this communication.

**Keywords:** battery, layered oxide, NMC, morphology, reactivity, performance