

Coupling of Deep Learning on Graphs and Model Order Reduction for Efficient Preliminary Sizing of Mechanical Structures in Aircraft Crash Simulations

Victor Matray, Faisal Amlani, Frédéric Feyel, David Néron

► To cite this version:

Victor Matray, Faisal Amlani, Frédéric Feyel, David Néron. Coupling of Deep Learning on Graphs and Model Order Reduction for Efficient Preliminary Sizing of Mechanical Structures in Aircraft Crash Simulations. MORTech 2023 – 6th International Workshop on Model Reduction Techniques, Nov 2023, Gif sur Yvette, France. hal-04585040

HAL Id: hal-04585040 https://hal.science/hal-04585040v1

Submitted on 23 May 2024


HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Coupling of Deep Learning on Graphs and Model Order Reduction for Efficient Preliminary Sizing of Mechanical Structures in Aircraft Crash Simulations


Victor Matray^a, Faisal Amlani^a, Frédéric Feyel^{b,a}, David Néron^a

^a LMPS - Laboratoire de Mécanique Paris-Saclay, Université Paris-Saclay, CentraleSupélec, ENS Paris-Saclay, CNRS, 4 Av. des Sciences, 91190, Gif-sur-Yvette, France. ^b Safran Tech, Digital Sciences & Technologies Department, Rue des jeunes bois, Châteaufort, 78114, Magny-les-Hameaux, France.

Keywords: Reduced Model (POD-PGD), Non-Parametric Problem, Deep Learning, Graph Neural Networks



3-Graph Neural Networks (GNN):




- input features (through permutation-invariant aggregate function)
- $\bullet~{\rm High}~{\bf flexibility}~{\rm and}~{\bf generalisability}$
- Developed spatial convolution layer:

node *i* embedding: $\mathbf{v}_{i}^{0} = \mathrm{MLP}_{\mathrm{encoder}}(\mathbf{F}_{i}, \mathbf{n}_{i}),$


edge $j \rightarrow i$ message: $\mathbf{m}_{ij}^{l} = \phi \left(\mathbf{v}_{i}^{l}, \mathbf{v}_{j}^{l}, \mathbf{F}_{i}, \mathbf{F}_{j}, \mathbf{n}_{i}, \mathbf{n}_{j} \right),$ [Huang et al., 2018] node i update: $\mathbf{v}_{i}^{l+1} = \psi \left(\mathbf{v}_{i}^{l}, \sum_{j \in \mathcal{N}(i)} \mathbf{m}_{ij}^{l}, \mathbf{F}_{i}, \mathbf{n}_{i} \right),$ node i final state: $\Lambda_{i}^{GNN} = \mathrm{MLP}_{\mathrm{decoder}} \left(\mathbf{v}_{i}^{L} \right)$ [Brandstetter, 2022]


Popular approach in the literature: $\mathbb{E}[Pfaff et al., 2021]$





• Autoregressive approach

- Inference time proportional to number of time steps N_t
- Error increases during simulation









This work was granted access to the HPC resources of IDRIS under the allocation 2023-[AD011014260] made by GENCI.

