



**HAL**  
open science

# The eXtreme Mesh deformation approach (X-MESH) to follow contact fronts in a sharp manner

Benoît Lé, Nicolas Moës, Nicolas Chevaugéon, Jean-François Remacle

## ► To cite this version:

Benoît Lé, Nicolas Moës, Nicolas Chevaugéon, Jean-François Remacle. The eXtreme Mesh deformation approach (X-MESH) to follow contact fronts in a sharp manner. 11th European Solid Mechanics Conference (ESMC2022), Jul 2022, Galway, Ireland. hal-04585561

**HAL Id: hal-04585561**

**<https://hal.science/hal-04585561>**

Submitted on 23 May 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# The eXtreme Mesh deformation approach (X-MESH) to follow contact fronts in a sharp manner

Benoît Lé<sup>1</sup>, Nicolas Moës<sup>1</sup>, Nicolas Chevaugéon<sup>1</sup>, Jean-François Remacle<sup>2</sup>

<sup>1</sup> Ecole Centrale de Nantes, GeM, UMR 6183, 44321 Nantes, France

E-mail: [benoit.le@ec-nantes.fr](mailto:benoit.le@ec-nantes.fr), [nicolas.moes@ec-nantes.fr](mailto:nicolas.moes@ec-nantes.fr), [nicolas.chevaugéon@ec-nantes.fr](mailto:nicolas.chevaugéon@ec-nantes.fr)

<sup>2</sup> Université Catholique de Louvain, Institute of Mechanics, Materials and Civil Engineering, 1348 Louvain-la-Neuve, Belgium

E-mail: [jean-francois.remacle@uclouvain.be](mailto:jean-francois.remacle@uclouvain.be)

**Keywords:** X-MESH, contact mechanics, sharp interface

Contact problems are governed by inequality constraints, which have been at the core of many research during the past decades [1, 2]. Most of these methods are quite efficient in modeling the inside of the contact zone, however only a few of them are able to sharply model the contact front (contact zone boundary). Yet, a sharp representation of the contact front is necessary to get optimal convergence rate, as it was shown by [3] for instance.

In this work, an efficient way to model sharp contact front is proposed, based on the X-MESH approach which was originally introduced in [4] to model phase-change fronts. The key idea is to move the nodes of a finite element mesh to have a time continuous, sharp representation of the contact front. These nodes movements allow to model topological change of the contact front, including coalescence and splitting, without remeshing or changing the mesh topology. Some finite elements may eventually reach zero measure, but we show in this work that this can be properly tackled.

The method could be applied to any contact problems, but we chose to illustrate its capabilities on several 1D and 2D quasi-static membrane problems in small perturbation. In particular we show that the X-MESH method allows to recover optimal mesh convergence rates, and how it allows to model complex topological changes of the contact zone.

## References

- [1] Laursen, T.A., *Computational Contact and Impact Mechanics (Springer Edition)* (2002).
- [2] Wriggers, P., *Computational Contact Mechanics (Wiley Edition)* (2002).
- [3] Graveleau, M. and Chevaugéon, N. and Moës, N., The inequality level-set approach to handle contact: membrane case, *Advanced Modeling and Simulation in Engineering Sciences*, (2015) **2**: 1–16..
- [4] Moës, N. and Remacle, J.-F. and Lambrechts, J. and Lé, B., The eXtreme Mesh deformation approach (X-MESH) for the Stefan phase-change model, *arxiv preprint* (<http://arxiv.org/abs/2111.04179>) (2021).