

### Phenomenology of a bubble plume: from the leak of an underwater storage tank to the seawater surface

Camille Deberne, Jorge César Brändle de Motta, Marie-Charlotte Renoult,

Thibault Neu, Jean-Bernard Blaisot, David Guyomarc'H

#### ▶ To cite this version:

Camille Deberne, Jorge César Brändle de Motta, Marie-Charlotte Renoult, Thibault Neu, Jean-Bernard Blaisot, et al.. Phenomenology of a bubble plume: from the leak of an underwater storage tank to the seawater surface. SEANERGY, Jun 2024, Nantes (France), France. hal-04612459

#### HAL Id: hal-04612459 https://hal.science/hal-04612459

Submitted on 14 Jun2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.







# From the leak of an underwater storage tank to the seawater surface C. Deberne<sup>a,b</sup>, J.C. Brändle de Motta<sup>a</sup>, M.-C. Renoult<sup>a</sup>, T. Neu<sup>b</sup>, J.-B. Blaisot<sup>a</sup>, D. Guyomarc'h<sup>b</sup>

<sup>a</sup> INSA Rouen Normandie, Univ Rouen Normandie, CNRS, Normandie Univ, CORIA UMR 6614, F-76000 Rouen, France

<sup>b</sup> SEGULA Technologies, 1 rue Charles Lindbergh, Bouguenais, France


### **Context and Objectives**

Helping designing an underwater compressed air energy storage system (UWCAES)

- Predicting the impacts induced by a massive leak of compressed air into seawater
- Implementing a suitable risk analysis study

## Application

UWCAES system configurationSubmerged at 200 m depth







• Leak orifice of 30 cm diameter

# Results

- A. Tank empties in less than 4 minutes
  Initial gas flow rate is 136 kg/s → Jetting flow regime
  - Leak behaviour depends on tank dimension
- B1. Gas density has no effect on bubble dynamics Dynamics is driven by bubble height h
  - Initial shape influences bubble velocity





- B2. Expansion rate is negligible compared with bubble rise velocity
  - Bubbles increase in number but decrease in size
  - Fragmentation prevails over coalescence and expansion
- C. Seawater surface fountain is 1 m high and 42 m wide
   o Fountain width increases with immersion depth



### **Conclusion and Perspectives**

Using multiple tools to study an air bubble plume offers a deeper insight into its dynamics.

Greater accuracy could be achieved by considering the interaction between plume and seawater

DNS have been realized with in-house code ARCHER



The financial support of this work by ANRT (CIFRE Convention 2021 / 1876) is acknowledged camille.deberne@coria.fr



[1] Deberne, C., Renoult, M. C., Blaisot, J. B. (2023) « A mathematical model describing an unsteady leak of compressed air from an open underwater storage tank ». Journal of Energy Storage, 81 (110318)
 [2] Solsvik, J., Jakobsen, H. A. (2015) « The Foundation of the Population Balance Equation : A Review ». Journal of Dispersion Science and Technology, 36:4, 510-520

[3] Friedl, M. J., Fanneløp, T. K. (2000) « Bubble plumes and their interaction with the water surface ». Applied Ocean Research, 22, 2