



Optimal structures for a model of crop irrigation with constraints

Ruben Chenevat, Bruno Cheviron, Alain Rapaport, Sébastien Roux

► To cite this version:

Ruben Chenevat, Bruno Cheviron, Alain Rapaport, Sébastien Roux. Optimal structures for a model of crop irrigation with constraints. Journées SMAI MODE 2024, Mar 2024, Lyon, France. hal-04630409

HAL Id: hal-04630409

<https://hal.science/hal-04630409>

Submitted on 1 Jul 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Optimal structures for a model of crop irrigation with constraints

Ruben Chenevat, Bruno Cheviron, Alain Rapaport, Sébastien Roux


Irrigation model

$$(\mathcal{S}) \quad \begin{cases} \dot{S}(t) = k_1(-\varphi(t)K_S(S(t)) - (1-\varphi(t))K_R(S(t)) + k_2 u(t)) \\ \dot{B}(t) = \varphi(t)K_S(S(t)) \\ \dot{V}(t) = u(t) \end{cases}$$

Initial conditions : $S(0) = S_0 \in (S^*, 1]$, $B(0) = V(0) = 0$.

Constraints : $\begin{cases} S_{tol} \leq S(t) \leq 1 & \text{(state constraints)} \\ V_{tol} < V(T) < V^* & \text{(deficit irrigation)} \end{cases}$

S : soil moisture
 B : biomass
 V : water consumption



Objectives and targets

Maximizing biomass, limited water quota

$$(B1) : \max_{u(\cdot)} B(T) \quad \text{st} : V(T) \leq V_{init}$$

Minimizing biomass, wasting water quota

$$(W1) : \min_{u(\cdot)} B(T) \quad \text{st} : V(T) \geq V_{init}$$

Structures of optimal solutions


Time-varying feedback controls, parametrized "best" and "worst" strategy families :

$$\Psi_{V_d, t_c, t_e}^+(t, X) = \begin{cases} 0 & \text{if } (S \geq S_{tol} \wedge t \leq t_d) \vee V = V_c \vee t \geq t_c \\ \tilde{u}(t, S_{tol}) & \text{if } S = S_{tol} \wedge t \leq t_d \\ \tilde{u}(t, S^*) & \text{if } S = S^* \wedge V < V_c \wedge t < t_c \\ 1 & \text{otherwise} \end{cases}$$

(t_d : trigger time)

$$\Psi_{V_d, t_c, t_e}^-(t, X) = \begin{cases} 1 & \text{if } (V < V_d \wedge S < 1) \vee V_c - V = T - t \\ \tilde{u}(t, 1) & \text{if } V < V_d \wedge S = 1 \\ \tilde{u}(t, S_{tol}) & \text{if } S = S_{tol} \wedge V < V_c \wedge t < t_c \\ 0 & \text{otherwise} \end{cases}$$

(V_d : trigger volume)





Sketch of proof for optimality


- To apply the non-smooth PMP, additional state variables and targets : $\dot{Y}(t) = \min(0, S(t) - S_{tol})$, $\dot{Z}(t) = \max(0, S(t) - 1)$; $Y(0) = Z(0) = Y(T) = Z(T) = 0$
- Denoting u_P the optimal control for problem (P) , and $(S_P, B_P, V_P, Y_P, Z_P)$ the corresponding solution, then the target is saturated : $V_{B1}(T) = V_{W1}(T) = V_{init}$
- Common Hamiltonian for the problems : $H_P = \lambda_P^S k_1 (k_2 u - (\varphi(t)K_S(S(t)) + (1-\varphi(t))K_R(S(t)))) + \lambda_P^B \varphi(t)K_S(S(t)) + \lambda_P^V u + \lambda_P^Y f_Y(S(t)) + \lambda_P^Z f_Z(S(t))$
- Adjoint equations, with the Clarke generalized gradients : $\begin{cases} \dot{\lambda}_P^S(t) \in \varphi(t)(\lambda_P^S(t)k_1 - \lambda_P^B)\partial_C K_S(S(t)) + (1-\varphi(t))\lambda_P^S(t)k_1\partial_C K_R(S(t)) - \lambda_P^Y \partial_C f_Y(S(t)) - \lambda_P^Z \partial_C f_Z(S(t)) \\ \dot{\lambda}_P^B = \dot{\lambda}_P^V = \dot{\lambda}_P^Y = \dot{\lambda}_P^Z = 0 \end{cases}$
- Switching function : $\phi_P(t) = \lambda_P^S(t)k_1k_2 + \lambda_P^V$. Signs of adjoints : $\lambda_{B1}^S(T) = 0 \quad \lambda_{B1}^S \geq 0 \quad \lambda_{B1}^B = 1 \quad \lambda_{B1}^V < 0 \quad \lambda_{W1}^S(T) = 0 \quad \lambda_{W1}^S \leq 0 \quad \lambda_{W1}^B = -1 \quad \lambda_{W1}^V > 0$
- Singular arcs : $S_P(t) = \tilde{S}$ where \tilde{S} is a non-differentiable point of K_S, K_R, f_Y or f_Z . Singular control : $\tilde{u}(t, \tilde{S}) = \frac{\varphi(t)K_S(\tilde{S}) + (1-\varphi(t))K_R(\tilde{S})}{k_2}$
- The sets $\chi_{B1} = \{t \in [t^*, T], \phi_{B1}(t) \geq 0\}$ and $\chi_{W1} = \{t \in [0, T], \phi_{W1}(t) \leq 0\}$ are connected.

Numerical exploration



Sensitivity analysis for the maximal biomass :



Sensitivity analysis for the optimal trigger time :




Sensitivity analysis for the stress of optimal strategy :



Exploration settings

- $S_0 \in [0.7, 1]$
- $ET_0 \in [2, 7]$
- $Vol \in [50, 300]$
- $S^* \in [0.55, S_0]$
- $k_2 \in [2, 6]$
- $\delta \in [0.1, 0.9]$
- $\gamma \in [2, 8]$


Parametrization of φ :




$$(Rk : k_1 = \frac{ET_0}{Vol})$$

Relative gain best/worst

Gap between best Ψ^+ and worst Ψ^-
Gap between best and worst Ψ^+



Distributions and average of relative gain :



Reference

- [1] R. Chenevat et al., <https://hal.science/hal-04506794>, Working paper, March 2024.

Acknowledgements

This work was supported by Labex Numev (ANR-10-LABX-0020) and by the French National Research Agency under the Investments for the Future Program, referred as ANR-16-CONV-0004.