

#### Stand-Alone and Traffic Sensitive Speed Advisory System based on Lagrangian Traffic Indicators for Eco-Driving or GLOSA Strategies near Traffic Lights

Pierre-Antoine Laharotte, Kinjal Bhattacharyya, Jonathan Perun,

Nour-Eddin El Faouzi

#### ▶ To cite this version:

Pierre-Antoine Laharotte, Kinjal Bhattacharyya, Jonathan Perun, Nour-Eddin El Faouzi. Stand-Alone and Traffic Sensitive Speed Advisory System based on Lagrangian Traffic Indicators for Eco-Driving or GLOSA Strategies near Traffic Lights. TRB Annual Meeting 2022, Jan 2022, Washinghton, United States. hal-04638077

#### HAL Id: hal-04638077 https://hal.science/hal-04638077v1

Submitted on 8 Jul2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# **Université Gustave Eiffel**



## Stand-Alone and Traffic Sensitive Speed Advisory System based on Lagrangian Traffic Indicators for Eco-Driving or GLOSA Strategies near Traffic Lights

Pierre-Antoine Laharotte<sup>1</sup>, Kinjal Bhattacharyya<sup>1</sup>, Jonathan Perun<sup>1,2</sup>, Nour-Eddin El Faouzi<sup>1</sup>

<sup>1</sup>LICIT (Traffic and Transportation Engineering Laboratory, Universite Gustave Eiffel, Lyon, France <sup>2</sup> ENTPE, Lyon, FRANCE

#### Introduction

#### Context

**GLOSA** (Green Light Optimal Speed Advisory) or eco-driving strategies in the vicinity of intersection are widely studied systems enabling Connected Vehicles drive through the intersection without getting stopped. In its basic implementation, the 'simple GLOSA' aims at targeting the beginning of the green phases and neglect queue length. Accordingly, its area of application is restricted to medium degree of saturations ( $\leq$  50%) and the algorithm becomes inefficient with high demand.



Main challenges



Positioning

Few studies (e.g. Yang et al.) have developed algorithms taking consideration into downstream traffic conditions, but it requires a large set of intrusive or dedicated sensors, not systematically available at any location. Can we achieve to perform GLOSA with

**Queue-Length prediction only from tracks left** by Connected Vehicles?

## Estimation process



#### **Requirements to predict Queue Length**

- Assess forward propagation shockwave W<sub>CB</sub>
  - $\rightarrow$  depend on **road configuration**
- Assess backward propagation shockwave V<sub>AC</sub>
  - → depend on **traffic demand**

#### **Identification of** over-estimation

## **Temporal relocation of** expected stops position

).

).

**Eulerian estimators** 

Use GPS data

Use loop sensor...

Lagrangian estimators

Legend

11140

Observed Stop

Relocated Stop



## **Key concepts**

- **Prediction of V\_{AC}** is performed at each time-step based on a subset of previous ).( observations selected by a sliding window
- Each new measurement is weighted by a Confidence Level and combined with ).( prediction to enhance stability
- **Over-estimation** is prevented by targetting a slightly sub-optimal solution ).( (systematic reduction applied when no stops occured)

#### Use cases

#### Simulation Framework

#### **Experimental Design**



## Main findings

N

SUMO





#### Acknowledgements

Yang et al – 2016 - Yang, H., Rakha, H., & Ala, M. V. (2016). Eco-cooperative adaptive cruise control at signalized intersections considering queue effects. IEEE Transactions on Intelligent Transportation Systems, 18(6), 1575-1585.

C-Roads (www.c-roads.eu) C-The-Difference (www.c-thedifference.eu)