

Optimal Strategy for Spatial Inference of Speed Profiles on Large Scale Road Network: OSSI-SPLN

Pierre-Antoine Laharotte, Loic Bonnetain, Matthieu Guillot, Angelo Furno,

Nour-Eddin El Faouzi

► To cite this version:

Pierre-Antoine Laharotte, Loic Bonnetain, Matthieu Guillot, Angelo Furno, Nour-Eddin El Faouzi. Optimal Strategy for Spatial Inference of Speed Profiles on Large Scale Road Network: OSSI-SPLN. TRB Annual Meeting 2024, Jan 2024, Wahington DC, United States. hal-04638507

HAL Id: hal-04638507 https://hal.science/hal-04638507v1

Submitted on 8 Jul2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Optimal Strategy for Spatial Inference of Speed Profiles Université Gustave Eiffel on Large Scale Road Network: OSSI-SPLN

Introduction

Problem statement

Floating Car Data (FCD) is a usual and convenient resource to generate traffic speed indicators, but it comes with an expensive cost to cover large road networks.

Where should we focus the data collection when reproducing speed profiles for any road section on an extensively large road network with limited resources?

Most studies involving FCD focus on issues related to sparse data collection, and the Sensor Location Problem is only considered from the road manager's perspective, assuming controlled Mobile Sensors.

Our problem statement and formulation are distinct as it aims at optimizing the spatial coverage to achieve high representativeness of the diversity of road link speed profiles. Consequently, our methodology is inspired by Optimal Spatial Coverage strategies for Sensor Networks, developed in distinct domains, especially the works developed by Hoffman *et al* (2013).









Note: The historical speed profiles might be collected on a subpart of the targeted road network.

Pierre-Antoine Laharotte, Loïc Bonnetain, Matthieu Guillot, Angelo Furno , Nour-Eddin El Faouzi Univ. Eiffel, Univ. Lyon, ENTPE, LICIT-ECO7, F-69675 Lyon, France.

Methodology overview



STEP 1: Edge Profiles definition and road sections clustering



 \forall section $s \in S$, $EP(s) = EP_i$,

where $EP_i \in \{EP_p ; p \in [|1; P|]\}$

✓ Feature 1

Feature 2

E

E



 EP_{P}

Associate one Edge Profile (EP) to any road section by drawing among the set of P available profiles

STEP 2 & 3: Determination of the targeted utility per Edge Profile

networks)



Speed Limit (30; 50; 70 - 90; 110; 130)

(number of connected edges : ≤ 2 ; ≤ 4 ; ≤ 6 ; > 6) IsEndedByTrafficLight (True; False) Density range for population volume

STEP 4: Computation of tile's utility

 $_{P1}Card_t(EP_k)$



- the one issued by the k selected tiles;
- issued by the k selected tiles.



Case study: city of Lyon





Hoffman, F. M., Kumar, J., Mills, R. T., & Hargrove, W. W. (2013). Representativeness-based sampling network design for the State of Alaska. Landscape Ecology, 28, 1567-1586.

Kanaroglou, P. S., Jerrett, M., Morrison, J., Beckerman, B., Arain, M. A., Gilbert, N. L., & Brook, J. R. (2005). Establishing an air pollution monitoring network for intra-urban population exposure assessment: A location-allocation approach. Atmospheric Environment, 39(13), 2399-2409. Lerner, U., Hirshfeld, O., & Fishbasin, B. (2019). Optimal deployment of a heterogeneous air quality sensor network. J. Environ. Inform, 34(2), 99-107.

STEP 5: Optimization to select K tiles