

DECOMICS, a shiny application for unsupervised cell type deconvolution and biological interpretation of bulk omic data

Slim Karkar, Ashwini Sharma, Carl Herrmann, Yuna Blum, Magali Richard

▶ To cite this version:

Slim Karkar, Ashwini Sharma, Carl Herrmann, Yuna Blum, Magali Richard. DECOMICS, a shiny application for unsupervised cell type deconvolution and biological interpretation of bulk omic data. Bioinformatics Advances, 2024, 4 (1), 10.1093/bioadv/vbae136 . hal-04660629v1

HAL Id: hal-04660629 https://hal.science/hal-04660629v1

Submitted on 24 Jul 2024 (v1), last revised 21 Oct 2024 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

| 1 | DECOMICS, a shiny application for |
|---|---------------------------------------|
| 2 | unsupervised cell type deconvolution |
| 3 | and biological interpretation of bulk |
| 4 | omic data |
| | |

- 6 7 Slim Karkar^{1,*}, Ashwini Sharma², Carl Herrmann², Yuna Blum^{3,*,⊕}, Magali Richard^{4,*,⊕} 8 ¹IBGC, UMR 5095, University of Bordeaux, CNRS, Bordeaux Bioinformatic Center, 9 10 Bordeaux, France, 2 Health Data Science Unit, Medical 11 ² Faculty Heidelberg and BioQuant, Heidelberg, Germany, 3 IGDR (Institut de Genetique et 12 Developpement de Rennes), UMR 6290, ERL 13 ³ U1305, Equipe Labellisée Ligue Nationale contre le Cancer, Univ Rennes, CNRS, INSERM, 14 35000, Rennes, France 15 ⁴ TIMC, UMR 5525, Univ. Grenoble Alpes, CNRS, F-38700, Grenoble, France 16 *Corresponding authors : <u>slim.karkar@u-bordeaux.fr</u>; <u>magali.richard@univ-grenoble-</u>
- 17 <u>alpes.fr; yuna.blum@univ-rennes1.fr</u>
- 18 [⊕]Equal co-last contributors

5

keywords: R shiny, deconvolution, unsupervised approaches, transcriptomic data,methylome, tissue heterogeneity

21 Abstract

22

23 Unsupervised deconvolution algorithms are often used to estimate cell composition from bulk tissue samples. However, applying cell type deconvolution and interpreting the 24 25 results remains a challenge, even more without prior training in bioinformatics. We 26 propose here a tool for estimating and identifying cell type composition from bulk transcriptomes or methylomes. DECOMICS is a shiny-web application dedicated to 27 28 unsupervised deconvolution approaches of bulk omic data. It provides (i) a variety of 29 existing algorithms to perform deconvolution on the gene expression or methylation-level matrix, (ii) an enrichment analysis module to aid biological interpretation of the 30 deconvolved components, based on enrichment analysis, and (iii) some visualisation 31 tools. Input data can be downloaded in csv format and pre-processed in the web 32 application (normalisation, transformation and feature selection). The results of the 33 34 deconvolution, enrichment and visualisation processes can be downloaded.

35 Availability and implementation: DECOMICS is an R-shiny web application that can be 36 launched (i) directly from a local R session using the R package available here 37 https://gitlab.in2p3.fr/Magali.Richard/decomics (either by installing it locally, or via a 38 virtual machine and a Docker image that we provide); or (ii) in the Biosphere - IFB Clouds 39 Federation for Life Science (French Institute of Bioinformatics), a multi-cloud environment 40 scalable for high performance computing: https://biosphere.france-41 bioinformatique.fr/catalogue/appliance/193/, which requires creating an account and 42 logging onto the platform

43 Introduction

44 Identification of the cell composition contributing to bulk molecular signals is a major 45 challenge in molecular analysis in various applications such as cancer¹. The development 46 of in silico deconvolution methods has made it possible to revisit existing bulk omic data 47 from large patient cohorts with regard to intra-sample heterogeneity, and thus to compare 48 sample cell composition with available clinical annotations such as treatment response. Both supervised² and unsupervised³⁻⁷ deconvolution methods have been proposed in the 49 50 literature. Supervised methods estimate the component proportions using known cell-type 51 reference matrices, whereas unsupervised methods estimate both the reference profiles 52 and the component proportions, without prior knowledge except for the number of 53 components to be considered. Supervised approaches are therefore limited by the quality 54 of the reference signatures, while unsupervised approaches present difficulties in interpreting the inferred components and estimating the number of components to be 55

56 considered.

57 An intriguing advantage of unsupervised methods is that, unlike supervised methods, they 58 can identify new cell populations or populations that would not have been taken into 59 account a priori. Unsupervised deconvolution approaches have recently been used to 60 identify radiogenomic signatures to predict prognosis of colorectal cancer⁸, to identify 61 cellular compartment in unknown tumoral samples⁹, or to infer clinical outcomes in 62 melanoma patients¹⁰.

Applying unsupervised deconvolution approaches to patient cohorts is now possible thanks to recent advances in high-throughput sequencing that have generated an enormous amount of transcriptomic data as well as numerous methylome data. This is particularly true in the field of oncology, where more and more biological samples are being sequenced to help with patient stratification and prognosis. However, analyzing this type of data requires professional coding skills, which are rarely available to clinicians.

In order to appeal large data analysis to a wider audience, user-friendly alternatives have been devised, including the development of the R-shiny package, which enables interactive web applications to be built using the R statistical and data mining software¹¹. If web applications exist to apply supervised algorithms on clinical datasets¹², exploration of unsupervised algorithms have been so far limited to bioinformaticians with computing skills and do not provide guidance for biological interpretation of their outputs.

Here we propose DECOMICS, a user-friendly shiny interactive web application designed to
 perform unsupervised deconvolution on transcriptomic and methylome (DNAm) data. Six

different unsupervised methods are implemented in DECOMICS, including the most
commonly used (ICA and NMF), and more recent algorithms (CDSeq⁴, debCAM³ and
PREDE⁵, EDec⁷). Our tool also provides guidance during the process and helps with the
biological interpretation of the results, which should be of significant interest for both
bioinformaticians and clinicians.

82 Software description

DECOMICS is a Shiny application available as an R package that can be built from source (GitLab access) or used online through the biosphere cloud of the IFB (Institut Français de Bioinformatique). DECOMICS workflow is illustrated in Figure 1. It includes a Guide section, that can be used as a material and methods, and two main modules: the deconvolution module and a biological interpretation module (Figure 1A-B).

88



89

90 Figure 1: An overview of DECOMICS workflow to perform deconvolution of omics data. A.

91 Screenshot of the application. B. Summary of the DECOMICS process. C. Workflow of the

92 module 'Deconvolution'. D. Workflow of the module 'Biological interpretation'.

93 Deconvolution module

94 The deconvolution module (Figure 1C) is used to load the data, carry out the pre-95 processing, estimate the number of components, run the deconvolution and visualize the 96 results. File input (1) requires a .csv file containing the omic data (either gene expression 97 or DNAm) with samples in columns and features in row. Gene expression can be in the 98 form of raw counts, processed counts or processed gene expression in the case of 99 microarray-based technologies. We offer basic pre-processing features for gene expression data in step 2. DNAm data should be provided in the form of 2-values. Basic 100 101 **Pre-Processing (2)** of the gene expression data can be achieved within the application, 102 including normalization adapted to RNA-seq data (Read-per-million or DESeq2) and 103 transformation (log2 or pseudoLog). Pre-processing also includes the option to select a 104 subset of features. Specifically, one can choose the top 1,000 or 5,000 gene expressions, 105 or the top 10,000 or 20,000 2-values, based on the highest coefficients of variation. The 106 **Number of components (3)** to infer (corresponding to the deconvoluted components) 107 have to be estimated by the user. In general, the optimal number of components can be 108 identified through various methods, including Cattell's rule applied to Principal 109 Component Analysis (PCA) eigenvalues¹³, the Minimum Description Length (MDL)³, 110 bootstrapping techniques¹⁴, and cross-validation methods²¹. However, in a prior 111 benchmark analysis, we found that different methods yielded comparable results⁵. For the 112 sake of clarity, we have chosen to present a single method in the application: a guidance plot based on PCA eigenvalues. Then **Deconvolution (4)** is run by one of the six 113 114 unsupervised algorithms provided in the application. Depending on the type of omic data

provided, a subset of algorithms is available: (i) Independent Component Analysis, Nonnegative Matrix Factorization, CDSeq, debCAM and PREDE for gene expression data, and (ii) ICA, NMF, debCAM and EDec for DNAm data. Finally, deconvolution **Results (5)** can be visualized by (i) a 'cell-type' signature heatmap displaying the 5 top markers of each component, and (ii) a 'cell-type' proportion heatmap of each component.

120 Biological interpretation module

121 The biological interpretation module (Figure 1D) performs an enrichment analysis on the 122 components estimated by the chosen deconvolution algorithm and displays the 123 deconvoluted proportion matrix. First, we propose an Enrichment analysis (6) step, to 124 help with the biological interpretation of the components identified by unsupervised 125 approaches. It proposes to perform Enrichment analysis (Gene Set Enrichment analysis¹⁶ 126 or Over-representation analysis¹⁷) using various biological databases: 'CellMatch'¹⁸, a 127 reference database derived from various resources and other reference ones (GO, GTEx, 128 KEGG, Reactome, Tissue Cell Types, Cancer Cell Types and Cancer Cell lines).

Second, a Proportion Visualisation (7) section offers the possibility to visualize the full
component distribution for a single sample, or the distribution of a single component
throughout the total cohort.

132 Material and methods

133 Deconvolution Algorithms

134 Unsupervised deconvolution problem applied to omic bulk data consists in solving an 135 equation of form X = T * A where T and A are jointly inferred from X. This is achieved by 136 estimating the mixture of K cell-types, present in different proportion in each sample (cell-137 type proportion matrix A). Therefore, X can be described as a combination of cell-type 138 specific molecular profiles (cell-type specific gene expression matrix T). The specifics of 139 each existing unsupervised deconvolution algorithm and the reasons for choosing to 140 include them or not in the DECOMICS application are presented in Supplementary Table 1. 141 In DECOMICS, we provide six different algorithms to run deconvolution:

ICA: Independent Component Analysis is a blind source separation algorithm that
decomposes signal into statistically independent components. In DECOMICS ICA
deconvolution is run using fastICA (*R CRAN*) and the Deconica¹⁹ R packages. By default, 30
significant gene markers are selected to get component scores, using the
"weighted.mean" summary metric.

- NMF²⁰: In non-negative matrix factorization approach, the molecular profile matrix X is factorized into two matrices A and T, with the property that all three matrices have no negative elements. DECOMICS uses the *R CRAN* NMF package with method ="snmf/r". The estimated A matrix is constrained to sum the proportion to 1, and T is computed as 151 $T = A^{-1}X$ using the *ginv* inverse function from MASS R package. Finally, all negative values 152 for *T* are set to 0.

- CDSeq⁴ aims at simultaneously estimating *A* and *T* matrices using a probabilistic model based on latent Dirichlet allocation (LDA). DECOMICS uses the R implementation of the CDseq method CDSeqR with the following parameters: beta = 0.5, alpha = 5, mcmc_iterations = 300. Reduction factor is computed to avoid expression values > 10^5 , block numbers and gene block size are computed *s*. *t*., a block do not exceed 10^3 genes.

- debCAM³ stands for deconvolution by Convex Analysis of Mixtures. This method uses a
geometric approach to identify a solution to the NMF problem in the simplex space. Thus,
the proposed solution for *A* is always a proportion matrix. In DECOMICS, the function CAM
is called from the debCAM R packages using the following empirical parameters:
cluster.num is computed to be 5 times greater than the number of expected components,
and dim.rdc set to divide the number of input genes by a tenth.

PREDE⁵ is a method that offers the possibility to conduct partial reference-based
 deconvolution method solved via an iterative Quadratic Programming procedure. In
 DECOMICS, PREDE function is used from PREDE R package, with the following
 parameters: W1 = NULL (which corresponds to a complete deconvolution approach), type
 = "GE", iters = 100 and rssDiffStrop = 1e-5.

EDec-step1⁷ estimates both average component methylation profiles and component
proportions using an iterative constrained matrix factorization algorithm. This algorithm
identifies cell type-specific methylation profiles and constituent cell type proportions by

minimizing the Euclidean distance between the reconstituted and original mixed
methylation matrices. In DECOMICS, we use the EDec::run_edec_stage_1 function with
the parameters max_its = 2000 and rss_diff_stop = 1e-10.

175 Gene Set Enrichment Analysis

176 In order to biologically characterize each of the unsupervised components identified, 177 biological enrichment analyses are performed. For each component, the first step consists in ranking the genes according to their coordinates on the component, in order to identify 178 179 the most contributing genes of the component. For methylation data, CpG coordinates are 180 aggregated at the gene level, taking the maximum value observed for CpGs of the same 181 gene. This approach is a way of considering a gene as strongly contributing to the 182 component if it has at least one strongly contributing CpG. In a second step, an 183 enrichment analysis is performed either based on Gene Set Enrichment Analysis (GSEA)¹⁶ or Over-Representation Analysis (ORA)¹⁷. If the coordinates contain sufficient non-184 185 duplicate values (threshold set at 30% by default) to enable reliable ordering of the values, 186 a GSEA analysis is performed using the fgsea R package²¹; otherwise, an ORA analysis is 187 performed, taking as gene selection the top 20% of the component's most contributing 188 genes and as gene universe all the genes available in the user's dataset.

Various biological databases can be queried. DECOMICS includes the CellMatch database
restricted to the human species and cell types with at least 3 marker genes per cell type.
After filtering, it provides marker genes for 120 different cell types across 103 normal

- 192 tissues and 26 tumoral tissues. DECOMICS also includes the latest versions of the
- 193 following biological databases provided on the Enrichr²² tool website:
- 194 Cancer Cell Line Encyclopedia (967 terms)
- 195 CellMarker Augmented 2021 (1097 terms)
- 196 GO Biological Process 2023 (5407 terms)
- 197 GO Cellular Component 2023 (474 terms)
- 198 GO Molecular Function 2023 (1147 terms)
- 199 *GTEx Tissues V8 2023* (511 terms)
- 200 *KEGG 2021 Human* (320 terms)
- 201 MSigDB Oncogenic Signatures (189 terms)
- 202 NCI 60 Cancer Cell Lines (93 terms)
- 203 *Reactome 2022* (1818 terms)
- 204 Previously to the enrichment analysis, components obtained from ICA-based method are
- subjected to a reorientation, as proposed in the deconica R package based on the
- 206 hypothesis that the highest absolute values of a component weight should be positive

207 Availability

208 Installation instructions can be found on DECOMICS gitlab webpage: 209 https://gitlab.in2p3.fr/Magali.Richard/decomics. There are three installation options: (i) full local installation, (ii) running locally a virtual machine (VM), or (iii) using the Biosphere-210 211 IFB cloud. Local installation requires several packages to be loaded. To help users, we 212 propose a conda recipe on the DECOMICS gitlab webpage. To offer the possibility to run 213 DECOMICS on a local VM, we built a docker container. The user simply needs to install 214 docker on his machine and to launch the image we provide. Finally, DECOMICS is 215 deployed on the Biosphere portal (searchable through the RAINBio catalogue). To use the 216 clouds of IFB-Biosphere, users need to create an account and get membership of an active 217 group (more information can be found here : https://ifb-elixirfr.github.io/biosphere/signin). 218 Then users can deploy and connect to VM using the web interface (tutorial here: https://ifb-219 elixirfr.github.io/biosphere/vm_connect).

220 Application and results

We have provided two use cases to illustrate the DECOMICS pipeline. The first use case is based on gene expression data (GSE64385²³) dataset is available for download in .csv format from the DECOMICS application. This dataset consists of a mixture of six cell types: HTC116, neutrophils, natural killer cells, monocytes, B cells, and T cells. As shown in Figure 2, the unsupervised components identified by DECOMICS are highly consistent with the constituent cell types. In this example, the deconvolution algorithm employed is debCAM and the functional enrichment analyses was performed using the CellMatch database. The second use case utilizes DNAm profiles from reconstituted mixtures of six purified immune cells derived from human blood samples (GSE77797²⁴). This example further showcases the efficacy of the DECOMICS pipeline for DNAm unsupervised deconvolution and biological interpretation of the unsupervised components. Detailed information on this use case is provided in Supplementary Figure 1, and the corresponding .csv dataset is available for download from the DECOMICS application.

234 In the DECOMICS pipeline, the input data consist of simple count tables in .csv format, 235 which can be uploaded directly to the application. Example input files demonstrating the 236 input format are available for download from the application. The pre-processed data 237 (.csv), deconvolution results (.rds), top 100 contributing genes of each component (.csv), 238 estimated typical gene expressions for components (.csv), and proportion estimates (.csv) 239 can also be downloaded from the application. Additionally, enrichment analyses can be 240 downloaded in the form of a .csv table containing the enrichment scores and P-values for 241 the queried database.



Figure 2: Illustration of DECOMICS based deconvolution of gene expression data. A. 244 245 Parameters used in the DECOMICS application are described. **B.** Scree plot illustrating the 246 selection process for the number of components to be deconvolved (module 1, step 3: 247 Number of cell types). C-D. Deconvolution results are presented: (C) Component 248 signatures are plotted, and (**D**) a heatmap showing component proportions (module 1, 249 step 5: Results). E-F. Visualization of component distribution: (E) Distribution of a specific 250 component across the cohort, and (F) distribution of all components within a given sample 251 (module 2, step 7: Proportion visualization). **G**. Enrichment plot displaying the enrichment 252 analysis for each component (module 2, step 6: Enrichment analysis) ORA indicates if an 253 Overrepresentation Analysis has been performed, GSEA indicates if a Gene Set 254 Enrichment Analysis has been performed for a given sample. Pval corresponds to the 255 adjusted p-values of the Enrichment Score (ES) after correction for multiple testing.

256 Discussion

Despite their advantages over supervised methods, the use of unsupervised deconvolution methods is not trivial, as it requires a priori knowledge of the number of cell populations to be considered, as well as a biological interpretation of the estimated components. Here we provide a user-friendly interactive web-application to perform unsupervised deconvolution by assisting the user in the choice of the number of components and biological interpretation of the results. 263 Significant efforts have been made by colleagues to integrate unsupervised deconvolution 264 into analysis pipelines, including determining the number of components to infer and 265 interpreting the biological data^{25,26}. However, executing these pipelines in their entirety necessitates the installation of R packages and the use of command line interfaces, which 266 267 our web application avoids. Additionally, these pipelines offer a limited selection of 268 deconvolution methods, restricted to those developed by the authors of the integrative 269 pipeline. In this work, we propose an unbiased approach that incorporates several 270 deconvolution methods.

271 DECOMICS stands out for its ease of use, speed, and comprehensive documentation. It is 272 designed to be accessible to users without expertise in R or biostatistics. With its 273 integrated biological interpretation feature, users can seamlessly perform both 274 deconvolution and interpretation within the same platform, eliminating the need for 275 external tools. Moreover, DECOMICS is highly adaptable, allowing for easy updates and 276 redeployment as new reference-free methods or enrichment analysis databases become 277 available. This flexibility ensures that DECOMICS remains at the cutting edge, capable of 278 incorporating the latest technical and methodological advancements.

279 Competing interests

280 No competing interest is declared.

281 Authors contributions and statements

282 S.K., Y.B and M.R. conceived the project. S.K., A.S., C.H., Y.B and M.R. contributed to code

283 development and results analysis. S.K., Y.B. and M.R. wrote the manuscript.

284 Acknowledgements

This work is a contribution of the EIT Health program COMETH. It has been partially supported by MIAI @ Grenoble Alpes (ANR-19-P3IA-0003), and by the French Agency for National Research (CauseHet // ANR-22-CE45-0030). Finally, it has also been carried out with financial support from ITMO Cancer of Aviesan within the framework of the 2021-2030 Cancer Control Strategy, on funds administered by Inserm (ACACIA project AAP-MIC-2021). We thank E. Amblard, H. Barbot, F. Pittion and L. Lamothe for testing the application.

292

293 Bibliography

```
    Nguyen, H., Nguyen, H., Tran, D., Draghici, S. & Nguyen, T. Fourteen years of cellular
    deconvolution: methodology, applications, technical evaluation and outstanding
    challenges. Nucleic Acids Res. 52, 4761–4783 (2024).
```

- 297 2. Avila Cobos, F., Alquicira-Hernandez, J., Powell, J. E., Mestdagh, P. & De Preter, K.
- 298 Benchmarking of cell type deconvolution pipelines for transcriptomics data. *Nat*.

- 299 *Commun.* **11**, 5650 (2020).
- 300 3. Chen, L. et al. debCAM: a bioconductor R package for fully unsupervised
- deconvolution of complex tissues. *Bioinforma*. Oxf. Engl. **36**, 3927–3929 (2020).
- 302 4. Kang, K., Huang, C., Li, Y., Umbach, D. M. & Li, L. CDSeqR: fast complete
- deconvolution for gene expression data from bulk tissues. BMC Bioinformatics 22, 1–
- 304 12 (2021).
- 305 5. Qin, Y. *et al.* Deconvolution of heterogeneous tumor samples using partial reference
 306 signals. *PLoS Comput. Biol.* **16**, e1008452 (2020).
- 307 6. Sompairac, N. *et al.* Independent Component Analysis for Unraveling the Complexity of
- 308 Cancer Omics Datasets. *Int. J. Mol. Sci.* **20**, 4414 (2019).
- 309 7. Onuchic, V. et al. Epigenomic Deconvolution of Breast Tumors Reveals Metabolic
- 310 Coupling between Constituent Cell Types. *Cell Rep.* **17**, 2075–2086 (2016).
- 311 8. Zhong, M.-E. *et al.* CT-based radiogenomic analysis dissects intratumor heterogeneity
- and predicts prognosis of colorectal cancer: a multi-institutional retrospective study. J.
- 313 Transl. Med. **20**, 1–12 (2022).
- 9. Peng, X. L., Moffitt, R. A., Torphy, R. J., Volmar, K. E. & Yeh, J. J. De novo compartment
- 315 deconvolution and weight estimation of tumor samples using DECODER. *Nat.*
- 316 *Commun.* **10**, 4729 (2019).
- 317 10. Nazarov, P. V. et al. Deconvolution of transcriptomes and miRNomes by independent
- 318 component analysis provides insights into biological processes and clinical outcomes
- of melanoma patients. *BMC Med. Genomics* **12**, 1–17 (2019).
- 11. Jia, L. *et al.* Development of interactive biological web applications with R/Shiny. *Brief.*

321 *Bioinform*. **23**, bbab415 (2022).

- 322 12. Li, T. *et al.* TIMER2.0 for analysis of tumor-infiltrating immune cells. *Nucleic Acids Res.*323 48, W509–W514 (2020).
- 324 13. Cattell, R. B. The Scree Test For The Number Of Factors. *Multivar. Behav. Res.* 1, 245–
 325 276 (1966).
- 326 14. Houseman, E. A. *et al.* Reference-free deconvolution of DNA methylation data and
 327 mediation by cell composition effects. *BMC Bioinformatics* **17**, 259 (2016).
- 328 15. Lutsik, P. et al. MeDeCom: discovery and quantification of latent components of
- heterogeneous methylomes. *Genome Biol.* **18**, 1–20 (2017).
- 330 16. Mootha, V. K. et al. PGC-1α-responsive genes involved in oxidative phosphorylation are
- 331 coordinately downregulated in human diabetes. *Nat. Genet.* **34**, 267–273 (2003).
- 17. Goeman, J. J. & Bühlmann, P. Analyzing gene expression data in terms of gene sets:
- methodological issues. *Bioinformatics* **23**, 980–987 (2007).
- 18. Shao, X. et al. scCATCH: Automatic Annotation on Cell Types of Clusters from Single-
- 335 Cell RNA Sequencing Data. *iScience* **23**, 100882 (2020).
- 336 19. Czerwinska, U. UrszulaCzerwinska/DeconICA: DeconICA first release. Zenodo
- 337 https://doi.org/10.5281/zenodo.1250070 (2018).
- 338 20. Gaujoux, R. & Seoighe, C. A flexible R package for nonnegative matrix factorization.
- 339 *BMC Bioinformatics* **11**, 367 (2010).
- 21. Korotkevich, G. et al. Fast gene set enrichment analysis. 060012 Preprint at
- 341 https://doi.org/10.1101/060012 (2021).
- 342 22. Chen, E. Y. et al. Enrichr: interactive and collaborative HTML5 gene list enrichment

- analysis tool. *BMC Bioinformatics* **14**, 128 (2013).
- 344 23. Becht, E. *et al.* Estimating the population abundance of tissue-infiltrating immune and
- 345 stromal cell populations using gene expression. *Genome Biol.* **17**, 1–20 (2016).
- 346 24. Koestler, D. C. et al. Improving cell mixture deconvolution by identifying optimal DNA
- 347 methylation libraries (IDOL). *BMC Bioinformatics* **17**, 1–21 (2016).
- 25. Li, Z. & Wu, H. TOAST: Improving reference-free cell composition estimation by cross-
- cell type differential analysis. *Genome Biol.* **20**, (2019).
- 26. Scherer, M. et al. Reference-free deconvolution, visualization and interpretation of
- 351 complex DNA methylation data using DecompPipeline, MeDeCom and FactorViz. *Nat*.
- 352 *Protoc.* **15**, 3240–3263 (2020).

353 Supplementary material

354



| 356 | Figure S1: Illustration of DECOMICS based deconvolution of DNA methylation data. A. |
|-----|--|
| 357 | Parameters used in the DECOMICS application are described. B. Scree plot illustrating the |
| 358 | selection process for the number of components to be deconvolved (module 1, step 3: |
| 359 | Number of cell types). C-D. Deconvolution results are presented: (C) Component |
| 360 | signatures are plotted, and (${f D}$) a heatmap showing component proportions (module 1, |
| 361 | step 5: Results). E-F. Visualization of component distribution: (E) Distribution of a specific |
| 362 | component across the cohort, and (\mathbf{F}) distribution of all components within a given sample |
| 363 | (module 2, step 7: Proportion visualization). G . Enrichment plot displaying the enrichment |
| 364 | analysis for each component (module 2, step 6: Enrichment analysis) ORA indicates if an |
| 365 | Overrepresentation Analysis has been performed, GSEA indicates if a Gene Set |
| 366 | Enrichment Analysis has been performed for a given sample. Pval corresponds to the |
| 367 | adjusted p-values of the Enrichment Score (ES) after correction for multiple testing. |

| footing | 404 | 40 43eon | ad is all it | ALSILISION CONTRACT | 00 4010 110100 | | O ² CO ¹¹⁰ | Salille Salill | Storig | Strever | "Stoyley | 745 |
|-----------------------|--------------------------------------|-------------|--------------|---------------------|-------------------------------------|-----|--|--|---|--|---|---|
| l a ting i | ICA | poth | ۲ | 2023 | 10.32614/CRAN.package.lastICA | NA | NA | cran | | R (≥ 4.0.0) | https://cran.r project.org/web//pack ages//fastICA/index. html | se, |
| INSUI | NMF | both | ۲ | 2010 | doi:10.1186/1471-2105-11-367 | 640 | NA | cran | graphics, stats, stringt (≥ 1.0.0), digest, grid, gr0evices, gridBase, colorspace, RColorBrewer, foreach, do Parallel, ggplot2, reshape2, Biobase, codetools, BiodManager | R (≥ 3.0.0), methods, utils, registry, mgtools (≥ 1.2.3), cluster | https://cran.r. project.org/web//pack ages//NMF/index.htm I | sej |
| 5 Servi | NMF + constrains | DNAm | ۲ | 2017 | 10.1186/s13059-017-1182-6 | 64 | Only bin any release accessible for MacOS, docker image for windows | github | RoppEigen (>= 0.3) | R (>= 3.2.0), Ropp, pracma, gtools, gplots, parallel, RUnit, RnBeads | https://aithub.com/lut sik/Me.DeCom | vo (probl |
| sed o | Convex analysis | both | ۲ | 2020 | 10.1093/bioinformatics/btaa205 | 6 | NA | bioconductor | methods, rJava, BiocParallel, stats, Biobase, Summarized Experiment, corp cor, geometry, NMF, nnls, DMMR2, pcaPP, apoluster, graphics | R (>= 3.5) | https://www.biocondu ctor.org/packages/rei ease/bioc/html/debC AM.html | sej |
| | NMF | DNAm | ۲ | 2016 | 10.1186/s12859-016-1140-4 | 74 | NA | removed from cran in 2021 | NA | VN | AN AN | vo, no lo but simik |
| nvoli | NMF, equivalent to RefFreeEWAS | DNAm | ۲ | 2016 | <u>10.1016/j.celrep.2016.10.057</u> | 51 | NA | github | quadprog, gtools, stats, clue, utils | R (>= 3.1.2) | https://github.com/B RL-BCM/EDec | sej |
| ۳ ition | NMF | RNA | Ľ | 2020 | <u>10.1371/joumal.pcbi.1008452</u> | ى | NA | github | | R (>= 3.5.0), matrixStats, stats, u tils, quadprog, gtools | https://github.com/Xi aogizheng/PREDE/bi ob/master/DESCRIP TION | (luc) se |
| ة عامر | Probab ilistic mod el | RNA | ۲ | 2021 | 10.1186/s12859-021-04186-5 | в | NA | github | Ropp (>= 1.0.3), MASS, foreach, doParallel, dimult, RoppThread, iterators, parallel, grDevices, Seurat, ggp.kl2, magrittr, dplyr, flang, Matrix, matrixStats, ggp.ubr, pheatmap, harmony | R (>= 3.6.0) | https://github.com/kk ang7/CDSeg_R_Pac kage | sej |
| ^π rithn | SISAL (geometric algorithm) | DNAm | ۲ | 2021 | 10.1093/bioinformatics/btaa930 | 4 | NA | bioconductor | stats, methods, Summarized Experiment, corpcor, doParallel, parallel, ggp.kr2, tidyr, Ggally | R (>= 3.6), EpiDISH, limma, nnls, quadprog | https://bioconductor. oro/packages/releas e/bioc/html/TOAST.ht | vo, becar generate output, ra selected - |
| ± n Thi | NMF | DNAm | ۲ | 2022 | <u>10.1186/s12859-022-04893-7</u> | ٣ | NA | not a package | | | https://github.com/he dinaain/PRMeth | lo (no R |
| ş is tah | Convex analysis | both | ۲ | 2024 | 10.1093/bioinfo matics/btae107 | 0 | NA | github | methods, debCAM, stats, Biobase , Summarized Experiment, corp.cor, geometry, NMF, mnis, graphics, geometry | R (>= 3.6) | https://github.com/Ch jungTingWu/CAM3/ | |
| 2 | | | | | | | | | | | | |

368

369 Table S1: Descriptive table of existing unsupervised deconvolution algorithm. This table

370 provides a brief overview of each algorithm, highlighting their methodologies and key

371 features.