

# New approach in metallic fatigue strength methods with enhanced consideration of size effect and stress gradient

Geoffrey Veragen, Jérôme Rousset, Sébastien Amiable, David Algisi, Pascale

Kanouté, Charles Bianchetti

# ▶ To cite this version:

Geoffrey Veragen, Jérôme Rousset, Sébastien Amiable, David Algisi, Pascale Kanouté, et al.. New approach in metallic fatigue strength methods with enhanced consideration of size effect and stress gradient. 39èmes journée de printemps, May 2023, Paris, France. hal-04669021

# HAL Id: hal-04669021 https://hal.science/hal-04669021v1

Submitted on 7 Aug 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



# New approach in metallic fatigue strength methods with enhanced consideration of size effect and stress gradient

Geoffrey Veragen<sup>1,a</sup>, Jérôme Rousset<sup>1</sup>, Sébastien Amiable<sup>1</sup>, David Algisi<sup>1</sup>, Pascale Kanouté<sup>2</sup> et Charles Bianchetti<sup>2,b</sup>

<sup>1</sup>Airbus Operations, Toulouse, France

<sup>2</sup>DMAS, ONERA, Université Paris Saclay F-92322 Châtillon, France

#### Points d'intérêt.

- Fatigue in large aircrafts
- Current airbus analytical method could be optimized for complex geometries
- Investigation on highly stress volume, critical distance and probabilistic approaches
- Encouraging results, but extra tests needed

## 1 Context

Metal fatigue cracking is a well-known phenomenon in large aircraft environment. It implies various type of design (splicing, stress raiser, lugs...) and materials. In the 90's Airbus has developped an analytic method to design its aircraft, with the objective to guaranty a minimal fatigue life. This method assesses the effect of the different parameters affecting fatigue life, of which the scale effect.

In the current approach, a knockdown factor estimated through a 1D geometric model using Equation (1) covers the scale effect and the stress gradient. [1]

$$E = \left(\frac{a}{r}\right)^{0.08} \tag{1}$$

Where *a* is a constant, and *r* the notch radius (in millimeter).

This approach has proven to be adequate for most of aircraft designs to be analysed. Nevertheless, this approach could be optimised for more complex structures. In addition, 3D finite element models could provide more quantities of interest such as stress gradients and spatial stress fields. Therefore, Airbus is investigating an approach to assess quantitatively the size effect and the stress gradient from detailed 3D finite element models.

Eventually, the selected approach could be integrated in future Airbus fatigue assessment methods.

# 1 Study

Several approaches have been investigated by Airbus and ONERA: the highly stressed volume, critical distance (point, line, surface, or volumic methods)[2], and probabilistic [3].

These approaches have been applied on available coupon test results for an 7175-T7351 aluminum alloy. These coupons included round notch specimens with elastic stress concentration ( $K_t$ ) of 1.0, 1.7, and 3.3.

<sup>&</sup>lt;sup>a</sup> Auteur assurant la présentation : geoffrey.veragen@airbus.com

<sup>&</sup>lt;sup>b</sup> Auteur assurant la présentation : charles.bianchetti@onera.fr



The probabilistic approach was not able to predict properly the behavior, mainly due to the input coupon test results that was not adequete to calibrate the method.

The critical distance approach gives encouraging results. However, none of the 3 methods covers the full fatigue cycles ranging from  $10^4$  cycles to  $10^6$  cycles for the coupon test available.




Figure 1. notched specimen with uniaxial loading(a), and schematic representation of the critical distance approach at point (b), line (c), and surface (c) (Luo et al., 2019).




Figure 2. Critical distance approach result for Kt=1.7 and Kt=3.3 coupons, R= -1

## 2 Conclusion

This study will continue in the following years with new testing to correctly implement the probabilitic approach, and with cyclic hardening caraterisation to hopefully improve the fatigue life prediction of notched structure.

### Références

- 1. S. Turchi, D. Campassens, 14th International Conference on Fracture 2017 (ICF-14), 2017, Rhodes, Grecja
- 2. Taylor, David. "Geometrical effects in fatigue: a unifying theoretical model." International Journal of Fatigue 21.5 (1999): 413-420.
- 3. M. Ben Rabha, M.F. Boujmil, M. Saadoun, B. Bessaïs, Eur. Phys. J. Appl. Phys. (to be published)