



HAL
open science

Machine learning (ML) classification of cells on the basis of their viscoelastic properties

Ophélie Thomas- -Chemin, Childéric Séverac, Yara Abidine, Emmanuelle Trévisiol, Etienne Dague

► **To cite this version:**

Ophélie Thomas- -Chemin, Childéric Séverac, Yara Abidine, Emmanuelle Trévisiol, Etienne Dague. Machine learning (ML) classification of cells on the basis of their viscoelastic properties. European Microscopy Congress (EMC 2024), Aug 2024, Copenhagen, Denmark. , 2024. hal-04673995

HAL Id: hal-04673995


<https://hal.science/hal-04673995>

Submitted on 20 Aug 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Dynamic mechanical assay (DMA) with atomic force microscopy (AFM)



DMA measurements to access viscoelastic properties [1]

- Elastic component (G')
- Viscous component (G'')
- Operates in liquid
- Compatible for live sample

$$\text{Indentation } \gamma^* = \gamma_0 \sin(\omega t)$$


$$\text{Force } \tau^* = \tau_0 \sin(\omega t + \varphi)$$

$$\frac{\tau^*}{\gamma^*} = G' + iG''$$

In phase with indentation γ In phase with rate of indentation $\dot{\gamma}$

Loss tan < 1: Elastic behaviour
Loss tan > 1: Viscous behaviour







$$\text{Loss tan} = \frac{G''}{G'}$$



19 features per DMA measurement: formation of high-density data

19 FEATURES

- G' at 6 frequencies (1-6)
- G'' at 6 frequencies (7-12)
- Loss tan = G''/G' at 6 frequencies (13-18)
- 1 transition frequency (19)



94 cancerous cells (PC3-GFP)
77 non-cancerous cells (RWPE-1)

Statistical differences, but 52 to 98 % of common values
→ Impossible to attribute a single measurement to one class or another



Classification of non-malignant and malignant cells by machine learning (ML) using LAMDA algorithm [2]

Training base:
40 PC3-GFP + 40 RWPE-1

Test base:
54 PC3-GFP + 37 RWPE-1

Trained to classify PC3-GFP and RWPE-1

Correct classification: 75 %
Sensitivity: 79 %
Specificity: 70 %



Discrimination of malignant cells from non-malignant cells at 75 %

[1] Abidine et al., *Comput Methods Biomech Biomed Engin.*, 2013
[2] Hedjazi et al., *Pattern Recognition Letters*, 2011

Conclusion and perspectives

- ✓ 51 984 features in total with mechanobiological sense were generated indenting only 2 736 times on 171 cells
- ✓ Dataset compatible with AI algorithms
- ✓ Useful for classifying samples with few cells (stem cells, circulating tumor cells)
- ✓ 1 Hz measurements could be avoided to increase throughput
- ✓ DMA could be useful to push AFM toward diagnostic