



HAL
open science

A dynamic 1D+1D physical model of the PEMFC hydrogen stack for embedded systems

Raphaël Gass, Zhongliang Li, Rachid Outbib, Samir Jemei, Daniel Hissel

► To cite this version:

Raphaël Gass, Zhongliang Li, Rachid Outbib, Samir Jemei, Daniel Hissel. A dynamic 1D+1D physical model of the PEMFC hydrogen stack for embedded systems. International Conference on Fundamentals and Development of Fuel Cells, Sep 2023, Ulm, Germany. <hal-04680227>

HAL Id: hal-04680227

<https://hal.science/hal-04680227v1>

Submitted on 28 Aug 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire HAL, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



HAL Authorization

A dynamic 1D+1D physical model of the PEMFC hydrogen stack for embedded systems

Raphaël Gass^{*,1,2}, Zhongliang Li¹, Rachid Outbib², Samir Jemei¹, Daniel Hissel¹

¹Université de Franche-Comté, UTBM, CNRS, institut FEMTO-ST, Belfort, France

²Aix Marseille Univ, CNRS, LIS, Marseille, France

³Institut Universitaire de France

Fuel cell technologies are rapidly developing in recent years to decarbonize heavy transports with the use of hydrogen¹. However, the automated control of these systems is generally based on dynamic 0D models that consider fuel stacks as black boxes, sacrificing accuracy for simplicity and short computation times². Other models in the literature are generally 2D or 3D, which offer accuracy, but require a lot of computing time and power³, and therefore cannot be used for embedded systems. Models based on artificial intelligence (AI) are also being developed, which offer a combination of accuracy and speed, but are ineffective when it comes to extrapolating operating conditions that are too different from those for which they were trained⁴, which bring risk.

To address this issue, the team proposes a dynamic 1D+1D model which consists of two dynamic 1D modules in two different spatial directions. The first one analyses the evolution of matter in the stack by considering its thickness only. The second module then examines the matter's behaviour along the bipolar plate's channel only. Combining the two modules gives a 1D+1D model which offers a good compromise between time, computational power, scientific complexity, and accuracy. This is ideal for embedded systems.

The model's validation is also essential. In the current literature, most models are considered valid when they give results consistent with the experimental data of a single polarisation curve. However, this procedure is not sufficient since it is necessary to adjust some model parameters to the real system. Thus, at least a second comparison with different experimental data, after this adjustment and on the same stack, should be added to ensure the validity of the model⁵.

Finally, a two-step experimental validation has been successfully performed for the 1D module in the thickness direction, and the 1D+1D model is currently in construction.

References:

- [1] The Future of Hydrogen. Seizing today's opportunities, <https://www.iea.org/reports/the-future-of-hydrogen>, 2019.
- [2] J.T. Pukrushpan, H. Peng, A.G. Stefanopoulou, *J. Dyn. Sys., Meas., Control* 2004, 126(1): 14-25.
- [3] H. Wu, *Mathematical Modeling of Transient Transport Phenomena in PEM Fuel cells*, thesis, 2009.
- [4] S. Jemei, D. Hissel, M.C. Péra, J. M. Kauffmann. *IEEE Transactions on Industrial Electronics* **2008**, 55(1), 437-447.
- [5] B. Xie, M. Ni, G. Zhang, X. Sheng, H. Tang, Y. Xu, K. Jiao, *International Journal of Heat and Mass Transfer* 2022, 189.

*author to whom correspondence should be addressed: raphael.gass@femto-st.fr