



HAL
open science

FABRICATION AND CHARACTERIZATION TECHNIQUES TO STUDY FLEXIBLE MICRO LIGHT-EMITTING DIODES WITH A MILLIMETRIC RADIUS OF CURVATURE

Jules Duraz, Edmond Cambril, Etienne Herth, Benjamin Damilano, Suresh Sundaram, Phuong Vuong, Abdallah Ougazzaden, Maria Tchernycheva,
Sophie Bouchoule

► To cite this version:

Jules Duraz, Edmond Cambril, Etienne Herth, Benjamin Damilano, Suresh Sundaram, et al.. FABRICATION AND CHARACTERIZATION TECHNIQUES TO STUDY FLEXIBLE MICRO LIGHT-EMITTING DIODES WITH A MILLIMETRIC RADIUS OF CURVATURE. Journées Nationales sur les Technologies Emergentes en micro-nanofabrication (JNTE), Nov 2022, Besançon, France. hal-04683281

HAL Id: hal-04683281

<https://hal.science/hal-04683281>

Submitted on 1 Sep 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

FABRICATION AND CHARACTERIZATION TECHNIQUES TO STUDY FLEXIBLE MICRO LIGHT-EMITTING DIODES WITH A MILLIMETRIC RADIUS OF CURVATURE

J. Duraz^{1*}, E. Cambri¹, E. Herth¹, B. Damilano², S. Sundaram^{3,4}, P. Vuong³, A. Ougazzaden^{3,5}, M. Tchernycheva¹, S. Bouchoule¹

¹C2N, CNRS - Université Paris-Saclay, 91120 Palaiseau, France

²CRHEA, Université Côte d'Azur, CNRS, 06560 Valbonne, France

³CNRS, IRL 2958 Georgia Tech - CNRS, 2 rue Marconi, 57070 Metz, France

⁴Georgia Tech-Lorraine, 2 rue Marconi, 57070 Metz, France

⁵Georgia Institute of Technology, School of Electrical and Computer Engineering, Atlanta, GA 30332-0250, US

*jules.duraz@c2n.upsaclay.fr

Keywords: flexible, micro light-emitting diode (μ LED), van der Waals epitaxy

The interest in flexible micro light-emitting diodes (μ LEDs) is growing in high-tech industries with foldable smartphones or unconventional surfaces (glasses, windshields, or e-papers), more specific applications can also be found in biomedical research. For example, in optogenetics stimulations by using μ LEDs one could improve cochlear implants (CIs) since, contrary to electrical signals, there is no spreading of light in the ear, and the neurons responsible for hearing can be made sensible to blue light (~ 450 nm). GaN-based μ LEDs are good candidates, however, inserting light-based CIs inside the cochlea of a mouse or human being, requires LEDs with reduced dimensions, and improved flexibility (typical dimensions $< 50\mu\text{m}$ and radius of curvature (ROC) down to ~ 1 mm). Standard, relatively thick LEDs will be limited by their rigidity. In this work, we present the fabrication of flexible μ LEDs and their opto-electronic characterization down to millimetric ROC.

Considering GaN-based LEDs generally grown on sapphire, the thinning of the substrate down to a thickness of $\sim 100\mu\text{m}$ or less is challenging; moreover, such LEDs still too rigid to reach the required ROC. Thin-film LEDs with a \sim micrometric thickness are targeted; however, removing the native substrate represents a complex process. Some prototypes of optical-CIs (oCIs) were already demonstrated using laser lift off to decompose the GaN at the GaN-sapphire interface [1], which is a sequential, and costly process. To address this limitation, we aim at developing GaN μ LEDs grown on sapphire using van der Waals epitaxy with h-BN. It has been recently demonstrated that a GaN LED structure grown on a few 2D layers of h-BN, grown on sapphire, could be easily removed "at will" from the sapphire wafer due to the weaker van der Waals bonds at the 2D layer interface [2]. Another possibility to fabricate the flexible μ LEDs would be to start from a Si(111) growth substrate and then use silicon-processing techniques to remove the substrate after having reported the LEDs to a flexible host substrate.

As for the μ LED flexibility assessment, the main challenge is to develop a set-up allowing the reproducible characterization of the LED opto-electronic properties with a variable ROC in the millimetric range. In the literature, two different methods were found: the sample is either stuck to a cylinder [3] or constrained laterally [4]. In one case, it is hard to change the ROC; in the other, obtaining the ROC at a fixed lateral constraint can be complicated. In both cases, the sample height may vary between ROC changes and measurements, if the sample is removed, making optical measurement difficult. We have developed a characterization bench to avoid these issues and to ensure a fixed height for variable ROCs down to 3 mm (fig. 1) With this, the IV characteristic of the LEDs, their electroluminescence (EL) spectrum, or optical power can be measured repeatably.

We will present the thin-film μ LED fabrication and their first opto-electronic characterization down to millimetric ROC to assess their advantage compared to the standard "thick" LEDs.

Acknowledgment: Alexis POIZAT (C2N-CNRS) is gratefully acknowledged for his support in the characterization bench design and fabrication. This work was partially supported by LEDFLEX project in the FRAME of ANR Labex GaNext.




Figure 1. Representation of the measurement setup with (a) a side view of the setup to show the position of the different detectors while making measurements, all of them being removable at will and (b) the principle of bending the system at the center of the setup, allowing a fixed height of the LED for variable ROC from 10-mm to 3-mm (the position of the sample shown in red).

- [1] C. Göbner et al., J. Phys. D: Appl. Phys., 47, 205401 (2014).
- [2] T. Ayari et al., Adv. Mater. Technol., 4, 1900164 (2019).
- [3] G. Tabares et al., IEEE Photon. Technol. Lett., vol. 28, no. 15, pp. 1661-1664 (2016).
- [4] H.-Y. Kuo et al., IEEE Photon. Technol. Lett., vol. 20, no. 7, pp. 523-525 (2008).