



HAL
open science

Automatic detection of river bankfull parameters from high density lidar data

Alexandre Rétat, Nathalie Thommeret, Frédéric Gob, Thomas Depret, Jean-Stéphane Bailly, Laurent Lespez, Karl Kreutzenberger

► To cite this version:

Alexandre Rétat, Nathalie Thommeret, Frédéric Gob, Thomas Depret, Jean-Stéphane Bailly, et al.. Automatic detection of river bankfull parameters from high density lidar data. EGU General Assembly 2024, European Geoscience Union, Apr 2024, Vienna, Austria. 10.5194/egusphere-egu24-21396 . hal-04698434

HAL Id: hal-04698434

<https://hal.science/hal-04698434v1>

Submitted on 16 Sep 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Automatic detection of river bankfull parameters from high density lidar data

Alexandre RÉTAT¹, Nathalie THOMMERET², Frédéric GOB³, Thomas DEPRET¹, Jean-Stéphane BAILLY⁴, Laurent LESPEZ², Karl KREUTZENBERGER⁵

¹ CNRS UMR 8591, Laboratoire de Géographie Physique

² Université Paris-Est Créteil, Laboratoire de Géographie Physique (UMR 8591)

³ Université Paris 1 Panthéon-Sorbonne, Laboratoire de Géographie Physique (UMR 8591)

⁴ LISAH, Université Montpellier, AgrosParisTech, INRAE, Institut Agro, IRD, Montpellier, France

⁵ Office français de la biodiversité

alexandre.retat@cnrs.fr ; nathalie.thommeret@u-pec.fr ; frederic.gob@univ-paris1.fr ;

thomas.depret@cnrs.fr ; bailly@agroparistech.fr ; laurent.lespez@u-pec.fr ;

karl.kreutzenberger@ofb.gouv.fr

The European Water Framework Directive (WFD), adopted in 2000, set out requirements for a better understanding of aquatic environments and ecosystems. In 2006, following the transposition of the WFD into French law (LEMA), France began work on a field protocol for the geomorphological characterization of watercourses, as part of a partnership between the Centre National de la Recherche Scientifique (CNRS) and the Office Français de la Biodiversité (OFB). This protocol, known as "Carhyce" (For « River Hydromorphological Characterisation »), has been tested, strengthened and approved over the last 15 years at more than 2500 reaches. It consists of collecting standardised qualitative and quantitative data in the field, essential for the characterisation of a watercourse: channel geometry, substrate, riparian vegetation... However, certain rivers that are difficult to survey (too deep or too wide) pose problems for data collection.

To address these issues, and to extend the analysis to a wider scale (full river section), using remote sensing, and in particular LiDAR data, was considered. The major advantages of LiDAR over passive optical sensors are better geometric accuracy and especially under vegetation. For a long time, LiDAR data rarely exists at national scale with data density similar to passive imagery. Today, the French LiDAR HD dataset (10 pulses per meter square) program run by the French mapping agency offers an unprecedented amount of data at this scale. Thanks to them, a national 3D coverage of the ground can be used, and numerous geomorphological measurements can be carried out on a more or less large scale. This is the case for hydromorphological parameters such as water level and width.

The aim of this study is therefore to use this high-density lidar to automatically determine the hydromorphological parameters sought in the Carhyce protocol. In particular, we have developed a lidar-based algorithm to reconstruct the topography from point cloud and automatically identify the bankfull level at reach scale. Designed to be applicable to every French river, the method must be robust to all river features such as longitudinal slope, width, sinuosity, multi-channel etc... For validation purposes, the bankfull geometry calculated by the algorithm has been compared with field measurements at some twenty Carhyce stations across France. To determine the test stations, we looked for the diversity of situations in terms of river characteristics describe above to observed the influence of this features on the results.

- Preference : oral presentation
- I intend to present my abstract on-site in Vienna
- Billing address : Laboratoire de Géographie Physique, 2 rue Henri Dunant, 94320 Thiais