



HAL
open science

Direct recycling of lithium-ion batteries positive electrodes production scraps, an innovative process assisted by supercritical CO₂

Gilles Philippot, Neil Hayagan, François Rabuel, Laurence Croguennec, Cyril Aymonier, Mathieu Morcrette, Rémi Dedryvère, Jacob Olchowka

► To cite this version:

Gilles Philippot, Neil Hayagan, François Rabuel, Laurence Croguennec, Cyril Aymonier, et al.. Direct recycling of lithium-ion batteries positive electrodes production scraps, an innovative process assisted by supercritical CO₂. 8th International Solvothermal Hydrothermal Association Conference - ISHA 2023, ISHA, Sep 2023, Valladolid, Spain. hal-04722149

HAL Id: hal-04722149

<https://hal.science/hal-04722149v1>

Submitted on 4 Oct 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

TUESDAY – SEPTEMBER 12th, 2023

Room Rey Felipe II - Applications

17:00 - 17:15 ORAL PRESENTATION 81705.

Direct recycling of lithium-ion batteries positive electrodes production scraps, an innovative process assisted by supercritical CO₂**N. Hayagan^{1,4}, F. Rabuel², L. Croguennec^{1,4}, C. Aymonier^{1,4}, M. Morcrette^{2,3}, R. Dedryvère^{3,4}, J. Olchowka^{1,4}, and G. Philippot^{1,4}**¹Université de Bordeaux, CNRS, Bordeaux INP, ICMCB, UMR 5026, F-33600 Pessac, France²Laboratoire de Réactivité et Chimie des Solides, Université de Picardie Jules Verne, Hub de l'énergie, Amiens, France³IPREM, CNRS, Univ. Pau & Pays Adour, E2S UPPA, 64000, Pau, France⁴Réseau sur le Stockage Electrochimique de l'Energie (RS2E) Hub de l'Energie, Amiens, FranceCorresponding author email: gilles.philippot@icmcb.cnrs.fr

The ecological transition is at the center of our daily life and the issue of energy production and its storage are now the focus of many research projects. With the increasing electrification of our everyday life devices, in particular with the rise of electric vehicles, the question of the batteries' end-of-life, particularly the lithium-ion batteries (LIBs), becomes a real challenge. Indeed, the building elements of this type of batteries, such as copper, aluminum but especially cobalt or nickel are not only expensive, but also present in very localized areas and in limited quantities on earth. It is therefore essential to implement recycling processes for these batteries to reclaim these metals and meet the growing demand of the market. Recycling techniques such as pyro- and hydrometallurgy are already employed to recover elements of economic interest. However, these destructive processes have limitations: i) the purity of the recovered elements is not high enough to reuse them to make new batteries, and also, ii) they require either high-energy inputs or massive use of acids. On the other hand, the direct recycling strategy, which aims to separate the different parts of a battery and recycle them independently, therefore, becomes the most credible alternative to achieve this goal.

In this communication, we will focus on the use of supercritical carbon dioxide (scCO₂) process for the direct recycling of LIBs positive electrodes production scraps. Indeed, production scraps can represent from 5 up to 30 wt.% of the electrode production. With the increased LIBs production rate, their recovery becomes a priority.^{1,2} The objective aims to separate all the electrode components while preserving their properties and integrity. For this, we use a technology based on supercritical CO₂. We will first highlight the influence of several optimized parameters including the temperature, time, co-solvent ratio and dosages to successfully delaminate 100% of the active material. Multiple characterization techniques will then be combined to qualify the structure, chemical composition and physical properties of the recycled active material LiNi_{0.6}Mn_{0.2}Co_{0.2}O₂ (NMC622) and current collector (Al foil). Lastly, the performance of the recycled NMC622 electrode material in new batteries will be highlighted.

Keywords: Li-ion battery, direct recycling, supercritical CO₂, production scraps

¹Schmuck, R., Wagner, R., Hörpel, G., Placke, T., & Winter, M. (2018). Performance and cost of materials for lithium-based rechargeable automotive batteries. *Nature Energy*, 3(4), 267-278.2

²Aymonier, C., Philippot, G., Erriguible, A., & Marre, S. (2018). Materials Processing and Recycling with Near- and Supercritical CO₂-based Solvents. In *Supercritical and Other High-pressure Solvent Systems* (pp. 304-339).