

Enhancing biomedical metal implants with synthetic peptides: improved bioactivity and in vitro safety

Adrien Mourgout, F. Arjmand, E. Groult, Olivier Monasson, S. Ammar, A.

Hattal, M. Djemai, G. Dirras, M. Boissiere, E. Peroni

To cite this version:

Adrien Mourgout, F. Arjmand, E. Groult, Olivier Monasson, S. Ammar, et al.. Enhancing biomedical metal implants with synthetic peptides: improved bioactivity and in vitro safety. European Peptide symposium 2024, Aug 2024, Florence, Italy. hal-04727725

HAL Id: hal-04727725 <https://hal.science/hal-04727725v1>

Submitted on 9 Oct 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Modern solutions in biomedical engineering imply innovative strategies at the frontier between chemistry, material science, and biology to develop biofunctionalized substitutes able to restore, maintain or improve tissue integrity. These substitutes are materials that are designed to positively interact with a living biological system for a therapeutic purpose while introducing mechanical, physical and/or chemical functions to the body. Commonly speaking, they are defined as biomaterials [1].

It is of paramount importance to enhance the bioactivity of materials scaffolds by combining

biomaterials with biological cues to drive a particular tissue function [2]. In practice, biocompatibility can be achieved by first choosing bioinert solids and then coating them with bioactive molecules.

enabling to address two or more biological effects. In this way, multifunctionality may be installed on biomaterials without using proteins.

Interestingly, different biological effects may be targeted when implanting a biomaterial by combining peptides from diverse nature. In the field of bone regeneration, the use of BMP-2 derived peptides is of crucial importance to promote osteodifferentiation of mesenchymal stem cells (MSCs) and guide bone formation [3].

> [1]. Will Williams, D.F. Biomaterials 2009, 30, 5897-5909. [2] Förster Y, Rentsch C, Schneiders W, et al. Biomatter. 2012; 2(3): 149- 157. [3] Mas-Moruno C. et al. ACS Appl. Mater. Interfaces 2014, 6, 9, 6525-36. [4] Willi **2011**;32(18):4195-4197. [5]. A. Saito, et al, *J. Biomed. Mater. Res. A* **2005**, 72 77–82 [6] A.K. Jha, et al *PLoS One* **2014**, 9, e98640

Peptides are easily modifiable for functionalization of surfaces, reaching, in some cases, similar biological activity to the total protein for a specific target [4]. A simple though useful approach to improve the

performance of peptidic molecules is to combine peptide sequences with synergistic or complementary effects,

The introduction of an additional lysine (Lys⁹³) in the BPM-2(73-92) fragment allows the introduction of the fluorescent probe in C terminus by coupling of the carboxylic moiety of TAMRA to the amino function of the side chain through the formation of an amide bond. For this purpose, we chose 4-methyltrityl group (Mtt) which is removed in very weak acid conditions. In order to increase the peptide solubility and to facilitate the on resin TAMRA coupling, a PEG9 linker has been introduced in C terminus.

Polyethylene glycol-based spacer (PEG), containing 9-atoms chain (Fmoc-8-amino-3,6-dioxaoctanoic acid) (2.5 equiv) and TAMRA were coupled in C and N terminal position of peptide P2 and P3, respectively, as follows: Fmoc-8-amino-3,6-dioxaoctanoic acid (2.5 equiv) and TAMRA (2,5 equiv), TBTU (2,5 equiv) and DIPEA (3,5 equiv) were dissolved in DMF with a final dilution of 1 mL DMF for 100 mg of resin. Couplings were performed 45 min at room temperature

Proadhesion and osteogenic peptides synthesis for multifunctional alloy coating

References:

¹Université Sorbonne Paris Nord, LSPM, CNRS-UPR 3408, 93430 Villetaneuse, France; ²Université Paris Cité, CNRS, ITODYS (UMR 7086), 75205 Paris; *France; ³CY Cergy Paris Université, CNRS, BioCIS, 95000, Cergy Pontoise, France; ⁴CY Cergy Paris Université, ERRMECe, 95000, Cergy Pontoise, France. ⁵*Z3DLAB, SAS, 2 Chemin de Coye, 95270-Chaumontel, France

Synthetic conditions:

In vitro cytotoxicity evaluation of biofunctionalized alloy surfaces and assessment of their biological performances toward osseointegration

Peptide assembly was performed by repeating the standard MW-SPPS coupling cycle for each amino acid, using Fmoc-protected amino acids (5 equiv, 0.2 M in DMF), OxymaPure® (5 equiv, 1 M in DMF), and DIC (5 equiv, 0.5 M in DMF).

Cleavage from the resin and side-chain deprotection were achieved by treatment with a TFA/TIS/water solution (95 : 2.5 : 2.5 v/v/v, 1ml/100mg of resin-bound peptide). Lyophilized crude peptides were purified by semi-preparative Waters RP-HPLC (Milford, MA, USA) on a Phenomenex Jupiter C18 (10 μm, 250mm× 10mm) column at 4 ml/min. The solvent systems used were 0.1% TFA in H₂O (A) and 0 TFA in CH_3CN (B), and the gradients used are presented in Table 1. All peptides were obtained with a purity >95%. Characterization of the peptides was performed by analytical RP-UPLC ESI-MS (Waters Acquity UPLC coupled to a Waters 3100 ESI-SQD MS) supplied with an Aeris Widepore C1 200A (3.6 µm 250 × 4.6 mm) column at 25 °C at 0.6 mL/ with solvent systems A (0.1% TFA in H₂O) and B (0.1% TFA in CH₃CN). Data were acquired and processed using MassLynx software (Waters, Milford, MA, USA).

Peptide immobilization protocole

Enhancing biomedical metal implants with synthetic peptides: improved bioactivity and in vitro safety

Morphology of cell incubated with peptide grafted alloys Formulated HEAs with peptide 24h **Formulated HEAs with peptide 72h** Pre-alloyed HEAs with peptide 24h

Elisa.peroni@cyu.fr

Our goal is to develop a new family of

This work was funded by: CY Initiative (grant "Investissements d'avenir" ANR-16-IDEX-0008) ANR CoCoA-Bio (ANR-20-CE08-0032-01) CY Fondation "Chaire RETIS"

Epifluorescence Microscopy images

Biological data

BMP2 like peptide bioactivity \rightarrow **change in C2C12 morphology (21 days)**

Assessment of the safety and biological activity of the BMP2 like peptide in cultured cell line models

Fluorescent Probe *5(6)-Carboxytetramethylrhodamine (TAMRA).*

λex = 555 nm et λem = 580 nm

High Entropy Alloys (HEAs) are a novel class of materials known for their exceptional mechanical properties and corrosion resistance. These alloys generally are composed of multiple principal elements in equimolar or non/near-equimolar ratios, with elemental concentrations ranging from 5% to 35%. Among these HEAs have been specifically developed for biomedical applications. Notable examples include equiatomic and non-equiatomic alloys like TiZrNbTaMo, which have attracted significant attention as a new generation of biomaterials. However the integration of such materials as implants into bone is only adressed as a passive process. In such an approach, the fixation is mainly mechanical, with anchorage failure. Therefore, the increase of

TODYS

the biointegration of the implant and the bone tissue is becoming a research hotspot. Such an active integration is usually achieved by

grafting bioactive molecules on the surface of the metal implant.

Mtt deprotection

After the Lys(Mtt) loading, the synthesis was carried out with MW-assisted SPPS strategy. The following peptidil-resin was then washed several times with DCM and dried under vacuum: **K**(Boc)**IPK**(Boc)**AS**(tBu)**S**(tBu)**VPT**(tBu)**E**(tBu)**LS**(tBu)**AIS**(tBu)**T**(tBu)**LY**(tBu)**LK**(Mtt)-PEG⁹ ---*RinkResin*

A satisfactory deprotection of Lys(Mtt) was accomplished in just three cycles of 1% TFA in DCM. The reaction was monitored by RP-HPLC from collected solutions.

Epifluorescence Microscopy images of peptide grafted HEAs

CultureMedium with peptide BMP2 -like

AFM 3D images of grafted grafted HEAs

Before Etching **After Etching After Etching**

