



**HAL**  
open science

## On the interaction between a rising bubble and a settling particle

Abdullah Abdal, Lyes Kahouadji, Seungwon Shin, Jalel Chergui, Damir Juric, Colm-Cille P. Caulfield, Omar Matar

► **To cite this version:**

Abdullah Abdal, Lyes Kahouadji, Seungwon Shin, Jalel Chergui, Damir Juric, et al.. On the interaction between a rising bubble and a settling particle. *Journal of Fluid Mechanics*, In press, 10.1017/jfm.2024.686 . hal-04739732

**HAL Id: hal-04739732**

**<https://hal.science/hal-04739732v1>**

Submitted on 16 Oct 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# On the interaction between a rising bubble and a settling particle

A. M. Abdal<sup>1,2</sup>, L. Kahouadji<sup>1</sup>, S. Shin<sup>3</sup>, J. Chergui<sup>4</sup>, D. Juric<sup>4,5</sup>,  
C.-C. P. Caulfield<sup>5</sup>, and O. K. Matar<sup>1†</sup>

<sup>1</sup>Department of Chemical Engineering, Imperial College London, South Kensington Campus, London SW7 2AZ, United Kingdom

<sup>2</sup>Department of Environmental and Sustainability Engineering, College of Engineering and Energy, Abdullah Al Salem University, 12037, Kuwait City, Kuwait

<sup>3</sup>Department of Mechanical and System Design Engineering, Hongik University, South Korea

<sup>4</sup>Université Paris Saclay, Centre National de la Recherche Scientifique (CNRS), Laboratoire Interdisciplinaire des Sciences du Numérique (LISN), 91400 Orsay, France

<sup>5</sup>Department of Applied Mathematics and Theoretical Physics, Centre for Mathematical Sciences, University of Cambridge, Wilberforce Road, Cambridge CB3 0WA, United Kingdom

(Received xx; revised xx; accepted xx)

This study investigates the interaction between a freely-rising, deformable bubble and a freely-settling particle of the same size due to gravity. Initially, an in-line configuration is considered while varying the Bond, Galilei and Archimedes numbers. The study shows that as the bubble and particle approach each other, a liquid film forms between them that undergoes drainage. The formation of the liquid film leads to dissipation of kinetic energy, and for sufficiently large bubble velocities, particle flotation takes place. Increasing the Bond number causes the bubble to deform more severely, which may allow the particle to pass through the bubble as it ruptures. This work also considers an offset configuration, which shows that the bubble slides away from the particle, affecting its settling trajectory.

## 1. Introduction

The transport and dynamics of rigid or deformable particles and their interaction with surfaces are of considerable importance in various scientific and industrial fields due to their potential for efficient, and sustainable applications. Understanding these interactions is crucial for optimising processes ranging from wastewater treatment to mineral beneficiation and food processing. In many engineering applications, a deformable surface, or interface separating two fluids, affects the motion of rigid or deformable bodies. Furthermore, in oceanography, particles and marine snow settle in a background fluid that consists of large density gradients caused by variations in salinity and temperature levels, which may greatly affect their fate. Bubbles rising in the ocean may also interact with sedimenting particles, which may play a role in their transport (Masry *et al.* 2021). Comprehensive reviews have been carried out on the motion in viscosity and/or density stratified fluids by (Govindarajan & Sahu 2014; Ardekani *et al.* 2017; Magnaudet & Mercier 2020; More & Ardekani 2023).

At the core of these interactions is the dynamic behaviour of bubbles. When a bubble impacts and interacts with a horizontal (Klaseboer *et al.* 2014; Manica *et al.* 2015, 2016) or curved (Basařová *et al.* 2019; Esmaili *et al.* 2019) solid surface, a hydrodynamic dimple (Ascoli *et al.* 1990) might form on the surface of the bubble closest to the solid boundary.

† Email address for correspondence: o.matar@imperial.ac.uk

If the approach velocity of the interaction is sufficiently high, the bubble may rebound, or bounce, after colliding with the solid surface (Chan *et al.* 2011; Zawala *et al.* 2007; Zawala & Dabros 2013). If the approach velocity is low, a trapped liquid film in the gap region between the bubble and the solid surface will start to drain. Klaseboer *et al.* (2000) and Chan *et al.* (2011) have studied the film drainage and coalescence of bubbles and drops, which present further complexities. The deformation of these bodies can be characterised across six orders of magnitude in length scales, which presents difficulties when studying the dynamic nature of the interaction both experimentally and numerically. Moreover, as a bubble impacts a solid wall, it exerts forces that can dislodge contaminants or biofilms (Gómez-Suárez *et al.* 2001; Sharma *et al.* 2005*a,b*; Parini & Pitt 2006; Esmaili *et al.* 2019). Menesses *et al.* (2017) have shown that a continuous stream of single bubbles can effectively prevent biofouling by generating consistent shear stress. This principle extends beyond cleaning, influencing the behavior of bubbles in different mediums and applications. The adhesion behaviour of bubbles or droplets with solids is influenced by the properties of the deformable interface and the surrounding fluid (Danov *et al.* 2016), the presence of contaminants (Basarova *et al.* 2018; Legawiec *et al.* 2023), and the surface characteristics of the solid, such as its geometry or wettability (Krasowska *et al.* 2009). As a bubble adheres to a solid surface, it forms a three-phase contact line, which is the interface where the bubble, solid, and liquid meet. The dynamics and stability of the contact line are crucial in understanding how bubbles interact with solid surfaces.

In the context of mineral beneficiation, froth flotation relies on bubbles to separate valuable minerals from waste material. The process of flotation depends heavily on the characteristics of the separated particles, and the bubbles. Specifically, the surface wettability of the solid particles is crucial for allowing the bubbles to selectively separate hydrophobic from hydrophilic particles (Xie *et al.* 2021), and the bubbles must be appropriately sized to enhance the probability of collision between the bubbles and the particles (Yoon & Luttrell 1989). The main causes behind the detachment of particles from bubbles during flotation separation systems were summarised by Klassen & Mokrousov (1963) and Wang *et al.* (2023). These include the sliding of the particle on the bubble surface, the overall hydrodynamic behaviour of the bubble, such as its lateral migration or deformation, or the collision of the aggregate with a solid wall. When a bubble/particle aggregate collides with a solid horizontal wall, Wang *et al.* (2023) have found that the detachment of the particle is dependent on the inclination angle of the major axis of the bubble with the solid wall during the collision. Comprehensive reviews of recent advancements in understanding the hydrodynamics and surface interactions in froth flotation systems can be found in Wang & Liu (2021) and Xie *et al.* (2021).

In liquid-solid suspensions, the behavior of bubbles is equally important. Bubbles interact with the solid particles, affecting their rise velocity and overall dynamics. Hooshyar *et al.* (2013) have considered the interaction between a rising bubble and a neutrally buoyant particle suspension. The particles were characterised based on their diameter, and when the size of the particles is sufficiently small, the bubble rises without collision. The work has shown that as the rising bubble interacts with larger particles, the bubble's rise velocity decreases, its surface deforms, and it imparts momentum on the surrounding particles. The bubble will then continue to rise until it interacts with another particle, repeating the cycle of the interaction.

Many experimental (Clift *et al.* 1978; Bhaga & Weber 1981) and computational (Sussman & Puckett 2000; Dijkhuizen *et al.* 2010) studies have considered the hydrodynamic behaviour of particles or bubbles settling or rising in a quiescent background fluid. At small Reynolds number,  $Re = D_p U_t \rho_l / \mu_l$ , the particle terminal speed is  $U_t = \frac{2}{9}(\rho_p - \rho_l)gR^2/\mu_l$  where  $\rho_p$  is the particle density,  $R = D_p/2$  is the particle

(bubble) radius,  $g$  is the gravitational acceleration, and  $\rho_l$  and  $\mu_l$  are the fluid density and viscosity, respectively. At larger  $Re$ , (Mordant & Pinton 2000; Ten Cate *et al.* 2002) considered the inertial regime, where  $1.5 < Re < 7700$ , such that  $U_t$  is unknown *a priori*. An alternative way of characterising the particle motion in a homogeneous fluid is through the Archimedes number,  $Ar = \rho_l(\zeta_p g)^{1/2} R^{3/2} / \mu_l$ , where  $\zeta_p = \rho_p - \rho_l / \rho_l$ , which corresponds to a particle Reynolds number based on a gravitational velocity scale (Magnaudet & Mercier 2020). Tripathi *et al.* (2015) recently conducted three-dimensional direct numerical simulations (DNS) of a rising bubble in a quiescent, Newtonian fluid. The study found that the rising bubble has five distinct regimes, governed by two non-dimensional parameters, which are the bubble Galilei,  $Ga = \rho_l g^{1/2} R^{3/2} / \mu_l$ , and Bond,  $Bo = \rho_l g R^2 / \gamma$ , numbers, where  $\gamma$  is the surface tension. The computational study was in wide agreement with the experimental work of Bhaga & Weber (1981), and the five distinct regimes are (1) axisymmetric bubble geometry at small  $Ga$  and small  $Bo$ , (2) skirted spherical cap bubble at small  $Ga$  and large  $Bo$ , (3) a spiraling bubble at large  $Ga$  and small  $Bo$ , and (4) peripheral or (5) central breakup at large  $Ga$  and  $Bo$ . The bubble dynamics can be further classified based on surface mobility; mobile bubbles with low contamination, by the presence of surfactants for example, achieve higher terminal velocities, while immobile, contaminated bubbles rise more slowly due to the absence of tangential velocity (Esmaili *et al.* 2019).

The aim of this paper is to investigate the interaction between a freely rising, deformable bubble and a freely settling spherical particle in a quiescent, Newtonian fluid. This study examines the impact of several parameters on the interaction behavior, including the Galilei number, the Bond number, the density contrast between the solid and the fluid ( $\zeta_p$ ), the ratio of the particle radius to the bubble radius ( $\Omega$ ), and the surface wettability characteristics of the particle. The paper implements a three-dimensional particle-resolved DNS using the Level Contour Reconstruction Method (LCRM), which is a hybrid level-set/front-tracking method to accurately capture the motion and the interaction of the bubble and the particle. The outline of the paper is as follows: Section 2 contains the methodology and the numerical method; Section 3 provides a discussion of the results; and Section 4 contains the conclusions and future directions.

## 2. Methodology

This section contains the problem formulation, governing equations, and the numerical method used in this paper. We perform highly-resolved numerical simulations of the incompressible Navier-Stokes equations in a three-dimensional cubical Cartesian domain with  $L_x = L_y = L_z = 16R$ , as shown in Figure 1. The computational domain is divided into parallel subdomains, which are each uniformly discretised by a  $64^3$  finite-difference mesh. The equations governing Newtonian and incompressible two-phase flows correspond to mass and momentum conservation respectively expressed in the present work using a single-field formulation:

$$\nabla \cdot \mathbf{u} = 0, \quad (2.1)$$

$$\rho \left( \frac{\partial \mathbf{u}}{\partial t} + \mathbf{u} \cdot \nabla \mathbf{u} \right) = -\nabla p + \rho \mathbf{g} + \nabla \cdot \mu (\nabla \mathbf{u} + \nabla \mathbf{u}^T) + \mathbf{F} + \mathbf{F}_{FSI}, \quad (2.2)$$

where  $\mathbf{u}$ ,  $\rho$ ,  $p$ ,  $\mu$ ,  $\mathbf{g}$ ,  $\mathbf{F}$ , and  $\mathbf{F}_{FSI}$  denote the velocity, density, pressure, viscosity, gravitational acceleration, the local surface tension force at the interface, and the direct forcing term for Fluid-Structure Interaction, respectively. Here,  $\mathbf{F}_{FSI}$  can be computed






Figure 1: (a) The three-dimensional Cartesian cubic domain with a size of  $16R \times 16R \times 16R$ , showing the subdomain decomposition and the initial problem setup; (b) the initial separation distance between the particle and the bubble is shown.

based on the work of Fadlun *et al.* (2000) as:

$$\mathbf{F}_{FSI} = \rho \left( \frac{\mathbf{u}_s - \mathbf{u}}{\Delta t} \right), \quad (2.3)$$

where  $\mathbf{u}_s$  is the velocity of the immersed solid boundary. Direct forcing can be considered as imposing the particle velocity directly on the boundary which is equivalent to applying  $\mathbf{F}_{FSI}$  inside the solid structure (Pathak & Raessi 2016). (Feedback forcing (Goldstein *et al.* 1993) to obtain the necessary force to satisfy the desired velocity of the particle is an alternative approach, however, direct forcing is found to be faster and more efficient (Yang & Stern 2012; Pathak & Raessi 2016).)

We employ a hybrid formulation for the surface tension force,  $\mathbf{F}$  (Shin *et al.* 2005, 2017).

$$\mathbf{F} = \gamma \kappa_{H_f} \mathcal{H}_f. \quad (2.4)$$

Here  $\gamma$  is the surface tension, considered constant,  $\mathcal{H}_f$  is the Heaviside function, and  $\kappa_{H_f}$  is twice the mean interface curvature calculated on the Eulerian grid using the following equations,

$$\kappa_{H_f} = \frac{\mathbf{F}_L \cdot \mathbf{N}}{\mathbf{N} \cdot \mathbf{N}}, \quad (2.5)$$

$$\mathbf{F}_L = \int_{\Gamma(t)} \kappa_f \mathbf{n}_f \delta_f(\mathbf{x} - \mathbf{x}_f) dS, \quad (2.6)$$

$$\mathbf{N} = \int_{\Gamma(t)} \mathbf{n}_f \delta_f(\mathbf{x} - \mathbf{x}_f) dS. \quad (2.7)$$

In equations 2.6-2.7,  $\mathbf{x}_f$  is a parameterisation of the interface,  $\Gamma(t)$ , and  $\delta_f(\mathbf{x} - \mathbf{x}_f)$  is

a three-dimensional Dirac delta function that is non-zero only at the interface,  $\mathbf{x} = \mathbf{x}_f$ .  $\mathbf{n}_f$  is the unit normal vector to the interface, where the interface has an area element,  $dS$ .  $\kappa_f$  is again twice the mean interface curvature, however, it is now obtained from the Lagrangian interface structure (Shin *et al.* 2017; Kahouadji *et al.* 2018). The geometric information in  $\mathbf{N}$ , such as the unit normal  $\mathbf{n}_f$  and the interface infinitesimal area  $dS$ , are directly computed from the Lagrangian interface, then distributed onto the Eulerian grid using a discrete delta function and the Immersed Boundary Method developed by Peskin (1977). The Lagrangian elements of the interface are advected by integrating the following equation using a second-order Runge-Kutta method:

$$\frac{d\mathbf{x}_f}{dt} = \mathbf{V}; \quad (2.8)$$

here, the interface velocity  $\mathbf{V}$  is interpolated from the Eulerian velocity. Further details on calculating the force, constructing the function field  $\mathbf{N}$  and the Heaviside function, and advecting the interface can be found in (Shin *et al.* 2005; Shin & Juric 2007; Shin 2007; Shin & Juric 2009*a,b*; Shin *et al.* 2011).

The particle's motion and interaction with the fluid are modeled using a fictitious domain method, such that the Navier-Stokes equations are applied to the entire flow field. Tracking the solid body's motion is achieved by introducing a distance function  $\phi_s$ . At the start of the simulation,  $\phi_s^0$  is calculated at the cell center of the Eulerian grid  $(x_i^0, y_i^0, z_i^0)$  to create the solid volume, which is then updated to calculate  $\phi_s^n$  at  $(x_i^n, y_i^n, z_i^n)$  by tracking the solid's center position and rotation over time. The solid object's movement is updated by its momentum averaged translational and rotational velocities, which are calculated in equations 2.9 and 2.10.

$$m_p \mathbf{u}_p = \int_{\mathcal{V}} \rho \mathbf{u} d\mathcal{V}, \quad (2.9)$$

$$I_p \boldsymbol{\omega}_p = \int_{\mathcal{V}} \mathbf{r} \times \rho \mathbf{u} d\mathcal{V}, \quad (2.10)$$

where  $m_p$  is the mass of the solid,  $\mathbf{u}_p$  is its translational velocity,  $\mathcal{V}$  is the solid volume,  $\mathbf{r}$  is the radial vector from its center,  $I_p$  is the moment of inertia, and  $\boldsymbol{\omega}_p$  is the rotational velocity. The moment of inertia can be calculated using equation 2.11,

$$I_p = \int_{\mathcal{V}} \rho_p |(\mathbf{r} \cdot \mathbf{r})I - \mathbf{r} \otimes \mathbf{r}| d\mathcal{V}, \quad (2.11)$$

and the position of the solid can be tracked by the following velocity field:

$$\mathbf{u}_s(x, y, z) = \mathbf{u}_p + \boldsymbol{\omega}_p \times \mathbf{r}. \quad (2.12)$$

Utilising equation 2.12, the updated solid distance function can be calculated at the current position  $(x_i^n, y_i^n, z_i^n)$  by tracing back to the original position  $(x_i^0, y_i^0, z_i^0)$  using equation 2.13.

$$\phi_s(x^n, y^n, z^n) = \phi_s(x^n - u_s \Delta t, y^n - v_s \Delta t, z^n - w_s \Delta t) = \phi_s(x^0, y^0, z^0). \quad (2.13)$$

Rigid body constraints are applied to the solid volume for the momentum-averaged translational and rotational velocities, and an additional high viscosity, i.e. 500 times that of water, coefficient is utilised for the solid volume.

Within the single-fluid formulation, the material properties in the domain are calcu-

lated as follows

$$\rho(\mathbf{x}, t) = [\rho_b + (\rho_l - \rho_b)\mathcal{H}_f(\mathbf{x}, t)] \mathcal{H}_s(\mathbf{x}, t) + \rho_p(1 - \mathcal{H}_s(\mathbf{x}, t)), \quad (2.14)$$

$$\mu(\mathbf{x}, t) = [\mu_b + (\mu_l - \mu_b)\mathcal{H}_f(\mathbf{x}, t)] \mathcal{H}_s(\mathbf{x}, t) + \mu_p(1 - \mathcal{H}_s(\mathbf{x}, t)), \quad (2.15)$$

where the subscripts ( $l, b, p$ ) denote the background liquid, the bubble, and the solid phase, respectively. A smoothed three-dimensional Heaviside function  $\mathcal{H}_f(\mathbf{x}, t)$  for the fluid phases is defined as zero in the bubble phase, and unity in the background liquid phase. A similar approach has been used for defining the properties of the solid particle,  $\mathcal{H}_s(\mathbf{x}, t)$  which is considered as zero in the solid phase and unity for both fluid phases (the bubble and the surrounding liquid). The sharp transition between the two phases is resolved numerically with a steep, yet smooth transition across three to four grid cells (Shin *et al.* 2017; Kahouadji *et al.* 2018).

To non-dimensionalise the governing equations, we introduce the following scaling:

$$(x, y, z) = R(\tilde{x}, \tilde{y}, \tilde{z}), \quad \mathbf{u} = \sqrt{gR} \tilde{\mathbf{u}}, \quad t = \left( \frac{R}{\sqrt{gR}} \right) \tilde{t},$$

$$p = (\rho_l g R) \tilde{p}, \quad \mu = \mu_l \tilde{\mu}, \quad \rho = \rho_l \tilde{\rho}, \quad (2.16)$$

where the tildes, introduced temporarily, designate dimensionless variables. After dropping the tildes, the non-dimensional governing equations read:

$$\nabla \cdot \mathbf{u} = 0, \quad (2.17)$$

$$\rho \left( \frac{\partial \mathbf{u}}{\partial t} + \mathbf{u} \cdot \nabla \mathbf{u} \right) = -\nabla p - \rho \mathbf{e}_z + \frac{1}{Ga} \nabla \cdot [\mu (\nabla \mathbf{u} + \nabla \mathbf{u}^T)] + \frac{\mathbf{F}}{Bo} + \mathbf{F}_{FSI}, \quad (2.18)$$

where  $\mathbf{e}_z$  denotes the unit vector in the  $z$ -direction (see figure 1),  $Ga$  is the Galilei number and  $Bo$  is the Bond number. The non-dimensional material properties then read:

$$\rho(\mathbf{x}, t) = \left[ \frac{\rho_b}{\rho_l} + \left( 1 - \frac{\rho_b}{\rho_l} \right) \mathcal{H}_f(\mathbf{x}, t) \right] \mathcal{H}_s(\mathbf{x}, t) + \frac{\rho_p}{\rho_l} (1 - \mathcal{H}_s(\mathbf{x}, t)), \quad (2.19)$$

$$\mu(\mathbf{x}, t) = \left[ \frac{\mu_b}{\mu_l} + \left( 1 - \frac{\mu_b}{\mu_l} \right) \mathcal{H}_f(\mathbf{x}, t) \right] \mathcal{H}_s(\mathbf{x}, t) + \frac{\mu_p}{\mu_l} (1 - \mathcal{H}_s(\mathbf{x}, t)). \quad (2.20)$$

To mitigate the stress singularity at the contact line (Sui *et al.* 2014), the Generalised Navier Boundary Condition is employed in the framework of the LCRM to model the contact line motion (Yamamoto *et al.* 2013; Shin *et al.* 2018), which may be crucial for the interaction between bubbles and particles over a certain range of parameters as will be discussed in the following section. Derived from molecular dynamics simulations (Qian *et al.* 2003), the boundary condition indicates that the interaction force in a thin layer adjacent to the solid wall includes contributions from both viscous shear stress and an uncompensated Young's stress. The boundary condition thereby combines Navier slip, which relates the contact line displacement to the shear stress at the wall, with the uncompensated Young's stress. This approach models microscale slip information at the macroscale, addressing the infinite shear stress problem near the contact line observed under no-slip conditions. The non-dimensional slip velocity  $u_{cl}$  is defined as follows:

$$u_{cl} = \lambda_s \left( \frac{\partial u}{\partial n} \Big|_{wall} + \frac{\cos \theta_{cont} - \cos \theta_{ext}}{Ca \Delta x} \right), \quad (2.21)$$

where  $\lambda_s$  is the slip length, set at a quarter of the size of a grid cell in this work,  $Ca$  is the Capillary number defined as  $Ca = \mu_l \sqrt{gR} / \gamma$ ,  $\theta_{cont}$  is the apparent contact angle governed by the tangential component of the interface element  $\mathbf{t}_{cont}$ , and  $\theta_{ext}$  is the

extended contact angle (see figure 15 in Appendix B) for an extended interface inside the wall modeled by tracing a new vector  $\mathbf{t}_{\text{ext}}$  in the extended surface. The extended interface contact angle  $\theta_{\text{ext}}$  is used to account for the contact angle hysteresis, such that the hysteresis model is as follows:

$$\theta_{\text{ext}} = \begin{cases} \theta_{\text{ext}} = \theta_A & \text{if } \theta_{\text{cont}} > \theta_A, \\ \theta_{\text{ext}} = \theta_R & \text{if } \theta_{\text{cont}} < \theta_R, \\ \theta_R < \theta_{\text{ext}} < \theta_A & \text{otherwise,} \end{cases} \quad (2.22)$$

where  $\theta_A$  and  $\theta_R$  are the advancing and receding contact angles, respectively.

The numerical method involves temporally discretising Equation 2.2 into the following form

$$\frac{\mathbf{u}^{n+1} - \mathbf{u}^n}{\Delta t} = -(\mathbf{u} \cdot \nabla \mathbf{u})^n + \frac{1}{\rho^n} [\mathbf{G}^n - \nabla p], \quad (2.23)$$

where  $\mathbf{G}$  contains the gravitational, surface tension, fluid-structure interaction, and viscous forces. The momentum solver computes the velocity and pressure variables on a fixed and uniform Eulerian mesh by means of Chorin's Projection method (Chorin 1968). For spatial discretisation, the well-known staggered mesh, MAC method, is used (Harlow & Welch 1965). The non-linear term is spatially-discretised using a second-order essentially non-oscillatory (ENO) scheme (Shu & Osher 1989; Sussman *et al.* 1998), whereas the other terms are spatially-discretised using standard second-order centered differences.

The time integration of Eq.(2.23) is split into two sub-steps. An intermediate unprojected velocity,  $\mathbf{u}^*$ , is first calculated neglecting the pressure gradient:

$$\frac{\mathbf{u}^* - \mathbf{u}^n}{\Delta t} = -(\mathbf{u} \cdot \nabla \mathbf{u})^n + \frac{\mathbf{G}^n}{\rho^n}, \quad (2.24)$$

followed by the calculation of the final velocity,  $\mathbf{u}^{n+1}$ ,

$$\frac{\mathbf{u}^{n+1} - \mathbf{u}^*}{\Delta t} = -\frac{1}{\rho^n} \nabla p, \quad (2.25)$$

where  $\Delta t$  is the time-step. By enforcing the divergence-free condition on  $\mathbf{u}^{n+1}$ , the elliptic pressure Poisson equation,

$$\nabla \cdot \left( \frac{1}{\rho^n} \nabla p \right) = \frac{\nabla \cdot \mathbf{u}^*}{\Delta t}, \quad (2.26)$$

is solved using a multigrid iterative method whence  $\mathbf{u}^{n+1}$  is obtained:

$$\mathbf{u}^{n+1} = \mathbf{u}^* - \frac{\Delta t}{\rho^n} \nabla p. \quad (2.27)$$

The temporal integration scheme for all the simulations performed is based on a second-order Gear method (Tucker 2013), with implicit solution of the viscous terms of the velocity components (Kahouadji *et al.* 2018). The time-step,  $\Delta t$ , at each temporal iteration is set to satisfy the following criterion:

$$\Delta t = \min\{\Delta t_{\text{cap}}, \Delta t_{\text{CFL}}, \Delta t_{\text{int}}, \Delta t_{\text{vis}}\}, \quad (2.28)$$

where  $\Delta t_{\text{cap}}$ ,  $\Delta t_{\text{CFL}}$ ,  $\Delta t_{\text{int}}$ ,  $\Delta t_{\text{vis}}$  are the capillary, Courant-Friedrichs-Lewy (CFL), interfacial, and viscous time-steps, respectively. These time-steps are defined as follows




Figure 2: Validation of the numerical technique: Panels (a) and (b) show a comparison of our predictions with the experimental data of Kosior *et al.* (2014) for a freely-rising bubble interacting with a solid wall; (a) compares the bubble deformation as a ratio of the horizontal over the vertical bubble axis, and (b) depicts the spatio-temporal evolution of the bubble-wall collision; (c) (i)-(iii) compare the results of a rising bubble shape with the experimental results of Bhaga & Weber (1981). The top panel shows the three-dimensional illustrations of the terminal bubble shapes, and the bottom panel illustrates a slice of the interface superposed on the experimental results of Bhaga & Weber (1981). The parameter values are  $(Ga, Bo) = (2.316, 29)$ ,  $(3.094, 29)$ , and  $(4.935, 29)$  for panels (i), (ii), and (iii), respectively.

$$\begin{aligned}
 \Delta t_{cap} &\equiv \frac{1}{2} \sqrt{\frac{(\rho_b + \rho_l) \Delta x_{\min}^3}{\pi \sigma}}, & \Delta t_{CFL} &\equiv \min_j \left( \min_{\text{domain}} \left( \frac{\Delta x_j}{u_j} \right) \right), \\
 \Delta t_{int} &\equiv \min_j \left( \min_{\Gamma(t)} \left( \frac{\Delta x_j}{\|\mathbf{V}\|} \right) \right), & \Delta t_{vis} &\equiv \min \left( \frac{\rho_b}{\mu_b}, \frac{\rho_l}{\mu_l} \right) \frac{\Delta x_{\min}^2}{6},
 \end{aligned} \tag{2.29}$$

where  $\Delta x_{\min} = \min_j(\Delta x_j)$  is the minimum size  $x$  for cell  $j$ . The mesh size used in this study is  $512^3$ , which corresponds to a resolution of  $R/\Delta x = 32$ . No-penetration boundary conditions are imposed on the lateral domain walls, and no-slip, no-penetration boundary conditions are imposed on the top and bottom boundaries.

In this paper, the viscosity ratio  $\lambda = \mu_l/\mu_b = 100$ , and the density ratio  $\beta = \rho_l/\rho_b = 1000$  between the bubble and the background fluid are kept constant. The bubble and the particle radii are kept constant  $\Omega = R_b/R_p = 1$ , with an initial distance of  $6R$  from the center of the bubble to the center of the particle. The non-dimensional parameters governing the problem are  $Ar$ ,  $Bo$ , and  $Ga$ . The parameter  $Ar$ , governed by  $\zeta_p$ , is used instead of  $Re$  as the particle terminal velocity is unknown *a priori*. Unless otherwise




Figure 3: Validation of the numerical technique: comparison of the temporal evolution of the particle settling velocity obtained from our predictions and published experimental data; (a) and (b), and (c) show results for  $Re = 11.6$  and  $31.9$  (Ten Cate *et al.* 2002), and  $Re = 41$  (Mordant & Pinton 2000), respectively.

stated, the particle Archimedes number ( $Ar = 10$ ) is kept constant by setting  $\zeta_p = 1$ . This study explores the bubble parameter range of  $Bo = [0.5 - 5]$  and  $Ga = [10, 20]$ ;  $Ga$  is kept relatively low to explore the regime wherein the bubble follows a rectilinear path and interacts with the settling particle.

The numerical method utilised in this study has been extensively validated with experimental works found in the literature. In Figure 2, two different validation results are provided. Panels (a) and (b) show a bubble rising from rest in a quiescent Newtonian fluid, approaching a terminal velocity, and interacting with a solid, immobile, and impermeable wall. The results are compared to the experimental work of Kosior *et al.* (2014). The bubble terminal velocity found using this numerical method is approximately  $350 \text{ mm/s}$ , which is in excellent agreement with the terminal velocity found in the experiments. Panel (a) shows the temporal evolution of the bubble horizontal over vertical deformation, superposed with the results found in the experiments; panel (b) shows a comparison between the bubble shapes obtained from the experiments (top) and our numerical method (bottom); panel (c) shows the results of the numerical framework of a rising deformable bubble in a quiescent, Newtonian fluid compared to the experimental results of Bhaga & Weber (1981). When comparing the terminal shape of the bubble predicted by the simulations to that observed in the experiments, excellent agreement is found. Furthermore, the numerical framework was validated against the experimental works on settling solid particles (Ten Cate *et al.* 2002; Mordant & Pinton 2000), as seen in figure 3. The particle velocity profiles obtained from our numerical method are in agreement with the results found in the experiments, which ultimately inspires confidence in the accuracy and reliability of our computations. Additional validation case studies are provided in Appendix B.

### 3. Results and Discussion

The purpose of this study is to gain insight into the interaction between a freely-rising deformable bubble and a freely-settling particle. We employed a hybrid level-set/front-tracking method to capture the interaction dynamics between the bubble and the particle. Unless otherwise stated, the particle and bubble radii are kept equal,  $\Omega = 1$ , and the particle and the bubble are released in-line, with a distance of  $6R$  from their relative centres. The results in this section will investigate the effect of the bubble Bond and Galilei numbers on the interaction between a bubble and a particle. This work will also




Figure 4: Spatio-temporal evolution of the rising bubble as it approaches the particle is shown in (a) and (b). The snapshots of the bubble contours are shown for  $t = 1, 2, 3, 4$ , and the particle is only shown at  $t = 4$ . In panel (a), a scale indicating the separation distance is provided between the bubble and the particle, indicating the bubble and the particle's initial centre positions at  $z_b^0$  and  $z_p^0$ , respectively. The non-dimensional parameters are (a)  $Bo = 0.5, Ga = 10, Ar = 10$ , (b)  $Bo = 5, Ga = 10, Ar = 10$ ; panels (d), (e) and (f) show the change in energy of the system for three different  $Bo$  numbers and maintaining  $Ga = 10$ , and they are  $Bo = 0.5, Bo = 2.0$ , and  $Bo = 5.0$ , respectively. Here,  $E_m$  is the mechanical energy of the system, such that  $\Delta E_m = \Delta E_p + E_k$ . A new timescale is introduced here,  $t^*$ , which corresponds to the time for the reversal of kinetic energy due to the interaction. Panel (c) showcases the relative velocity of the bubble and the particle when varying  $Bo$  and  $Ga$  at  $t^*$ , and also showcases the difference in buoyancy force between the bubble and the particle when varying  $\zeta_p$ .

consider the effect of varying the solid to fluid density contrast  $\zeta_p$ , varying the bubble-to-particle size ratio  $\Omega$  and the initial bubble position on the interaction dynamics.

### 3.1. In-line bubble-particle interactions

The first part of the discussion will consider the interaction between a rising bubble and a settling particle with  $Ar = 10$  ( $\zeta_p = 1$ ) and  $Ga = 10$ . The bubble Bond number will be varied between 0.5 and 5. At these conditions, the bubble trajectory is expected to follow a rectilinear path as found by Zhang *et al.* (2021). Since the bubble and the particle are initially released in line, they will interact through head-on collisions. Panels (a) and (b) in figure 4 show the spatio-temporal evolution of a rising bubble interacting




Figure 5: Temporal evolution of the aspect ratio,  $\chi$ , and the distance between the bottoms of the bubble and particle,  $S$ , shown in (a) and (b), respectively, for  $Bo = 0.5$ ,  $Bo = 2.0$ , and  $Bo = 5$ , with  $Ga = 10$ , and  $\zeta_p = 1$ . Panel (c) showcases the minimum aspect ratio when varying  $Bo$  and maintaining  $Ga = 10$ , while also plotting the change in interfacial surface area at that timestep ( $t_{\chi_{min}}$ ). The film thickness profile is presented for these cases at  $t_{\chi_{min}}$  in panel (d), and the temporal evolution of the dimple radius  $R_D$  is presented in panel (e).

with a settling particle with  $Bo = 0.5$  and  $Bo = 5$ , respectively. As the bubble rises in a quiescent Newtonian fluid, several different bubble-shape regimes were found by Tripathi *et al.* (2015). Under the conditions considered in this study, the rising bubble has an axisymmetric shape, as seen in panels (a) and (b) of figure 4.

Prior to the interaction with the settling particle, the bubble is found to rise in a spherical shape when  $Bo = 0.5$ , and an ellipsoidal shape when  $Bo = 5$ . This is because when surface tension forces dominate at lower  $Bo$ , the deformation of the bubble will be weak (Qin *et al.* 2013). During the initial interaction process, the particle surface



begins to deform the bubble as seen in figure 4 (a) and (b), such that a dimple forms at the bubble apex, the part of the bubble closest to the particle; dimple formation at the bubble apex was observed for all the parameters studied in the present work, which is expected due to the increase of hydrodynamic pressure in the gap region between the bubble and the particle (Chan *et al.* 2011). The dimple can be characterised by a negative mean curvature at the centre, such that  $(\kappa_1 + \kappa_2)/2 < 0$ , indicating a concave deformation. A liquid film also begins to develop between the bubble and the particle surface, which drains due to capillary and gravitational forces, causing it to thin over time, as seen in figure 8. The liquid film drainage described in this work during the interaction between the bubble and the particle is observed until they are at most one grid cell apart. In dimensional terms, one grid cell is in the order of  $\sim O(10\mu m)$ , such that the drainage process is purely hydrodynamic and disjoining forces from the interaction can be neglected (Lee *et al.* 2023). Furthermore, the contact line dynamics between the bubble and the particle are considered for different particle wettability parameters.

Upon increasing  $Bo$  to  $Bo = 2$  or  $Bo = 5$ , the gravitational forces play a more significant role compared to the surface tension forces. As the bubble and the particle approach each other, two distinct observations can be made. Firstly, the onset of dimpling occurs at a position where the bubble and particle are further away compared to when  $Bo = 0.5$ . This can be seen in figure 4(a,b) and by comparing the bubble aspect ratio  $\chi$  and the normalised distance  $S$  between the bubble and the particle as seen in figure 5(a,b), respectively; here,  $\chi$  is defined as the ratio of the bubble's height to its width, and is a measure of the its deformation during its rise and interaction with the particle. The dimple formed at the apex is also more pronounced compared to the case when  $Bo = 0.5$ , and the deformation starts at the cap of the bubble, which leads to a change in the overall bubble shape. The increase in Bond number leads to flattening of the side of the bubble furthest away from the particle, as seen in the interaction between droplets and solid walls at low Reynolds numbers (Ascoli *et al.* 1990). It proves instructive to carry out an energy analysis of the system when considering the dynamics of the bubble-particle interactions. The four contributions to the total system energy are the potential energy  $E_p$ , surface energy  $E_s$ , kinetic energy  $E_k$ , and viscous dissipation  $E_\eta$ . The changes in the potential and surface energies respectively read

$$\Delta E_p = \rho V g(z_c - z_0), \quad (3.1)$$

$$\Delta E_s = \gamma(A - A_0), \quad (3.2)$$

while the kinetic energy and viscous dissipation are respectively expressed by

$$E_k = \frac{1}{2} \rho \int_V (u^2 + v^2 + w^2) dV, \quad (3.3)$$

$$E_\eta = \int_0^t \int_V \xi dV dt, \quad (3.4)$$

where  $A$  is the surface area,  $V$  is the volume,  $z_0$  is the bottom of the domain, and  $\xi$  is the viscous dissipation function. The temporal evolution of the energy budget during the initial interaction process when  $Bo = 0.5$ ,  $Bo = 2$ , and  $Bo = 5$  are shown in panels (d-f) of figure 4, respectively. Here,  $\Delta E_m$  is the mechanical energy of the system, such that  $\Delta E_m = \Delta E_p^{total} + E_k^{total}$ , and the results are normalised to the total energy of the system  $E_t = E_p + E_k + E_s + E_\eta$ . As the bubble rises and the particle settles,  $E_k$  is found to increase up to a maximum, until the flow field of the particle and the bubble interact. At

this point,  $E_k$  starts to decrease as the gap distance between the bubble and the particle thins. We introduce a new time scale  $t^*$  which specifies the time of kinetic energy reversal in panels (d-f) of figure 4. For  $Bo = 0.5$ ,  $t^* \approx 3.0$  and for  $Bo = 2$  or  $Bo = 5$ ,  $t^* \approx 3.5$ . In panel (c), the relative interaction velocity at the peak kinetic energy is presented for the case of  $Ga = 10$  and  $Ga = 20$  when varying the  $Bo$  number. When  $Ga = 10$ , it can be seen that the relative velocity does not vary significantly when increasing  $Bo$ , however the relationship between the relative velocity and  $Bo$  remains the same for both  $Ga$ . When increasing  $Bo$ , the bubble rising velocity decreases, which allows the particle to attain a larger velocity as it settles. However, this increase in particle velocity does not compensate for the difference in bubble rise speed, which causes a decrease in the relative velocity prior to the interaction. A similar trend is observed for  $Ga = 20$ , with a larger increase in relative velocity when decreasing  $Bo$ . Furthermore, the difference in buoyancy force between the bubble and the particle is also presented when varying  $\zeta_p$ , where the buoyancy force was taken as  $F_b^i = Vg(\rho_i - \rho_l)$ , where  $i = (b, p)$  for the bubble or the particle, respectively. When  $\zeta_p = 1$ , the buoyancy force of the particle is comparable to that of the bubble, however, decreasing  $\zeta_p$  leads to a larger difference between the bubble and particle buoyancy force. A larger difference in buoyancy force between the bubble and the particle allows for the bubble to ‘push’ the particle upwards during the initial interaction, rather than remain in the same vertical position during film drainage. For low  $Bo$ , the particle kinetic energy is seen to decrease to zero at later times, which shows that the film drainage process causes the bubble and the particle to remain at approximately the same vertical position as the liquid film thins (see figure 4(d)). The formation of the liquid film between the bubble and the particle causes an outward radial velocity of the background fluid, which leads to the dissipation of kinetic energy, as seen at  $t = 3.5$  in figure 6 (Zawala & Dabros 2013).

As film drainage is a gradual process driven by pressure differences in the film region, this allows time for the surface tension forces to help the bubble recover a semi-spherical shape with a small dimple at the bubble apex. The dimple radius decreases during the drainage of the liquid film, which can be seen at  $t \approx 5$  when  $Bo = 0.5$  (see figure 6) and by comparing the liquid film thickness profiles and the bubble interface shape in figure 9(a,b). Yiantsios & Davis (1990) have considered the interaction between a droplet and a solid surface and their numerical simulations showed that the terminal value of the dimple radius scales with  $Bo$  as  $R_D \sim (\frac{2}{3}Bo)^{\frac{1}{2}}R$ , which is in great agreement with the dimple radius found in this work when  $Bo = 0.5$  ( $R_D \approx 0.5$ ). This result was first obtained by Derjaguin & Kussakov (1939) by assuming the pressure in the dispersed phase is approximately equal to the pressure in the dimple, and balancing the pressure with the buoyancy force such that  $\frac{2\gamma}{R}\pi R_D^2 \sim \frac{4}{3}\pi(\rho_l - \rho_b)gR^3$ . In panel (e) of figure 5, the dimple radius is presented during the initial interaction period for different  $Bo$  numbers when  $Ga = 10$  and  $\zeta_p = 1$ , where the scaling of the dimple radius presents a good approximation of the results.

Upon increasing the  $Bo$  number to  $Bo = 5$ , a significantly different interaction process is observed at later times. As the particle deforms the bubble interface, the dimple that forms interacts with the southernmost part of the bubble, such that the bubble will rupture. Prior to its rupture, the bubble is seen to deform severely with a film thickness larger than that associated with the  $Bo = 0.5$  case (see panel (d) of figure 5 and figure 6 at  $t = 5$ ). The bubble topology resembles the splashing configuration found by Yoon & Shin (2021) when considering the interaction between a droplet and a particle, with a liquid film between the bubble and the particle in the present work. In figure 5, the minimum aspect ratio attained during the interaction is presented when varying  $Bo$  in panel (c). The time of maximum bubble deformation (minimum  $\chi$ ) is taken as  $t_{\chi_{min}}$ , and




Figure 6: Spatio-temporal evolution of the bubble-particle interaction dynamics shown for the same parameters used to generate Figure 4; the rows are associated with  $Bo = 0.5$ ,  $Bo = 2.0$ , and  $Bo = 5$ , from top to bottom. The contours on the left part of the figures in the panels show the logarithm of the viscous dissipation function  $\log_{10} \xi$  in the fluid, and the contours on the right show the velocity magnitude in the fluid  $V$ . The bubble is shown with glyphs of the velocity to illustrate the relative motion of the bubble at different time-steps.

the change in interfacial surface area  $\Delta A/A_0$  is presented. At  $t_{\chi_{min}}$ , the film thickness profile between the bubble and the particle is plotted in panel (d). The profiles of the film thickness show that at larger  $Bo$ , the minimum gap distance is found at the bubble centre, and when decreasing  $Bo$ , the minimum gap distance shifts towards the bubble dimple. The aspect ratio  $\chi$  reaches a minimum of  $\sim 0.2$ , and the normalised distance between the particle and the bubble,  $S$ , continues to decrease. The distortion of the bubble surface caused by the particle drives the increase in  $\chi$  at later times, up to the point of bubble rupture. Figure 7(b) shows the passage of the particle post-bubble rupture. The particle's kinetic (potential) energy continues to increase (decrease) as seen in figure 7(d), which shows that the particle continues to settle post bubble rupture. This bubble rupture mechanism was also found by the two-dimensional, axisymmetric simulations of the interaction between a rising bubble and a solid surface (Qin *et al.* (2013)), where bubble rupture was observed at large  $Bo$  numbers. As the bubble and the particle approach each other when  $Bo = 2$ , the bubble is found to deform similarly to the  $Bo = 5$  case (see panel (a) of Figure 5), however the bubble does not rupture. Therefore, the liquid film in the gap region between the bubble and the particle starts to drain. As the liquid film drains, the bubble's buoyancy drives it to shift away from




Figure 7: The spatio-temporal evolution of the bubble-particle interaction dynamics is shown in (a) for  $Ga = 10$ ,  $Bo = 2$  and  $\zeta_p = 1$ , where the contours depict the velocity magnitude. Panel (b) shows the spatio-temporal evolution of the interaction dynamics when  $Ga = 10$ ,  $Bo = 5$  and  $\zeta_p = 1$ . The timesteps presented are relative to  $t^*$ , such that  $t - t^*$  varies from 2.5 to 7.0. When  $Bo = 2$  and  $t - t^* = 7$ , a top view of the interaction between the bubble and the particle is presented to showcase that no contact is found between them. In panels (c) and (d), the normalised energy budget  $\tilde{E}/\tilde{E}_0$  is presented for  $Bo = 2$  and  $Bo = 5$ , respectively, where  $\tilde{E}_0 = E_{p_0}^{particle} + E_{s_0}$ .

the particle, as seen in panel (a) of figure 7, interrupting the film draining process. As the bubble moves away from the particle, we note that no contact was found between the bubble and the solid surface, as seen from the presented top view. The bubble then continues to rise, and the particle continues to settle, as seen by considering the change in mechanical energy in the energy budget plot presented in panel (c) of figure 7.

In figure 8(a, b), the temporal evolution of  $h(t)$ , defined as the shortest bubble-particle distance at every time step, is presented for different  $Bo$  numbers. As the bubble rises at early times, it assumes a spherical or ellipsoidal shape such that  $h(t)$  is measured along centreline of the bubble and particle, which we define as  $h_0(t)$ . Figure 8(a) provides an illustration of  $h_0(t)$  and  $h(\mathbf{x}, t)$ , such that  $h(t) = \min h(\mathbf{x}, t)$ . As the dimple forms on




Figure 8: Panels (a) and (b) show the temporal evolution of the minimum gap thickness  $h(t)$  for different  $Bo$  when  $Ga=10$  and  $\zeta_p = 1$ . Two different scaling are also provided, such that  $h \sim (t - t^*/t_d)^{-\alpha}$  where  $\alpha$  here is either  $-4/5$  or  $-1/2$ .

the bubble surface,  $h(t)$  begins to deviate from  $h_0$ . When comparing the minimum gap distance for different  $Bo$ , it can be seen that for smaller  $Bo$ , the film drainage process occurs fastest as the bubble deformations are less severe. This leads to the liquid in the film to drain over a smaller surface area (Manga & Stone 1993). Furthermore, increasing  $Bo$  leads to an increase in surface area in the gap region, which delays the film drainage process. This is found to occur up to  $Bo = 2$ , because at  $Bo = 5$ , the bubble ruptures. Comparing the difference between the gap thickness at the centre and the minimum gap thickness when increasing  $Bo$ , two different conclusions can be made. First, at low  $Bo$ , the development of the dimple occurs at earlier times as compared to the larger  $Bo$  number cases. However, the dimple is much more pronounced with increasing  $Bo$ , at later times. Nevertheless, when the bubble ruptures at  $Bo = 5$ , the minimum gap distance is always found at the centreline as the particle continues to settle. Previous studies (Jones & Wilson 1978; Yiantsios & Davis 1990; Chan *et al.* 2011; Quan 2012; Denner 2018) have shown that the film thickness during the interaction between a deformable interface and a solid surface scales as  $t^{-\alpha}$  where  $0 \leq \alpha \leq 1$ . During film drainage, we can assume that the outward radial velocity of the fluid is much greater than the vertical velocity of the bubble or the particle. Therefore, a new characteristic velocity scale  $U$  can be obtained by balancing the buoyancy and viscous drag ( $\Delta\rho R^3 g \sim \mu_b R U$ ), such that  $U = g\rho_l(2R)^2/6\mu_l\phi$  since  $\rho_l \gg \rho_b$ , and  $\phi = (2 + 3/\lambda)/(1 + 1/\lambda)$  is a correction factor for the viscosity ratio  $\lambda$  (Denner 2018). We introduce a new draining time scale,  $t_d = 2R\sqrt{\mu_l/\gamma U}$ , which can be obtained by assuming the film drainage is dominated by the balance of surface tension and viscous stresses (Klaseboer *et al.* 2000; Chan *et al.* 2011; Denner 2018). At smaller Bond numbers, the liquid film thickness is found to scale as  $h \sim (t - t^*/t_d)^{-4/5}$ , whereas when increasing the Bond number, the scale varies to  $h \sim (t - t^*/t_d)^{-1/2}$ . This result can be seen in panel (b) of figure 8. We note that when  $Bo = 2$ , the film drainage result presented is prior to the bubble sliding away from the particle.

Panels (c) to (f) in figure 9 presents the interaction between a bubble and a particle when  $\Omega = 2$  when  $Ga = 10$ ,  $Bo = 0.5$ , and  $\zeta_p = 1$ . As the bubble and the particle interact, the approach velocity of the particle when  $\Omega = 2$  is smaller, such that the larger bubble's kinetic energy is transferred to the particle, allowing it to reverse its direction and float. Here,  $t^*$  was found to be around  $t \approx 3.5$ . As this kinetic energy from the bubble is transferred to the particle, the bubble's second approach to the particle is at a




Figure 9: This figure showcases the film thickness and the bubble shape as it approaches the particle when  $Ga = 10$ ,  $\zeta_p = 1$ , and  $Bo = 0.5$  in panels (a) and (b). In panels (c) and (d), the temporal evolution of the kinetic energy and particle velocity is presented for two cases, and they are when  $\Omega = 1$ , which is the base case, and when  $\Omega = 2$ . In panels (e) and (f), the film thickness profile and the bubble shape at different time steps during the interaction for  $\Omega = 2$  are presented.

substantially smaller velocity, such that the total kinetic energy stabilises around  $t = 5$  to  $t = 5.9$ . The radius of the dimple on the bubble apex starts to decrease, as seen from the liquid film thickness profiles in panel (e), and the liquid film ruptures at  $t - t^* \approx 2.5$ . It can be seen that as opposed to the case where  $\Omega = 1$ , decreasing the particle size leads to the bubble continuing to rise during the film-draining process, which can be seen from the bubble apex position in panels (b) and (f) for the two cases. When the film ruptures, the larger bubble continues to push the particle upwards, until reaching the top boundary.

We further consider the effect of increasing  $Ga$  and varying  $\zeta_p$  on the interaction dynamics in figure 10. Seven different cases are presented, which correspond to  $(Bo, Ga, \zeta_p) = (0.5, 20, 1)$ ,  $(1, 20, 1)$ ,  $(2, 20, 1)$ ,  $(5, 20, 1)$ ,  $(0.5, 20, 0)$ ,  $(0.5, 20, 0.25)$ , and  $(0.5, 20, 0.75)$ . In panel (a), the temporal evolution of the particle velocity is presented. Previously, at a Bond number of 0.5, a Galilei number of 10, and a particle-to-fluid density ratio of 1, the bubble and the particle remained at relatively the same vertical position throughout the film draining process. This indicates that the bubble and particle experienced minimal vertical displacement relative to each other due to the difference in buoyancy force between the bubble and the particle. When  $Ga$  is increased to 20 while maintaining  $\zeta_p = 1$ , the bubble approaches the particle with a greater velocity compared to when  $Ga = 10$ . However, the interaction dynamics remain consistent with the case when  $Ga = 10$ , where the magnitude of the particle velocity decreases, and the particle remains at relatively the same vertical position during film drainage (see panel (c) of figure 10). In this investigation, we consider the effects of decreasing the particle-to-fluid density ratio ( $\zeta_p$ ), which introduces new dynamics into the interaction process. Specifically, a lower  $\zeta_p$  makes the particle less dense relative to the fluid, increasing its susceptibility to the forces exerted by the bubble. This increased sensitivity results






Figure 10: In panels (a), (b) and (c), the particle settling velocity, total kinetic energy, and the change in particle potential energy are presented, respectively. These results correspond to when  $Ga = 20$ ,  $Bo = 0.5$  and varying  $\zeta_p$ . Temporal evolution of the minimum gap thickness  $h_m(t)$  is shown in (d) for  $\zeta_p = 1$ ,  $Ga = 20$ , and  $Bo = [0.5 - 5]$ ; an enlarged view of the plot in (d) is shown in panel (e), for  $Bo = 0.5$  and  $Bo = 1$  as at these  $Bo$  numbers, the bubble did not rupture. A scaling for the film drainage is provided such that  $h \sim (t - t^*)/t_d^{-4/5}$ . Panel (e) showcases the film thickness profile at  $t_{\chi_{min}}$  when varying  $Bo$  and maintaining  $Ga = 20$  and  $\zeta_p = 1$ .

in more pronounced motion reversals and changes in velocity, demonstrating a critical dependence on the density ratio for the overall behavior of the bubble-particle interaction. When  $\zeta_p$  is decreased, the increased velocity of the bubble causes it to push the particle upwards as the gap distance between them decreases. The extent of flotation of the particle increases as  $\zeta_p$  decreases. This can be verified by examining panels (a), (b) and (c), which show the particle velocity, the total kinetic energy, and the change in potential energy of the particle, respectively. Specifically, the bubble's kinetic energy becomes significant, imparting momentum to the particle and causing it to reverse its motion. This reversal is similar to the behavior observed when  $\Omega = 2$ . As the particle reverses its motion due to the bubble's kinetic energy, the bubble's velocity decreases post-interaction. This deceleration results from the transfer of energy from the bubble to the particle, leading to a redistribution of momentum. The interaction process when  $\zeta_p = [0, 1]$ ,  $Ga = 20$ , and  $Bo = 0.5$  can be seen in figure 10.

When considering the temporal evolution of the gap thickness between the bubble and the particle for  $Ga = 20$  and  $\zeta_p = 1$ , a similar general trend is found compared to that shown in figure 8. Increasing  $Bo$  leads to an increase in the surface area between the bubble and the particle, delaying the process of film drainage. However, when comparing figure 10(d) to figure 8(a), the bubble ruptured for both  $Bo = 2$  and  $Bo = 5$  when increasing the impact relative velocity by varying  $Ga$ . Panel (e) of figure 10 shows the film thickness when varying  $Bo$  and maintaining  $Ga = 20$  and  $\zeta_p = 1$  at  $t_{\chi_{min}}$ . As seen in panel (d) of figure 5, the film thickness profile indicates an increase in distance between the bubble and the particle when increasing  $Bo$ , and the minimum thickness shifts from




Figure 11: This figure showcases the dynamics of the interaction after the formation of the contact line, when  $Ga = 10$ ,  $Bo = 0.5$ , and  $\zeta_p = 1$ . In panel (a), the particle’s vertical velocity is presented for different particle wettability parameters, which correspond to a base case with  $\theta_e = 105^\circ$ , and two additional cases with  $\theta_e = 55$ , and  $\theta_e = 125$ . The figures on the right-hand side correspond to  $t - t^*$  from 8 to 11 for the base case and  $t - t^*$  from 5 to 7 when  $\theta_e = 55^\circ$ . Panel (b) showcases the aspect ratio  $\chi$  for the three different cases, and the pentagram indicates reaching the top boundary. Lastly, panel (c) showcases the temporal evolution of radius of the contact line  $R_{TPC}$  when varying  $\theta_e$  and  $\Omega$ . Note that the  $x$ -axis is scaled with the contact line time  $t_{TPC}$ .

the bubble dimple to the centreline. Following a similar scaling method to Figure 8, the minimum film thickness when  $Bo = 0.5$  and  $Bo = 1$  scales as  $h \sim (t - t^*/t_d)^{-4/5}$ .

For head-on collisions at relatively small  $Bo$  numbers, a contact line forms between the bubble and the particle after liquid film drainage. In figure 11, the evolution of the contact line dynamics and the effect of particle wettability on the overall dynamics is studied. Three different equilibrium contact angles are considered, and they are  $\theta_e = (55, 105, 125)$  for  $\Omega = \zeta_p = 1$ ,  $Ga = 10$ , and  $Bo = 0.5$ . First, panel (a) showcases the particle vertical velocity for the three cases. When  $\theta_e = 55$ , the particle velocity is seen to increase significantly post contact-line formation, which indicates that the bubble has attached to the particle and is pushing it upwards. When increasing  $\theta_e$  to  $105^\circ$  or  $125^\circ$ , the particle velocity is not as significantly affected, indicating the bubble is attempting to minimise its contact area with the particle. In panel (c), the radius of the contact line  $R_{TPC}$  is shown when varying  $\theta_e$  and  $\Omega$ . When  $\theta_e = 55^\circ$ , the contact line initially expands, and during the expansion, the bubble vertically deforms which leads to a peak in the aspect ratio  $\chi$  at  $t - t^* \approx 4.8$  (panel (b)). The contact line radius then maintains the same size as it floats with the particle until reaching the top boundary. When increasing  $\theta_e$ , the contact line radius initially expands, however, the bubble ‘slides’ across the particle






Figure 12: Spatio-temporal evolution of off-centre bubble-particle interaction dynamics with  $Ar = 10$ ,  $Ga = 10$ , and an initial bubble location offset of  $\delta = 1$ . The results shown in the top and bottom two rows were generated with  $Bo = 0.5$  and  $Bo = 5$ , respectively. The contours are of the logarithm of the viscous dissipation function  $\log_{10} \xi$  in the fluid. The bubble is shown with glyphs of the velocity to illustrate the relative motion of the bubble at different time-steps. The snapshots are shown between  $t = 2.5$  and  $t = 6$  in time-increments of  $\delta t = 0.5$ .

and attempts to minimise the contact area. This leads to a decrease in the contact line radius as the bubble moves to the particle's apex, and the bubble then detaches due to buoyancy and continues to rise. The bubble detaches at  $t - t^* \approx 9$  when  $\theta_e = 105^\circ$  and  $\theta_e = 125^\circ$ , with a small part of the bubble still attached to the particle surface. When decreasing the particle size ( $\Omega = 2$ ) and maintaining  $\theta_e = 105^\circ$ , the radius of the contact line expands during contact. However, due to the particle's upward velocity induced by the bubble during the initial interaction, the bubble and the particle continue to rise and the contact line remains relatively the same size. It is crucial to note that the initial radius of the contact line indicates the position at which the contact line forms, such that the dimple radius has a direct influence on the dynamics of the contact line.




Figure 13: Temporal evolution of the total kinetic energy, and the change in bubble surface area are shown in (a)-(b), respectively, for off-centre bubble-particle interactions with  $(Bo, Ga, Ar, \delta) = (0.5, 10, 10, 1)$  and  $(5, 10, 10, 1)$ . Panels (c) and (d) show the temporal evolution of the settling velocity, and the  $x$ -component of the particle velocity, respectively. In panels (e) and (f), the side view of the particle trajectory with respect to the  $x$ -axis and the  $y$ -axis are presented, respectively.

### 3.2. Off-centre bubble-particle interactions

Here we consider bubble-particle interactions that do not correspond to head-on collisions. These are initiated by introducing a horizontal deviation  $\delta$  in the initial bubble position. In this section, we study the dynamics associated with  $\delta = [0.25, 0.5, 1]$  and keep  $(Ga = 10, \zeta_p = 1)$  fixed. In figure 12, the spatio-temporal evolutions of the interaction between the bubble and the particle are presented for  $Bo = 0.5$  (top two rows) and  $Bo = 5$  (bottom two rows), and  $\delta = 1$ . The background field shows the logarithm of the viscous dissipation function  $\xi$  in the fluid. When initiating an offset between the bubble and the particle, it can be seen in figure 12 that for  $Bo = 0.5$ , the bubble initially rises in a similar fashion as observed with the in-line collisions, but the dimple at the apex of the bubble forms on the side of the bubble rather than at the centreline. This causes the bubble to shift its velocity towards the other side (as seen in the glyphs) as it deforms during the interaction process. A liquid film forms between the bubble and the particle at the side of the bubble, at which point we have the largest dissipation of energy. The bubble tends to exhibit a ‘sliding’ motion, which is similar to the drafting-kissing-tumbling (DKT) regime found by Zhang *et al.* (2021) between two bubbles rising in line. The bubble is then seen to continue its rise as it recover its original spherical shape, which can be seen at  $t = 5.5$  and  $t = 6$ . This can also be observed by the change in surface area plot in figure 13(b), where the change in surface area decreases after the interaction with the particle.

Upon further increasing  $Bo$  to  $Bo = 5$ , a similar initial interaction process is observed such that the bubble rises with an ellipsoidal shape, and a dimple forms at the side of the bubble rather than at the centreline. However, due to the large deformations associated with this  $Bo$  value, it can be seen that although a DKT scenario is found, the side of the bubble associated with the impact forms a ‘tail’ ( $t = 4.5$ – $5.5$ ). As the tail forms, we have a sharp increase in the bubble interfacial area and energy dissipation, while the

centre of mass of the bubble continues to rise as the total kinetic energy increases (see figure 13(a)). The tail of the bubble then retracts to its centre of mass ( $t = 6$  in figure 12) and continues to rise, and the particle continues to settle.

From figure 13(d) it can be seen that upon increasing  $Bo$ , the deviation in the particle settling trajectory is not as affected as for low  $Bo$ . This is associated with the significant deformation of the bubble, which tends not to affect the  $x$ -component of the particle velocity as much as the sliding motion of the bubble observed for  $Bo = 0.5$ . Furthermore, when fixing  $Bo = 0.5$  and varying  $\delta$  between 0.25-0.5, figure 13(e-f) shows that the particle trajectory is affected more by decreasing the value of  $\delta$ . For  $\delta = 0.25$  and  $\delta = 0.5$ , the particle's settling velocity (see figure 13(c)) decreases during the initial interaction process. Although the decrease in settling velocity is more pronounced as  $\delta$  decreases, i.e., approaching the case of in-line bubble-particle interactions, the variation in the  $x$ -component of the velocity is more pronounced when  $\delta = 0.5$  compared to  $\delta = 0.25$  (see figure 13(f)). This leads to the particle trajectory being rather similar when  $\delta = 0.25$  and 0.5 (see figure 13(e)).

#### 4. Conclusion

This paper considered the interaction between a freely-rising deformable bubble and a freely-settling particle in a quiescent, Newtonian background fluid. The considered non-dimensional parameters were the bubble Bond and Galilei numbers, the particle Archimedes number, governed by the solid-fluid density contrast, and the size ratio between the bubble and the particle. The results highlighted the spatio-temporal evolution of the bubble shape during the interaction process, the bubble aspect ratio as a measure of its deformation, the liquid film thickness, and an energy analysis of the system. When considering the bubble shape, it was found that increasing the Bond number led to more severe bubble deformations, leading up to bubble rupture and its penetration by the particle. This is caused by the north and south poles of the bubble coalescing due to the intensity of the deformation. When the  $Bo$  number is relatively low, the interaction includes the formation of a liquid film between the bubble and the particle, which is associated with the dissipation of kinetic energy. When decreasing  $\zeta_p$ , the buoyancy force of the bubble exceeds that of the particle, and the bubble can lift the particle upwards if the approach velocity of the bubble is considerably larger than that of the particle. However, if the particle and the bubble approach velocities are similar in magnitude, the initial interaction process is associated with the dissipation of kinetic energy which causes the bubble and the particle to remain at their interaction position as the liquid film drains. The study also considered the temporal evolution of the minimum gap thickness ( $h(t)$ ) between the bubble and the particle and found that increasing  $Bo$  led to an increase in surface area in the gap region, further delaying the film-draining process. The effect of particle wettability on the contact line dynamics were also considered, such that the bubble remains attached to the particle surface at lower  $\theta_e$  and slides away at larger  $\theta_e$ .

A complex situation arises when introducing an offset between the bubble and the particle initial positions. In this study, an offset is only considered for the bubble initial position in the horizontal direction at constant Archimedes and Galilei numbers. For low Bond numbers, a sliding motion of the bubble was observed as it approaches the particle, causing the bubble to push the particle away from its original settling trajectory. However, with increasing Bond number, the bubble deformation is seen to be much more severe such that the bubble centre of mass continues to rise with the formation of a tail in the particle's proximity. The tail then retracts, the bubble continues to rise, and the particle trajectory is not as significantly affected.

This work has considered one viscosity and density ratio between the bubble and the background fluid  $\lambda = \mu_l/\mu_b = 100$  and  $\beta = \rho_l/\rho_b = 1000$ . Possible avenues for future work may include the effects varying the viscosity and density ratios, considering a larger difference between the particle and bubble sizes, introducing asymmetric particle shapes, and the effect of density stratification in the background fluid. Furthermore, the effects of surface mobility of the bubble on the interaction process, by introducing surfactants to the system for example, presents an interesting avenue of future work due to its relevance for industrial processes. All of these configurations may lead to different interaction dynamics between the bubble and the particle. Lastly, this work has considered the interaction between a single rising bubble and a single settling particle, however the collective effect of the interaction between a rising bubble, or a group of bubbles, in the presence of a particle suspension remains an area for further exploration.

## Appendix A

In this section, a resolution test is presented for the case when  $(Bo, Ga, Ar) = (0.5, 10, 10)$  in figure 14. Two different mesh resolutions are considered, and they correspond to  $\Delta x/R = 1/24$  and  $\Delta x/R = 1/32$ . When considering the distance between the particle south pole and the bubble south pole, and the total kinetic energy of the system, an excellent agreement is found between the two mesh resolutions. The most difficult part to resolve is the film thickness. The lower resolution RMSE compared to the higher resolution is approximately 0.5%, which is acceptable considering the higher resolution is the coarsest mesh utilised in this study. In panel (c), a domain size independence test is performed when  $Bo = 0.5$  and  $Ga = 10$ , by increasing the domain size to  $24R \times 24R \times 24R$ . The results show that when increasing the domain size, there is no difference in the attained result, further increasing our confidence in the numerical setup. In panel (d), a mesh size independence considering three different grid cell sizes is presented for the case of  $Bo = 5.0$  and  $Ga = 10$ , where a resolution of up to  $\Delta x/R = 1/64$  is presented.

## Appendix B

This section presents additional validation case studies for the numerical method utilised in this work. At first, figure 15 presents illustrations for the contact line methodology that is utilised in our inhouse solver code BLUE. Furthermore, the adhesion of a bubble on a solid wall is presented and qualitatively compared to the experiments of Basarova *et al.* (2018). The bubble is initialised close to the flat wall ( $0.1R$  from surface to surface), and as the contact line forms, the deformation of the bubble is accurately captured when compared to the results of the experiment. The bubble size is 0.705 mm, and the viscosity and density ratios correspond to an air/water system. The equilibrium contact angle  $\theta_e$  was set at  $\theta_e \approx 100^\circ$ , which corresponds to the surface wettability characteristics utilised in the experiments.

Furthermore, additional validation cases are presented for a solid particle settling through an initially unperturbed interface with different fluid and particle properties. The particle was initially placed a distance of  $6R$  away from the unperturbed interface (from the centre of the particle) and is allowed to settle due to gravity. The results attained from the numerical method are in close agreement with the results of the experiments of Pierson & Magnaudet (2018*a,b*), where a few differences were found in the case of a top fluid of V500 silicone oil with water as the bottom fluid and a steel sphere. The differences are mainly in the development of axisymmetric corollas near the particle surface as the particle penetrates the bottom fluid. The reason behind the difference may




Figure 14: The top two panels (a) and (b) show the total kinetic energy of the system and the distance between the particle south pole and the bubble south pole ( $S$ ), at two different resolutions for  $Ga = 10$ ,  $Bo = 0.5$ , and  $\zeta_p = 1$ , respectively. Panel (c) shows the temporal evolution of the total kinetic energy when increasing the domain size for the same case. It can be seen that increasing the domain size leads to no difference in the results. Panel (d) shows the total kinetic energy for different mesh sizes for  $Ga = 10$ ,  $Bo = 5.0$ , and  $\zeta = 1$ , up to a resolution of  $\Delta x/R = 1/64$ . The results show that the domain size and mesh resolution utilised in this work is sufficient to capture the dynamics of the interaction between the bubble and the particle.




Figure 15: The left hand side of the figure provides an illustration of the contact line numerical methodology between a bubble and a solid wall or solid particle. The plot showcases the temporal evolution of the south pole of the bubble as it adheres to a solid wall with negligible inertia. The contact angle for this case was  $\theta_A = 102$ ,  $\theta_R = 99$ . A qualitative comparison with the experimental results of Basarova *et al.* (2018) is provided at different time steps.




Figure 16: This figure showcases the experimental results of Pierson & Magnaudet (2018*a,b*) for a spherical particle crossing an immiscible interface under different configurations. The plots showcase the performance of this numerical method compared to the experimental results in estimating the entrained fluid volume  $V_e$  and the particle velocity. Qualitative results from the simulations are also provided.

be attributed to the different initial position of the particle in the experiments as this parameter was not exactly specified, or due to the utilised resolution of the case study, which was  $\Delta x/R = 1/32$ . Nonetheless, the quantitative results of the entrained volume of the first fluid into the second fluid ( $V_e$ ) is in close agreement with the experimental results, and the particle settling velocity is accurately captured. We note that in this case study, no contact line forms between the solid and the background fluids, such that an oil film coats the solid surface at all times, which is in agreement with the results found in the experiments of (Pierson & Magnaudet 2018*a*).

#### Acknowledgements

This work was supported by the Engineering and Physical Sciences Research Council, UK, through the MEMPHIS (EP/K003976/1) and PREMIERE (EP/T000414/1) programme grant. O.K.M. acknowledges funding from PETRONAS and the Royal Academy of Engineering for a Research Chair in Multiphase Fluid Dynamics. A.A. acknowledges the Kuwait Foundation for the Advancement of Sciences (KFAS) for their financial support. A.A. and L.K. acknowledge HPC facilities provided by the Imperial College London Research Computing Service. A.A. also acknowledges fruitful discussions with Debashis Panda (Imperial, Chemical Engineering). D.J. and J.C. acknowledge support through HPC/AI computing time at the Institut du Développement et des Ressources en Informatique Scientifique (IDRIS) of the Centre National de la Recherche Scientifique (CNRS), coordinated by GENCI (Grand Equipement National de Calcul Intensif) grant 2023 A0142B06721. The numerical simulations were performed with code BLUE (Shin *et al.* 2017) and the visualisations were generated using ParaView.

Declaration of Interests. The authors report no conflict of interest.

#### REFERENCES

- ARDEKANI, AREZOO M, DOOSTMOHAMMADI, AMIN & DESAI, NIKHIL 2017 Transport of particles, drops, and small organisms in density stratified fluids. *Physical Review Fluids* **2** (10), 100503.
- ASCOLI, EP, DANDY, DS & LEAL, LG 1990 Buoyancy-driven motion of a deformable drop toward a planar wall at low reynolds number. *Journal of Fluid Mechanics* **213**, 287–311.
- BASAROVA, PAVLINA, SOUŠKOVÁ, K & ZAWALA, JAN 2018 Three-phase contact line expansion during air bubble attachment to hydrophobic solid surface—experiment and modeling. *Physicochemical Problems of Mineral Processing* **54** (4), 1095–1106.
- BASAŘOVÁ, PAVLÍNA, ZAWALA, JAN & ZEDNÍKOVÁ, MÁRIA 2019 Interactions between a small bubble and a greater solid particle during the flotation process. *Mineral Processing and Extractive Metallurgy Review* **40** (6), 410–426.
- BHAGA, DAHYA & WEBER, ME 1981 Bubbles in viscous liquids: shapes, wakes and velocities. *Journal of fluid Mechanics* **105**, 61–85.
- CHAN, DEREK YC, KLASEBOER, EVERT & MANICA, ROGERIO 2011 Film drainage and coalescence between deformable drops and bubbles. *Soft Matter* **7** (6), 2235–2264.
- CHORIN, ALEXANDRE JOEL 1968 Numerical solution of the navier-stokes equations. *Mathematics of computation* **22** (104), 745–762.
- CLIFT, R, GRACE, JR & WEBER, ME 1978 Bubbles, particles and drops.
- DANOV, KRASSIMIR D, STANIMIROVA, RUMYANA D, KRALCHEVSKY, PETER A, MARINOVA, KRSTANKA G, STOYANOV, SIMEON D, BLIJDENSTEIN, THEODORUS BJ, COX, ANDREW R & PELAN, EDDIE G 2016 Adhesion of bubbles and drops to solid surfaces, and anisotropic surface tensions studied by capillary meniscus dynamometry. *Advances in Colloid and Interface Science* **233**, 223–239.
- DENNER, FABIAN 2018 Wall collision of deformable bubbles in the creeping flow regime. *European Journal of Mechanics-B/Fluids* **70**, 36–45.
- DERJAGUIN, BV & KUSSAKOV, M 1939 Anomalous properties of thin polymolecular films. *Acta Physicochim. URSS* **10** (1), 25–44.
- DIJKHUIZEN, W, VAN SINT ANNALAND, M & KUIPERS, JAM 2010 Numerical and experimental investigation of the lift force on single bubbles. *Chemical engineering science* **65** (3), 1274–1287.
- ESMAILI, EHSAN, SHUKLA, PRANAV, EIFERT, JOSEPH D & JUNG, SUNGHWAN 2019 Bubble impact on a tilted wall: Removing bacteria using bubbles. *Physical Review Fluids* **4** (4), 043603.
- FADLUN, EVER A, VERZICCO, ROBERTO, ORLANDI, PAOLO & MOHD-YUSOF, JAMALUDIN 2000 Combined immersed-boundary finite-difference methods for three-dimensional complex flow simulations. *Journal of computational physics* **161** (1), 35–60.
- GOLDSTEIN, D, HANDLER, R & SIROVICH, L 1993 Modeling a no-slip flow boundary with an external force field. *Journal of computational physics* **105** (2), 354–366.
- GÓMEZ-SUÁREZ, CRISTINA, BUSSCHER, HENK J & VAN DER MEI, HENNY C 2001 Analysis of bacterial detachment from substratum surfaces by the passage of air-liquid interfaces. *Applied and environmental microbiology* **67** (6), 2531–2537.
- GOVINDARAJAN, RAMA & SAHU, KIRTI CHANDRA 2014 Instabilities in viscosity-stratified flow. *Annual review of fluid mechanics* **46**, 331–353.
- HARLOW, FRANCIS H & WELCH, J EDDIE 1965 Numerical calculation of time-dependent viscous incompressible flow of fluid with free surface. *The physics of fluids* **8** (12), 2182–2189.
- HOOSHYAR, NASIM, VAN OMMEN, J RUUD, HAMERSMA, PETER J, SUNDARESAN, SANKARAN & MUDDÉ, ROBERT F 2013 Dynamics of single rising bubbles in neutrally buoyant liquid-solid suspensions. *Physical Review Letters* **110** (24), 244501.
- JONES, AF & WILSON, SDR 1978 The film drainage problem in droplet coalescence. *Journal of Fluid Mechanics* **87** (2), 263–288.
- KAHOUDJI, LYES, NOWAK, EMILIA, KOVALCHUK, NINA, CHERGUI, JALEL, JURIC, DAMIR, SHIN, SEUNGWON, SIMMONS, MARK JH, CRASTER, RICHARD V & MATAR, OMAR K 2018 Simulation of immiscible liquid–liquid flows in complex microchannel geometries using a front-tracking scheme. *Microfluidics and Nanofluidics* **22** (11), 1–12.
- KLASEBOER, E, CHEVALLIER, J PH, GOURDON, C & MASBERNAT, OLIVIER 2000 Film drainage between colliding drops at constant approach velocity: experiments and modeling. *Journal of colloid and interface science* **229** (1), 274–285.

- KLASEBOER, EVERT, MANICA, ROGERIO, HENDRIX, MAURICE HW, OHL, CLAUS-DIETER & CHAN, DEREK YC 2014 A force balance model for the motion, impact, and bounce of bubbles. *Physics of Fluids* **26** (9).
- KLASSEN, VILLI IVANOVICH & MOKROUSOV, VLADIMIR ALEKSEEVICH 1963 An introduction to the theory of flotation. (*No Title*).
- KOSIOR, D, ZAWALA, J & MALYSA, K 2014 Influence of n-octanol on the bubble impact velocity, bouncing and the three phase contact formation at hydrophobic solid surfaces. *Colloids and Surfaces A: Physicochemical and Engineering Aspects* **441**, 788–795.
- KRASOWSKA, MARTA, ZAWALA, JAN & MALYSA, K 2009 Air at hydrophobic surfaces and kinetics of three phase contact formation. *Advances in colloid and interface science* **147**, 155–169.
- LEE, BENJAMIN J, RUDMAN, MURRAY & SLIM, ANJA C 2023 Modelling thin films of truncated power-law fluids between bubbles and surfaces. *Journal of Non-Newtonian Fluid Mechanics* **312**, 104988.
- LEGAWIEC, KRZYSZTOF JAN, KRUSZELNICKI, MATEUSZ, ZAWADZKA, MICHALINA, BASAŘOVÁ, PAVLÍNA, ZAWALA, JAN & POLOWCZYK, IZABELA 2023 Towards green flotation: Investigating the effect of rhamnolipid biosurfactant on single bubble adhesion dynamics. *Journal of Molecular Liquids* **388**, 122759.
- MAGNAUDET, JACQUES & MERCIER, MATTHIEU J 2020 Particles, drops, and bubbles moving across sharp interfaces and stratified layers. *Annual Review of Fluid Mechanics* **52**, 61–91.
- MANGA, MICHAEL & STONE, HA 1993 Buoyancy-driven interactions between two deformable viscous drops. *Journal of Fluid Mechanics* **256**, 647–683.
- MANICA, ROGERIO, KLASEBOER, EVERT & CHAN, DEREK YC 2015 Force balance model for bubble rise, impact, and bounce from solid surfaces. *Langmuir* **31** (24), 6763–6772.
- MANICA, ROGERIO, KLASEBOER, EVERT & CHAN, DEREK YC 2016 The hydrodynamics of bubble rise and impact with solid surfaces. *Advances in colloid and interface science* **235**, 214–232.
- MASRY, MARIA, ROSSIGNOL, STÉPHANIE, ROUSSEL, BRICE TEMIME, BOURGOGNE, DAVID, BUSSIÈRE, PIERRE-OLIVIER, R'MILI, BADR & WONG-WAH-CHUNG, PASCAL 2021 Experimental evidence of plastic particles transfer at the water-air interface through bubble bursting. *Environmental Pollution* **280**, 116949.
- MENESSES, MARK, BELDEN, JESSE, DICKENSON, NATASHA & BIRD, JAMES 2017 Measuring a critical stress for continuous prevention of marine biofouling accumulation with aeration. *Biofouling* **33** (9), 703–711.
- MORDANT, NICOLAS & PINTON, J-F 2000 Velocity measurement of a settling sphere. *The European Physical Journal B-Condensed Matter and Complex Systems* **18**, 343–352.
- MORE, RISHABH V & ARDEKANI, AREZOO M 2023 Motion in stratified fluids. *Annual Review of Fluid Mechanics* **55**.
- PARINI, MICHAEL R & PITT, WILLIAM G 2006 Dynamic removal of oral biofilms by bubbles. *Colloids and Surfaces B: Biointerfaces* **52** (1), 39–46.
- PATHAK, ASHISH & RAESSI, MEHDI 2016 A 3d, fully eulerian, vof-based solver to study the interaction between two fluids and moving rigid bodies using the fictitious domain method. *Journal of computational physics* **311**, 87–113.
- PESKIN, CHARLES S 1977 Numerical analysis of blood flow in the heart. *Journal of computational physics* **25** (3), 220–252.
- PIERSON, JEAN-LOU & MAGNAUDET, JACQUES 2018a Inertial settling of a sphere through an interface. part 1. from sphere flotation to wake fragmentation. *Journal of Fluid Mechanics* **835**, 762–807.
- PIERSON, JEAN-LOU & MAGNAUDET, JACQUES 2018b Inertial settling of a sphere through an interface. part 2. sphere and tail dynamics. *Journal of Fluid Mechanics* **835**, 808–851.
- QIAN, TIEZHENG, WANG, XIAO-PING & SHENG, PING 2003 Molecular scale contact line hydrodynamics of immiscible flows. *Physical Review E* **68** (1), 016306.
- QIN, TONG, RAGAB, SAAD & YUE, PENGTAO 2013 Axisymmetric simulation of the interaction of a rising bubble with a rigid surface in viscous flow. *International journal of multiphase flow* **52**, 60–70.
- QUAN, SHAOPIG 2012 Dynamics and thin film drainage of a deformable droplet moving towards a solid wall with finite inertia. *RSC advances* **2** (5), 1927–1935.



- SHARMA, PRASHANT K, GIBCUS, MARJON J, VAN DER MEI, HENNY C & BUSSCHER, HENK J 2005a Influence of fluid shear and microbubbles on bacterial detachment from a surface. *Applied and environmental microbiology* **71** (7), 3668–3673.
- SHARMA, PRASHANT K, GIBCUS, MARJON J, VAN DER MEI, HENNY C & BUSSCHER, HENK J 2005b Microbubble-induced detachment of coadhering oral bacteria from salivary pellicles. *European journal of oral sciences* **113** (4), 326–332.
- SHIN, SEUNGWON 2007 Computation of the curvature field in numerical simulation of multiphase flow. *Journal of Computational Physics* **222** (2), 872–878.
- SHIN, SEUNGWON, ABDEL-KHALIK, SI, DARU, VIRGINIE & JURIC, DAMIR 2005 Accurate representation of surface tension using the level contour reconstruction method. *Journal of Computational Physics* **203** (2), 493–516.
- SHIN, SEUNGWON, CHERGUI, JALEL & JURIC, DAMIR 2017 A solver for massively parallel direct numerical simulation of three-dimensional multiphase flows. *Journal of Mechanical Science and Technology* **31** (4), 1739–1751.
- SHIN, SEUNGWON, CHERGUI, JALEL & JURIC, DAMIR 2018 Direct simulation of multiphase flows with modeling of dynamic interface contact angle. *Theoretical and Computational Fluid Dynamics* **32**, 655–687.
- SHIN, SEUNGWON & JURIC, DAMIR 2007 High order level contour reconstruction method. *Journal of mechanical science and technology* **21** (2), 311–326.
- SHIN, SEUNGWON & JURIC, DAMIR 2009a A hybrid interface method for three-dimensional multiphase flows based on front tracking and level set techniques. *International Journal for Numerical Methods in Fluids* **60** (7), 753–778.
- SHIN, SEUNGWON & JURIC, DAMIR 2009b Simulation of droplet impact on a solid surface using the level contour reconstruction method. *Journal of mechanical science and technology* **23** (9), 2434–2443.
- SHIN, SEUNGWON, YOON, IKROH & JURIC, DAMIR 2011 The local front reconstruction method for direct simulation of two-and three-dimensional multiphase flows. *Journal of Computational Physics* **230** (17), 6605–6646.
- SHU, CHI-WANG & OSHER, STANLEY 1989 Efficient implementation of essentially non-oscillatory shock-capturing schemes, ii. In *Upwind and High-Resolution Schemes*, pp. 328–374. Springer.
- SUI, YI, DING, HANG & SPELT, PETER DM 2014 Numerical simulations of flows with moving contact lines. *Annual Review of Fluid Mechanics* **46**, 97–119.
- SUSSMAN, MARK, FATEMI, EMAD, SMERKA, PETER & OSHER, STANLEY 1998 An improved level set method for incompressible two-phase flows. *Computers & Fluids* **27** (5-6), 663–680.
- SUSSMAN, MARK & PUCKETT, ELBRIDGE GERRY 2000 A coupled level set and volume-of-fluid method for computing 3d and axisymmetric incompressible two-phase flows. *Journal of computational physics* **162** (2), 301–337.
- TEN CATE, A, NIEUWSTAD, CH, DERKSEN, JJ & VAN DEN AKKER, HEA 2002 Particle imaging velocimetry experiments and lattice-boltzmann simulations on a single sphere settling under gravity. *Physics of Fluids* **14** (11), 4012–4025.
- TRIPATHI, MANOJ KUMAR, SAHU, KIRTI CHANDRA & GOVINDARAJAN, RAMA 2015 Dynamics of an initially spherical bubble rising in quiescent liquid. *Nature communications* **6** (1), 6268.
- TUCKER, PAUL G 2013 *Unsteady computational fluid dynamics in aeronautics*, , vol. 104. Springer Science & Business Media.
- WANG, DAOWEI & LIU, QI 2021 Hydrodynamics of froth flotation and its effects on fine and ultrafine mineral particle flotation: A literature review. *Minerals Engineering* **173**, 107220.
- WANG, GUICHAO, WANG, YUNPING, YU, JIANGUO, YAO, NING, ZHAO, LE, LIU, YAN, CHEN, SONGYING & WANG, PEIPEI 2023 Detachment of a particle from the surface of a bubble colliding with a solid surface. *Powder Technology* **430**, 119045.
- XIE, LEI, WANG, JINGYI, LU, QIUYI, HU, WENJIHAO, YANG, DILING, QIAO, CHENYU, PENG, XUWEN, PENG, QIONGYAO, WANG, TAO, SUN, WEI & OTHERS 2021 Surface interaction mechanisms in mineral flotation: Fundamentals, measurements, and perspectives. *Advances in Colloid and Interface Science* **295**, 102491.
- YAMAMOTO, YASUFUMI, ITO, TAKAHIRO, WAKIMOTO, TATSURO & KATOH, KENJI 2013

- Numerical simulations of spontaneous capillary rises with very low capillary numbers using a front-tracking method combined with generalized navier boundary condition. *International Journal of Multiphase Flow* **51**, 22–32.
- YANG, JIANMING & STERN, FREDERICK 2012 A simple and efficient direct forcing immersed boundary framework for fluid–structure interactions. *Journal of Computational Physics* **231** (15), 5029–5061.
- YIANTSIOS, STERGIOS G & DAVIS, ROBERT H 1990 On the buoyancy-driven motion of a drop towards a rigid surface or a deformable interface. *Journal of Fluid Mechanics* **217**, 547–573.
- YOON, IKROH & SHIN, SEUNGWON 2021 Direct numerical simulation of droplet collision with stationary spherical particle: A comprehensive map of outcomes. *International Journal of Multiphase Flow* **135**, 103503.
- YOON, RH & LUTTRELL, GH 1989 The effect of bubble size on fine particle flotation. *Mineral Processing and Extractive Metallurgy Review* **5** (1-4), 101–122.
- ZAWALA, JAN & DABROS, TADEUSZ 2013 Analysis of energy balance during collision of an air bubble with a solid wall. *Physics of Fluids* **25** (12), 123101.
- ZAWALA, J, KRASOWSKA, M, DABROS, T & MALYSA, K 2007 Influence of bubble kinetic energy on its bouncing during collisions with various interfaces. *The Canadian Journal of Chemical Engineering* **85** (5), 669–678.
- ZHANG, JIE, NI, MING-JIU & MAGNAUDET, JACQUES 2021 Three-dimensional dynamics of a pair of deformable bubbles rising initially in line. part 1. moderately inertial regimes. *Journal of Fluid Mechanics* **920**, A16.