

## Correction to: Model reduction in computational homogenization for transient heat conduction

Abdullah Waseem, Thomas Heuzé, Laurent Stainier, M G D Geers, V G

Kouznetsova

### ▶ To cite this version:

Abdullah Waseem, Thomas Heuzé, Laurent Stainier, M G D Geers, V G Kouznetsova. Correction to: Model reduction in computational homogenization for transient heat conduction. Computational Mechanics, 2021, 68 (1), pp.231-231. 10.1007/s00466-021-02040-2 . hal-04739846

## HAL Id: hal-04739846 https://hal.science/hal-04739846v1

Submitted on 16 Oct 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

#### CORRECTION



# Correction to: Model reduction in computational homogenization for transient heat conduction

A. Waseem<sup>1,2</sup> · T. Heuzé<sup>1</sup> · L. Stainier<sup>1</sup> · M. G. D. Geers<sup>2</sup> · V. G. Kouznetsova<sup>2</sup>

Published online: 13 June 2021 © The Author(s) 2021

#### Correction to: Computational Mechanics (2020) 65:249–266 https://doi.org/10.1007/s00466-019-01767-3

In the original publication of the article, there was a mistake in recording the simulation times for Fig. 9. The correct version of the Fig. 9 is provided in this correction. The simulations to produce the new figure were run on a computer with a core-i7@4.4GHz processor and 16 Gb RAM using Matlab 2018b. According to the corrected results in the new Fig. 9, the computational gains, in section 4.3.3, given in terms of the ratio between the simulation times using CTH and RTH should be of the order of  $10^4$  approximately.

The original article can be found online at https://doi.org/10.1007/s00466-019-01767-3.

☑ V. G. Kouznetsova V.G.Kouznetsova@tue.nl

- <sup>1</sup> Institut de Recherche en Génie Civil et Mécanique, GeM, UMR 6183 - CNRS - École Centrale de Nantes, Université de Nantes, Nantes, France
- <sup>2</sup> Department of Mechanical Engineering, Eindhoven University of Technology, 5600 MB Eindhoven, The Netherlands



**Fig.9** CPU time as a function of the number of microscopic problems solved with computationally expensive CTH and the proposed reduced order RTH method

**Open Access** This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit http://creativecomm ons.org/licenses/by/4.0/.

**Publisher's Note** Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.