



HAL
open science

Plenary Lecture: Biomimetic membranes incorporating artificial water channels for highperformance water reverse osmosis desalination

M Barboiu

► **To cite this version:**

M Barboiu. Plenary Lecture: Biomimetic membranes incorporating artificial water channels for high-performance water reverse osmosis desalination. 1st International Symposium on Transmembrane Transporters (ISTT2024), <https://21244.scimeeting.cn/>, Apr 2024, Hangzhou, China. hal-04742245

HAL Id: hal-04742245

<https://hal.science/hal-04742245v1>

Submitted on 18 Oct 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Biomimetic membranes incorporating artificial water channels for high-performance water reverse osmosis desalination


M. Barboiu*

*Institut Européen des Membranes, Adaptive Supramolecular Nanosystems Group,
University of Montpellier, ENSCM, CNRS, Place Eugène Bataillon, CC 047, F-34095, Montpellier, France.
mihail-dumitru.barboiu@umontpellier.fr


Inspired by biological models, artificial water channels can be used to overcome the permeability/selectivity trade-off of traditional desalination membranes. We demonstrate that rational incorporation of I-quartet artificial water channels in composite polyamide membranes synthesized *via* interfacial polymerization, provide defect free biomimetic membranes with intrinsic water-to-salt permeability on the operational SWRO-BWRO/TWRO desalination pressure and high/medium/low salinity conditions. The best biomimetic composite membranes, which can be easily scaled for industrial standards ($> \text{m}^2$), provide remarkable 99.5% rejection of NaCl and 91.2% boron rejection with water flux of $75 \text{ L m}^{-2} \text{ h}^{-1}$ at 65 bar applied pressure with a 35000 ppm NaCl feed solution at pH 8, representative of seawater desalination. This flux is more than 75% higher than that observed with current state-of-the-art membranes with equivalent solute rejection, translating into an equivalent reduction of the membrane effective area for the same water output and a $\sim 12\%$ reduction of the required energy for desalination.

« Towards the ultimate reverse osmosis desalination membranes »


**Fundamental
science
Artificial Water
Channels**



**Lab scale
Membranes**



**Industrial
Modules**



Acknowledgments

“This project has received funding from the European Union’s Horizon 2020 research and innovation programme under grant agreement INTELWAT No 958454”.

References

1. M. Di Vincenzo, A. Tiraferri, V.-E. Musteata, S. Chisca, R. Sougrat, L.-B. Huang, S. P. Nunes, M. Barboiu, *Nature Nanotechnol.* 2021, 16, 190-196
2. L.-B. Huang, M. Di Vincenzo, M. Göktuğ Ahunbay, A. van der Lee, D. Cot, S. Cerneaux, G. Maurin*, M. Barboiu, *J. Am. Chem. Soc.* 2021, 143, 14386-14393.
3. M. Di Vincenzo, A. Tiraferri, V.-E. Musteata, S. Chisca, M. Deleanu, F. Ricceri, D. Cot, S. P. Nunes, M. Barboiu, *Proc. Natl. Acad. Sci.*, 2021, 118(37), e2022200118.