



Integration of a GaAs solar cell in a hybrid photovoltaic-thermoelectric system

Léopold Boudier, Jean Baptiste Doucet, Guilhem Almuneau, Inès Revol

► To cite this version:

Léopold Boudier, Jean Baptiste Doucet, Guilhem Almuneau, Inès Revol. Integration of a GaAs solar cell in a hybrid photovoltaic-thermoelectric system. ELaboration of NANOMaterials for the recovery, conversion, transport and storage of energy, Jun 2023, Aussois, France. 2013. hal-04743680

HAL Id: hal-04743680

<https://hal.science/hal-04743680v1>

Submitted on 18 Oct 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Integration of a GaAs solar cell in a hybrid photovoltaic-thermoelectric system

Léopold Boudier, Jean-Baptiste Doucet, Guilhem Almuneau, Inès Massiot

LAAS – CNRS, Toulouse, France
Contact: leopold.boudier@laas.fr


Context

Photovoltaic cell (PV) converts only partially energy above the bandgap into electricity.

The rest is either not absorbed or converted into heat.

Infrared part of the spectrum is not absorbed.




Excess heat loss is converted with the thermoelectric generator (TEG) via Seebeck effect [1].




Objectives

Create a PV cell optimised for integration in hybrid PV-TEG system


- Use of a thermally conductive substrate
- Reduce thermal resistivity at the PV-TEG interface



Process for design and transfer of a PV cell onto a host substrate






Selective etching of GaAs/AlGaAs using $\text{NH}_4\text{OH}(30\%):\text{H}_2\text{O}_2(\text{xx}\%)$



(black) values obtained by Uenishi et. al [3]
(red) GaAs etching rate for etching time up to 4h

Back contact deposition


- Metal deposition via sputtering
- Contact resistivity checked via transmittance length method (TLM)



Thermocompression


We use thermocompression as both a wafer bonding step and an annealing step for the electric back contact.

Bonding done via interdiffusion
Au - Au




2 types of contact

p-type cell:
Ti-Au



n-type cell:
AuGeNi-Au



Conclusion & Perspectives

- Original process to integrate a PV cell into a hybrid PV-TEG system
- Multiple technological challenges: wafer etching, wafer bonding, metallic contact deposition
- Multiphysics approach needed to quantify the improvement compared to classic PV-TEG system

References

1. Narducci, D., Bermel, P., Lorenzi, B., Wang, N. & Yazawa, K. vol. 268 (Springer International Publishing, 2018).
2. Pohl, U. W. . (Springer Berlin Heidelberg, 2013). doi:10.1007/978-3-642-32970-8.
3. Uenishi, Y., Tanaka, H. & Ukita, H. IEEE Trans. Electron Devices 41, 1778–1783 (1994).