



HAL
open science

4D imaging of water ice under high-pressure nonhydrostatic load by time-domain Brillouin scattering

Nicolas Pajusco, Samuel Raetz, Nikolay Chigarev, Sathyan Sandeep, Mathieu E Edely, Alain Bulou, Andreas Zerr, Vitalyi Gusev

► **To cite this version:**

Nicolas Pajusco, Samuel Raetz, Nikolay Chigarev, Sathyan Sandeep, Mathieu E Edely, et al.. 4D imaging of water ice under high-pressure nonhydrostatic load by time-domain Brillouin scattering. The 22nd International Conference on Photoacoustic and Photothermal Phenomena (ICPPP22), Carlos Serpa, Aug 2024, Coimbra, Portugal. pp.206-208. hal-04750941

HAL Id: hal-04750941

<https://hal.science/hal-04750941v1>

Submitted on 24 Oct 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

4D imaging of water ice under high-pressure non-hydrostatic load by time-domain Brillouin scattering

**Pajusco N^{(1)*}, Raetz S^{(1)*}, Chigarev N⁽¹⁾, Sandeep S⁽¹⁾, Edely M⁽²⁾, Bulou A⁽²⁾,
Zerr A⁽³⁾, Gusev VE⁽¹⁾**

(1) Laboratoire d'Acoustique de l'Université du Mans (LAUM), UMR 6613, Institut d'Acoustique – Graduate School (IA-GS), CNRS, Le Mans Université, France.

(2) Institut des Molécules et Matériaux du Mans (IMMM), UMR 6283, CNRS, Le Mans Université, France

(3) Laboratoire de Sciences des Procédés et des Matériaux (LSPM-CNRS UPR-3407), Université Sorbonne Paris Nord (USPN), Villetaneuse, 93430, France

*Corresponding authors' email: Nicolas.pajusco@gmail.com, Samuel.raetz@univ-lemans.fr

Time-domain Brillouin scattering (TDBS) is a technique that involves generating a coherent acoustic pulse (CAP) at GHz frequencies using a picosecond/femtosecond pump laser pulse. This method operates by detecting the interaction between a time-delayed probe laser pulse and the CAP [1-2]. The resulting signal comprises Brillouin oscillations, whose time-varying frequency is directly related to the local optical and elastic properties of a transparent material. In an anisotropic elastic solid, three types of bulk waves can propagate: one quasi-longitudinal and two quasi-shear. Depending on the polarization of each wave, given by the propagation direction in the crystalline axis, and the probe laser polarization up to three distinct Brillouin frequencies can be detected. The detected signal is in terms of time-delay between the CAP generation and the probe laser allowing to follow the CAP. The instantaneous frequency allows to extract the product of the refractive index at the probe wavelength and the acoustic wave velocity at a given time delay, representing the properties at the CAP position. By knowing the refractive index, it is possible to extract the acoustic velocity as a function of depth allowing depth profiling along z direction. Then by doing a 2D lateral scan in the x-y plane, it is possible to reconstruct the 3D map of bulk velocity. This method has been demonstrated for imaging coexisting grains of water ice VI and VII [3]. Varying the non-hydrostatic pressures and repeating the 3D extraction leads to 4D imaging, i.e., space (3D) + pressure (1D), which allows to follow the pressure-induced movement of interfaces.

To control the non-hydrostatic pressure, a membrane diamond anvil cell (DAC) is employed. It is based on two diamond anvils with working surface of 0.3 mm diameter, which allow to apply pressure up to 150 GPa. A 20 nm-thick Au layer is deposited on the bottom diamond acting as an opto-acoustic transducer (OAT). The water ice is sandwiched between the OAT and the top diamond. Figures 1a-b show the optical images of water ice VII at 2.3 and 4.5 GPa, respectively. The experimental setup employs asynchronous optical sampling (ASOPS) with a 535 nm probe laser, focused through the top diamond at the OAT/water ice VII interface to a beam diameter at $1/e^2$ in intensity of 2.6 μm by a 50x, 0.45 NA microscope objective. The pump laser has 515 nm wavelength and is focused from the opposite side at the bottom diamond/OAT interface to a beam diameter at $1/e^2$ in intensity of 5.7 μm by a 20x, 0.4 NA microscope objective. At each pressure step, a 2D scan is performed with 93x93 points and a 1.5 μm lateral step leading to 4D imaging. The thermal background is filtered out using a third-

order bandpass Butterworth filter from 5 to 80 GHz. Subsequently, the frequency of the spectral maximum is extracted in the range of 25 – 50 GHz for quasi-longitudinal CAP and 5 – 25 GHz for quasi-shear CAP.




Fig. 1. Experimental data on water ice VII in a DAC at 2.3 GPa (first row) and 4.5 GPa (second row). (a-b) Optical images. (c-e) Colormaps depicting the spatial distribution of the frequency with the maximum amplitude in the range of: (c-d) [25-50] GHz, corresponding to the quasi-longitudinal CAP, and (e-f) [5-25] GHz, corresponding to a quasi-shear CAP. In (c-e), colormaps are depicted on top of the optical image shown in (a).

Figures 1c-d show the Brillouin frequency map of quasi-longitudinal CAP on top of the optical image at 2.3 and 4.5 GPa, respectively. At 2.3 GPa, there are five distinct Brillouin frequencies in the range of 25-50 GHz, indicating five different crystal orientations of water ice VII. Quasi-shear Brillouin frequencies are also visible in four regions and absent in one, as shown in Fig.1e. At 4.5 GPa, the number of Brillouin frequency regions increases to 7, depicting grain' separation and movement of interfaces as shown in Figs. 1d and 1f. Through time-frequency analysis, the Brillouin frequencies are extracted as a function of time, leading to depth imaging.

Water ice VII, having cubic crystalline structure is optically isotropic, making it appear uniform under optical methods, while it is elastically anisotropic. Therefore, traditional microscope imaging cannot detect different grain orientations of water ice VII. However, acoustic measurements enable the tracking of grain orientation and the movement of interfaces in 3D under varying non-hydrostatic pressures.

References

- [1] H. T. Grahn, H.J. Maris, J. Tauc, Picosecond ultrasonics, *IEEE J. Quantum. Electron.* 25 (1989), 2562-2569. <https://doi.org/10.1109/3.40643>
- [2] V. E Gusev, P. Ruello, Advances in applications of time-domain Brillouin scattering for nanoscale imaging, *Appl. Phys. Rev.* 5 (2018), 031101. <https://doi.org/10.1063/1.5017241>

[3] S. Sandeep, T. Thréard, E. De Lima Savi, N. Chigarev, A. Bulou, V. Tournat, A. Zerr, V. E. Gusev, S. Raetz, 3D characterization of individual grains of coexisting high-pressure H₂O ice phases by time-domain Brillouin scattering, *J. Appl. Phys.* 130 (2021), 053104. <https://doi.org/10.1063/5.0056814>