



HAL
open science

3D printing of WC-Co by Binder Jetting: From powder to final parts

Erwan Marciano, Olivier Dezellus, X Bounat, Sebastien Dezecot, Rodica Chiriac, Francois Toche, Alexis Burr

► To cite this version:

Erwan Marciano, Olivier Dezellus, X Bounat, Sebastien Dezecot, Rodica Chiriac, et al.. 3D printing of WC-Co by Binder Jetting: From powder to final parts. TOFA 2024 - 19th meeting on Thermodynamics of Alloys, Sep 2024, Lyon, France. . hal-04751912

HAL Id: hal-04751912

<https://hal.science/hal-04751912v1>

Submitted on 24 Oct 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

3D printing of WC-Co by Binder Jetting : From powder to final parts

Erwan Marciano^{1,2}, Xavier Boulnat¹, Olivier Dezellus², Sébastien Dezecot³, Alexis Burr⁴, Rodica Chiriac², François Toche²
¹INSA Lyon, ²Université Lyon 1, ³Evatec Tools, ⁴CEA Liten

Why changing process ?


Compaction → **Binder Jetting + Sintering**

B.J. key points

- Time/energy saving
- Powder recycling
- Complex form
- Near net shape

Problems to solve

- Which powder to use ?
- How to print ?
- Debinding/sintering cycle
- Shrinkage modeling ?




Control of final properties


Good balance between **hardness** and **toughness**
 High **transverse rupture strength (TRS)**
Carbon content window
Density and grain size control

Debinding study by mass spectroscopy and carbon analysis

The aim of this study is to gain a better understanding of **binder deterioration during debinding**, and to **optimize the debinding cycle**. The objective is to **establish a link between carbon content and the debinding cycle**. Carbon content should be within the **carbon window** in order to maintain good **mechanical properties** : hardness, toughness, transverse rupture strength (TRS).



Dilatometry with the Netzsch TMA 402 F1 Hyperion




Conclusions

- All debinding cycles are acceptable although study of impact on final properties is needed
- Final properties of binder jetted part can match the one from the press/sinter process
- Sintering anisotropy was quantified to be implemented in the shrinkage model

Perspectives

- Impact of printing parameters on the green part strength and the final properties
- Predict the shrinkage during sintering using dilatometry data

Final properties



[1] J. García, V. Collado Ciprés, A. Blomqvist, et B. Kaplan, « Cemented carbide microstructures: a review », *International Journal of Refractory Metals and Hard Materials*, vol. 80, p. 40-68, avr. 2019, doi: 10.1016/j.ijrmhm.2018.12.004.
 [2] A. Chychko, J. García, V. Collado Ciprés, E. Holmström, et A. Blomqvist, « HV-KIC property charts of cemented carbides: A comprehensive data collection », *International Journal of Refractory Metals and Hard Materials*, vol. 103, p. 105763, févr. 2022