

Electrochemical study of the microbially-induced surface modifications on a 5083 aluminium alloy in marine environment

Chavie Nkoua, Bernard Tribollet, Régine Basséguy, Christine Blanc

▶ To cite this version:

Chavie Nkoua, Bernard Tribollet, Régine Basséguy, Christine Blanc. Electrochemical study of the microbially-induced surface modifications on a 5083 aluminium alloy in marine environment. Eurocorr 2021, Sep 2021, Virtual, France. hal-04753788

HAL Id: hal-04753788 https://hal.science/hal-04753788v1

Submitted on 25 Oct 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

EUROCORR - 2021

Electrochemical study of the microbially-induced surface modifications on a 5083 aluminium alloy in marine environment

Chavie Nkoua^{1,2}, Bernard Tribollet³, Régine Basseguy², Christine Blanc¹

¹CIRIMAT, Université de Toulouse, CNRS, INP, ENSIACET, Toulouse, France

²LGC, Université de Toulouse, CNRS, INP, UPS, Toulouse, France

³LISE UMR 8235, CNRS-Sorbonne Universités, Paris, France

Al-Mg alloys are commonly used in marine environment, even though they are susceptible to localized corrosion in such an aggressive environment. Therefore, anticorrosive coatings are used to improve their corrosion behavior. The present study is carried out as part of the ANR MICOATEC project selected in 2019; it ambitions to develop a new anticorrosive coating technology for metal protection based on a biomimetic strategy. In this framework, the modified surface due to the exposure of Al-Mg alloys to a marine environment has to be studied, and its electrochemical properties evaluated in order to check whether the modified surface can be considered as an efficient anticorrosive coating. This is the aim of the present work.

The material used in the present study is a 5083 aluminum alloy. It has been exposed to marine environment at GENES for different durations, i.e. 15 days, 1 and 2 months. The electrochemical properties of the modified surfaces, following the exposure to marine environment, were investigated by performing open circuit potential (OCP) measurements, polarization tests and electrochemical impedance spectroscopy (EIS) measurements. Two electrolytes were selected, i.e. a 0,5 M NaCl solution and a 10^{-1} M Na₂SO₄ + 10^{-3} M NaCl solution. Prior to each polarization test, a 30min exposure to the electrolyte at OCP was performed. Concerning EIS, measurements were performed after 1h, 24h, 72h, 168h, 240h, 288h and 350h of immersion.

Electrochemical tests were combined with surface observations and analyzes in order to correlate the electrochemical properties of the modified surface to its morphology and structure, by taking into account parameters such as the conditions and the duration of exposure to the marine environment. The final aim is to understand the mechanisms linked to the surface modifications and to assess the anticorrosion properties of these modified surfaces. This knowledge will be the basis needed to enable the artificial replication of the modified surface as an anti-corrosive coating.

This work was financially supported by the ANR, in the framework of the MICOATEC project (ANR-19-CE08-0018).