



Combining Optimization and Machine Learning for Orienteering Problems : Reference Data conception

Mohammed Bati, Rym Nesrine Guibadj, Omar Rifki

► To cite this version:

Mohammed Bati, Rym Nesrine Guibadj, Omar Rifki. Combining Optimization and Machine Learning for Orienteering Problems : Reference Data conception. Séminaire Intelligence Artificielle et Optimisation de l'A2U, Jun 2023, Montreuil sur Mer, France. hal-04763624

HAL Id: hal-04763624

<https://hal.science/hal-04763624v1>

Submitted on 2 Nov 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Problem definition and objectives

1. Orienteering Problems :



- Two conflicting objectives: maximize the collected profit and minimize the routing costs.
- Constraints: Time budget T_{max} , each node can be visited at most once.

2. Objectives :

- Concepting a new dataset based on Phase Transition.
- Using a machine learning routine exploiting the phase transition results in order to enhance the efficiency of the Resolution Algorithm

Phase Transition in NP-Complete Problems

- Phenomenon observed in randomly generated NP-complete problems.
- Relationship between the satisfiability of an instance and the computational effort of the solving algorithm.
- Comparison between three methods : Cutting Plane Method, IDCH, PSO



- The plots show that the hard instances occur around the phase transition from solvability to unsolvability

Figure 1: Phase transition and average running time (CPU sec) for OP.




Figure 2: The projection of Chao instances ($n=66$) onto the phase transition map.


Machine learning to enhance the insertion criterion in construction heuristic

1. Problem statement:


- The insertion cost for an unrouted customer z between customers i and j is calculated as follows :
$$\frac{c_{i,z} + c_{z,j} - c_{i,j}}{(P_z)^\alpha}$$
- The manual adjustment of α can be challenging and requires deep expertise => Using machine learning to learn how to adjust α .

2. Proposed method :


• Collection of data



• Instance features




• Training



✓ Several approaches to be tested: neural networks, Random Forest, nonlinear regressions.

3. Combination of model and the IDCH heuristic.



Results

- The results show that the phase transition occurs when independently varying the parameter Profit/Tmax (tour cost).
- The Profit/Tmax parameter is an indicator of the difficulty of Orienteering Problem instances.

Perspectives

- Using the Profit/Tmax parameter as a measure of difficulty to generate new dataset to train machine learning model.
- Using machine learning to enhance resolution algorithms.

References

- [1] N. Yadav, S. Sardina, C. Murawski, P. Bossaerts, 2018. Phase transition in the knapsack problem.
- [2] Rifki, O., Garaix, T. and Solnon, C., 2022. Étude de la satisfiabilité du problème du voyageur de commerce avec fenêtres de temps. In 23ème congrès annuel de la Société Française de Recherche Opérationnelle et d'Aide à la Décision.
- [3] Amarouche, Y., Guibadj, R.N., Chaalal, E. and Moukrim, A., 2020. Effective neighborhood search with optimal splitting and adaptive memory for the team orienteering problem with time windows. Computers & Operations Research, 123, p.105039
- [4] Y. Bengio, A. Lodi, A. Prouvost, 2020. Machine Learning for Combinatorial Optimization: a Methodological Tour d'Horizon