



Green Hydrogen Storage in LOHCs via Catalytic Hydrogenation: In-depth Compound Analysis and Kinetic Study of Commercial Dibenzyltoluene Mixture

Xiaolong Ji, Casimir Maudet, Fabienne Fache, Essyllt Louarn, Valérie Meille,
Isabelle Pitault

► To cite this version:

Xiaolong Ji, Casimir Maudet, Fabienne Fache, Essyllt Louarn, Valérie Meille, et al.. Green Hydrogen Storage in LOHCs via Catalytic Hydrogenation: In-depth Compound Analysis and Kinetic Study of Commercial Dibenzyltoluene Mixture. 28th International Symposium on Chemical Reaction Engineering (ISCRE 28), Jun 2024, Turku, Finland. 2024. hal-04767403

HAL Id: hal-04767403

<https://hal.science/hal-04767403v1>

Submitted on 5 Nov 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Green Hydrogen Storage in LOHCs via Catalytic Hydrogenation: In-depth Compound Analysis and Kinetic Study of Commercial Dibenzyltoluene Mixture

Xiaolong Ji^{1,2}, Casimir Maudet², Fabienne Fache³, Essyllt Louarn¹, Valérie Meille¹, Isabelle Pitault²

¹IRCELYON, ²LAGEPP, ³ICBMS, Université Claude Bernard Lyon 1, 69100 Villeurbanne, France
isabelle.pitault@univ-lyon1.fr; valerie.meille@ircelyon.univ-lyon1.fr Grant N° ANR-21-CE50-0045

Introduction

The storage and transport of hydrogen is one of the major challenges in hydrogen processes.


Liquid Organic Hydrogen Carriers (LOHCs) → cheap, safe and efficient storage method using (de)hydrogenation.

Dibenzyltoluene and benzylbenzyltoluene (H0-DBT/BBT) mixture → wide liquid range (-34 to 386 °C), high storage capacity (6.2 wt-%).


In this study:

- Identification of Hx-DBT/BBT isomers with the help of GC/MS and mass balance.
- Hydrogenation experiments in a batch reactor under different conditions.
- Kinetic studies using commercial 5 wt-% Pt/C catalyst under different conditions.


Nomenclature



Reaction schematic



Isomer Identification




Fast GC analysis: Separation and study of most isomers present during reactions.

Fragmentation and rearrangement mechanisms combined with reaction mass balance: Identification of isomers.

Model Fitting

Experimental Results



➤ Mass transfer limitation

➤ Deactivation increases with temperature

Kinetic and Reactor Model

Pseudo-LH reaction kinetics with aromatic ring inhibition

$$r_i^s = \frac{f_d k_i^0 e^{-\frac{E_{a,i}}{RT}} C_i^S C_{H_2}^S}{1 + K_{in,m} C_{aromatic,m} + K_{in,s} C_{aromatic,s}}$$

$$\text{Catalyst deactivation } f_d = 1 - \frac{\theta_{in}}{\theta_{Pt}}$$

$$r_{in,Hx} = f_d k_{in}^0 e^{-\frac{E_{a,in}}{RT}} C_{Hx}$$

➤ Deactivating molecules formed from H6 and H18 are also influenced by deactivation

Mass balance – Gas phase

$$H_2: F_{H_2}(t) = V^L k_L a \left(C_{H_2}^* - \frac{n_{H_2}^L}{V^L} \right) + \frac{dn_{H_2}^G}{dt}$$

Mass balance – Liquid phase

$$Hx: 0 = V^P k_{D,j} a_s \left(\frac{n_j^L}{V^L} - \frac{n_{Hx}^S}{V^{L_{in}}} \right) + \frac{dn_j^L}{dt}$$

$$H_2: V^L k_L a \left(C_{H_2}^* - \frac{n_{H_2}^L}{V^L} \right) = V^P k_{D,H_2} a_s \left(\frac{n_{H_2}^L}{V^L} - \frac{n_{Hx}^S}{V^{L_{in}}} \right) + \frac{dn_{H_2}^L}{dt}$$

$$\text{Volume (v molar volume): } \frac{dV^L}{dt} = \sum \frac{dn_j^L}{dt} v_j^L$$

$$H_2 \text{ Solubility (s}_{H_2}\text{): } \frac{ds_{H_2}^L}{dt} = \sum \frac{dn_j^L}{dt} s_{H_2}^j$$

Modeling using Python Fast optimization routine

Mass balance – Solid phase

$$Hx: V^P k_{D,H_2} a_s \left(\frac{n_{H_2}^L}{V^L} - \frac{n_{Hx}^S}{V^{L_{in}}} \right) + V^P \sum_i v_{Hx,i} \eta_i r_i^S = \frac{dn_{Hx}^S}{dt}$$

$$H_2: V^P k_{D,H_2} a_s \left(\frac{n_{H_2}^L}{V^L} - \frac{n_{Hx}^S}{V^{L_{in}}} \right) + V^P \sum_i v_{j,i} \eta_i r_i^S = \frac{dn_{Hx}^S}{dt}$$


$$\text{Active sites: } \frac{d\theta_{in}}{dt} = V^P (r_{in,H6} + r_{in,H18})$$

$$\text{Mass balance – H}_2\text{ Reservoir}$$

$$H_2: \frac{dn_{H_2}^{res}}{dt} = -F_{H_2}(t)$$

Scipy.integrate.solve_ivp
Scipy.optimize.least-squares

Concentration of lumps in solid and liquid phases



Parameter estimation (SI) and confidence intervals

| Parameter | k ₁ ⁰ | k ₂ ⁰ | k ₃ ⁰ | E _{a,1} | E _{a,2} | E _{a,3} | K _{in,s} | K _{in,m} |
|-----------|---------------------------------|----------------------------------|-----------------------------|--------------------|----------------------|----------------------|----------------------|----------------------|
| Opt value | 5.1·10 ⁵ | 2700 | 2.9 | 48000 | 33000 | 17000 | 0.026 | 7.8·10 ⁻³ |
| CI | 3100 | 94 | 2.2·10 ⁻³ | 19 | 14 | 100 | 8.2·10 ⁻⁴ | 2.6·10 ⁻⁴ |
| Parameter | k _{in,H6} ⁰ | k _{in,H18} ⁰ | E _{a,in1} | E _{a,in2} | k _{La} | k _{D,H2} | k _{D,Hx} | |
| Opt value | 0.69 | 0.42 | 38000 | 39000 | 0.32 | 1.8·10 ⁻³ | 4.7·10 ⁻⁵ | |
| CI | 0.015 | 2.6·10 ⁻⁴ | 0.26 | 0.38 | 2.3·10 ⁻³ | 2.5·10 ⁻⁴ | 3.0·10 ⁻⁸ | |

➤ Successful fitting of model and experimental results with small CI.
➤ G-L mass transfer limitation at the beginning at higher T (°C).
➤ Small but visible gap between C^L and C^{L_{su}}, characteristic for L-S mass transfer limitation.

Conclusions

- ✓ Identification of all Hx-DBT isomers and H0, H6-BBT isomers.
- ✓ Experiments under different conditions demonstrated transfer limitations and catalyst deactivation during hydrogenation.
- ✓ Kinetic model taking into account reaction mixture property change (density, H₂ solubility), mass transfer (G-L-S), compound adsorption and catalyst deactivation.
- ✓ The sources of deactivating species were found to be H6 and H18-DBT/BBT, which largely depend on the reaction temperature.
- ✓ Modeling of single isomers in progress.