



HAL
open science

Bridging Computational Notions of Depth

Laurent Bienvenu, Christopher P. Porter

► **To cite this version:**

Laurent Bienvenu, Christopher P. Porter. Bridging Computational Notions of Depth. 2024. hal-04784252

HAL Id: hal-04784252

<https://hal.science/hal-04784252v1>

Preprint submitted on 14 Nov 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

BRIDGING COMPUTATIONAL NOTIONS OF DEPTH

LAURENT BIENVENU, CHRISTOPHER P. PORTER

ABSTRACT. In this article, we study the relationship between notions of depth for sequences, namely, Bennett’s notions of strong and weak depth, and deep Π_1^0 classes, introduced by the authors and motivated by previous work of Levin. For the first main result of the study, we show that every member of a Π_1^0 class is order-deep, a property that implies strong depth. From this result, we obtain new examples of strongly deep sequences based on properties studied in computability theory and algorithmic randomness. We further show that not every strongly deep sequence is a member of a deep Π_1^0 class. For the second main result, we show that the collection of strongly deep sequences is negligible, which is equivalent to the statement that the probability of computing a strongly deep sequence with some random oracle is 0, a property also shared by every deep Π_1^0 class. Finally, we show that variants of strong depth, given in terms of a priori complexity and monotone complexity, are equivalent to weak depth.

1. INTRODUCTION

Bennett introduced the notion of logical depth in [Ben95] as a measure of complexity, formulated in terms the amount of computation time required to reproduce a given object. Whereas the Kolmogorov complexity of a string $\sigma \in 2^{<\omega}$ measures the length of the shortest input given to a fixed universal machine that reproduces σ as its output, logical depth measures the number of steps it takes to recover σ from this shortest input. Bennett further defined a sequence $X \in 2^\omega$ to be strongly deep if

Date: June 30, 2024.

for every computable function t the logical depth of almost all of the initial segments $X \upharpoonright n$ of X is greater than $t(n)$.

Bennett established several fundamental facts about strongly deep sequences, namely that the halting set K is strongly deep, that no computable sequence and no Martin-Löf random sequence is strongly deep, and that strong depth is closed upwards under truth-table reducibility (a result he referred to as the *slow growth law*). Bennett further introduced the notion of weak depth, where a sequence is weakly deep if it is not truth-table reducible to a random sequence.

An analogue of deep sequences for Π_1^0 classes, i.e., effectively closed subsets of 2^ω , was developed by the present authors in [BP16]. The authors isolated the notion of a deep Π_1^0 class as a generalized of work of Levin [Lev13], who implicitly showed that the Π_1^0 class of consistent completions of Peano arithmetic is deep. The basic idea, made precise in the next section, is that a Π_1^0 class \mathcal{P} is deep if the probability of computing some length n initial segment of some member of \mathcal{P} via some Turing functional equipped with a random oracle rapidly approaches zero as n grows without bound. In [BP16], the authors proved a number of results about deep Π_1^0 classes, including an analogue of the slow growth law for deep Π_1^0 classes in the Medvedev degrees, as well as identifying a number of examples of deep Π_1^0 classes based on properties studied in computability theory and algorithmic information theory.

The aim of this study is to show that the relationship between strongly deep sequences and deep Π_1^0 classes is no mere analogy. In particular, we prove that every member of a deep Π_1^0 class is strongly deep, from which it follows that we gain a significant number of newly identified examples of strongly deep sequences based on results from [BP16]. We further show that a strongly deep sequence need not be a member of a deep Π_1^0 class. Next, as every deep Π_1^0 class is negligible, in the sense that the probability of computing a member of such a class with a Turing functional equipped with a random oracle is zero, in light of the fact that all members of deep

Π_1^0 classes are strongly deep, it is reasonable to ask whether the collection of strongly deep sequences is negligible. We answer this question in the affirmative, while further showing that the collection of sequences that are deep with respect to any fixed time bound is not negligible. Finally, we consider variants of strong depth given in terms of a priori and monotone complexity and demonstrate that these two variants are equivalent to Bennett's notion of weak depth (with the latter equivalence following from work by Schnorr and Fuchs [SF77]).

One takeaway we aim to emphasize in this study is the importance of the slow growth law for the study of depth, akin to the role of randomness preservation in the study of algorithmic randomness. According to the latter, every sequence that is truth-table reducible to a sequence that is random with respect to a computable measure is itself random with respect to a computable measure, which is precisely the dual of the slow growth law for deep sequences. We anticipate that the slow growth law will continue to be a useful tool in the study of notions of depth.

The outline of the remainder of this article is as follows. In Section 2 we provide background on notions from computability theory and algorithmic randomness that we draw upon in this study. Next, in Section 3, we provide a short proof of the slow growth law for strongly deep sequence and use it to identify some hitherto unnoticed examples of strongly deep sequences from classical computability theory. In Section 4 we prove the main result of our study, namely that every member of a deep Π_1^0 class is strongly deep. Here we observe some consequences of this result and separate several depth notions, showing in particular that not every strongly deep sequence is a member of a deep Π_1^0 class. Section 5 contains our second main result, that the collection of strongly deep sequences is negligible, while in Section 6 we show the equivalence of depth notions given in terms of a priori and monotone complexity with Bennett's notion of weak depth.

2. BACKGROUND

2.1. Turing functionals. Recall that a *Turing functional* $\Phi : \subseteq 2^\omega \rightarrow 2^\omega$ can be defined in terms of a c.e. set S_Φ of pairs of strings (σ, τ) such that if $(\sigma, \tau), (\sigma', \tau') \in S_\Phi$ and $\sigma \preceq \sigma'$, then $\tau \preceq \tau'$ or $\tau' \preceq \tau$. For each $\sigma \in 2^{<\omega}$, we define Φ^σ to be the maximal string in $\{\tau : (\exists \sigma' \preceq \sigma)(\sigma', \tau) \in S_\Phi\}$ in the order given by \preceq . To obtain a map defined on 2^ω from the set S_Φ , for each $X \in 2^\omega$, we let Φ^X be the maximal $y \in 2^{<\omega} \cup 2^\omega$ in the order given by \preceq such that $\Phi^{X \upharpoonright n}$ is a prefix of y for all n .

2.2. Semimeasures. A *discrete semimeasure* is a function $m : 2^{<\omega} \rightarrow [0, 1]$ satisfying $\sum_{\sigma \in 2^{<\omega}} m(\sigma) \leq 1$. Similarly, a *continuous semimeasure* is a function $P : 2^{<\omega} \rightarrow [0, 1]$ satisfying (i) $P(\emptyset) \leq 1$ and (ii) $P(\sigma) \geq P(\sigma 0) + P(\sigma 1)$ for all $\sigma \in 2^{<\omega}$. Given a continuous semimeasure P and some $S \subseteq 2^{<\omega}$, we set $P(S) = \sum_{\sigma \in S} P(\sigma)$.

A discrete semimeasure m is computable if its output values $m(\sigma)$ are computable uniformly in the input $\sigma \in 2^{<\omega}$ (and similarly for continuous semimeasures). Here we will also consider *lower semicomputable* semimeasures (both discrete and continuous), where a function $f : 2^{<\omega} \rightarrow [0, 1]$ is lower semicomputable if each value $f(\sigma)$ is the limit of a computable, nondecreasing sequence of rationals, uniformly in $\sigma \in 2^{<\omega}$.

An important development due to Levin [LZ70] was the identification of *universal* semimeasures: for discrete semimeasures, m is universal if for every lower semicomputable measure m_0 there is some constant c such that $m_0(\sigma) \leq c \cdot m(\sigma)$. Similarly, a continuous semimeasure M is universal if for every lower semicomputable measure P there is some constant c such that $P(\sigma) \leq c \cdot M(\sigma)$. Hereafter, \mathbf{m} and \mathbf{M} will denote fixed universal discrete and continuous semimeasures, respectively.

2.3. Initial segment complexity. Recall that the prefix-free Kolmogorov complexity of a string $\tau \in 2^{<\omega}$ is defined by setting $K(\tau) = \min\{|\sigma| : U(\sigma) \downarrow = \tau\}$, where U is a fixed universal prefix-free machine (i.e., recall that a machine M is prefix-free if for $\sigma, \rho \in 2^{<\omega}$, if $M(\sigma) \downarrow$ and $\sigma \prec \rho$, then $M(\rho) \uparrow$). Moreover, we can

define time-bounded versions of Kolmogorov complexity. A function $t : \omega \rightarrow \omega$ is called a *time bound* if t is total and non-decreasing. Then for a fixed computable time bound t , the t -time-bounded complexity of $\tau \in 2^{<\omega}$ is defined by setting $K^t(\tau) = \min\{|\sigma| : U(\sigma)\downarrow = \tau \text{ in } \leq t(|\tau|) \text{ steps}\}$.

Note that by Levin's coding theorem, $K(\sigma) = -\log \mathbf{m}(\sigma) + O(1)$ for all $\sigma \in 2^{<\omega}$. A similar relationship holds for computable discrete semimeasures and time-bounded Kolmogorov complexity. First, we define a time-bounded version of \mathbf{m} as follows. As \mathbf{m} is lower semicomputable, for each $s \in \omega$, we have an approximation \mathbf{m}_s of \mathbf{m} (i.e., for each $\sigma \in 2^{<\omega}$, $\mathbf{m}_s(\sigma)$ is the s -th rational number in computable sequence that converges to $\mathbf{m}(\sigma)$). Then given a computable time bound t , we set $\mathbf{m}^t(\sigma) = \mathbf{m}_{t(|\sigma|)}$, which is clearly a computable semimeasure. We will make use of the following lemma from [BDM23] (where for functions f, g , $f \leq^\times g$ means that there is some c such that $f(n) \leq c \cdot g(n)$ for all $n \in \omega$).

Lemma 1 ([BDM23]).

- (i) *For every computable discrete semimeasure m , there is some computable time bound t such that $m \leq^\times \mathbf{m}^t$.*
- (ii) *For every computable time bound t , 2^{-K^t} is a computable discrete semimeasure.*
- (iii) *For every computable time bound t , there is some computable time bound t' such that $2^{-K^t} \leq^\times \mathbf{m}^{t'}$.*

In addition, we need the following theorem (see, e.g. [JLL94, Theorem 4.3(2)]).

Theorem 2. *For every computable time bound t , there is a computable time bound t' such that $\mathbf{m}^t \leq^\times 2^{-K^{t'}}$.*

Note that by combining Lemma 1(iii) and Theorem 2, we obtain a resource-bounded analogue of Levin's coding theorem.

In the case of continuous semimeasures, we directly define $KA(\sigma) := -\log \mathbf{M}(\sigma)$ to be the *a priori complexity* of $\sigma \in 2^{<\omega}$. Just as we defined \mathbf{m}^t for any computable time bound t , we can similarly define \mathbf{M}^t , which is a computable continuous semimeasure. Moreover, we can establish the analogue of Lemma 1(i): For every computable continuous semimeasure P , there is some computable time bound t such that $P \leq^\times \mathbf{M}^t$. We will also define $KA^t := \mathbf{M}^t$ for any given computable time bound t .

Lastly, we define monotone complexity in terms of monotone machines, where a monotone machine $M : 2^{<\omega} \rightarrow 2^{<\omega}$ satisfies the property that for $\sigma, \tau \in \text{dom}(M)$, if $\sigma \preceq \tau$, then either $M(\sigma) \preceq M(\tau)$ or $M(\tau) \preceq M(\sigma)$. Given a universal monotone machine U , we set $Km(\tau) = \min\{|\tau| : U(\sigma) \downarrow \succeq \tau\}$. Given a computable time bound, we can also define Km^t in the obvious way.

2.4. Randomness and depth notions. Given a computable measure μ on 2^ω (i.e., a measure on 2^ω where the values $\mu(\llbracket \sigma \rrbracket)$ are computable uniformly in $\sigma \in 2^{<\omega}$), recall that a μ -Martin-Löf test is a uniformly Σ_1^0 sequence $(U_i)_{i \in \omega}$ such that $\mu(U_i) \leq 2^{-i}$. Recall further that a sequence $X \in 2^\omega$ passes the test $(U_i)_{i \in \omega}$ if $X \notin \bigcap_{i \in \omega} U_i$ and X is μ -Martin-Löf random if it passes all μ -Martin-Löf tests. In the case that μ is the Lebesgue measure on 2^ω (which we denote by λ), we will refer to λ -Martin-Löf random sequences simply as Martin-Löf random sequences.

Next, $X \in 2^\omega$ is *strongly deep* if for every computable time bound t , we have $K^t(X \upharpoonright n) - K(X \upharpoonright n) \rightarrow \infty$. A slightly stronger notion is given by order-depth, where $X \in 2^\omega$ is *order-deep* if there is a computable order function $g : \omega \rightarrow \omega$ such that $K^t(X \upharpoonright n) - K(X \upharpoonright n) \geq g(n)$ for almost every $n \in \omega$. Here we use the term ‘order function’, or simply ‘order’ to mean a non-decreasing and unbounded function. When h is such a function, $h^{-1}(k)$ denotes the smallest n such that $h(n) \geq k$. Note that h^{-1} is computable when h is.

In the rest of the paper we will sometimes use an equivalent characterization of order-depth, given by the following lemma.

Lemma 3. *For $X \in 2^\omega$, the following are equivalent.*

- (i) X is order-deep
- (ii) For some computable increasing function h , for any computable time bound t and almost all n , $K^t(X \upharpoonright h(n)) - K(X \upharpoonright h(n)) \geq^+ n$.
- (iii) For some computable increasing function h , for any computable time bound t and almost all n , $\frac{\mathbf{m}(X \upharpoonright h(n))}{\mathbf{m}^t(X \upharpoonright h(n))} \geq^\times 2^n$.

The proof of this lemma is technical; for the sake of readability, we defer it to the appendix.

One of the key properties of strong depth is the slow growth law, given in terms of truth-table reductions. Recall that a tt -functional is a Turing functional that is total on all oracles; equivalently, there is a computable function f such that for all $X \in 2^\omega$, $|\Phi^{X \upharpoonright f(n)}| \geq n$.

Theorem 4 (Slow Growth Law [Ben95]). *For $X, Y \in 2^\omega$, if X is strongly deep and $X \leq_{tt} Y$, then Y is strongly deep.*

The slow growth law also holds for order-depth.

Bennett proved that no computable sequence and no Martin-Löf random sequence is strongly deep. Hereafter, we will refer to sequences that are not strongly deep as being *shallow*. Bennett further showed that the halting set $\emptyset' = \{e : \phi_e(e) \downarrow\}$ (where $(\phi_e)_{e \in \omega}$ is a standard enumeration of the partial computable functions) is strongly deep.

Bennett defined a weaker notion of depth: a sequence $X \in 2^\omega$ is *weakly deep* if X is not tt -reducible to a Martin-Löf random. By the slow growth law and the fact that

no Martin-Löf random sequences are strongly deep, it follows that every strongly deep sequence is weakly deep; as shown by Bennett [Ben95], the converse does not hold. Note that it is a folklore result that a sequence is not truth-table reducible to a Martin-Löf random sequence if and only if it is not random with respect to a computable measure, thereby providing an alternative characterization of weak depth.

2.5. Deep Π_1^0 classes and negligibility. As noted in the introduction, the authors in [BP16] introduced the notion of a deep Π_1^0 class as the abstraction of a phenomenon first isolated by Levin in [Lev13]. Given a Π_1^0 class \mathcal{P} , recall that there is a canonical co-c.e. tree $T \subseteq 2^{<\omega}$ such that $\mathcal{P} = [T]$, i.e., \mathcal{P} is the collection of all infinite paths through T ; more specifically, this tree T is the set of all initial segments of members of \mathcal{P} . For $n \in \omega$, let T_n be the set of all strings in T of length n . We say that a Π_1^0 class \mathcal{P} is *deep* if there is some order g such that $\mathbf{M}(T_n) \leq 2^{-g(n)}$. Equivalently, \mathcal{P} is deep if there is some order h such that $\mathbf{M}(T_{h(n)}) \leq 2^{-n}$.

An analogue of the slow growth law holds for deep Π_1^0 classes in a suitable degree structure, namely the strong degrees (also referred to as the Medvedev degrees). Given Π_1^0 classes \mathcal{P} and \mathcal{Q} , we say that \mathcal{P} is strongly reducible to \mathcal{Q} , written $\mathcal{P} \leq_s \mathcal{Q}$, if there is some Turing functional Φ such that for every $Y \in \mathcal{Q}$, there is some $X \in \mathcal{P}$ such that $X = \Phi(Y)$; equivalently, we have $\Phi(\mathcal{Q}) = \mathcal{P}$. As noted in [BP16], we can assume here that Φ is a *tt*-functional, a fact that will be useful in this study. Then we have:

Theorem 5 (Slow Growth Law for Π_1^0 classes, [BP16]). *For Π_1^0 classes $\mathcal{P}, \mathcal{Q} \subseteq 2^\omega$, if \mathcal{P} is deep and $\mathcal{P} \leq_s \mathcal{Q}$, then \mathcal{Q} is deep.*

Depth for Π_1^0 classes implies a property that holds more broadly for subsets of 2^ω , namely the property of being negligible. First, observe that a lower semicomputable semimeasure P can be trimmed back to a measure $\bar{P} \leq P$ (see [BHPS14] details). In

particular, we can trim back the universal lower semicomputable semimeasure \mathbf{M} to get a measure $\overline{\mathbf{M}}$. One key result concerning $\overline{\mathbf{M}}$ is that for a measurable set $\mathcal{A} \subseteq 2^\omega$, $\overline{\mathbf{M}}(\mathcal{A}) = 0$ if and only if $\lambda(\{X : (\exists Y \in \mathcal{A}) Y \leq_T X\}) = 0$; that is, from the point of view of Lebesgue measure, only relatively few sequences can compute a member of \mathcal{A} . Following Levin (see for example [Lev84]), we call such sets \mathcal{A} *negligible*. As we can equivalently consider the collection of random sequences that compute a member of \mathcal{A} , we can recast negligibility in terms of probabilistic computation: a collection \mathcal{A} is negligible if the probability of probabilistically computing a member of \mathcal{A} is zero. Note that every deep Π_1^0 class is thus negligible; in fact, we can interpret the property of depth for a Π_1^0 class \mathcal{P} as the property that the probability of computing the first n bits of a member of \mathcal{P} converges to 0 effectively in $n \in \omega$. As shown in [BP16], not every negligible Π_1^0 class is deep.

Two other notions related to depth and negligibility for Π_1^0 classes studied in [BP16] are the notions of *tt*-depth and *tt*-negligibility:

- A Π_1^0 class \mathcal{P} with canonical co-c.e. tree T is *tt-deep* if for every computable measure μ there is some computable order g such that $\mu(T_n) \leq 2^{-g(n)}$ for all $n \in \omega$, or equivalently, for every computable measure μ , there is some computable order h such that $\mu(T_{h(n)}) \leq 2^{-n}$.
- A measurable set $\mathcal{C} \subseteq 2^\omega$ is *tt-negligible* if $\mu(\mathcal{C}) = 0$ for every computable measure μ , or equivalently, $\lambda(\{X \in \mathcal{C} : \exists Y \in 2^\omega X \leq_{tt} Y\}) = 0$.

Unlike the notions of depth and negligibility, we have the following equivalence:

Theorem 6 ([BP16]). *Let $\mathcal{P} \subseteq 2^\omega$ be a Π_1^0 class. The following are equivalent:*

- (i) \mathcal{P} is *tt-deep*.
- (ii) \mathcal{P} is *tt-negligible*.
- (iii) For every computable measure μ on 2^ω , \mathcal{P} contains no μ -Martin-Löf random element.

Note that by the alternative characterization of weak depth discussed in the previous subsection, Theorem 6, a Π_1^0 class is *tt*-deep if and only if all of its members are weakly deep.

3. ON THE SLOW GROWTH LAW

In this section, we provide a proof of the slow growth law and provide some hitherto unobserved consequences of the result. In particular, the proof of the slow growth law that we offer here is distinct from others in the literature in two respects. First, unlike other proofs in the literature, such as the one found in [JLL94], which are more complexity-theoretic (using the machinery of Kolmogorov complexity), our proof is measure-theoretic, being based on computable semimeasures. Second, the proof offered here is much more direct than currently available proofs of the slow growth law.

We begin with a few words to simplify the setting. First, as noted in the previous section $X \in 2^\omega$ is strongly deep when

$$K^t(X \upharpoonright n) - K(X \upharpoonright n) \rightarrow \infty$$

for every computable time bound t , but a more pleasant way to rephrase this, by elevating to the power of 2 on both sides, is to require that

$$\frac{\mathbf{m}(X \upharpoonright n)}{p(X \upharpoonright n)} \rightarrow \infty$$

for every computable discrete semi-measure p (that the two phrasings are equivalent follows directly from Lemma 1 and Theorem 2).

Second, if Γ is a *tt*-functional with use γ , we can naturally extend Γ to strings by defining $\Gamma(\sigma)$ to be the first n bits of Γ^σ , where n is such that $|\sigma| \in [\gamma(n), \gamma(n+1))$. Seen as a function on strings, Γ has two properties that we will need:

- (i) Γ is total;
- (ii) For every string τ , the preimage $\Gamma^{-1}(\tau)$ is a finite set that can be computed uniformly in τ .

We are now ready to prove our main theorem.

Theorem 7. *Let F be total computable function on strings such that for all τ , $F^{-1}(\tau)$ is a finite set which can be computed uniformly in τ . Let p be a computable discrete semimeasure. Then, there exists a computable discrete semimeasure q such that*

$$\frac{\mathbf{m}(F(\sigma))}{q(F(\sigma))} \leq^{\times} \frac{\mathbf{m}(\sigma)}{p(\sigma)}$$

It is now clear that this theorem implies the slow growth law with F identified with the extension of Γ to $2^{<\omega}$, setting $\sigma = X \upharpoonright n$, and letting n tend to ∞ . Let us prove the theorem.

Proof. Define q simply as the push-forward measure of p under F :

$$q(\tau) = \sum_{\sigma \in F^{-1}(\tau)} p(\sigma)$$

Our assumption on F and p imply that q is computable. It is a semimeasure as $\sum_{\tau} q(\tau) = \sum_{\tau} \sum_{\sigma \in F^{-1}(\tau)} p(\sigma) = \sum_{\sigma} p(\sigma) \leq 1$.

Now, define for all σ :

$$m(\sigma) = \frac{\mathbf{m}(F(\sigma))}{q(F(\sigma))} \cdot p(\sigma)$$

We claim that m is a lower semicomputable discrete semimeasure. That m is lower semicomputable is clear, since \mathbf{m} is lower semicomputable and p, q , and F are computable. That m is a discrete semimeasure can be established as follows:

$$\begin{aligned} \sum_{\sigma} m(\sigma) &= \sum_{\tau} \sum_{\sigma \in F^{-1}(\tau)} m(\sigma) = \sum_{\tau} \sum_{\sigma \in F^{-1}(\tau)} \frac{\mathbf{m}(F(\sigma))}{q(F(\sigma))} \cdot p(\sigma) \\ &= \sum_{\tau} \frac{\mathbf{m}(\tau)}{q(\tau)} \cdot \left(\sum_{\sigma \in F^{-1}(\tau)} p(\sigma) \right) = \sum_{\tau} \frac{\mathbf{m}(\tau)}{q(\tau)} \cdot q(\tau) = \sum_{\tau} \mathbf{m}(\tau) \leq 1. \end{aligned}$$

By maximality of \mathbf{m} , we have $m(\sigma) \leq^{\times} \mathbf{m}(\sigma)$, which by definition of m gives the desired inequality. \square

We note in passing that our proof also implies the slow growth law for order-depth: indeed if in the above we have $\frac{\mathbf{m}(\Gamma^X \upharpoonright n)}{q(\Gamma^X \upharpoonright n)} \geq h(n)$ for some computable order h , then $\frac{\mathbf{m}(X \upharpoonright \gamma(n))}{p(X \upharpoonright \gamma(n))} \geq h(n)$ where γ is the use of Γ , which by Lemma 3 shows that X is order-deep.

We note here some previously unnoticed consequence of slow growth law. First, observe that the standard unsolvable problems from computability theory are strongly deep, including:

- $\text{Fin} = \{x : W_x \text{ is finite}\}$
- $\text{Inf} = \{x : W_x \text{ is infinite}\}$
- $\text{Tot} = \{x : \phi_x \text{ is total}\}$
- $\text{Cof} = \{x : W_x \text{ is cofinite}\}$
- $\text{Comp} = \{x : W_x \text{ is computable}\}$
- $\text{Ext} = \{x : \phi_x \text{ is extendible to a total computable function}\}$

Indeed, for each such class C , we have $\emptyset' \leq_1 C$, i.e., there is a computable function $f : \omega \rightarrow \omega$ such that $n \in \emptyset'$ if and only if $f(n) \in C$ for all $n \in \omega$. Since every

1-reduction defines a tt -functional, the result follows from the slow growth law and the fact that \emptyset' is strongly deep.

In fact, we can strengthen this observation for *all* non-trivial index sets, thereby strengthening Rice's theorem in terms of strong depth:

Theorem 8. *If $C \subseteq \omega$ is a shallow index set, i.e., C is not strongly deep, then either $C = \emptyset$ or $C = \omega$.*

This follows immediately from the classical version of Rice's theorem, for if C is a non-trivial index set, then either $\emptyset' \leq_1 C$ or $\overline{\emptyset'} \leq_1 C$. Since $\overline{\emptyset'}$ is strongly deep by the slow growth law, the result is clear.

We will see additional applications of the slow growth law in the remaining sections.

4. MEMBERS OF DEEP Π_1^0 CLASSES

When deep Π_1^0 classes were defined in [BP16], the authors referred to the notion as a type of depth in analogy with Bennett's original notion of logical depth (as, for instance, an analogue of the slow growth law for deep Π_1^0 classes was established in [BP16]). We now show that the connection between these two depth notions is much closer than merely satisfying an analogy, as we prove that the members of deep Π_1^0 classes are strongly deep; in fact, we prove the stronger result that all such members are order-deep. Note that this is analogous to the result that every member of a tt -deep Π_1^0 class is weakly deep, a consequence of Theorem 6 discussed at the end of Section 2.5.

Theorem 9. *Every member of a deep Π_1^0 class \mathcal{P} is order-deep.*

Proof. Let T be the canonical co-c.e. tree associated to the Π_1^0 class \mathcal{P} . Let h be a computable order such that

$$\sum_{\sigma \in T_{h(n)}} \mathbf{M}(\sigma) \leq 2^{-2n}.$$

for all n .

Let t be a computable time bound. By virtue of the inequalities $\mathbf{M} \geq^\times \mathbf{m} \geq^\times \mathbf{m}^t$, the above inequality implies

$$\sum_{\sigma \in T_{h(n)}} \mathbf{m}^t(\sigma) \leq 2^{-2n}.$$

Since \mathbf{m}^t is computable and T is co-c.e., one can effectively compute a sequence s_n such that

$$\sum_{\sigma \in T_{h(n)[s_n]}} \mathbf{m}^t(\sigma) \leq 2^{-2n}.$$

Let now p be the computable discrete semimeasure defined by $p(\tau) = 2^n \cdot \mathbf{m}^t(\tau)$ if τ belongs to $T_{h(n)[s_n]}$ for some $n > 0$, and $p(\tau) = 0$ otherwise. That p is computable is clear from the definition (and the computability of the sequence s_n), and that it is a semimeasure follows from

$$\sum_{\tau} p(\tau) = \sum_{n>0} \sum_{\tau \in T_{h(n)[s_n]}} 2^n \cdot \mathbf{m}^t(\tau) \leq \sum_{n>0} 2^n \cdot 2^{-2n} \leq 1.$$

Now, if X is a member of \mathcal{P} , that is, X is a path through T , then for each $n > 0$, we have $X \upharpoonright h(n) \in T_{h(n)}$ and thus

$$p(X \upharpoonright h(n)) = 2^n \cdot \mathbf{m}^t(X \upharpoonright h(n)).$$

As $\mathbf{m} \geq^\times p$ (because p is a discrete semi-measure), we have

$$\mathbf{m}(X \upharpoonright h(n)) \geq^\times 2^n \cdot \mathbf{m}^t(X \upharpoonright h(n))$$

By Lemma 3, we can conclude that X is order-deep. \square

One immediate consequence of Theorem 9 is the following.

Corollary 10. *If \mathcal{P} is a deep Π_1^0 class, then the canonical co-c.e. tree T associated with \mathcal{P} is order-deep.*

Proof. Let $X \in \mathcal{P}$ be the leftmost path through \mathcal{P} , which is order-deep by Theorem 9. Then if T is the canonical co-c.e. tree associated with \mathcal{P} , we have $X \leq_{tt} T$, so by the slow growth law, T is order-deep. \square

The converse of this result does not hold.

Theorem 11. *There is an order-deep co-c.e. tree T such that $[T]$ is not a deep Π_1^0 class.*

Proof. Let $S \subseteq 2^{<\omega}$ be any order-deep co-c.e. tree and let $T = 0 \frown S \cup 1 \frown 2^{<\omega}$. Clearly T is a co-c.e. tree because S is. To see that T is order-deep, note that $\sigma \in S$ if and only if either (i) σ is the empty string or (ii) $0 \preceq \sigma$ and $\sigma \in T$. It thus follows that $S \leq_{tt} T$, and so by the slow growth law, T is order-deep. Finally, as the sequence 1^ω is a member of the Π_1^0 class $[T]$ and every member of a deep Π_1^0 class must be order-deep by Theorem 9, it follows that $[T]$ cannot be deep. \square

A similar pair of results hold for tt -deep Π_1^0 classes.

Theorem 12. *If \mathcal{P} is a tt -deep Π_1^0 class, then the canonical co-c.e. tree T associated with \mathcal{P} is weakly deep.*

Proof. Given a Π_1^0 class \mathcal{P} with canonical co-c.e. tree T , suppose that T is not weakly deep. Then T is Martin-Löf random with respect to some computable measure. As in the proof of Corollary 10, if $X \in \mathcal{P}$ is the leftmost path through \mathcal{P} , then have

$X \leq_{tt} T$. By randomness preservation (according to which if Y is Martin-Löf random with respect to a computable measure and $X \leq_{tt} Y$, then X is Martin-Löf random with respect to a computable measure; see, e.g., [BP12]), X is Martin-Löf random with respect to a computable measure, and hence \mathcal{P} is not tt -deep. \square

Theorem 13. *There is a weakly deep co-c.e. tree T such that $[T]$ is not a tt -deep Π_1^0 class.*

Proof. The proof is nearly identical to that of Theorem 11. Given any weakly deep co-c.e. tree T_0 , let $T = 0 \smallfrown T_0 \cup 1 \smallfrown 2^{<\omega}$. Since $T_0 \leq_{tt} T$, it follows that T must be weakly deep. However, $[T]$ contains every Martin-Löf sequence that begins with a 1, it cannot be tt -deep. \square

Note earlier that we stated the result that being a tt -deep Π_1^0 class not only implies that every member of the class is weakly deep, but also that this latter condition is equivalent to the property of being tt -deep. This equivalence does not hold in the case of deep Π_1^0 classes:

Theorem 14. *There is a Π_1^0 class \mathcal{P} such that (i) every $X \in \mathcal{P}$ is strongly deep but (ii) \mathcal{P} is not deep.*

Proof. As shown in [BP16, Theorem 4.7], given any deep Π_1^0 class \mathcal{Q} , there is a non-deep Π_1^0 class \mathcal{P} such that every member of \mathcal{P} is a finite modification of some member of \mathcal{Q} . By the slow growth law, order-depth is invariant under finite modifications, so every member of any such class \mathcal{P} is strongly deep. \square

4.1. Additional examples of deep sequences. Theorem 9 also allows us to derive a number of examples of deep sequences. In [BP16] it was shown that the following collections of sequences form deep Π_1^0 classes:

- (1) the collection of consistent completions of Peano arithmetic;

- (2) the collection of (α, c) -shift-complex sequences for computable $\alpha \in (0, 1)$ and $c \in \omega$, where a sequence $X \in 2^\omega$ is (α, c) -shift-complex if $K(\tau) \geq \alpha|\tau| - c$ for every substring τ of X ;
- (3) the collection of DNC_q functions with $\sum_{n \in \omega} \frac{1}{q(n)} = \infty$, where $f : \omega \rightarrow \omega$ is a DNC_q function if f is total function such that $f(n) \neq \phi_n(n)$ and $f(n) < q(n)$ for all $n \in \omega$;
- (4) the collection of codes of infinite sequences of finite sets (F_0, F_1, \dots) of strings of maximal complexity, i.e., there are computable functions $\ell, f, d : \omega \rightarrow \omega$ such that for all $n \in \omega$, (i) $|F_n| = f(n)$, (ii) $|\sigma| = \ell(n)$ for $\sigma \in F_n$, and (iii) $K(\sigma) \geq \ell(n) - d(n)$ for $\sigma \in F_n$; and
- (5) the collection of codes of K -compression functions with constant c , where $g : 2^{<\omega} \rightarrow \omega$ is a K -compression function with constant c if (i) $g(\sigma) \leq K(\sigma) + c$ for all $\sigma \in 2^{<\omega}$ and (ii) $\sum_{\sigma \in 2^{<\omega}} 2^{-g(\sigma)} \leq 1$.

As an immediate consequence of Theorem 9 and the above results from [BP16], we have:

Corollary 15. *Every sequence in the following collections is strongly deep:*

- (1) *the collection of consistent completions of Peano arithmetic;*
- (2) *the collection of shift-complex sequences (i.e., the sequences that are (α, c) -shift complex for some computable $\alpha \in (0, 1)$ and $c \in \omega$);*
- (3) *the collection of codes of DNC_q functions with $\sum_{n \in \omega} \frac{1}{q(n)} = \infty$;*
- (4) *the collection of codes of infinite sequences of finite sets of strings of maximal complexity; and*
- (5) *the collection of codes of K -compression functions (i.e., K -compression functions with constant c for some $c \in \omega$).*

We can obtain further examples of members of deep Π_1^0 classes using a version of the slow growth law for members of deep Π_1^0 classes.

Lemma 16. *If X is a member of a deep Π_1^0 class and $X \leq_{tt} Y$, then Y is a member of a deep Π_1^0 class.*

Proof. Let \mathcal{P} be a Π_1^0 class contain X , and let Φ be a total Turing functional satisfying $\Phi(Y) = X$. Then by the slow growth law for deep Π_1^0 classes, $\Phi^{-1}(\mathcal{P})$ is a deep Π_1^0 class that contains Y , which must be strongly deep by Theorem 9. \square

Theorem 17.

- (i) *The halting set $\emptyset' = \{e \in \omega : \phi_e(e) \downarrow\}$ is a member of a deep Π_1^0 class.*
- (ii) *For every $X \in 2^\omega$, $X' = \{e : \phi_e^X(e) \downarrow\}$ is a member of a deep Π_1^0 class.*
- (iii) *Every non-trivial index set is a member of a deep Π_1^0 class.*

Proof. (i) There is a DNC_2 function f such that $f \leq_{tt} \emptyset'$ (see [Nie09, Remark 1.8.30]). Since the collection of DNC_2 functions forms a deep Π_1^0 class, the result follows from Lemma 16.

(ii) Since $\emptyset' \leq_{tt} X'$ for every $X \in 2^\omega$ and \emptyset' is a member of a deep Π_1^0 class by part (i), the result follows from Lemma 16.

(iii). By Rice's theorem, every non-trivial index set C satisfies $\emptyset' \leq_1 C$ or $\overline{\emptyset'} \leq_1 C$, and so the result follows again from part (i) and Lemma 16. \square

4.2. Separating depth notions. In light of Theorem 9, it is natural to ask whether every order-deep sequence is a member of a deep Π_1^0 class. We show that this does not hold by establishing several propositions of independent interest.

Recall that a sequence X is complex if there is some computable order g such that $K(X \upharpoonright n) \geq g(n)$. As shown explicitly in [HP17], one can equivalently define a sequence to be complex in terms of a priori complexity, i.e., X is complex if and only if there is some computable order h such that $KA(X \upharpoonright n) \geq h(n)$. We use this second characterization to derive the following:

Proposition 18. *Every member of a deep Π_1^0 class is complex.*

Proof. Let \mathcal{P} be a deep Π_1^0 class with associated co-c.e. tree T . Then there is some computable order $h : \omega \rightarrow \omega$ such that $\mathbf{M}(T_n) \leq 2^{-h(n)}$. Given $X \in \mathcal{P}$, since $X \upharpoonright n \in T_n$, we have $\mathbf{M}(X \upharpoonright n) \leq \mathbf{M}(T_n) \leq 2^{-h(n)}$. Taking the negative logarithm yields $KA(X \upharpoonright n) \geq h(n)$, from which the conclusion follows. \square

Next, we have:

Proposition 19. *No sequence that is Turing equivalent to an incomplete c.e. set is a member of a deep Π_1^0 class.*

Proof. Suppose that X is a member of a deep Π_1^0 class and is Turing equivalent to some incomplete c.e. set Y . By Proposition 18, X is complex. It follows from work of Kjos-Hanssen, Merkle, and Stephan [KHMS11] that X has DNC degree. But then Y is an incomplete c.e. set of DNC degree, which contradicts Arslanov's completeness criterion (see, e.g., [Nie09, Theorem 4.1.11]). \square

Theorem 20. *There is an order-deep sequence that is not complex (hence is not a member of any deep Π_1^0 class).*

Proof. In [JLL94], Juedes, Lathrop, and Lutz introduced the notion of weakly useful sequence (we do not recall the definition of this notion here and refer the reader to their paper) and showed that (i) every weakly useful sequence is order-deep and (ii) every high degree contains a weakly useful sequence. Our theorem then follows: Let X be high, incomplete, and weakly useful (hence order-deep). By the same reasoning in the proof of Proposition 19, X is not complex. \square

We note another consequence of Proposition 19, namely that the leftmost path of every deep Π_1^0 class is Turing complete. Indeed, the leftmost path of a Π_1^0 class has c.e. degree and thus must be Turing complete by Proposition 19.

Having separated order-depth from being a member of a deep Π_1^0 class, we can use a similar line of reasoning to further separate order-depth from Bennett's original notion of depth. We need one auxiliary result.

Theorem 21 (Moser, Stephan [MS17]). *Every order-deep sequence is either high or of DNC degree.*

Theorem 22. *There is a strongly deep sequence that is not order-deep.*

Proof. Downey, MacInerney, and Ng [DMN17] constructed a low, deep sequence A of c.e. degree. As A can neither be high nor of DNC degree (as it is incomplete), it follows from Theorem 21 that A is not order-deep. \square

We have seen by Theorem 9 that members of deep Π_1^0 classes are order-deep, and by Proposition 18 that they are complex. We end this section by showing that these two properties alone are not enough to characterize members of deep Π_1^0 classes.

Theorem 23. *There exists a sequence X which is complex, order-deep, and not a member of any deep Π_1^0 class.*

We will need the following auxiliary lemma of independent interest. Recall that the join $Y \oplus Z$ of two sequences Y and Z is the sequence obtained by interleaving their bits: $Y \oplus Z = Y(0)Z(0)Y(1)Z(1)\dots$. Similarly, for two strings σ and τ of the same length we can define $\sigma \oplus \tau$ in the same way.

Lemma 24. *If a sequence Y is not a member of any deep Π_1^0 class, then for almost every Z (in the sense of Lebesgue measure), $Y \oplus Z$ is not a member of any deep Π_1^0 class.*

Proof. We prove this lemma by contrapositive. Suppose that Y is such that for positive measure many sequences Z , $Y \oplus Z$ is a member of a deep Π_1^0 class. If this is

so, as there are only countably many deep Π_1^0 classes, this means that there is a fixed deep Π_1^0 class \mathcal{C} such that with probability $> \delta$ over Z (with δ a positive rational), we have that $Y \oplus Z$ belongs to \mathcal{C} . Consider the Π_1^0 class \mathcal{D} consisting of sequences A such that for any n , there are at least $\delta \cdot 2^n$ strings τ such that $(A|n) \oplus \tau$ is in the canonical tree T of \mathcal{C} . By definition, Y belongs to \mathcal{D} . We claim that \mathcal{D} is deep, which will prove the lemma. Since \mathcal{C} is deep, there is a computable order h such that $\mathbf{M}(T_{2n}) < 1/h(n)$ for all n . Let P be the continuous semimeasure defined on strings of even length by $P(\sigma \oplus \tau) = \mathbf{M}(\sigma)\lambda(\tau)$. If S is the canonical co-c.e. tree of \mathcal{D} , then by definition of \mathcal{D} , we have

$$P(T_{2n}) \geq \mathbf{M}(S_n) \cdot \delta.$$

By universality of \mathbf{M} , we also have $\mathcal{P}(T_{2n}) \leq^\times \mathbf{M}(T_{2n}) < 1/h(n)$. Putting these two inequalities together, it follows that

$$\mathbf{M}(S_n) \leq^\times \frac{1}{\delta \cdot h(n)}$$

which shows \mathcal{D} is a deep Π_1^0 class. □

Proof of Theorem 23. Having proven Lemma 24, take now Y a sequence that is order-deep and not a member of any deep Π_1^0 class (whose existence was established in Theorem 20). Pick Z at random and form the sequence $X = Y \oplus Z$. With probability 1 over Z :

- X is complex. Indeed $K(X|2n) \geq^+ K(Z|n) \geq^+ n$ by the Levin-Schnorr theorem.
- X is not a member of any deep Π_1^0 class by Lemma 24.

Moreover, regardless of the value of Z , X *tt*-computes Y which is order-deep, hence by the slow growth law for order-deep sequences, X is itself order-deep. These three properties tell us that with probability 1 over Z , $X = Y \oplus Z$ is as desired. □

5. STRONG DEPTH IS NEGLIGIBLE

While we know that deep Π_1^0 classes must all be negligible, we have established (Theorems 9 and 20) that the collection of strongly deep sequences forms a strict superclass of the collection of members of all deep Π_1^0 classes. It is therefore natural to ask whether the collection of strongly deep sequences is negligible, which we answer in the affirmative.

Theorem 25. *The class of strongly deep sequences is negligible.*

Proof. For the sake of contradiction, assume there exists a functional Φ such that

$$\lambda\{X : \Phi^X \text{ is deep}\} > 0.9$$

(where we choose this latter value without loss of generality by the Lebesgue Density Theorem). Let p be a computable semimeasure such that $\liminf_n \frac{m(n)}{p(n)} < \infty$. The existence of such a p follows from the existence of *Solovay functions* (see [BDNM15]), which are functions $f \geq^+ K$ such that $\liminf_n f(n) - K(n) < \infty$. Setting $p(n) = 2^{-f(n)-c}$ with f a Solovay function and c large enough gives us the properties of p we need.

We now define a computable discrete semimeasure as follows. For every $n \in \omega$, effectively find a family of clopen sets $\{C_\sigma : |\sigma| = n\}$ such that $\Phi^X \succeq \sigma$ for all $X \in C_\sigma$ and $\sum_{|\sigma|=n} \lambda(C_\sigma) > 0.9$. Then, set for all σ of length n :

$$q(\sigma) = \lambda(C_\sigma) \cdot p(n)$$

It is clear that q is computable. Moreover, q is a discrete semimeasure, since

$$\sum_{\sigma \in 2^{<\omega}} q(\sigma) = \sum_{n \in \omega} \sum_{|\sigma|=n} \lambda(C_\sigma) \cdot p(n) = \sum_{n \in \omega} p(n) \sum_{\sigma \in 2^{<\omega} : |\sigma|=n} \lambda(C_\sigma) \leq \sum_{n \in \omega} p(n) \leq 1.$$

For any Y that is strongly deep, we must have $\frac{\mathbf{m}(Y|n)}{q(Y|n)} \rightarrow \infty$. For all (n, d) , define

$$B_n^d = \{\sigma : |\sigma| = n \text{ and } \mathbf{m}(\sigma) > d \cdot q(\sigma)\}$$

By our hypothesis on the functional Φ , this means that for every constant d , for almost all n , $\lambda(\{X : \Phi^X \upharpoonright n \in B_n^d\}) > 0.9$.

Now, consider the quantity $\sum_{\sigma \in B_n^d} \lambda(C_\sigma)$. On the one hand,

$$\begin{aligned} \sum_{\sigma \in B_n^d} \lambda(C_\sigma) &= \sum_{\sigma \in B_n^d} \frac{q(\sigma)}{p(n)} && \text{(by definition of } q) \\ &\leq \sum_{\sigma \in B_n^d} \frac{\mathbf{m}(\sigma)}{d \cdot p(n)} && \text{(by definition of } B_n^d) \\ &\leq \frac{1}{d \cdot p(n)} \sum_{|\sigma|=n} \mathbf{m}(\sigma) \\ &\leq \frac{\mathbf{m}(n) \cdot O(1)}{d \cdot p(n)} && \text{(using the identity } \sum_{|\sigma|=n} \mathbf{m}(\sigma) = \mathbf{m}(n)) \end{aligned}$$

On the other hand, for almost all n :

$$\begin{aligned} \sum_{\sigma \in B_n^d} \lambda(C_\sigma) &\geq \lambda(\{X : \Phi^X \upharpoonright n \in B_n^d\}) - 0.1 && \text{(because } \lambda(\bigcup_{|\sigma|=n} C_\sigma) > 0.9) \\ &\geq 0.9 - 0.1 \\ &\geq 0.8 \end{aligned}$$

Putting the two together, we have established that for all d , for almost all n , $\frac{\mathbf{m}(n)}{p(n)} > d/O(1)$, i.e., $\lim_n \frac{\mathbf{m}(n)}{p(n)} = \infty$. This contradicts the choice of p . \square

Note, by contrast, that the collection of weakly deep sequences is not negligible. Indeed, as shown by Muchnik et al. [MSU98], no 1-generic sequence is Martin-Löf random with respect to a computable measure, and thus every 1-generic is weakly deep. Moreover, as shown by Kautz [Kau91], every 2-random sequence computes a 1-generic, and hence the collection of 1-generics is not negligible.

As the collection of strongly deep sequences is negligible, it is worth asking whether the collection of sequences that are strongly deep with respect to one fixed computable time bound is negligible. We first introduce some notation. For a computable time bound t and $c \in \omega$, let $D_c^t(n) = \{X \in 2^\omega : K^t(X \upharpoonright n) - K(X \upharpoonright n) \geq c\}$, which is clopen uniformly in n , hence $\bigcap_{n \geq m} D_c^t(n)$ is a Π_1^0 class. In addition, we set $D_c^t = \bigcup_{m \in \omega} \bigcap_{n \geq m} D_c^t(n)$. Then we have:

Theorem 26. *Let t be a computable time bound and $c \in \omega$. Then D_c^t is not negligible and hence does not consist entirely of strongly deep sequences.*

Proof. Suppose on the contrary that D_c^t is negligible for some computable time bound t and $c \in \omega$. Then for each $m \in \omega$, $\bigcap_{n \geq m} D_c^t(n)$ is a negligible Π_1^0 class. As shown in [BP16, Theorem 5.2], no weakly 2-random sequence can compute a member of a negligible Π_1^0 class, hence no weakly 2-random sequence can compute a member of $\bigcap_{n \geq m} D_c^t(n)$ (recall that $X \in 2^\omega$ is weakly 2-random if X is not contained in any Π_2^0 of Lebesgue measure zero). It follows that no weakly 2-random sequence can compute a member of D_c^t . However, there is some weakly 2-random sequence that computes a sequence of high Turing degree [Kau91], and as shown by Juedes, Lathrop, and Lutz [JLL94], every high degree contains a strongly deep sequence. In particular, every high degree contains an element of D_c^t , and thus there is some weakly 2-random sequence that computes a member of D_c^t , a contradiction. Note further that under the assumption that D_c^t consists entirely of strongly deep sequences, then by Theorem 25, it would follow that D_c^t is negligible, which we have shown cannot hold. \square

6. VARIANTS OF STRONG DEPTH

6.1. **Depth via continuous semimeasures.** In [BP16], the authors show that the definition of a deep Π_1^0 class can be equivalently defined simply by replacing the universal continuous semimeasure \mathbf{M} with the universal discrete semimeasure \mathbf{m} : a Π_1^0 class \mathcal{P} with canonical co-c.e. tree T is deep if and only if there is a computable order h such that $\mathbf{m}(T_n) < 2^{-h(n)}$ for all $n \in \omega$, if and only if there is a computable order f such that $\mathbf{m}(T_{f(n)}) < 2^{-n}$ for all $n \in \omega$. Given the characterization of deep sequences in terms of discrete semimeasures in Section 3, it is natural to ask whether we can equivalently characterize strong depth by replacing the discrete semimeasures in the definition with continuous semimeasures. We show that, in this case, we only obtain a characterization of weak depth.

Theorem 27. *$X \in 2^\omega$ is weakly deep if and only if for every computable continuous semimeasure P ,*

$$\frac{\mathbf{M}(X \upharpoonright n)}{P(X \upharpoonright n)} \rightarrow \infty.$$

Proof. Suppose that X is not weakly deep. Then there is some computable measure μ such that X is μ -Martin-Löf random. By the Levin-Schnorr theorem for a priori complexity with respect to the measure μ (implicit in [Lev73]), there is some c such that

$$KA(X \upharpoonright n) \geq -\log \mu(X \upharpoonright n) - c$$

for all $n \in \omega$. Equivalently, we have

$$\mathbf{M}(X \upharpoonright n) \leq 2^c \cdot \mu(X \upharpoonright n)$$

Since every computable measure is a computable semimeasure, the conclusion follows.

For the other direction, suppose that there is some computable, continuous semimeasure and some $c \in \omega$ such that for all $n \in \omega$,

$$(1) \quad \frac{\mathbf{M}(X \upharpoonright n)}{P(X \upharpoonright n)} < c.$$

From P , we can define a computable measure μ as follows. First, we define a function $g : 2^{<\omega} \rightarrow 2^{<\omega}$ by setting

$$g(\sigma) = P(\sigma) - (P(\sigma 0) + P(\sigma 1))$$

for every $\sigma \in 2^{<\omega}$. Clearly g is computable since P is. Next we define a computable measure μ on 2^ω by setting

$$\mu(\sigma) = P(\sigma) + \sum_{\tau \prec \sigma} 2^{|\tau| - |\sigma|} g(\tau).$$

One can readily verify that μ is a measure (see the proof of Proposition 3.5 in [BHPS14]) and $P(\sigma) \leq \mu(\sigma)$ for all $\sigma \in 2^{<\omega}$. From Equation (1) we can derive

$$KA(X \upharpoonright n) \geq -\log P(X \upharpoonright n) - O(1) \geq -\log \mu(X \upharpoonright n) - O(1).$$

It thus follows from the Levin-Schnorr theorem for a priori complexity that X is μ -Martin-Löf random and hence is not weakly deep. \square

We define a sequence to be *KA-deep* if

$$KA^t(X \upharpoonright n) - KA(X \upharpoonright n) \rightarrow \infty$$

where $KA^t := -\log \mathbf{M}^t$ as discussed in Section 2.3. Recall further from Section 2.3 that for every computable continuous semimeasure P , there is some computable time bound t such that $P \leq^\times \mathbf{M}^t$. It is thus straightforward to show that for $X \in 2^\omega$ and

every computable continuous semimeasure P ,

$$\frac{\mathbf{M}(X \upharpoonright n)}{P(X \upharpoonright n)} \rightarrow \infty$$

if and only if for every computable time bound t ,

$$\frac{\mathbf{M}(X \upharpoonright n)}{\mathbf{M}^t(X \upharpoonright n)} \rightarrow \infty$$

(see the proof of [BDM23, Lemma 2.6] for discrete semimeasures which directly translates to the case of continuous semimeasures). Thus we can conclude:

Corollary 28. $X \in 2^\omega$ is *KA-deep* if and only if X is *weakly deep*.

6.2. Depth and monotone complexity. We can obtain a similar characterization of weak depth in terms of monotone complexity. Define a sequence to be *Km-deep* if

$$Km^t(X \upharpoonright n) - Km(X \upharpoonright n) \rightarrow \infty$$

This notion was studied by Schnorr and Fuchs [SF77], who used the term *superlearnable* to refer to the failure of being *Km-deep*. In particular, Schnorr and Fuchs proved that a sequence is superlearnable if and only if it is Martin-Löf random with respect to a computable measure. Given that a sequence is weakly deep if and only if it is not Martin-Löf random with respect to a computable measure, we have the following.

Theorem 29. $X \in 2^\omega$ is *Km-deep* if and only if X is *weakly deep*.

REFERENCES

- [BDM23] Laurent Bienvenu, Valentino Delle Rose, and Wolfgang Merkle. Relativized depth. *Theoretical Computer Science*, 949:113694, 2023.
- [BDNM15] Laurent Bienvenu, Rodney G. Downey, André Nies, and Wolfgang Merkle. Solovay functions and their applications in algorithmic randomness. *Journal of Computer and System Sciences*, 81(8):1575–1591, 2015.

- [Ben95] Charles H. Bennett. Logical depth and physical complexity. In *The Universal Turing Machine A Half-Century Survey*, pages 207–235. Springer, 1995.
- [BHPS14] Laurent Bienvenu, Rupert Hölzl, Christopher P. Porter, and Paul Shafer. Randomness and semi-measures. preprint, arXiv:1310.5133, 2014.
- [BP12] Laurent Bienvenu and Christopher P. Porter. Strong reductions in effective randomness. *Theoretical Computer Science*, 459:55–68, 2012.
- [BP16] Laurent Bienvenu and Christopher P Porter. Deep classes. *Bulletin of Symbolic Logic*, 22(2):249–286, 2016.
- [DMN17] Rod Downey, Michael McInerney, and Keng Meng Ng. Lowness and logical depth. *Theoretical Computer Science*, 702:23–33, 2017.
- [HP17] Rupert Hölzl and Christopher P Porter. Randomness for computable measures and initial segment complexity. *Annals of Pure and Applied Logic*, 168(4):860–886, 2017.
- [JLL94] David W Juedes, James I Lathrop, and Jack H Lutz. Computational depth and reducibility. *Theoretical Computer Science*, 132(1-2):37–70, 1994.
- [Kau91] Steven M. Kautz. *Degrees of random sequences*. PhD thesis, Cornell University, 1991.
- [KHMS11] Bjørn Kjos-Hanssen, Wolfgang Merkle, and Frank Stephan. Kolmogorov complexity and the recursion theorem. *Transactions of the American Mathematical Society*, 363(10):5465–5480, 2011.
- [Lev73] Leonid A Levin. On the notion of a random sequence. In *Soviet. Math. Dokl.*, volume 14, pages 1413–1416, 1973.
- [Lev84] Leonid Levin. Randomness conservation inequalities; information and independence in mathematical theories. *Information and Control*, 61:15–37, 1984.
- [Lev13] Leonid Levin. Forbidden information. *Journal of the ACM*, 60(2):9, 2013.
- [LZ70] L. A. Levin and A. K. Zvonkin. The complexity of finite objects and the basing of the concepts of information and randomness on the theory of algorithms. *Uspehi Mat. Nauk*, 25(6(156)):85–127, 1970.
- [MS17] Philippe Moser and Frank Stephan. Depth, highness and dnr degrees. *Discrete Mathematics & Theoretical Computer Science*, 19(special issue FCT’15), 2017.
- [MSU98] Andrei A Muchnik, Alexei L Semenov, and Vladimir A Uspensky. Mathematical metaphysics of randomness. *Theoretical Computer Science*, 207(2):263–317, 1998.
- [Nie09] André Nies. *Computability and randomness*, volume 51. Oxford University Press, 2009.

- [SF77] Claus-Peter Schnorr and P Fuchs. General random sequences and learnable sequences.
The Journal of Symbolic Logic, 42(3):329–340, 1977.

APPENDIX A. PROOF OF LEMMA 3

Working towards the proof of Lemma 3, we first establish the following result.

Lemma 30. *Let E be a computable function which maps every string to a finite set of strings. For every time bound t , there exists a time bound s such that for every $\sigma \in 2^{<\omega}$ and every $\tau \in E(\sigma)$:*

$$K^s(\sigma) + K^s(\tau \mid \sigma) \leq^+ K^t(\sigma, \tau).$$

Proof. Given the computable time bound t , t' be a computable time bound such that $2^{-K^t} \leq^{\times} \mathbf{m}^{t'}$ as guaranteed by Lemma 1(iii). Let p be the conditional discrete semimeasure defined by

$$p(\tau \mid \sigma) = \frac{\mathbf{m}^{t'}(\sigma, \tau)}{\sum_{\rho \in E(\sigma)} \mathbf{m}^{t'}(\sigma, \rho)}$$

when $\tau \in E(\sigma)$ and $p(\tau \mid \sigma) = 0$ otherwise (note that a conditional discrete semimeasure $p(\cdot \mid \cdot)$ must satisfy the condition that $p(\cdot \mid \sigma)$ is a discrete semimeasure for each $\sigma \in 2^{<\omega}$). It is clear that p is indeed a conditional discrete semimeasure and that it is computable. The denominator in this expression $q(\sigma) := \sum_{\rho \in E(\sigma)} \mathbf{m}^{t'}(\sigma, \rho)$ is also a computable discrete semimeasure since $\sum_{\sigma} q(\sigma) \leq \sum_{\sigma} \sum_{\rho} \mathbf{m}^{t'}(\sigma, \rho) \leq \sum_{\sigma} \sum_{\rho} \mathbf{m}(\sigma, \rho) \leq 1$.

We thus have the identity

$$\mathbf{m}^{t'}(\sigma, \tau) = p(\tau \mid \sigma) \cdot q(\sigma)$$

with p, q computable discrete semimeasures. By Lemma 1, there is a computable time bound s' such that $p, q \leq \mathbf{m}^{s'}$ and thus

$$\mathbf{m}^{t'}(\sigma, \tau) \leq \mathbf{m}^{s'}(\tau \mid \sigma) \cdot \mathbf{m}^{s'}(\sigma).$$

Then by our initial assumption on t and t' , we have

$$2^{-K^t(\sigma, \tau)} \leq^{\times} \mathbf{m}^{s'}(\tau \upharpoonright \sigma) \cdot \mathbf{m}^{s'}(\sigma).$$

Finally, by Theorem 2, as there is a computable time bound s such that $\mathbf{m}^{s'} \leq^{\times} 2^{-K^s}$, we have

$$2^{-K^t(\sigma, \tau)} \leq^{\times} 2^{-K^s(\tau \upharpoonright \sigma)} \cdot 2^{-K^s(\sigma)}.$$

The lemma follows by taking the negative logarithm of this inequality. \square

We can now prove Lemma 3. The (i) \rightarrow (ii) implication is immediate. For the (ii) \rightarrow (i) implication, suppose X is a sequence and h a computable increasing function such that

$$K^t(X \upharpoonright h(n)) - K(X \upharpoonright h(n)) \geq^+ n$$

for any time bound t . If $k \in [h(n), h(n+1))$, we have

$$(2) \quad K(X \upharpoonright k) \leq^+ K(X \upharpoonright h(n)) + K(X \upharpoonright [h(n), k] \mid X \upharpoonright h(n)).$$

We now apply the previous lemma with $\sigma = X \upharpoonright h(n)$, $\tau = X \upharpoonright [h(n), k]$ and E the map such that, on input ρ , checks whether ρ has length $h(n)$ for some n and if so returns all strings whose length is between 0 and $h(n+1) - h(n)$ (otherwise $E(\rho)$ is empty). The lemma gives us a computable time bound s such that

$$(3) \quad K^s(X \upharpoonright h(n)) + K^s(X \upharpoonright [h(n), k] \mid X \upharpoonright h(n)) \leq^+ K^t(X \upharpoonright k).$$

Putting (2) and (3) together, and using the fact that $K(X \upharpoonright [h(n), k] \mid X \upharpoonright h(n)) \leq K^s(X \upharpoonright [h(n), k] \mid X \upharpoonright h(n))$, it follows that:

$$(4) \quad K^t(X \upharpoonright k) - K(X \upharpoonright k) \geq^+ K^s(X \upharpoonright h(n)) - K(X \upharpoonright h(n)) \geq^+ n.$$

This being true for all n and all $k \in [h(n), h(n+1))$, we have

$$(5) \quad K^t(X|k) - K(X|k) \geq^+ h^{-1}(k),$$

and thus X is order-deep.

Finally, the (ii) \leftrightarrow (iii) equivalence can be established using Lemma 1(iii) and Theorem 2.