

# Toujours plus haut, Toujours plus loin ou Thingsat un véhicule de recherche pour l'expérimentation in-vivo ouverte de l'Internet des Objets par Satellite




LIG (Didier Donsez, Olivier Alphand, Florent Dobler, Leo Cordier),  
CROMA (Tan Phu Vuong, Nhu Huan NGuyen, Vincent Grennerat)  
CSUG (Thierry Sequies, Mathieu Barthelemy, Jean-Louis Monin, Estelle Moraux)


# L'Internet des Objets

## Des objets connectés omniprésents

### Libelium Smart World



# Architecture d'un réseau pour l'IoT



# Internet des Objets et Temps Fréquence

- Applications
  - Suivi d'assets (logistique, bétail, vol ...)
  - Geo fencing
  - Datation d'événement
  - Opérations sur calendrier



invoia, tractive ...



invoia



abeeway



SoluM KeyCo



adeunis



scooter



LR1110 GNSS + Wifi  
LoRa tracker



making of Une cuvée concentrée grâce à un tri minutieux : 28


dossier 42  
**Le high-tech investit la viticulture**

# Internet des Objets et Temps Fréquence (suite)

Cœur de réseau (au sein du datacentre)



Stations de base (Gateway, eNB)

- Datation d'événement RX ( $\sim\mu\text{s}$ ,  $\sim\text{ns}$ )
  - TDOA
- Programmation d'une émission TX ( $\sim\mu\text{s}$ ,  $\sim\text{ns}$  sur PPS GNSS)
  - Sync NB-IoT
  - LoRaWAN beacon classe B
  - diffusion de temps



# Internet des Objets et Temps Fréquence (suite)


- LoRa (868, 2400) et GNSS RTK



N.Palix, D. Donsez @ Grenoble + Col du Lautaret

<https://hal.science/hal-04786259>


[https://github.com/i2hm/micro\\_climate\\_station/tree/main/kicad/lc29h\\_mikrobus](https://github.com/i2hm/micro_climate_station/tree/main/kicad/lc29h_mikrobus)



JM Friedt @ Corbel, Svalbard

## GPSJam GPS/GNSS Interference Map

<https://gpsjam.org/?lat=45.59926&lon=32.14739&z=4.1>



# Guerre électronique / Electronic Warfar

## Bouillage et Leurrage GNSS



A Russian Krasukha-4 jamming station was captured in Ukraine in March  
 The Russian Krasukha-4 is designed to jam low-orbit signals, drones and missiles



A Russian R-330ZH Zhitel station used to jam GPS signals

# Guerre électronique / Electronic Warfar Bouillage et Leurrage GNSS


<https://www.gps.gov/cgsic/meetings/2024/humphreys.pdf>




Russia may be pursuing a radical escalation of EW:  
A nuclear-powered interference source in space. [Project Ekipazh.](#)

# Exemple de leurrage GPS dans un réseau LoRaWAN (station de base et suiveur GPS)

Grenoble, 220m, 14/02/2020 → Svalbard, 8849m, 24/12/2019




# Technologies de communication sans fil pour l'IoT




# LoRa® vs LoRAWAN


- LoRa® : Technologie Radio LPWAN
  - Définit la couche physique d'une pile réseau : LoRa PHY
- LoRaWAN : un protocole réseau “sur” LoRa 
  - Définit la couche MAC (Medium Access Control)



# Modulation




# Modulation LR-FHSS





# Modulation LoRa

## Robustesse au Bruit



# Low-Power and Long Range WAN

Example: Elsys ELT2 (LoRa endpoint with temperature sensor)

- Battery lifetime from **6** to **18** years (**1 temp. msg/hour**)



Sample time	Sensor	Battery capacity
3600	ELT2 HP	2700
Seconds	Select Elsys sensor	Capacity(mAh)


Battery performance  
80  
Performance(%)

Spreading factor

SF7  SF8  SF9  SF10  SF11  SF12

**Result:**

The battery will last for **6.2** years\*. The sensor will draw **40**µA and **351**mAh in one year.



Sample time	Sensor	Battery capacity
3600	ELT2 HP	2700
Seconds	Select Elsys sensor	Capacity(mAh)


Battery performance  
80  
Performance(%)

Spreading factor

SF7  SF8  SF9  SF10  SF11  SF12

**Result:**

The battery will last for **18** years\*. The sensor will draw **14**µA and **120**mAh in one year.



# Low-Power and Long Range WAN



<https://www.elsys.se/en/battery-life-calculator/#>

<https://avbentem.github.io/airtime-calculator/ttn/eu868/13.12>

[https://demo.iot.imag.fr/d/ems/ems?orgId=1&var-deviceName=ELSYS\\_EMS\\_B1C0\\_PERRET\\_SSE&from=now-7d&to=now](https://demo.iot.imag.fr/d/ems/ems?orgId=1&var-deviceName=ELSYS_EMS_B1C0_PERRET_SSE&from=now-7d&to=now)

# Low-Power and Long Range WAN however Low Throughput

Duty cycle and airtime


AS923 AU915 AU915 DL CN470 EU868 IN865 KR920 US915 US915 DL

## EU863-870 uplink and downlink

overhead size<sup>i</sup>

payload size<sup>i</sup>


-	13	+	-	12	+
---	----	---	---	----	---



data rate	DR6	DR5	DR4	DR3	DR2	DR1	DR0
airtime	30.8 ms	61.7 ms	113.2 ms	205.8 ms	411.6 ms	823.3 ms	1,482.8 ms
1% max duty cycle	3.1 sec	6.2 sec	11.3 sec	20.6 sec	41.2 sec	82.3 sec	148.3 sec
	1,167 msg/hour	583 msg/hour	318 msg/hour	174 msg/hour	87 msg/hour	43 msg/hour	24 msg/hour

1% for g  
1% for g1  
10% for g4

# Low-Power and Long Range WAN



[https://demo.iot.imag.fr/d/ems/ems?orgId=1&var=deviceName=ELSYS\\_EMS\\_B1C0\\_PERRET\\_SSE&from=now-7d&to=now](https://demo.iot.imag.fr/d/ems/ems?orgId=1&var=deviceName=ELSYS_EMS_B1C0_PERRET_SSE&from=now-7d&to=now)

# Low-Power and Long Range WAN


Example: Elsys ELT2 (LoRa endpoint with temperature sensor)

- Mont-Blanc → Strasbourg 300 kms (Eclipse IoT Days 2018)




# Low-Power and Long Range WAN

PER 41% @ SF7BW125 Tx 2dBm (1.58 mW) airtime=62ms  
 109 Kms → FSPL=131.80 dB @ 868 MHz



# Mais beaucoup de zones “blanches” sur la planète



Couverture cellulaire et wifi <http://unwiredlabs.com/coverage>

# What is Direct-to-Satellite IoT ?





Figure from [Fraire et Al, « Space-Terrestrial Integrated Internet of Things: Challenges and Opportunities ». IEEE Communications Magazine 60, n° 12 (décembre 2022)]

# Glacier monitoring



# Transport maritime



(He + N pressure and level, GPS, 4G, LPGAN)

# I2HM (Internet of things and artificial Intelligent for Health monitoring) <https://i2hm.github.io/>

Application : Microclimate sensors for Malaria surveillance

- Malaria (WHO, 2021)
  - **247 million cases** worldwide
  - **619,000 deaths** : 25% attributed to environmental factors
- Surveillance (IoT)
  - low cost and low tech LoRaWAN weather stations for collecting environmental data
- Prediction/prevention (IA ML)
  - Machine (Deep) Learning for predicting and alerting in case of Malaria epidemic hotspots
- Sites (covered by terrestrial LoRaWAN gateways or sat)
  - Yaoundé (Cameroun), Niamey (Niger)
  - **Remote areas of African countries are badly covered by terrestrial networks**




# Volcanologie

Des volcans et des hommes


près de 50% de la population mondiale à moins de 31 km d'un volcan  
et environ 80% dans un rayon de moins de 60 km

Prévision des événements catastrophiques

Surveillance dans la caldera du volcan



mesure du **radon** et **gaz** (HCl, H<sub>2</sub>, CO et SO<sub>2</sub>)




[https://www.uca.fr/medias/fichier/gauthier\\_1664460585717-pdf](https://www.uca.fr/medias/fichier/gauthier_1664460585717-pdf)

[https://www.unisdr.org/files/15761\\_dmographieetrisquevolcanique.pdf](https://www.unisdr.org/files/15761_dmographieetrisquevolcanique.pdf)

<https://uca.hal.science/tel-03394909/>

## Test SatloT du volcan de l'Etna (Sicile)



Carte de communication Kinéis



kinéis

Carte STM32 Nucleo



Capteur de température



Batterie 5 Volt  
(7000 Ah)

Relevé GPS externe

10 sec avec un smartphone


## Test SatloT du volcan de l'Etna (Sicile)



Carte Carte de communication  
Echostar Mobile

Carte STM32 Nucleo

Carte capteurs de  
gaz (HCl, H<sub>2</sub>, CO et  
SO<sub>2</sub>)



+ batterie de 5 Volt (7000 Ah)



UNIVERSITÉ  
Clermont  
Auvergne



# Joli ! Non ?



# Smart environnement



anr<sup>®</sup>  
agence nationale  
de la recherche  
AU SERVICE DE LA SCIENCE



## Université de Grenoble-Alpes (UGA) LIG-CNRS laboratory

### Skills:

- **LpWAN technologies** (IoT satellite, LoRa, ...)
- **RTK over LoRaWAN**
- AI – Tiny ML
- Programming/use of large number of end devices



Cubesat mission



WildCount: Recognizing and counting the presence of humans and animals

Connected groundhog cage



### Developments & Experimentations

- ThingSat project
- Counting/recognition of animals – IA for birdsong
- Air Quality Station



Air quality station



OpenCollar (LR1110)

Station LORA station in Alpes




19/01/23

P 12

# Low Power **Global** Area Networks (LPGAN)

- Constellation des satellites (fat ou nano) relayant les messages de terminaux isolés
- Opérateurs LPGAN
  - Lacuna Space, Astrocast, Echostar Mobile, Kineis ...



images Lacuna space

# Low Power Global Area Networks (LPGAN)

## Exemple : Kinéis

### Connectivity provider

**20 000 active devices**


- 2-way communication
- **30-byte** messages
- Low-transmission power (**100mW**)
- Low-consumption, long-lasting batteries
- Native location via Doppler Effect
- **Miniaturized devices**



Global



IoT  
dedicated



Low  
consumption




Easy &  
Reliable

**Constellation of 8/24 cubesats**  
**400MHz (2.4GHz next)**




# “New space”: Space for the mass




# “New space”: Space for the mass

Cubesats : Agile and “affordable” LEO satellites




# The Cubesats ecosystem

- Component “off the shelf”  
(Standardized)
- Time development reduction
- Cost reduction
  - constellation
- Launch Vehicle Sharing
  - *slot & drop model*



Costs: From 500 k€ for 1U to 5 M€ for 1U




<https://www.cubesatshop.com/>  
<http://www.isispace.nl>

# Low Power Global Area Networks (LPGAN)

- Affordable Sat-IoT (LoRa, LR-FHSS, NB-IoT)
  - part of 6G architecture
- Goal
  - Miniaturized terminals
  - Affordable low power terminals
  - Affordable ground stations
  - Affordable subscription
  - License-free sat. communications (ISM bands)
  - “**Affordable**” cubesats constellations
  - Affordable and massive network of ground stations

# 6G Terrestrial and Non-Terrestrial Networks



# HAPS :


## High Altitude Pseudo Satellites | High Altitude Permanent Systems

UAV plus lourd ou plus léger que l'air

Zone blanche, emergency networks, tactical networks ...

Relai 5G  
 @ 20000-25000 m (-56.5 °c) d'altitude pendant qq semaines

Premiers tests de communication: Rwanda, Japon, Canaries ..



## for space com with LoRa + LR-FHSS

### LoRa/LR-FHSS link characterizations

- UL: Rx only LoRa sniffer
- DL: Tx only LoRa Beaconer


### LoRaWAN applications on test cases

- Repeater (with filtering)
- Store-carry-and-forwarder GW
- Time distribution synchronization (*hard discount* du LEO-PNT)
- Two-way ranging

### Test cases


- Monitoring helium bottles @ vessel (Air Liquide Maritime)
- Firm farms (Université Polynésie Française)
- Glacier temperature sensors @ Svalbard (IPEV)
- Microclimate for I2HM (Malaria @ Cameroon) UY1
- EWSS, SAR, AIS, Radio amateur SMS
- Space debris (*Beacon+Status*)

# 525-km LEO LoRa GW



## Delayed Tolerant Network


How does it work : Store-Carry & Forward LoRa frames



# Communication principles for IoT

## Delayed Tolerant Network


*CubeSat is a data « mule »*



## Delayed Tolerant Network


How it work : Store-Carry & Forward LoRa frames

*CubeSat is a data « mule »*



# Communication principles for IoT



## Delayed Tolerant Network




# Low-Power and Very Long Range WAN LoRa Experiments from High Altitude Balloon



# Very long range radio tests from HAB



# Thingsat board detail



- RPI → automotive-grade STM32 µC
- SX1302 design copy/paste on a spatial PCB
- Linux source code → RIOT-OS port
- SatRev Edge connector
- CAN Bus
- Front panel connector (Nicomatic) for testing and flashing

Semtech SX1302+SX1250: LoRa eu868 + eu433

Semtech SX1280: ism2400


# From Prototype to Flight Model

# Breadboard Model

## Nucleo + DevKit





## Engineering Model



## Flight Model






Contraintes


puissance carte électronique

taille (ex. antenne 8mm épaisseur, 10x10cm max)

# Development Platform (@ Home during Covid19)



# ThingSat FM integration into the STORK-1 Platform



# Shipping to transporter(s)

## ~~Momentum~~ then D-Orbit



# Payload #1 now in orbit

- January 13th, 2022, 15:25 UTC on SpaceX [Falcon 9 Block 5](#) Transporter 3 SSO Ride. ([Rewatch](#))
- 105 spacecrafts inside, 3 times a year, deployment over weeks





# Mission 2 : Thingsat payload #2 @ ~~SOWA-2~~ STORK-8





Launch SpaceX Falcon 9 Rideshare: ~~October 2024~~ April 2024

# Integration in April 2024

Funding : Requea; Labex Persyval, SatRev




# New space qualification : Test, Test and Test




# Mission 3 : Thingsat payload #3 @ Nymph (CSUT)

Launch 2026



# New space qualification : Test, Test and Test



VCC = 5V0

28 mA (peak 28mA at boot) in standby,

55 mA while the SX1303 is started,

70 mA during a frame reception (RX),


84 mA (peak 106 mA) during a frame transmit (TX) at 12 dBm (RFPower)

118 mA (peak 161 mA) during a frame transmit (TX) at 20 dBm (RFPower)

214 mA (peak 320 mA) during a frame transmit (TX) at 27 dBm (RFPower)

66 mA (peak 83 mA) during a frame transmit (TX) at 0 dBm (RFPower)

# Global Architecture



# ThingSat Firmware

## Requirements

- MCU STM32
- Open Source (Active community & INRIA leadership)
- Small footprint
- Multithreading
- Network drivers architecture (incl LoRaWAN)
- **Firmware Update Over The Space**



Thingsat firmware development (inherited from Thingsat @ Stork-1)

- SX1303 driver upgrading
- SX1262 driver upgrading (for LR-FHSS)
- semtech-loramac upgrading (for LR-FHSS)
- *Basic Modem porting*
- Protobuf over RS485 UP4 API
- SUIT over Protobuf over RS485 UP4 API
- Scenario engine
- TLE library (Orbital calc.) for blacklisting “sensible” earth areas
- *MEMS drivers*
- *TFLite integration*

# New Research Topics


- Firmware Update Over The Space
  - Femto containers
- (Tiny) Machine Learning @ Space
  - Cubesat attitude monitoring
- Delay tolerant routing over LEO cubesat constellation
- **Secure communications over LoRaWAN**
  - Asim crypto for DigSig (Elliptic Curves)
- **Post Quantum Cryptography (PQC)**
- **Positioning into extra-planetary cubesat swarms**
  - Tiny Atomic Clock on board (20 cm<sup>3</sup>)

Next step : Ranging into a  
satellite/HAPS swarm  
with LoRa




# Conflict GPS jamming impacting LEO satellites

<https://www.gps.gov/cgsic/meetings/2024/humphreys.pdf>



# Resilient positioning



## Broadcasted Two Way Ranging



$v=299700 \text{ km/s}$

# Resilient positioning


## Broadcasted Two Way Ranging



$v=299700 \text{ km/s}$

# Resilient positioning

## Broadcasted Two Way Ranging




$v=299700 \text{ km/s}$

# Testing Broadcasted Two Way Ranging with LoRa and Strato Balloons



# CubAClock EM then FM



<https://gricad-gitlab.univ-grenoble-alpes.fr/thingsat>



# Thingsat Partners



INSTITUT  
POLAIRE  
FRANÇAIS  
PAUL-ÉMILE VICTOR



GORGY TIME