

A three Dimensional Vector Potential Formulation for Solving Transonic Flows with Mixed Finite Elements

François Dubois, Jean-Marc Dupuy

▶ To cite this version:

François Dubois, Jean-Marc Dupuy. A three Dimensional Vector Potential Formulation for Solving Transonic Flows with Mixed Finite Elements. International symposium on finite element methods in flow problems, Jun 1986, Antibes, France. hal-04794647

HAL Id: hal-04794647 https://hal.science/hal-04794647v1

Submitted on 22 Nov 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

A THREE-DIMENSIONAL VECTOR POTENTIAL FORMULATION FOR SOLVING TRANSONIC FLOWS WITH MIXED FINITE ELEMENTS

F. DUBOIS J.M. DUPUY

CENTRE DE MATHÉMATIQUES APPLIQUÉES Ecole Polytechnique 91128 Palaiseau Cedex France We present in this paper a three dimensional extension of the work done by AMARA. We firstly recall the physical model. The iterative numerical algorithm of resolution introduces an elliptic problem which a variational formulation involving a vector potential is given in section 2. Furthermore we describe its approximation using the NEDELEC's element conforming in H (curl). Finally preliminary numerical experiment is presented in a subsonic case.

1. Potential transonic flow.

We study an inviscid fluid in stationary irrotational and isentropic evolution. With those assumptions it is known [1] that only the two physical fields density ρ and velocity \vec{u} are necessary to its description. The corresponding partial differential equations are

mass conservation (1.1) div
$$(\rho \stackrel{\rightarrow}{u}) = 0$$

no vorticity (1.2) curl $\stackrel{\rightarrow}{u} = 0$

furthermore the Bernoulli theorem can be written:

(1.3)
$$\rho = \left\{1 + \frac{\gamma - 1}{2} M_{\infty}^2 \left(1 - |\vec{u}|^2\right)^{1/\gamma - 1}\right\}$$

where M_{∞} is the upstream Mach number and γ the specific heat ratio. This problem is non-linear, and the type of the equations is mixed: elliptic in the subsonic zone and hyperbolic in the supersonic one. Moreover an entropy condition has to be added to select the physical shock waves [2,3].

The domain Ω is discretized with a triangulation T_h of finite elements (we used tetrahedrons and prisms) and the density ρ is taken to be constant in each element. The set of equations (1.1), (1.2), (1.3) is solved numerically with a fixed point technique and an artificial density [4,5].

2. Formulation of the linear problem.

In all this section we investigate the linear problem for the volocity ; so the density ρ is a fixed positive function in $L^\infty(\Omega)$.

(P)
$$\begin{cases}
(2.1) & \operatorname{div} (\rho \overrightarrow{u}) = 0 & \Omega \\
(2.2) & \operatorname{curl} \overrightarrow{u} = 0 & \Omega \\
(2.3) & \rho \overrightarrow{u} \cdot \overrightarrow{n} = g & \Gamma
\end{cases}$$

where \vec{n} is the exterior normal of the boundary Γ . Since we restrict our study to the case where both Ω and Γ are connected domains, the equation (2.1) gives the existence of a vector potential ψ [6] such that

$$(2.4) \rho \overrightarrow{u} - \operatorname{curl} \psi = 0 \Omega$$

The condition (2.3) is then equivalent to

(2.5)
$$\operatorname{div}_{\Gamma} (\psi \times \overrightarrow{n}) = g$$

where $\operatorname{div}_{\Gamma}$ is the Laplace-Beltrami divergence operator [7]. Note that the condi-

tions (2.4), (2.5) do not insure the uniqueness of a potential ψ ; it is therefore necessary to add gauge conditions [8,9] like

$$(2.6) div \psi = 0 \Omega$$

(2.7)
$$\operatorname{curl}_{\mathbf{r}} (\psi \times \overrightarrow{\mathbf{n}}) = 0 \quad \Gamma$$

• Let us introduce now some functional spaces :

H (curl) = {
$$\chi \in L^{2}(\Omega)$$
, curl $\chi \in L^{2}(\Omega)$ }

H⁰(curl) = { $\chi \in H$ (curl), $\chi \times \vec{n} = 0$ on Γ }

V = { $\chi \in H^{0}$ (curl), div $\chi = 0$ }

U = { $u \in H$ (div), div $u = 0$, $u \cdot \vec{n} = 0$ on Γ }

we know that there is some vector field $\alpha \in H^1(\Omega)$ satisfying (2.8) $\operatorname{div}_{\Gamma}(\alpha \times \vec{n}) = g$ and the problem (P) is equivalent to the variational problem

(Q)
$$\left\{ \begin{array}{c} \text{find } \phi \in V \\ \\ \text{(2.10)} \ \forall \chi \in V, \ \int_{\Omega} \frac{1}{\rho} \ \text{curl } \phi \text{ . curl } \chi \ \text{d}x = -\int_{\Omega} \frac{1}{\rho} \ \text{curl } \alpha \text{ . curl } \chi \ \text{d}x \text{ .} \end{array} \right.$$

which admits a unique solution since Poincaré inequality holds in V [6] .

3. Conformial element in H (curl).

As the continuous problem (Q) is well posed in a subspace of H (curl), a natural idea is to discretize this vector space. NEDELEC [10] proposed the following finite element (K, P_K , Σ_K) [fig.1]: K is a tetrahedron,

$$P_K = \{ \phi, \exists \alpha, \beta \in \mathbb{R}^3 , \forall x \in K , \phi(x) = \alpha + \beta \times x \}$$

$$\Sigma_K = \{ \phi.\tau, \tau \text{ is an edge of } K \} .$$

Let us introduce also the finite dimensional spaces :

$$\begin{split} & X_h &= \{ \ \phi_h \in \text{H (curl), } \forall \ \text{K} \in \mathcal{T}_h \ , \ \phi_h |_K \in \mathcal{P}_K \ \} \\ & X_h^0 &= \{ \ \phi_h \in X_h \ , \ \phi_h \times \vec{n} = 0 \ \text{on } \Gamma \ \} \\ & U_h &= \{ \ \text{curl} \ \phi_h \ , \ \phi_h \in X_h^0 \ \} \\ & H_{0,h}^1 = \{ \ v_h \in H_0^1, \ v_h \ \text{polynomial of degree 1 in each } K \in \mathcal{T}_h \ \} \end{split}$$

This was extended to prisms.

• We now focus on the boundary condition (2.8). In the continuous case the existence of α satisfying (2.8) is given by a Laplace-Beltrami problem on the manifold Γ . We discretize the boundary condition (2.8) in X_h by the relations

(3.1)
$$\sum_{\tau \in T} \alpha_{h} \cdot \tau = g_{h} \text{ (T)} \qquad \forall T \text{ triangle of } \Gamma$$

where $g_h(T)$ is constant. We just need a procedure to compute explicitly such an α_h : the edges of the triangulation lying on Γ allow to define a graph g [11] in

the set of all the vertices of Γ . Let A be a tree in this graph g [fig.2] . We choose the space $W_h(\Gamma)$ containing α_h as follow:

(3.2)
$$W_h(\Gamma) = \{ \varphi \in X_h , \varphi : \tau = 0 \text{ if } \tau \in \Gamma \cap A \text{ or } \tau \notin \Gamma \}$$
 and if
$$\int_{\Gamma} g_h d\gamma = 0 \text{ then (3.1) admits a unique solution } \alpha_h \in W_h(\Gamma).$$

 \bullet Assume now that $\alpha_{\underline{h}}$ is computed, we solve numerically the problem

$$\{Q_h\} \begin{cases} \text{find } \phi_h \in V_h \\ \forall \chi_h \in V_h , \int_{\Omega} \frac{1}{\rho} \operatorname{curl} \phi_h . \operatorname{curl} \chi_h dx = -\int_{\Omega} \frac{1}{\rho} \operatorname{curl} \alpha_h . \operatorname{curl} \chi_h dx \end{cases}$$

we have to choose the space V_h , $V_h \subset X_h^0$, in order to adapt the gauge condition (2.6) in a finite dimensional space. The constraint on V_h is to have :

(3.3) the application curl : $V_h \rightarrow U_h$ is one to one

(like in the continuous case for curl: $V \rightarrow U$). Since the kernel of curl: $X_h^0 \rightarrow U_h$ is not null, V_h must be a <u>strict</u> subspace of X_h^0 . Then if V_h is any subspace of X_h^0 satisfying (3.3), the solution ϕ (resp ϕ_h) of (Q) (resp (Q_h)) are such that the error || curl ϕ - curl ϕ_h || L^2 vanishes like h. Note that the fields ϕ and ϕ_h have no physical interpretation, furthermore it does not exist a priori any simple mathematical relation between them. NEDELEC in [12] proposed to use

$$\tilde{v}_h = \{ \phi_h \in x_h^0, \int_{\Omega} \phi_h, \forall \theta_h dx = 0 \quad \forall \theta_h \in H_{0,h}^1 \}$$

A basis of \tilde{V}_h is non local in space, and difficult to compute. For this reason we choose V_h in a purely algebrical way, following [13] and including references in an other context.

The space X_h^0 is generated by the edges of \mathcal{T}_h which are <u>not</u> lying in Γ . Consider the graph g' of the edges coupling two vertices of \mathcal{T}_h which are not on Γ (g' is a strict subset of all the edges of X_h^0), and A' a tree in this graph. Furthermore let τ' be an edge joining up one vertex of Γ and one in the interior of Ω . Then V_h , defined by

$$V_h = \{ \phi_h \in X_h^0 , \phi_h . \tau = 0 \text{ if } \tau \in A^* \text{ or } \tau = \tau^* \}$$

satisfies the condition (3.3) [fig.3].


4. Implementation.

The method described in paragraph 3 is beeing developed on the CRAY 1-S of CCVR. First results have been obtained in a subsonic case and compared with a 2D computation to validate the code [14]: from the channel of GAMM 79 workshop

[15] a 3D mesh using prisms has been generated [fig.4] (71 × 20 × 4 elements, 6879 unknowns). The linear problem is solved by a preconditioning conjugate gradient algorithm. Several preconditioning matrices have been tested. A good and cheap choise seems to be the SSOR method. The figure [fig.5] shows isomach curves on the top and the bottom of the channel for both 2D and 3D computations.

• Références.

- [1] COURANT-FRIEDRICHS, Supersonic flow and shock waves, Interscience 1948.
- [2] MORICE-VIVIAND CRAS Paris, série B, t291, 235-238, 1980.
- [3] HAFEZ-OSHER-WHITLOW, Math of Comp. 44, N°169, 1-29, 1985.
- [4] HAFEZ-SOUTH-MURMAN AIAA J 17, N°8, 1979.
- [5] AMARA, Doctoral thesis, Paris VI univ, 1983.
- [6] BENDALI-DOMINGUEZ-GALLIC, J of Math. Anal. and Appl. 107, N°2, 1985.
- [7] CHOQUET-BRUHAT, Géométrie différentielle et systèmes extérieurs, Dunod, 1968.
- [8] BERNARDI, Thèse de 3e cycle, Paris VI univ., 1979.
- [9] F.X. ROUX, personal communication.
- [10] NEDELEC, Numer Math 35, 315-341, 1980.
- [11] BERGE, Graphs and hypergraphs, North Holland, 1973.
- [12] NEDELEC, Numer Math 39, 97-112, 1982.
- [13] HECHT RAIRO Num Anal 15, N°2, 119-150, 1981.
- [14] DUBOIS in actes du 18e congrès national d'Analyse Numérique, Puy-St-Vincent, 1985.
- [15] RIZZI-VIVIAND, Notes on Numerical fluid Mechanics, Vol.3, Vieweg, 1981.






Figure 2 Example of a bouriary tree if the domain is a cube divisei in five tetrahedrons

