

# Uncertainty quantification oriented active learning for surrogates of simulators with functional outputs

Lucas Brunel, Mathieu Balesdent, Loïc Brevault, Rodolphe Le Riche, Bruno Sudret

#### ► To cite this version:

Lucas Brunel, Mathieu Balesdent, Loïc Brevault, Rodolphe Le Riche, Bruno Sudret. Uncertainty quantification oriented active learning for surrogates of simulators with functional outputs. 9th european congress on computational methods in applied sciences and engineering (ECCOMAS 2024), ECCOMAS, Jun 2024, Lisbonne, Portugal. hal-04800967

# HAL Id: hal-04800967 https://hal.science/hal-04800967v1

Submitted on 24 Nov 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License





# Uncertainty quantification oriented active learning for surrogates of simulators with functional outputs

L. Brunel<sup>1,2</sup>, M. Balesdent<sup>1</sup>, L. Brevault<sup>1</sup>, R. Le Riche<sup>2</sup> & B. Sudret<sup>3</sup> ECCOMAS, Lisbon, Portugal - 5 June 2024 -

<sup>1</sup>ONERA, Paris Saclay University, <sup>2</sup>LIMOS (CNRS, Mines Saint-Etienne and Université Clermont Auvergne), <sup>3</sup>ETH Zürich

Ce document est la propriété de l'ONERA. Il ne peut être communiqué à des tiers et/ou reproduit sans l'autorisation préalable écrite de l'ONERA, et son contenu ne peut être divulgué.

This document and the information contained herein is proprietary information of ONERA and shall not be disclosed or reproduced without the prior authorization of ONERA.

#### Introduction

 Design of complex systems (*e.g.*, aerospace vehicles) using costly simulations with functional outputs (black box functions)





- Design of complex systems (*e.g.*, aerospace vehicles) using costly simulations with functional outputs (black box functions)
- Uncertainty quantification (UQ), *i.e.*, quantify the impact of the uncertain input variables vector **u** on the outputs to help decision making (*e.g.*, positioning of thermal protections on an hypersonic vehicle)





- Design of complex systems (*e.g.*, aerospace vehicles) using costly simulations with functional outputs (black box functions)
- Uncertainty quantification (UQ), *i.e.*, quantify the impact of the uncertain input variables vector u on the outputs to help decision making (*e.g.*, positioning of thermal protections on an hypersonic vehicle)







• Compute the estimator  $\hat{q}_{\alpha}$  of the  $\alpha$ -quantile  $q_{\alpha}$  of the simulator output field  $(\alpha \in [0, 1])$ 





- Compute the estimator  $\hat{q}_{\alpha}$  of the  $\alpha$ -quantile  $q_{\alpha}$  of the simulator output field  $(\alpha \in [0, 1])$
- Scalar  $\alpha$ -quantile:

$$q_{\alpha} = \inf \left\{ y \in \mathbb{R} : \alpha \le \Pr[Y \le y] \right\}$$



Figure: Cumulative density function and 0.9-quantile





- Compute the estimator  $\hat{q}_{\alpha}$  of the  $\alpha$ -quantile  $q_{\alpha}$  of the simulator output field  $(\alpha \in [0, 1])$
- Scalar  $\alpha$ -quantile:

$$q_{\alpha} = \inf \left\{ y \in \mathbb{R} : \alpha \le \Pr[Y \le y] \right\}$$

• Extension to functional outputs: one scalar quantile per node of the mesh  ${\cal X}$ 



Figure: Cumulative density function and 0.9-quantile





- Compute the estimator  $\hat{q}_{\alpha}$  of the  $\alpha$ -quantile  $q_{\alpha}$  of the simulator output field  $(\alpha \in [0, 1])$
- Scalar  $\alpha$ -quantile:

$$q_{\alpha} = \inf \left\{ y \in \mathbb{R} : \alpha \le \Pr[Y \le y] \right\}$$

- Extension to functional outputs: one scalar quantile per node of the mesh  ${\cal X}$
- The estimation requires many runs of the costly simulator ⇒ need for surrogate modeling





Figure: Cumulative density function and 0.9-quantile



# **Dimensionality reduction (DR)**<sup>1</sup>

• Exploits the spatial/temporal/*etc.* correlation of the field to describe it with a reduced set of **latent variables** z

<sup>1</sup>L. van der Maaten et al. (2009). Dimensionality Reduction: A Comparative Review. TiCC TR 2009–005.





# **Dimensionality reduction (DR)**<sup>1</sup>

- Exploits the spatial/temporal/*etc.* correlation of the field to describe it with a reduced set of **latent variables** z
- To each **snapshot** of the output field corresponds a point in the **low-dimensional latent space**

<sup>1</sup>L. van der Maaten et al. (2009). Dimensionality Reduction: A Comparative Review. TiCC TR 2009–005.





# **Dimensionality reduction (DR)**<sup>1</sup>

- Exploits the spatial/temporal/*etc.* correlation of the field to describe it with a reduced set of **latent variables** z
- To each snapshot of the output field corresponds a point in the low-dimensional latent space
- Example (on the right): snapshots are mapped to a 1-dimensional manifold



<sup>1</sup>L. van der Maaten et al. (2009). Dimensionality Reduction: A Comparative Review. *TiCC TR 2009–005*.





Principal component analysis (PCA)<sup>2</sup>

• The mapping between the snapshots y and the latent space is **linear** 

$$\mathbf{y}(\mathbf{u}, x) = \sum_{i=1}^{N} \phi_i(x) z_i(\mathbf{u})$$

<sup>2</sup>Y. C. Liang et al. (2002). Proper Orthogonal Decomposition And Its Applications — Part I: Theory. *Journal of Sound and Vibration* 252.3.





Principal component analysis (PCA)<sup>2</sup>

• The mapping between the snapshots y and the latent space is **linear** 

$$\mathbf{y}(\mathbf{u}, x) = \sum_{i=1}^{N} \phi_i(x) z_i(\mathbf{u})$$



• Example (on the right): snapshots (top) and corresponding scaled PCA basis (bottom) of a space launcher trajectory

<sup>2</sup>Y. C. Liang et al. (2002). Proper Orthogonal Decomposition And Its Applications — Part I: Theory. *Journal of Sound and Vibration* 252.3.





Principal component analysis (PCA)<sup>2</sup>

• The mapping between the snapshots y and the latent space is **linear** 

$$\mathbf{y}(\mathbf{u}, x) = \sum_{i=1}^{N} \phi_i(x) z_i(\mathbf{u})$$



• Example (on the right): snapshots (top) and corresponding scaled PCA basis (bottom) of a space launcher trajectory

<sup>2</sup>Y. C. Liang et al. (2002). Proper Orthogonal Decomposition And Its Applications — Part I: Theory. *Journal of Sound and Vibration* 252.3.





Principal component analysis (PCA)<sup>2</sup>

• The mapping between the snapshots y and the latent space is **linear** 

$$\mathbf{y}(\mathbf{u}, x) = \sum_{i=1}^{N} \phi_i(x) z_i(\mathbf{u})$$

• Example (on the right): snapshots (top) and corresponding scaled PCA basis (bottom) of a space launcher trajectory



<sup>2</sup>Y. C. Liang et al. (2002). Proper Orthogonal Decomposition And Its Applications — Part I: Theory. *Journal of Sound and Vibration* 252.3.





• Probabilistic machine learning model



Figure: Gaussian process regression





- Probabilistic machine learning model
- The latent variables are modeled by a **Gaussian process** (GP):

 $\hat{z}_i(\cdot) \sim \mathcal{GP}\left(\mu_i(\cdot), k_i(\cdot, \cdot)\right)$ 

with  $\mu_i(\cdot)$  the mean and  $k_i(\cdot,\cdot)$  the covariance function



Figure: Gaussian process regression





- Probabilistic machine learning model
- The latent variables are modeled by a **Gaussian process** (GP):

 $\hat{z}_i(\cdot) \sim \mathcal{GP}\left(\mu_i(\cdot), k_i(\cdot, \cdot)\right)$ 

- with  $\mu_i(\cdot)$  the mean and  $k_i(\cdot, \cdot)$  the covariance function
- Comes with a "confidence" measure represented by the GP variance  $\sigma^2({\bf u},x)$



Figure: Gaussian process regression





- Probabilistic machine learning model
- The latent variables are modeled by a **Gaussian process** (GP):

 $\hat{z}_i(\cdot) \sim \mathcal{GP}\left(\mu_i(\cdot), k_i(\cdot, \cdot)\right)$ 

- with  $\mu_i(\cdot)$  the mean and  $k_i(\cdot,\cdot)$  the covariance function
- Comes with a "confidence" measure represented by the GP variance  $\sigma^2(\mathbf{u}, x)$
- Used as the latent surrogate model (LSM)



Figure: Gaussian process regression





#### Surrogate model with functional outputs







#### **Active learning**







#### UQ oriented active learning with scalar outputs

 The learning function g(·) is a compromise between points that are close to the estimated quantile q̂<sub>α</sub> (numerator) and points where the prediction variance is high (denominator)<sup>4</sup>

$$g(\mathbf{u}) = \frac{|\mu(\mathbf{u}) - \hat{q}_{\alpha}|}{\sigma(\mathbf{u})}$$
(2)

<sup>4</sup>R. Schöbi et al. (2017). Rare Event Estimation Using Polynomial-Chaos Kriging. ASCE-ASME Journal of Risk and Uncertainty in Engineering Systems, Part A: Civil Engineering 3.2. Publisher: American Society of Civil Engineers.





#### UQ oriented active learning with scalar outputs

 The learning function g(·) is a compromise between points that are close to the estimated quantile q̂<sub>α</sub> (numerator) and points where the prediction variance is high (denominator)<sup>4</sup>

$$g(\mathbf{u}) = \frac{|\mu(\mathbf{u}) - \hat{q}_{\alpha}|}{\sigma(\mathbf{u})}$$
(2)

• The sample that will be added is  $\mathbf{u}^\star$  such that

$$\mathbf{u}^{\star} = \arg\min_{\mathbf{u}} g(\mathbf{u}) \tag{3}$$

<sup>4</sup>R. Schöbi et al. (2017). Rare Event Estimation Using Polynomial-Chaos Kriging. ASCE-ASME Journal of Risk and Uncertainty in Engineering Systems, Part A: Civil Engineering 3.2. Publisher: American Society of Civil Engineers.





#### **Extension to functional outputs**

• Extension to functional outputs by taking the integral of the field over the mesh  $\mathcal{X}^5$ 

$$g(\mathbf{u}) = \int_{\mathcal{X}} \frac{|\mu(\mathbf{u}, x) - \hat{q}_{\alpha}(x)|}{\sigma(\mathbf{u}, x)} \mathrm{d}x$$
(4)

<sup>5</sup>L. Brevault et al. (2022). Active Learning Strategy for Surrogate-Based Quantile Estimation of Field Function. *Applied Sciences* 12.19. Number: 19 Publisher: Multidisciplinary Digital Publishing Institute.





#### **Extension to functional outputs**

• Extension to functional outputs by taking the integral of the field over the mesh  $\mathcal{X}^5$ 

$$g(\mathbf{u}) = \int_{\mathcal{X}} \frac{|\mu(\mathbf{u}, x) - \hat{q}_{\alpha}(x)|}{\sigma(\mathbf{u}, x)} \mathrm{d}x$$
(4)

- The sample that will be added is  $\mathbf{u}^{\star}$  such that

$$\mathbf{u}^{\star} = \operatorname*{arg\,min}_{\mathbf{u}} g(\mathbf{u}) \tag{5}$$

<sup>5</sup>L. Brevault et al. (2022). Active Learning Strategy for Surrogate-Based Quantile Estimation of Field Function. *Applied Sciences* 12.19. Number: 19 Publisher: Multidisciplinary Digital Publishing Institute.





#### UQ oriented active learning with functional outputs







• With functional outputs, the quantile might not correspond to any snapshot but rather a **composition of snapshots** 







- With functional outputs, the quantile might not correspond to any snapshot but rather a **composition of snapshots**
- To illustrate, we divide the mesh into multiple sections and measure which snapshot is the closest to the quantile for each section









 $\Rightarrow$  the quantile corresponds to a single snapshot, *i.e.*, one point in the input space

























 $\Rightarrow$  the quantile corresponds to two snapshots, *i.e.*, two points in the input space









































































 $\Rightarrow$  the entire input space contributes to the quantile





• Proposed approach compared to a **naive latin hypercube sampling** (LHS) scheme of the maximum budget and an active learning criterion based on the **maximization of the surrogate model variance** 





- Proposed approach compared to a **naive latin hypercube sampling** (LHS) scheme of the maximum budget and an active learning criterion based on the **maximization of the surrogate model variance**
- 20 repetitions for each test case and each criterion





- Proposed approach compared to a **naive latin hypercube sampling** (LHS) scheme of the maximum budget and an active learning criterion based on the **maximization of the surrogate model variance**
- 20 repetitions for each test case and each criterion
- The performance is measured through the **mean relative error** (MRE) of the estimated quantile





- Proposed approach compared to a **naive latin hypercube sampling** (LHS) scheme of the maximum budget and an active learning criterion based on the **maximization of the surrogate model variance**
- 20 repetitions for each test case and each criterion
- The performance is measured through the **mean relative error** (MRE) of the estimated quantile
- We do not solve the minimization problem (find **u**\*), we rely on a discretization of the input space





Goal: compute the 99%-quantile of

$$f(\mathbf{u}, x) = \tilde{a} \exp\left(-\frac{1}{2} \times \frac{0.5 + 0.01\tilde{a} - x}{\ln(1 + u_1)}\right)$$
(6)

with  $\tilde{a} = 1 + \sin(2nu_2)$ , n = 3.

The distribution of the uncertain variables  $\mathbf{u}$  are  $u_1 \sim \mathcal{U}(0.2, 0.4)$  and  $u_2 \sim \mathcal{U}(0, \pi)$ .

The mesh coordinate is  $x \in [0, 1]$  with 101 nodes.





With 3 regions that activate the quantile



#### Figure: Distribution in the input space

GENCE

INNOVATION

ONERA

THE FRENCH AEROSPACE LAB

RÉPUBLIQUE

FRANCAISE

Egelité Egelité





With 3 regions that activate the quantile





#### Input space for quantile oriented infill



#### Input space for variance based infill



With 3 regions that activate the quantile



Figure: Input space for quantile oriented infill



#### Figure: Convergence of the MRE



• Two-Stage-To-Orbit rocket (circular at 250 km)









- Two-Stage-To-Orbit rocket (circular at 250 km)
- The solver is the optimization of the trajectory







- Two-Stage-To-Orbit rocket (circular at 250 km)
- The solver is the optimization of the trajectory
- $u_1 \sim \mathcal{N}(0, 1)$  is a perturbation of the **specific impulse** of the first stage (measure of the engine performance) and  $u_2 \sim \mathcal{N}(0, 0.05)$  is a perturbation of the **pitch over angle**







- Two-Stage-To-Orbit rocket (circular at 250 km)
- The solver is the optimization of the trajectory
- $u_1 \sim \mathcal{N}(0, 1)$  is a perturbation of the **specific impulse** of the first stage (measure of the engine performance) and  $u_2 \sim \mathcal{N}(0, 0.05)$  is a perturbation of the **pitch over angle**
- 99%-quantile: flight envelope for safety purposes









#### Figure: Distribution in the input space

Figure: Snapshots and quantile







 $\Rightarrow$  -11% median MRE at cost 10 and -7% at cost 20 over a naive LHS







• The proposed strategy behavior is as expected **adding samples in areas of the inputs space that contribute the most to the quantile** or that bear a large variance, and it appears to be beneficial









- The proposed strategy behavior is as expected **adding samples in areas of the inputs space that contribute the most to the quantile** or that bear a large variance, and it appears to be beneficial
- We cannot simply transpose scalar active learning strategies to simulators with functional outputs







- The proposed strategy behavior is as expected **adding samples in areas of the inputs space that contribute the most to the quantile** or that bear a large variance, and it appears to be beneficial
- We cannot simply transpose scalar active learning strategies to simulators with functional outputs
- The effectiveness of our method is **highly dependent on which parts of the input space compose the quantile**, considering that the exact quantile is not known *a priori*







 Apply the method on other test cases (of increased dimensionality and complexity), in particular cases with varying quantile structure to better understand the effectiveness of the proposed method







#### **Future works**

- Apply the method on other test cases (of increased dimensionality and complexity), in particular cases with varying quantile structure to better understand the effectiveness of the proposed method
- Extend it to **multi-fidelity** simulators to take advantage of the lower computational cost of lower-fidelity simulators





Thank you for listening! Any questions?

www.onera.fr

With 5 regions that activate the quantile



#### Viscous free fall

-

Liberti Égaliti Fraterniti

RÉPUBLIQUE FRANÇAISE



ONERA

THE FRENCH AEROSPACE LAB

1

AGENCE

INNOVATION DÉFENSE





#### Viscous free fall





- · Adds samples where we want them again
- Ecart moins important que sur le cas analytique
- Quand ce sera animé analyser l'ordre dans lequel les points sont ajoutés
- · Le critère variance est moins intéressant qu'un LHS naif



