



**HAL**  
open science

## Memory for repeated auditory textures

Berfin Bastug, Vani Rajendran, Roberta Bianco, Trevor Agus, Maria Chait,  
Daniel Pressnitzer

► **To cite this version:**

Berfin Bastug, Vani Rajendran, Roberta Bianco, Trevor Agus, Maria Chait, et al.. Memory for repeated auditory textures. 2024. hal-04801538

**HAL Id: hal-04801538**

**<https://hal.science/hal-04801538v1>**

Preprint submitted on 25 Nov 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Memory for repeated auditory textures

Berfin Bastug<sup>1,2</sup>, Vani Rajendran<sup>1,3</sup>, Roberta Bianco<sup>4,5</sup>, Trevor Agus<sup>6</sup>, Maria Chait<sup>5</sup>, & Daniel Pressnitzer<sup>1</sup>

1- Laboratoire des systèmes perceptifs, Département d'études cognitives, École normale supérieure, PSL University, CNRS, 75005 Paris, France.

2- Ernst Strüngmann Institute for Neuroscience in Cooperation with Max Planck Society, Frankfurt am Main 60528, Germany

3- Institute of Neurobiology, National Autonomous University of Mexico, Campus Juriquilla, Querétaro, Qro 76230, México

4- Neuroscience of Perception & Action Lab, Italian Institute of Technology, Viale Regina Elena 291, 00161 Rome, Italy

5- UCL Ear Institute, 332 Gray's Inn Rd London WC1X 8EE, UK

6- School of Arts, English and Languages, Queen's University Belfast, University Road, Belfast BT7 1NN

**Declarations of interest:** none

**Corresponding authors:** Berfin Bastug ([berfin.bastug@esi-frankfurt.de](mailto:berfin.bastug@esi-frankfurt.de)) & Daniel Pressnitzer ([daniel.pressnitzer@ens.psl.eu](mailto:daniel.pressnitzer@ens.psl.eu))

1  
2  
3  
4  
5  
6  
7  
8  
9  
10

# Highlights

- Individual exemplars of natural auditory textures can be memorized when repeated.
- For long exemplars, the corresponding memory traces are likely based on temporally-local features.
- Temporally-local features can co-exist with time-averaged summary statistics in the representations of natural textures.
- Auditory cognition can flexibly recruit multi-scale representations of complex sounds, shaped by task demands and fine-tuned through rapid plasticity

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29

## **Abstract**

Even though memory plays a pervasive role in perception, the nature of the memory traces left by past sounds is still largely mysterious. Here, we probed the memory for natural auditory textures. For such stochastic sounds, two types of representations have been put forward: a representation based on sets of temporally-local features or a representation based on time-averaged summary statistics. We synthesized naturalistic sound texture exemplars and used them in an implicit memory paradigm based on repetition, previously shown to induce rapid learning for artificial stochastic signals such as white noise. On the one hand, if the brain represented natural texture exemplars only as time-averaged summary statistics, then repetition detection and learning should all but vanish for longer exemplar durations. On the other hand, if the learning of repeated noise and repeated textures relied on similar processes, presumably involving temporally-local features, then results should be similar for noise and natural textures. Results were highly similar for artificial and natural sounds, showing an effect of duration on baseline repetition detection performance but little to no effect on learning afforded by repeated exposure. Thus, naturalistic texture exemplars were amenable to learning when repeated exposure was available. This finding is consistent with two interpretations: the existence of a special processing mode when acoustic repetition is involved, to which textures are not immune; or a convergence of the feature set versus summary statistics description of sound representations if a continuum of time scales is considered.

## 30 **1. Introduction**

31           Auditory perception must combine the acoustic information reaching the ears at every  
32 moment in time with information from the past, stored in memory. This is obviously the case  
33 when rapidly recognizing sounds that have acquired meaning through exposure, such as for  
34 instance one’s own ringtone (Royer et al., 2010). More generally, a pervasive role of memory in  
35 perception is at the core of current theories based on predictive coding, which assume that a  
36 model of the world has been somehow internalized through experience (Heilbron & Chait, 2018;  
37 Lange et al., 2018). The nature of the memory traces left by past sounds, however, is still largely  
38 mysterious. Here, we probe the memory for natural auditory textures. For such stochastic sounds,  
39 two types of representations have been put forward: a representation based on temporally-local  
40 features (Agus & Pressnitzer, 2021), or a representation based on time-averaged summary  
41 statistics (McDermott et al., 2013).

42           The temporally-local features hypothesis stems from a line of research that characterized  
43 the perception of repeated sounds. When hearing a repeated exemplar of white noise, listeners  
44 report the emergence of individual events, often described as “rasping” or “clanks” (Guttman &  
45 Julesz, 1963; Warren et al., 2001). Subsequent experiments have confirmed that the features used  
46 to detect repetition in white noise generally seem to have a local time-frequency support  
47 (Kaernbach, 1993; Ringer et al., 2023). Recently, the technique has been extended to longer-term  
48 memory traces. When listeners were exposed to the same exemplar of white noise which  
49 reoccurred several times during an experimental block, behavioral evidence of a “memory for  
50 noise” lasting up to several weeks was observed (Agus et al., 2010; Viswanathan et al., 2016).  
51 As the duration of the learnt noise exemplars extended to the multi-second range, it seemed  
52 unreasonable that listeners memorized the thousands of samples defining one particular noise  
53 exemplar. Rather, as was the case for the immediate repetition of noise, it was hypothesized that  
54 listeners stored a limited set of temporally-local features, which could be used as a compact  
55 identifier for a given noise exemplar (Agus et al., 2010). Neural correlates of the phenomenon  
56 were consistent with the feature set hypothesis, with the added proposal that feature sets could be  
57 at least partly idiosyncratic and thus unique to each listener/noise combination (Andrillon et al.,  
58 2015; Luo et al., 2013; Ringer et al., 2023). Finally, similar findings were obtained with  
59 stochastic sounds other than white noise, such as random melodies (Bianco et al., 2020, 2023),  
60 random rhythms (Kang et al., 2017), or tone clouds with a broad range of spectro-temporal

61 complexities (Agus & Pressnitzer, 2021). Rapid plasticity was even evidenced with repeated  
62 exposure to noise exemplars during sleep (Andrillon et al., 2017). This all suggests that  
63 repetition automatically triggers the rapid formation of memory traces for many kinds of sounds.

64 The summary statistics hypothesis stems from work on auditory textures (McDermott et  
65 al., 2013; McDermott & Simoncelli, 2011). Such textures are natural sounds with stochastic but  
66 stationary characteristics, such as the sound of fire crackling, water flowing, or wind blowing.  
67 The first important finding was that synthetic sounds matched in certain long-term statistics to  
68 natural sounds, as extracted from an auditory model, were readily identified as natural sound  
69 textures by listeners (Geffen et al., 2011; McDermott & Simoncelli, 2011). This showed that  
70 summary statistics were sufficient to recognize textures. Perhaps even more intriguingly, when  
71 asked to discriminate between two exemplars of the same texture (e.g., two instances of fire  
72 crackling), listeners' performances *decreased* as the exemplar durations increased. This seems  
73 counter-intuitive, as for many other tasks, longer durations usually result in improved  
74 discrimination performance (Teng et al., 2016). However, such a seemingly paradoxical finding  
75 could be understood if the discrimination was based on time-averaged summary statistics, and  
76 not on temporally-local features that could be accrued as duration increased. To quote  
77 McDermott et al. (2013, abstract): "*These results indicate that once these sounds are of*  
78 *moderate length, the brain's representation is limited to time-averaged statistics, which, for*  
79 *different examples of the same texture, converge to the same values with increasing duration*".  
80 Similar results were observed with random melodies, whereby listeners could estimate the mean  
81 frequency of a melody without precise reports of the frequencies or temporal position of  
82 individual tones (Piazza et al., 2012, but see Bianco et al., 2020). Thus, summary statistics for  
83 textures could be the auditory equivalent of "ensemble coding" for visual perception, which is an  
84 efficient way to capture the gist of natural images (Whitney & Leib, 2016).

85 At face value, the logical consequence of the summary statistics hypothesis is that  
86 different exemplars of the same texture cannot be memorized, simply because they cannot be  
87 discriminated in the first place. Thus, unlike other stochastic sounds or even tone clouds with  
88 similar spectro-temporal statistics, repeated exposure to a texture exemplar should not trigger  
89 any memory trace specific to that exemplar. As suggested by Nelken & de Cheveigné (2013),  
90 this stark difference could be because the auditory system may enter a "texture mode" when it  
91 recognizes one. Indeed, it makes much more sense to recognize the physical cause of a texture

92 (McDermott et al., 2013; McDermott & Simoncelli, 2011) or even some of its characteristics,  
93 such as temperature for flowing water (Velasco et al., 2013), than to recall the acoustic details of  
94 a given texture exemplar. Auditory cognition may thus be tuned to efficient representations of  
95 natural sounds and their statistical properties (Gervain & Geffen, 2019) to facilitate the  
96 categorization of the physical events making up our environment (Traer et al., 2021). However,  
97 an alternative to this “textures are special” idea is that “repetition is special”, in that repetition  
98 may trigger powerful plasticity phenomena able to overcome or complement the summary  
99 statistics code. This possibility is experimentally tested here. We synthesized naturalistic sound  
100 textures using the original McDermott & Simoncelli algorithm (2011) and used them in the  
101 “memory for noise” paradigm of Agus et al. (2010), based on repetition.

## 102 **2. Methods**

### 103 *2.1. General procedure*

104 All experiments were performed online, as data collection took place during the  
105 pandemic. The method was otherwise identical to the original “memory for noise” study (Agus  
106 et al., 2010). Briefly, in such a paradigm, each trial consists of a single sound: either noise (N), or  
107 repeated noise (RN), that is, noise for which the first half is identical to the second half. The  
108 repetition is seamless, with no acoustic cue nor silent interruption between halves. The  
109 participant’s task is to report whether the trial contained a repeat or not. For some trials, the RN  
110 is randomly drawn anew, so participants only hear each RN stimulus once. Such a condition taps  
111 into short-term memory processes and provides a baseline repetition-detection performance,  
112 which may depend on various stimulus parameters such as duration (Kaernbach, 2004; Warren et  
113 al., 2001). However, without informing the participants, a third condition is introduced: one RN  
114 exemplar called the reference RN (RefRN), reoccurs over different trials throughout an  
115 experimental block. An improved performance for RefRN trials compared to RN trials is  
116 interpreted as learning of the RefRN exemplar.

117 The stochastic stimuli used here were white noise, replicating previous studies, but we  
118 also introduced natural textures. Three texture categories were chosen: fire crackling (Fire),  
119 water running down a stream (Stream), and wind blowing (Wind). Texture trials (Tx) were all  
120 different and generated as in McDermott & Simoncelli (2011). Repeated textures (RTx) and  
121 reference repeated texture (RefRTx) trials were obtained by cross-fading two copies of a same

122 texture exemplar. Illustrations of the stimuli are shown in Figure 1. As can be seen, even though  
123 the choice of texture was largely arbitrary, they all differed in their spectro-temporal  
124 characteristics, which in turn differed from white noise.

125 Different trial durations were tested on different experimental blocks: 250 ms, 500 ms,  
126 1000 ms, 2000 ms, and 4000 ms. For the RN/RTx and RefRN/RefRTx conditions, this  
127 corresponded to exemplar durations of 125 ms, 250 ms, 500 ms, 1000 ms, and 2000 ms,  
128 respectively. Testing different duration was critical as the summary statistics hypothesis predicts  
129 that the representation of longer textures will converge to the same statistics within a texture  
130 category, thus making the task harder.

### 131 2.2. *Participants*

132 72 individuals (13 female), aged between 18 and 38 ( $M = 29.7$   $SD = 1.66$ ), with self-  
133 reported normal hearing participated in the online experiment in return for monetary  
134 compensation. This corresponded to 18 participants per texture, similar to the number of  
135 participants in previous comparable in-lab studies. The sample size was preregistered (see  
136 below). Participants were recruited through Prolific (Oxford, UK). Before the experiment, all  
137 participants provided informed consent. At the end of the experiment, an online debriefing text  
138 was presented. The UCL Research Ethics Committee approved the protocol (#1490/009).

### 139 2.3. *Stimuli*

140 Because generating naturalistic textures can be computationally intensive, they were  
141 synthesized offline and stored as sound files, which were loaded to the participant's browser  
142 during the experiment. The synthesis algorithm was the one from McDermott and Simoncelli  
143 (2011) as available online (<http://mcdermottlab.mit.edu/downloads.html>). In total, 9 sound files  
144 with a different random seed, each 392 s long, were synthesized for each of the three categories  
145 of natural sound textures. For symmetry, 9 sound files, also 392 s long, were generated for white  
146 noise. Each of the 36 unique sound files (9 random seeds x 4 sound types) was used twice, but  
147 always for different participants. To generate a trial, short exemplars of the desired duration were  
148 cut sequentially (no overlap between exemplars) from the 392 s-long sounds. For repeated trials  
149 (RN/RTx and RefRN/RefRTx), the same exemplar was collated twice, with a 10-ms crossfade.  
150 For non repeated trials (N/Tx), two different exemplars were collated, with the same crossfade  
151 technique.



#### 152 2.4. Procedure

153 The experiment was conducted using the Gorilla platform (Cambridge, UK). Before  
154 starting the experiment, several checks were run to ensure data quality, including browser checks  
155 and headphone checks (Milne et al., 2021). Individuals who failed any of these checks were  
156 rejected from participating, so all participants are assumed to have been wearing headphones.  
157 Participants were then presented with an information sheet and gave their informed consent.

158 Each participant completed five experimental blocks, each of which corresponded to a  
159 different exemplar duration, all for the same sound type. Each participant was thus only tested on  
160 one sound type (e.g. White noise or Fire). Each block was preceded by a brief familiarization  
161 phase with feedback. The participant first heard a sound with 10 repetitions of a given exemplar,  
162 to illustrate the cues to repetition at the duration of the block. This familiarization sound could be  
163 played up to three times. Then, four training trials were provided. In the training trials, the  
164 stimulus either consisted of an exemplar repeated 10 times or of 10 different exemplars.  
165 Participants were instructed to report whether they heard a repetition. Immediate feedback was  
166 given. Further training trials followed, with gradually increasing difficulty. Those training trials  
167 contained 4 repetitions (10 trials), 3 repetitions (12 trials), and finally 2 repetitions as in the main  
168 experiment (20 trials). Training trials were always 50% RN/RTx and 50% N/Tx (no  
169 RefRN/RefRTx). The training session was immediately followed by the experimental block at  
170 the same duration. Unlike for training, participants did not receive immediate feedback but did  
171 see their cumulative accuracy (percent correct) at the end of each block. Each block consisted of  
172 40 N/Tx trials, 20 RN/RTx trials, and 20 RefRN/RefRTx trials, with those conditions presented  
173 in a pseudorandom order (Ref stimuli were never presented on successive trials).

174 Participants were incentivized through bonus payments that would be calculated based on  
175 their overall accuracy at the end of the experiment (Bianco et al., 2021). Finally, participants  
176 were also informed that their data would be rejected if they scored less than 60% accuracy on the  
177 task to discourage participants from guessing at random.

#### 178 2.5. Statistical Analyses


179 We used the  $d'$  sensitivity index of signal detection theory to estimate performance. Hits  
180 were defined as “repeated” responses for RN/RTx and RefRN/RefRTx trials. False alarms were  
181 defined as “repeated” responses for N/Tx trials. When the proportion of hits or false alarms

182 reached 0 or 1 for a given participant and measurement, a correction corresponding to plus or  
183 minus half-a-trial was applied (Macmillan & Creelman, 2004).

184 Analyses of variance (ANOVAs) and *t*-tests were used as inferential tests, with an  $\alpha$ -  
185 level of 0.05. Reporting convention follows the APA guidelines, 7<sup>th</sup> edition, so all *p*-values less  
186 than 0.001 are reported as  $p < 0.001$ . The main analysis was a mixed-design ANOVA, fully  
187 reported in Table A1. Because the false alarm rate was shared between RN/RTx and  
188 RefRN/RefRTx condition, which could have introduced correlations across measurements, the  
189 ANOVAs and the paired *t*-tests contrasting conditions were performed on the z-transformed hit  
190 rates used to compute *d'* (Agus & Pressnitzer, 2021). We further checked that performing the  
191 same analyses on *d'*, so z-transformed hit rates minus z-transformed false alarms, led to strictly  
192 identical conclusions. A Greenhouse-Geisser correction was applied when Mauchly's test  
193 indicated a violation of the sphericity assumption ( $p < 0.05$ ). Further partial ANOVAs and *t*-  
194 tests were run to help interpret the main analysis, as it included several factors and revealed  
195 second- and third-order interactions. The partial ANOVAs used repeated-measures or mixed-  
196 design ANOVAs as appropriate. When performing partial analyses where all natural textures  
197 were considered together, and because different participants ran different texture blocks, a  
198 "participant" was defined as the average of individual results in the three natural texture blocks,  
199 in order of enrolment. All ANOVAs were run using JASP (JASPTeam, 2024). Effect sizes are  
200 reported as generalized  $\eta^2$ , notated  $\eta^2_G$ , as recommended for mixed designs (Lakens, 2013, p. 6).

## 201 2.6. Preregistration and data availability


202 The study was preregistered (ResearchBox #2762). There were minor deviations to the  
203 preregistration: the noise sound category was added for comparison; the hit-rate over time  
204 analyses were omitted due to the large number of conditions; the ANOVAs were run on z(hits)  
205 and not *d'* as justified above; partial ANOVAs were added to interpret the outcome of the full  
206 analysis. The main characteristics of the design (sample size, exclusion criteria, duration  
207 conditions, test procedure, main analyses) exactly followed the preregistration. The full dataset is  
208 available online (ResearchBox #2762).



**Figure 1: Acoustic characteristics of white noise and natural textures.** Illustrative examples of cochleagrams for the four different sound categories. The time-frequency cochleagrams use brighter colors to represent energy within simulated auditory filters. In all cases, repeated trials are shown, so the first 500-ms are identical to the last 500-ms. Note that there is no acoustic discontinuity at the repetition onset. The temporal waveforms (top inset of each panel) and spectral average (right inset of each panel) are also provided.

209        2.7. *Acoustic analyses*

210            Illustration of the stimuli are provided in Figure 1. Stimuli were passed into an auditory  
 211 model as described in Agus et al. (2012), which consisted of a broadband pre-emphasis bandpass  
 212 filter (0.4-8.5 kHz), a gammatone auditory filterbank, half-wave rectification, square root  
 213 compression, and low-pass filtering at 100 Hz. Such a time-frequency representation, termed a  
 214 “cochleagram”, is intended to roughly mimic the information available after peripheral auditory  
 215 processing.



**Figure 2: Performance for 500-ms long exemplars. A). White noise.** Repetition detection performance is shown, expressed as the  $d'$  sensitivity index of signal detection theory. For the Repeated Noise condition (RN), the noise exemplar was novel in each trial. For the Reference Repeated Noise condition (RefRN), the same noise exemplar re-occured on 20 trials randomly interspersed in the experiment. Dots represent individual participants, connected by thin lines across conditions. Mean performance and standard error about the mean are shown as thick lines. **B). Natural textures.** Performance averaged for the three natural textures. Same as A).

## 216 3. Results

### 217 3.1. Validation of the online testing procedure

218 So far, all studies using variants of the “memory for noise” paradigm but one (Dauer et  
 219 al., 2022) were performed under highly controlled laboratory conditions. It was thus unclear  
 220 whether the findings, presumably dependent on subtle acoustic cues, would be robust enough to  
 221 translate to online testing.

222 Figure 2A shows the average results for the 0.5-s duration, for white noise, as this is the  
 223 duration condition that was most extensively tested in previous investigations. Performance is  
 224 expressed as the sensitivity index  $d'$  of signal detection theory. Baseline performance for the  
 225 within-trial repetition detection task RN, for which the repeated noise exemplar was novel on  
 226 each trial, was modest but still above chance ( $M = 0.67$ ;  $t$ -test against the chance value of  $d' = 0$ :  
 227  $t(17) = 5.54$ ,  $p < 0.001$ ). Importantly, in the RefRN condition for which the same noise exemplar  
 228 re-occured throughout a block, performance improved ( $M = 2.06$ ; paired  $t$ -test against RN

229 performance  $t(17) = 5.40, p < 0.001$ ). This pattern of results replicates in-lab findings using  
230 white noise (Agus et al., 2010; Agus & Pressnitzer, 2013), validating the online procedure.


231 Figure 2B shows the first set of results using natural textures, again for the 0.5-s duration,  
232 with performance for all three texture categories. For these relatively short-duration texture  
233 exemplars, performance was generally higher than for noise. In the baseline RTx condition,  
234 performance was well above chance ( $M = 2.07$ ;  $t$ -test against the chance value of 0:  $t(17) =$   
235  $13.67, p < 0.001$ ). In the RefRTx condition, performance further improved ( $M=2.74$ ; paired  $t$ -test  
236 against RTx performance  $t(17) = 5.64, p < 0.001$ ). This shows that within-trial repetition  
237 detection and across-trial learning are possible with relatively short texture exemplars.

### 238 3.2. Repetition detection and rapid learning for short and long texture durations

239 The main prediction of the summary statistics hypothesis is that texture exemplars should  
240 become more similar as their duration increases. Therefore, if performance on the memory for  
241 noise task relies on summary statistics, it should markedly decrease as texture duration increases.

242 With the durations tested here, this is not what was observed. Figure 3 shows the results  
243 for white noise and textures, as a function of exemplar duration (remember that trial duration  
244 itself was twice as long). For noise, there was a steady decrease in performance in the RN  
245 condition from short to long durations, but, importantly, the performance gain observed for  
246 RefRT was approximately constant across the whole range of durations. For textures,  
247 performance in the RTx condition was always good (average  $d'$  above 1), but had a band-pass  
248 shape with a peak at 250 ms. Importantly, again, the performance advantage for RefTx was  
249 observed throughout the whole range of durations.

250 These observations were formally tested by two separate repeated-measures ANOVAs,  
251 one for noise and one for textures, with factors “Condition” (2 levels, RN and RefRN for noise  
252 or RTx and RefRTx for textures) and “Duration” (5 levels, [125, 250, 500, 1000, 2000] ms). For  
253 noise, significant effects of Condition ( $F(1,17) = 44.81, p < 0.001, \eta^2_G = 0.32$ ) and Duration  
254 ( $F(4,68) = 11.14, p < 0.001, \eta^2_G = 0.18$ ) were observed, without any interaction between the two  
255 factors ( $F(4,68) = 1.42, p = 0.24, \eta^2_G = 0.03$ ). Similar findings were obtained with textures, with  
256 significant effects of Condition ( $F(1,17) = 470.4, p < 0.001, \eta^2_G = 0.47$ ) and Duration  
257 ( $F(2.53,46.0.6) = 14.28, p < 0.001, \eta^2_G = 0.23$ ). For textures, there was a significant interaction  
258 between Condition and Duration, with a small effect size ( $F(3.28,55.68) = 5.00, p = 0.003, \eta^2_G =$




**Figure 3: Effect of exemplar duration.** **A).** **White noise.** Mean performance across participants is shown for the RN and RefRN conditions, as a function of exemplar duration. Error bars represent standard error about the mean. **B).** **Natural textures.** Performance averaged for the natural textures. Same as A.).

259 0.09). Overall, the ANOVAs confirm that, while duration affected performance, the advantage  
 260 provided by repeated exposure to a same exemplar was about constant for all durations, for both  
 261 noise (RefRN vs RN) and textures (RefTx vs RTx).

262 Finally, for textures, post-hoc tests were run to compare each data point with all others,  
 263 using a conservative Bonferroni correction (45 comparisons). We only report the crucial tests for  
 264 the summary statistics hypothesis, namely the possible advantage of RefTx over RTx, reflecting  
 265 learning of the texture exemplar. At all tested durations, including the longest ones, a significant  
 266 effect of RefTx was observed over RTx (all Bonferroni-corrected  $p < 0.001$ , except for 125 ms  
 267 for which  $p = 0.003$  and 250 ms for which  $p = 0.002$ ).

### 268 3.3. Effect of sound categories

269 To investigate in further detail whether the different texture categories influenced  
 270 performance, a mixed-design ANOVA was run with factors “Condition” (2 levels, RN/RTx and  
 271 RefRN/RefRTx), “Duration” (5 levels, [125, 250, 500, 1000, 2000] ms), and “Sound category”  
 272 (4 levels, White noise, Fire, Stream, Wind). This main analysis is reported in full details in the  
 273 Appendix, Table A1. To summarize, all main effects were significant ( $p < 0.001$ ). The two-way  
 274 interactions Condition \* Duration and Texture \* Duration, as well as the three-way interaction



**Figure 4: Effect of sound categories. A).** Learning was assessed by computing the sensitivity increase due to repeated exposure. The memory gain was defined as performance for the trials where sound exemplars re-occurred across 20 trials (RefRN/RefTx) minus performance where sound exemplars were novel on each trial (RN/RTx) **B).** Performance for the within-trial repetition detection task (RN/RTx)

275 Condition \* Texture \* Duration, were also significant ( $p = 0.003$  or less), with relatively small  
 276 effect sizes ( $\eta^2 = 0.05$  or less).

277 To help interpret the effect of sound category in relation to our question of interest, the  
 278 memory for natural textures, we transformed the data to directly estimate the amount of learning  
 279 that was afforded by repeated exposure to a sound exemplar. To this effect, we computed a  
 280 “memory gain”, defined as performance for the trials where the sound exemplar re-occurred  
 281 throughout a block (RefRN/RefTx) minus performance where sound exemplars were novel on  
 282 each trial (RN/RTx). The memory gain obtained for the different sound categories and durations  
 283 is displayed in Figure 4A. Even though the results were somewhat noisy, there was no trend for a  
 284 smaller gain at longer texture durations, nor for a systematic advantage of white noise over natural  
 285 textures, which would both be predictions of the summary statistics for natural textures hypothesis.

286 A mixed-design ANOVA was performed on the memory gain with factors “Duration” (5  
 287 levels, [125, 250, 500, 1000, 2000] ms), and “Sound category” (4 levels, White noise, Fire, Stream,  
 288 Wind). An effect of Duration was observed, although with a small effect size ( $F(4,272) = 5.04$ ,  $p$   
 289  $< 0.001$ ,  $\eta^2_G = 0.05$ ), suggesting that the memory gain was in fact larger for longer durations.  
 290 Crucially, no effect of Sound category was found ( $F(3,68) = 2.21$ ,  $p = 0.10$ ,  $\eta^2_G = 0.02$ ). The



291 Duration \* Sound category was significant, with a medium effect size ( $F(12,272) = 2.57, p = 0.003,$   
292  $\eta^2_G = 0.08$ ).

293 Finally, for completeness, we examined the baseline performance for individual sound  
294 categories in the immediate repetition detection task, so for the conditions RN/RTx. The results  
295 are shown in Figure 4B. The breaking-up of the data into sound categories revealed that the peak  
296 at 250 ms observed in the mean texture data (see Fig. 3B) was due to the Fire and Stream textures,  
297 as the Wind texture rather displayed a peak at 1000 ms.

298 A mixed-design ANOVA was performed on the performance in the RN/RTx condition  
299 only, with factors “Duration” (5 levels, [125, 250, 500, 1000, 2000] ms), and “Sound category” (4  
300 levels, White noise, Fire, Stream, Wind). Like for the memory gain analysis, an effect of Duration  
301 was observed ( $F(4,272) = 24.14, p < 0.001, \eta^2_G = 0.19$ ). Unlike for the memory gain analysis, this  
302 time an effect of Sound category was observed ( $F(3,68) = 17.68, p < 0.001, \eta^2_G = 0.21$ ). The  
303 Duration \* Sound category was also significant ( $F(12,272) = 3.88, p < 0.001, \eta^2_G = 0.10$ ).

304 A post-hoc comparison of all data points for Figure 4B was performed (Duration \* Sound  
305 category interaction). Briefly, possibly because of large number of comparisons, the robustness of  
306 the pattern of performance seen in Figure 4B could not be confirmed. In particular, the apparent  
307 peaks in performance at 250 ms for Fire and Stream and at 1000 ms for Wind were not significantly  
308 different from their neighbors (Table A2). So, whereas there were differences across sound  
309 categories, pinpointing them to specific durations and textures would require further experimental  
310 data.

311 In summary, these analyses show that the texture type can influence baseline repetition-  
312 detection performance, in terms of overall performance but also in terms of performance change  
313 with exemplar durations. However, all sound categories produced about the same amount of  
314 memory gain for all durations tested. Importantly, there was no difference between noise and  
315 natural textures for the memory gain. In particular, no clear advantage of noise, which produced  
316 the amount of memory gain expected from previous studies, was found over natural textures,  
317 which produced sizeable memory gains even at the longest durations tested.



## 318 **4. Discussion**

319 Combining ideas and techniques from two different lines of research, we applied a  
320 “memory for noise” paradigm to natural auditory textures. Two different predictions were made  
321 based on the putative representation of natural textures. If natural textures were only represented  
322 as time-averaged summary statistics, then repetition-detection and learning should be impossible  
323 for longer exemplar durations, because all texture exemplars should be represented by virtually  
324 identical summary statistics. However, if the rapid plasticity mechanisms induced by repeated  
325 exposure were able to complement the summary statistics representation by temporally-local  
326 features, unique to each exemplar, then results should be similar for white noise and natural  
327 textures.

328 The experimental findings strongly supported the second hypothesis. Results replicated  
329 previous findings for white noise, showing an effect of duration on baseline repetition detection  
330 performance but little to no effect on learning afforded by repeated exposure. Incidentally, this  
331 confirmed that the presumably subtle acoustic features required to memorize different noise  
332 exemplars were available in an online setting (Dauer et al., 2022). For natural textures, results  
333 were highly similar. Importantly, in spite of differences across sound categories in baseline  
334 immediate repetition-detection, a similar amount of learning with repeated exposure was  
335 observed for all sound categories tested.

### 336 *4.1. Texture discrimination versus texture repetition detection*

337 It is useful at this point to provide more details about the experimental data that led to the  
338 original formulation of the summary statistics hypothesis (McDermott et al., 2013). The crucial  
339 finding was from McDermott et al.’s Experiment 2. Participants heard three different sounds in  
340 each trial. All sounds were from the same natural texture category (e.g. Fire). Two of them were  
341 acoustically identical, whereas the third one was a different exemplar from the same texture  
342 category. Participants had to indicate the odd one out. Exemplar durations ranged from 40 ms to  
343 2500 ms. Performance decreased with duration, from about 90% correct at 40 ms down to about  
344 75% correct at 2500 ms. This decrease showed that texture exemplars were perceived as more  
345 and more similar with duration, and this was interpreted by remarking that summary statistics  
346 converged towards their mean value for the texture category as duration increased.

347 Here, we used the exact same texture generation algorithm and tested exemplar durations  
348 over a similar range. A difference between the two studies, however, is that in the original  
349 texture discrimination paradigm, there was no immediate repetition of texture exemplars  
350 (McDermott et al., 2013). All sounds within a trial were surrounded by silent gaps. Here, within-  
351 trial repetitions were seamless. Could this account for the different outcomes, as repetition  
352 regularity (Rajendran et al., 2016) and predictability (Dauer et al., 2022) have been shown to  
353 modulate noise learning? This is a possibility, but with caveats. First, because of the trial  
354 structure of the texture discrimination task, there was always a direct repeat of the texture  
355 exemplars (the odd-one-out was either the first or the last sound of a trial). Second, the exact  
356 value of the inter-stimulus interval made no difference to the findings of McDermott et al.  
357 (2013). Finally, noise learning can occur even with non-contiguous repetition (Andrillon et al.,  
358 2015; Bianco et al., 2020; Kaernbach, 2004; Ringer et al., 2023), although in these experiments  
359 the gaps were not silent. Noise learning has also been observed without immediate repetitions  
360 and intervening silences, albeit less reliably than when there are immediate repetitions (Agus &  
361 Pressnitzer, 2013).

362 Perhaps a more critical difference is that texture exemplars were never presented more  
363 than twice in the original texture discrimination paradigm, as new exemplars were used on each  
364 trial. Here, the reference texture exemplars re-occurred over 20 trials, randomly interspersed  
365 within an experimental block. We suggest that this is the main difference between the two  
366 paradigms: the amount of exposure to a given texture exemplar.

#### 367 *4.2. Repetition is special?*

368 Given the similarity between the learning patterns for noise and textures, as well as  
369 similarities with previous results with tone clouds of comparable spectro-temporal complexity  
370 (Agus & Pressnitzer, 2021), it appears that the memory processes induced by repetition  
371 generalized to natural textures.

372 There are several speculative arguments suggesting that repetition should be special for  
373 the auditory modality. From an ecological point of view, it is not obviously possible to actively  
374 search “back in time” for additional information once a sound has ended, unlike for visual search  
375 (Demany et al., 2010; Garnier-Allain et al., 2023). Thus, the auditory system may have evolved  
376 to be exquisitely tuned to repetitions, as they provide a unique opportunity to re-examine

377 auditory cues with a deeper level of processing. Also, scene elements that reoccur likely indicate  
378 an agent in the environment that may be behaviorally significant. Finally, in a predictive coding  
379 framework, events that repeat in the past may reasonably be attributed to a higher-than-baseline  
380 probability of repeating in the future, so repeated sounds should be expected to alter neural  
381 processing in such a framework (Baldeweg, 2006). Perhaps relatedly, repetitions have been  
382 shown to actually change the very perceptual qualities of sound, such as in the speech-to-song  
383 illusion (Deutsch et al., 2011), which, interestingly, also generalizes to natural textures (Rowland  
384 et al., 2019).

385         Thus, one interpretation of the present findings is that repetition “overcame” the default  
386 processing mode for textures. If the detailed acoustic information could be initially preserved for  
387 at least the duration of the exemplar, 2000ms in our case, then an immediate repeat could be  
388 detected and the “repetition mode” recruited. This could then result in complementing the well-  
389 established summary statistics representation of natural textures, used in texture class  
390 recognition, with temporally-local features, useful to memorize unique exemplars. Such a  
391 mechanism could be related to auditory scene analysis processes, creating foreground events  
392 emerging from the background texture when repetition is involved (McDermott et al., 2011). The  
393 possibility of different processing modes for natural textures was floated in the original studies  
394 (McDermott et al., 2013; Nelken & de Cheveigné, 2013). The present data provides experimental  
395 support for the idea.

#### 396         4.3. *Time scales of representation*

397         Another possible interpretation relies on a loose interpretation of the feature set versus  
398 summary statistics dichotomy. The core difference between the two possible representations is  
399 the time scale over which features versus statistics are estimated. Thus, there could be an overlap  
400 between the two notions if auditory representations could be based on multiple or even flexible  
401 temporal time scales.

402         There is a large and growing body of evidence suggesting the auditory system represents  
403 sounds over different time scales, from behavioral (Divenyi, 2004; Teng et al., 2016) or neural  
404 (Albouy et al., 2020; Joris et al., 2004; Norman-Haignere et al., 2022) findings. The details of the  
405 underlying theories differ on important points, such as whether all time scales within the possible  
406 range are available simultaneously, whether they depend on the task and context (McWalter &

407 McDermott, 2019), or whether a limited number of fixed windows exist to encode fine and  
408 coarse details (Teng et al., 2016). However, all accounts suggest that short and long time scales  
409 for features/statistics may coexist in auditory representation of complex sounds.

410         Given such findings, the boundary between a relatively long-duration feature and a  
411 relatively short-duration statistics becomes blurry. Thus, instead of a dichotomy in kind, we  
412 suggest that the features versus statistics distinction may better be thought of in terms of a  
413 continuum over different time scales. To come back to the present findings, when presented with  
414 repeating sounds, the auditory systems could trigger plasticity mechanisms that require a  
415 compact but distinctive representation of the sound exemplar being repeated. This representation  
416 could be viewed as a feature set, or as a collection of short summary statistics. Note that such an  
417 interpretation also applies to the original texture discrimination findings, where performance  
418 decreased with duration but, importantly, still remained above chance even for the longest  
419 textures. In this task, a single repeat of a texture exemplar was available, so it may have been  
420 able to trigger the memory for distinctive features/statistics in at least in a subset of trials.

## 421 **5. Conclusion**

422         We have shown that naturalistic texture exemplars are amenable to learning when  
423 repeated exposure is available. In this respect, natural textures join the growing list of stochastic  
424 sounds that behave surprisingly similarly in a “memory for noise” paradigm. This main finding  
425 is consistent with two interpretations: the existence of a special processing mode when acoustic  
426 repetition is involved, to which textures are not immune; or a convergence of the feature set  
427 versus summary statistics description of sound representations, if a continuum of time scales is  
428 considered.

429         To conclude, whereas the computational appeal of summarizing a texture to its statistics  
430 is obvious, one may wonder what use there could be to store the detailed acoustic features of a  
431 given exemplar? It could be that such a finding is simply the by-product of powerful plasticity  
432 mechanisms triggered by repetition, which are useful to generate sparse representations of  
433 meaningful sounds (Gervain & Geffen, 2019; Wang et al., 2020). We speculate that, more  
434 generally, it is the sign of the auditory system adapting its very processing to the statistical  
435 peculiarities of its environment, even before the subsequent inferential processes required to  
436 recognize natural sound categories.

437 **Appendix A. Supplemental statistical reporting.**

438 **Table A1.** Results of the main mixed-design ANOVA on the full dataset.

**Within Subjects Effects**

| Cases                           | Sphericity Correction | Sum of Squares      | df                  | Mean Square        | F                   | p                   | $\eta^2_G$ |
|---------------------------------|-----------------------|---------------------|---------------------|--------------------|---------------------|---------------------|------------|
| Condition                       | None                  | 102.212             | 1.000               | 102.212            | 228.180             | < .001              | 0.260      |
| Condition * Category            | None                  | 2.968               | 3.000               | 0.989              | 2.209               | 0.095               | 0.010      |
| Residuals                       | None                  | 30.460              | 68.000              | 0.448              |                     |                     |            |
| Duration                        | None                  | 31.668 <sup>a</sup> | 4.000 <sup>a</sup>  | 7.917 <sup>a</sup> | 21.986 <sup>a</sup> | < .001 <sup>a</sup> | 0.098      |
|                                 | Greenhouse-Geisser    | 31.668              | 3.442               | 9.201              | 21.986              | < .001              | 0.098      |
| Duration * Category             | None                  | 16.000 <sup>a</sup> | 12.000 <sup>a</sup> | 1.333 <sup>a</sup> | 3.703 <sup>a</sup>  | < .001 <sup>a</sup> | 0.052      |
|                                 | Greenhouse-Geisser    | 16.000              | 10.325              | 1.550              | 3.703               | < .001              | 0.052      |
| Residuals                       | None                  | 97.944              | 272.000             | 0.360              |                     |                     |            |
|                                 | Greenhouse-Geisser    | 97.944              | 234.032             | 0.419              |                     |                     |            |
| Condition * Duration            | None                  | 6.868               | 4.000               | 1.717              | 5.043               | < .001              | 0.023      |
|                                 | Greenhouse-Geisser    | 6.868               | 3.612               | 1.901              | 5.043               | 0.001               | 0.023      |
| Condition * Duration * Category | None                  | 10.565              | 12.000              | 0.880              | 2.586               | 0.003               | 0.035      |
|                                 | Greenhouse-Geisser    | 10.565              | 10.837              | 0.975              | 2.586               | 0.004               | 0.035      |
| Residuals                       | None                  | 92.599              | 272.000             | 0.340              |                     |                     |            |
|                                 | Greenhouse-Geisser    | 92.599              | 245.634             | 0.377              |                     |                     |            |

Note. Sphericity corrections not available for factors with 2 levels.

Note. Type III Sum of Squares

<sup>a</sup> Mauchly's test of sphericity indicates that the assumption of sphericity is violated ( $p < .05$ ).

439

**Between Subjects Effects**

| Cases     | Sum of Squares | df | Mean Square | F      | p      | $\eta^2_G$ |
|-----------|----------------|----|-------------|--------|--------|------------|
| Category  | 45.467         | 3  | 15.156      | 14.834 | < .001 | 0.135      |
| Residuals | 69.477         | 68 | 1.022       |        |        |            |

Note. Type III Sum of Squares

440

441 **Assumption Checks**

**Test of Sphericity**

|                      | Mauchly's W | Approx. X <sup>2</sup> | df | p-value | Greenhouse-Geisser $\epsilon$ | Huynh-Feldt $\epsilon$ | Lower Bound $\epsilon$ |
|----------------------|-------------|------------------------|----|---------|-------------------------------|------------------------|------------------------|
| Duration             | 0.761       | 18.169                 | 9  | 0.033   | 0.860                         | 0.912                  | 0.250                  |
| Condition * Duration | 0.796       | 15.187                 | 9  | 0.086   | 0.903                         | 0.960                  | 0.250                  |

442

443 **Table A2.** Selected post-hoc comparisons for Figure 4B, showing the comparisons of peak  
 444 values to their neighbors for the natural textures. Due to the high number of comparisons, the  
 445 lenient Holm correction was applied.

446

**Post Hoc Comparisons - Texture \* Duration**

|             |             | Mean Difference | SE    | t      | p <sub>holm</sub> |
|-------------|-------------|-----------------|-------|--------|-------------------|
| Fire, 125   | Fire, 250   | -0.477          | 0.187 | -2.552 | 1.000             |
| Stream, 125 | Stream, 250 | -0.161          | 0.187 | -0.861 | 1.000             |
| Fire, 250   | Fire, 500   | 0.572           | 0.187 | 3.062  | 0.281             |
| Stream, 250 | Stream, 500 | 0.214           | 0.187 | 1.148  | 1.000             |
| Wind, 500   | Wind, 1000  | -0.026          | 0.187 | -0.139 | 1.000             |
| Wind, 1000  | Wind, 2000  | 0.190           | 0.187 | 1.019  | 1.000             |

*Note.* P-value adjusted for comparing a family of 190

447

448 **CRedit authorship**

449 Berfin Bastug: Conceptualization; Formal Analysis; Investigation; Methodology; Validation;  
450 Visualization; Writing – original draft; Writing – review & editing.

451 Vani Rajendran: Conceptualization; Investigation; Methodology; Supervision; Writing – original  
452 draft; Writing – review & editing.

453 Roberta Bianco: Conceptualization; Methodology; Writing – review & editing.

454 Trevor Agus: Formal Analysis; Writing – review & editing.

455 Maria Chait: Conceptualization; Methodology; Writing – review & editing

456 Daniel Pressnitzer: Conceptualization; Formal Analysis; Methodology; Supervision;

457 Visualization; Writing – original draft; Writing – review & editing.

458

459 **Funding**

460 Roberta Bianco was funded by the European Union (MSCA, PHYLOMUSIC, 101064334). Maria

461 Chait was partly supported by BBSRC project grant BB/P003745/1. Daniel Pressnitzer was partly

462 supported by grants ANR-17-EURE-0017 and ANR-22-CE28- 0023-01.

463

## 464 6. References

- 465 Agus, T. R. & Pressnitzer, D. (2013). The detection of repetitions in noise before and after  
466 perceptual learning. *The Journal of the Acoustical Society of America*, 134(1), 464–473.  
467 <https://doi.org/10.1121/1.4807641>
- 468 Agus, T. R. & Pressnitzer, D. (2021). Repetition detection and rapid auditory learning for  
469 stochastic tone clouds. *The Journal of the Acoustical Society of America*, 150(3), 1735.  
470 <https://doi.org/10.1121/10.0005935>
- 471 Agus, T. R., Suied, C., Thorpe, S. J. & Pressnitzer, D. (2012). Fast recognition of musical sounds  
472 based on timbre. *The Journal of the Acoustical Society of America*, 131(5), 4124–10.  
473 <https://doi.org/10.1121/1.3701865>
- 474 Agus, T. R., Thorpe, S. J. & Pressnitzer, D. (2010). Rapid Formation of Robust Auditory  
475 Memories: Insights from Noise. *Neuron*, 66(4), 610–618.  
476 <https://doi.org/10.1016/j.neuron.2010.04.014>
- 477 Albouy, P., Benjamin, L., Morillon, B. & Zatorre, R. J. (2020). Distinct sensitivity to  
478 spectrotemporal modulation supports brain asymmetry for speech and melody. *Science*,  
479 367(6481), 1043–1047. <https://doi.org/10.1126/science.aaz3468>
- 480 Andrillon, T., Kouider, S., Agus, T. & Pressnitzer, D. (2015). Perceptual Learning of Acoustic  
481 Noise Generates Memory-Evoked Potentials. *Current Biology : CB*, 25(21), 2823–2829.  
482 <https://doi.org/10.1016/j.cub.2015.09.027>
- 483 Andrillon, T., Pressnitzer, D., Léger, D. & Kouider, S. (2017). Formation and suppression of  
484 acoustic memories during human sleep. *Nature Communications*, 8(1), 1–15.  
485 <https://doi.org/10.1038/s41467-017-00071-z>
- 486 Baldeweg, T. (2006). Repetition effects to sounds: evidence for predictive coding in the auditory  
487 system. *Trends in Cognitive Sciences*, 10(3), 93–94. <https://doi.org/10.1016/j.tics.2006.01.010>
- 488 Bianco, R., Hall, E. T. R., Pearce, M. T. & Chait, M. (2023). Implicit auditory memory in older  
489 listeners: From encoding to 6-month retention. *Current Research in Neurobiology*, 5, 100115.  
490 <https://doi.org/10.1016/j.crneur.2023.100115>
- 491 Bianco, R., Harrison, P. M., Hu, M., Bolger, C., Picken, S., Pearce, M. T. & Chait, M. (2020).  
492 Long-term implicit memory for sequential auditory patterns in humans. *ELife*, 9, e56073.  
493 <https://doi.org/10.7554/elife.56073>
- 494 Bianco, R., Mills, G., Kerangal, M. de, Rosen, S. & Chait, M. (2021). Reward Enhances Online  
495 Participants' Engagement With a Demanding Auditory Task. *Trends in Hearing*, 25,  
496 23312165211025940. <https://doi.org/10.1177/23312165211025941>



- 497 Dauer, T., Henry, M. J. & Herrmann, B. (2022). Auditory Perceptual Learning Depends on  
498 Temporal Regularity and Certainty. *Journal of Experimental Psychology: Human Perception*  
499 *and Performance*, 48(7), 755–770. <https://doi.org/10.1037/xhp0001016>
- 500 Demany, L., Semal, C., Cazalets, J.-R. & Pressnitzer, D. (2010). Fundamental differences in  
501 change detection between vision and audition. *Experimental Brain Research*, 203(2), 261–  
502 270. <https://doi.org/10.1007/s00221-010-2226-2>
- 503 Deutsch, D., Henthorn, T. & Lapidis, R. (2011). Illusory transformation from speech to song.  
504 *The Journal of the Acoustical Society of America*, 129(4), 2245–2252.  
505 <https://doi.org/10.1121/1.3562174>
- 506 Divenyi, P. (2004). The Times of Ira Hirsh: Multiple Ranges of Auditory Temporal Perception.  
507 *Seminars in Hearing*, 25(3), 229–239. <https://doi.org/10.1055/s-2004-832857>
- 508 Garnier-Allain, A., Pressnitzer, D. & Sergent, C. (2023). Retrospective Cueing Mediates Flexible  
509 Conscious Access to Past Spoken Words. *Journal of Experimental Psychology: Human*  
510 *Perception and Performance*, 49(7), 949–967. <https://doi.org/10.1037/xhp0001132>
- 511 Geffen, M. N., Gervain, J., Werker, J. F. & Magnasco, M. O. (2011). Auditory Perception of  
512 Self-Similarity in Water Sounds. *Frontiers in Integrative Neuroscience*, 5, 15.  
513 <https://doi.org/10.3389/fnint.2011.00015>
- 514 Gervain, J. & Geffen, M. N. (2019). Efficient Neural Coding in Auditory and Speech Perception.  
515 *Trends in Neurosciences*, 42(1), 56–65. <https://doi.org/10.1016/j.tins.2018.09.004>
- 516 Guttman, N. & Julesz, B. (1963). Lower Limits of Auditory Periodicity Analysis. *The Journal of*  
517 *the Acoustical Society of America*, 35(4), 610–610. <https://doi.org/10.1121/1.1918551>
- 518 Heilbron, M. & Chait, M. (2018). Great Expectations: Is there Evidence for Predictive Coding in  
519 Auditory Cortex? *Neuroscience*, 389, 54–73.  
520 <https://doi.org/10.1016/j.neuroscience.2017.07.061>
- 521 JASPTeam. (2024). *JASP version 0.18.3* (0.18.3) [Computer software]. <https://jasp-stats.org/>
- 522 Joris, P. X., Schreiner, C. E. & Rees, A. (2004). Neural Processing of Amplitude-Modulated  
523 Sounds. *Physiological Reviews*, 84(2), 541–577. <https://doi.org/10.1152/physrev.00029.2003>
- 524 Kaernbach, C. (1993). Temporal and spectral basis of the features perceived in repeated noise.  
525 *The Journal of the Acoustical Society of America*, 94(1), 91–97. <http://pubmed.gov/8354764>
- 526 Kaernbach, C. (2004). The Memory of Noise. *Experimental Psychology*, 51(4), 240–248.  
527 <https://doi.org/10.1027/1618-3169.51.4.240>

- 528 Kang, H., Agus, T. R. & Pressnitzer, D. (2017). Auditory memory for random time patterns. *The*  
529 *Journal of the Acoustical Society of America*, 142(4), 2219–2232.  
530 <https://doi.org/10.1121/1.5007730>
- 531 Lakens, D. (2013). Calculating and reporting effect sizes to facilitate cumulative science: a  
532 practical primer for t-tests and ANOVAs. *Frontiers in Psychology*, 4, 863.  
533 <https://doi.org/10.3389/fpsyg.2013.00863>
- 534 Lange, F. P. de, Heilbron, M. & Kok, P. (2018). How Do Expectations Shape Perception? *Trends*  
535 *in Cognitive Sciences*, 22(9), 764–779. <https://doi.org/10.1016/j.tics.2018.06.002>
- 536 Luo, H., Tian, X., Song, K., Zhou, K. & Poeppel, D. (2013). Neural Response Phase Tracks How  
537 Listeners Learn New Acoustic Representations. *Current Biology*, 23(11), 1–7.  
538 <https://doi.org/10.1016/j.cub.2013.04.031>
- 539 Macmillan, N. A. & Creelman, C. D. (2004). *Detection Theory*. Psychology Press.  
540 [http://books.google.com/books/content?id=2\\_V5AgAAQBAJ&printsec=frontcover&img=1&](http://books.google.com/books/content?id=2_V5AgAAQBAJ&printsec=frontcover&img=1&zoom=1&edge=curl&source=gbs_api)  
541 [zoom=1&edge=curl&source=gbs\\_api](http://books.google.com/books/content?id=2_V5AgAAQBAJ&printsec=frontcover&img=1&zoom=1&edge=curl&source=gbs_api)
- 542 McDermott, J. H., Schemitsch, M. & Simoncelli, E. P. (2013). Summary statistics in auditory  
543 perception. *Nature Neuroscience*, 16(4), 493–498. <https://doi.org/10.1038/nn.3347>
- 544 McDermott, J. H. & Simoncelli, E. P. (2011). Sound Texture Perception via Statistics of the  
545 Auditory Periphery: Evidence from Sound Synthesis. *Neuron*, 71(5), 926–940.  
546 <https://doi.org/10.1016/j.neuron.2011.06.032>
- 547 McDermott, J. H., Wroblewski, D. & Oxenham, A. J. (2011). Recovering sound sources from  
548 embedded repetition. *Proceedings of the National Academy of Sciences*, 108(3), 1188–1193.  
549 <https://doi.org/10.1073/pnas.1004765108>
- 550 McWalter, R. & McDermott, J. H. (2019). Illusory sound texture reveals multi-second statistical  
551 completion in auditory scene analysis. *Nature Communications*, 10(1), 5096.  
552 <https://doi.org/10.1038/s41467-019-12893-0>
- 553 Milne, A. E., Bianco, R., Poole, K. C., Zhao, S., Oxenham, A. J., Billig, A. J. & Chait, M.  
554 (2021). An online headphone screening test based on dichotic pitch. *Behavior Research*  
555 *Methods*, 53(4), 1551–1562. <https://doi.org/10.3758/s13428-020-01514-0>
- 556 Nelken, I. & de Cheveigné, A. (2013). An ear for statistics. *Nature Neuroscience*, 16(4), 381–  
557 382. <https://doi.org/10.1038/nn.3360>
- 558 Norman-Haignere, S. V., Long, L. K., Devinsky, O., Doyle, W., Irobunda, I., Merricks, E. M.,  
559 Feldstein, N. A., McKhann, G. M., Schevon, C. A., Flinker, A. & Mesgarani, N. (2022).  
560 Multiscale temporal integration organizes hierarchical computation in human auditory cortex.  
561 *Nature Human Behaviour*, 6(3), 455–469. <https://doi.org/10.1038/s41562-021-01261-y>

- 562 Piazza, E. A., Sweeny, T. D., Wessel, D., Silver, M. A. & Whitney, D. (2012). Humans Use  
563 Summary Statistics to Perceive Auditory Sequences. *Psychological Science*, 24(8), 1389–  
564 1397. <https://doi.org/10.1177/0956797612473759>
- 565 Rajendran, V. G., Harper, N. S., Abdel-Latif, K. H. A. & Schnupp, J. W. H. (2016). Rhythm  
566 Facilitates the Detection of Repeating Sound Patterns. *Frontiers in Neuroscience*, 10(60),  
567 464–467. <https://doi.org/10.3389/fnins.2016.00009>
- 568 Ringer, H., Schröger, E. & Grimm, S. (2023). Within- and between-subject consistency of  
569 perceptual segmentation in periodic noise: A combined behavioral tapping and EEG study.  
570 *Psychophysiology*, 60(2), e14174. <https://doi.org/10.1111/psyp.14174>
- 571 Rowland, J., Kasdan, A. & Poeppel, D. (2019). There is music in repetition: Looped segments of  
572 speech and nonspeech induce the perception of music in a time-dependent manner.  
573 *Psychonomic Bulletin & Review*, 26(2), 583–590. <https://doi.org/10.3758/s13423-018-1527-5>
- 574 Roye, A., Schröger, E., Jacobsen, T. & Gruber, T. (2010). Is my mobile ringing? Evidence for  
575 rapid processing of a personally significant sound in humans. *The Journal of Neuroscience :  
576 The Official Journal of the Society for Neuroscience*, 30(21), 7310–7313.  
577 <https://doi.org/10.1523/jneurosci.1113-10.2010>
- 578 Teng, X., Tian, X. & Poeppel, D. (2016). Testing multi-scale processing in the auditory system.  
579 *Scientific Reports*, 6(1), 34390. <https://doi.org/10.1038/srep34390>
- 580 Traer, J., Norman-Haignere, S. V. & McDermott, J. H. (2021). Causal inference in  
581 environmental sound recognition. *Cognition*, 214, 104627.  
582 <https://doi.org/10.1016/j.cognition.2021.104627>
- 583 Velasco, C., Jones, R., King, S. & Spence, C. (2013). The Sound of Temperature. *Journal of  
584 Sensory Studies*, 28(5), 335–345. <https://doi.org/10.1111/joss.12052>
- 585 Viswanathan, J., Rémy, F., Bacon-Macé, N. & Thorpe, S. J. (2016). Long Term Memory for  
586 Noise: Evidence of Robust Encoding of Very Short Temporal Acoustic Patterns. *Frontiers in  
587 Neuroscience*, 10, 610–611. <https://doi.org/10.3389/fnins.2016.00490>
- 588 Wang, M., Liao, X., Li, R., Liang, S., Ding, R., Li, J., Zhang, J., He, W., Liu, K., Pan, J., Zhao,  
589 Z., Li, T., Zhang, K., Li, X., Lyu, J., Zhou, Z., Varga, Z., Mi, Y., Zhou, Y., ... Chen, X.  
590 (2020). Single-neuron representation of learned complex sounds in the auditory cortex.  
591 *Nature Communications*, 11(1), 4361. <https://doi.org/10.1038/s41467-020-18142-z>
- 592 Warren, R. M., Bashford, J. A., Cooley, J. M. & Brubaker, B. S. (2001). Detection of acoustic  
593 repetition for very long stochastic patterns. *Perception & Psychophysics*, 63(1), 175–182.  
594 <http://pubmed.gov/11304013>
- 595 Whitney, D. & Leib, A. Y. (2016). Ensemble Perception. *Annual Review of Psychology*, 69(1),  
596 1–25. <https://doi.org/10.1146/annurev-psych-010416-044232>

