



HAL
open science

How to improve the simulation of low flow discharges? (Use of the knowledge of low flow processes in a model)

Claire Lang Delus, Emmanuel Gille, Didier Francois

► To cite this version:

Claire Lang Delus, Emmanuel Gille, Didier Francois. How to improve the simulation of low flow discharges? (Use of the knowledge of low flow processes in a model). European Geosciences Union, General Assembly, Session HS36, Apr 2007, Wien, Österreich, Austria. hal-04821849

HAL Id: hal-04821849

<https://hal.science/hal-04821849v1>

Submitted on 5 Dec 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.


L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

"How to improve the simulation of low flow discharges? (Use of the knowledge of low flow processes in a model)"

Lang C., Gille E., François D.


I. BACKGROUND: PREVIOUS WORKS & OBJECTIVES

This research was first investigated for an applied project: the development of a daily model for low flow forecasting. The studied area is located in the East of France and 60 basins are concerned. Our objective was to use our knowledge about low flow processes in the model. In a previous work, we have showed that the results of the model can be improved especially in forecast by using recession coefficients. These were calculated from an hydrological analysis and directly put in the model to calibrate base flow coming out from the groundwater storage of the model (Lang et al., EGU 2006). The main difficulties of this stage were related to the recession parameter variability, and the way of introducing it into the model.



First the recession parameter variability (see fig.1) was palliated by using a statistical analysis to determine the "mean" recession coefficient.

Secondly the mean recession coefficient was put directly in the model to calibrate base flow coming out from the groundwater storage.




AT THE END OF THIS WORK WE HAVE FOCUSED ON TWO MAIN ASPECTS WHICH ARE THE OBJECT OF THIS POSTER

1. The variability of the recession coefficients has not been explained:

Fig. 3a: Correlation between recession coefficients and evapotranspirations: Period 1971-2003


The factors used classically to explain this variability did not give satisfactory results.



2. We have not taken into account this variability in the model:

Fig. 3b: During the 2003's recession

In the model the "mean" recession coefficient is used to simulate base flow; thus recession coefficients calculated from the simulated hydrograph are necessary constant if there is no influence of overland flow (anyway it is the condition to be in a recession period and recession coefficients are only calculated in this case).



II. RELATION BETWEEN OBSERVED PROCESSES & MODELING

PARTICULARITY IN THE RECESSION ANALYSIS

Among factors which could explain the variability of the recession coefficient (evapotranspiration, etc.) we analyzed the choice of Q_0 , i.e. the first discharge of a recession phase. Indeed, if this first discharge is badly chosen it can influence the recession coefficient value. If the first discharge chosen is too high (during recession flood) the obtained coefficient will not be representative of a recession situation (base flow has not to be mixed up with overland flow). In this case, Q_0 would be highly correlated to the recession parameter. However the choice of recession phases has been made by rigorous criteria and systematically checked. For this reason we are almost sure that the selected phases correspond only to recession periods which are not influenced by rainfall. Nevertheless relationships between Q_0 and the recession coefficients are interesting.

PARTICULARITY IN THE MODELING




The input of the "mean" recession parameter in the model gives satisfactory results. The model's efficiency is evaluated by the Nash criterion (Nash is always superior to 70% and reached for certain basins 90%). However both the analysis of the hydrograph and of the relation between simulated and observed discharges watch of the bad results for the most low flow discharges. The correlations between simulated and observed discharges have been realized and analyzed for all basins. It is interesting to note that a classification can be operated because the bad results do not concern all the basins:



High recession coefficients correspond to high Q_0 discharges.

Basins without groundwater resources

The Nash criterion is high: 83%. The graph shows a good correlation.






NO BIAS

The model shows deficiency in the simulations for permeable basins during severe low water. Simulated base flow discharges continue to decrease when observed discharges decrease slower.

High recession coefficients do not correspond necessarily to high Q_0 discharges.

Basins with groundwater resources

The Nash criterion is high too: 83%. But the correlation is bad.



BIAS

The Nash criterion is high too: 83%. But the correlation is bad.

Recession analysis conclusion:
A relation between physical features of the basins and the recession parameters has been established. High recession rates are observed in impermeable basins. Actually during recession period the river discharges correspond only to base flow. For an impermeable basin with no groundwater reservoir what do we quantify during recession period? Indeed obtained values seem more to correspond to recession flood coefficients than to recession coefficients.

Modeling conclusion:
Nash is a global criterion. To evaluate low flow simulation we have to use other criteria more specific at low flow discharges. The algorithm of the model has to be improved to correct the bad simulations for low flow discharges of permeable basins.

There are similar observations between the recession analysis and results of the low flow modeling: The low flow modeling can be improved by using these aspects (see part III).

III. HOW TO IMPROVE SIMULATIONS ?

To improve the simulations of low flow discharges we have to understand the origin of the biases to correct them. We also have to use other criteria than the only Nash criterion because this one is too global. A high value of Nash can mask important defects.

2. HYPOTHESES OF PHYSICAL EXPLANATIONS

The recession coefficient is variable because several groundwater storages are present in a basin.

In our climate long dry-spell are not frequent and in much cases the recession discharges do not represent the depletion rate of the only deep groundwater storage. It is a sum of various types of depletion (unsaturated zone, perched aquifer, deep groundwater storage, etc.).

A long time without rainfall is thus necessary before emptying every soil compartments and of reaching the "real" deep groundwater storage which has a slow recession rate.

These considerations can explain: the variability of the recession rate: there are a sum of various depletions; bad simulations during severe low flows; in our model the recession parameter is constant but it should be variable as in the reality: during severe low water it must be slower to avoid a too fast decrease of discharges.


1. SIMILAR OBSERVATIONS BETWEEN MODELING & RECESSION ANALYSIS

MODELING	RECESSION ANALYSIS
BIAS: OBSERVED DISCHARGES DECREASE LESS QUICKLY THAN SIMULATED	"VARIABILITY" OF THE RECESSION COEFFICIENT: THE ONE CAN SHOW VERY SLOW RHYTHMS OF RECESSION
SITUATION OBSERVED ONLY FOR THE LOWEST DISCHARGES	SITUATION OBSERVED DURING LONGEST AND MOST SEVERE LOW WATER

BOTH OBSERVATIONS AND MODELING SEEM TO CONCLUDE THAT THE RECESSION RATE IS MORE SLOWER DURING SEVERE LOW WATER

3. MODIFICATION OF THE MODEL TO TAKE INTO ACCOUNT THE PREVIOUS CONCLUSIONS

We add in the model a second groundwater storage called "deep groundwater storage". It must have a slower recession rate than the groundwater reservoir. During severe low flow only the deep groundwater reservoir is not empty and it produce base flow. The adding of this second groundwater reservoir must allow to reproduce the variability of the recession coefficient and to correct the bias because base flow decreases more slowly.



IV. RESULTS AND VALIDATION

CHOICE OF CRITERIA TO EVALUATE THE PERFORMANCE OF THE MODEL:



Criteria to evaluate the performance of the model have to focus on the deficiency of the model. The Nash criterion must be completed by other criteria especially adapted to low flow. We propose different criteria:

- Nash calculated from the logarithm of the values;
- Comparison of observed vs. simulated flow duration curves;
- Correlation of observed vs. simulated discharges;
- Correlation of observed vs. simulated MAM₁₀;
- Comparison of observed base flow index vs. simulated;
- Comparison of observed recession coefficients vs. simulated.

These criteria are more adapted to evaluate the low flow. The optimization of the model can be realized from certain of these criteria instead of using Nash.

VALIDATION:

First we observe that the adding of a second groundwater reservoir correct the bias previously observed (fig. 11). Indeed the deep groundwater storage avoid a too fast decrease of discharges during severe low flow. The correlation of MAM₁₀ (fig. 12) also shows good results (MAM₁₀ is a severe criterion which can be difficult to reproduce by a model). The using of two reservoirs allows also to reproduce the variability of the recession coefficient (fig. 13).



We have tested this model for impermeable basins: simulations are not improved and discharges coming out from the deep reservoir are insignificant. It is a proof of the role of the physical characteristics because for impermeable basins there is not or few groundwater resources. There is thus no reason of adding a second reservoir.

CONCLUSION: The unexplained variability of the recession coefficients has been resolved and the modeling has been improved by using the knowledge of physical processes generating the low flow.