

PRESAGES: a tool for low flow forecasting

Claire Lang Delus, Aline Freyermuth, Emmanuel Gille, Didier Francois

▶ To cite this version:

Claire Lang Delus, Aline Freyermuth, Emmanuel Gille, Didier Francois. PRESAGES: a tool for low flow forecasting. European Geosciences Union, General Assembly, Session HS5, Apr 2006, Wien, Österreich, Austria. 2006. hal-04821863

HAL Id: hal-04821863 https://hal.science/hal-04821863v1

Submitted on 5 Dec 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.





The summer 2003 hydrological drought has clearly shown the vulnerability of human activities exposed to water scarcity. Public authorities who have to monitor hydrological extremes should provide water resources assessment and forecasting tools. The objective of this research is to combine these two concerns through the development of a decision support system: PRESAGES. Low water levels generation being a long-time process, monitoring the monthly runoff production has been made with simple indicators. The long-term assessment of the worst case scenario can therefore be considered through modelling. If severe low flows may occur, short-range forecasts of daily mean discharges are proposed for the summer period.

1. CONTEXT AND OBJECTIVES



he domain of application of this study is the Rhineleuse basin in its French part (see the location map) The motivations of this research are to develop both ools to forecast and to evaluate low flows. Forecasting nd prediction tools are developed for about 60 stations even though assessment tools are applied at 108 gauging site.

The particularly long genesis of low water allows longterm prediction. Low flows prediction is so realized by mple indicators before low water period in order to ticipate the risk in hydrological drought. Long and hort-term forecasts are then proposed by using monthly and daily conceptual models. The main objective is to base all the methods on previous hydrological analyses.

Many methods have been developed to characterize treamflow drought. We prefer to favour FdF method as lassical frequency analysis because this one consider the low water duration.

2. CHARACTERIZATION AND EVALUATION OF LOW FLOWS

2.1. CHARACTERIZATION OF LOW FLOWS

The Flow-Duration-Frequency model (FdF) is used to characterize the severity of a low water. This model allows to consider the duration of low flows, from a statistical method (Galea & al.^[1] 1998; 2000). Hydrological variables concerned are the MAM for various durations « d » (1 day ≤ d ≤ 30 days). MAM used were extracted from 1971-2000 (the longest period which is common to all gauging stations). FdF is a three parameters mode



The FdF model allows determination of the non-exceedance probability of any MAM values and any durations

CARTOGRAPHIC DATA BASE



2.2. EVALUATION OF LOW FLOWS IN 2003



Example of the River MOSELLE at Epinal

livers Hydrometric stations

Sarralbe (Rec

Lay-Saint-Christop

Andlau

Vannes-le-Châte

Cheveuges

Autrey

Russ ["Wisches"

Koenigsmacke

Carignan

Montigny

Chauvency

0.017

0.949

0.546

0.155

6.547

1.255

0.219

Audun-le-Tiche



LOW FLOWS OF THE RIVER MOSELLE AT EPINAL IN 2003

The low flows of the River Moselle at Epinal in 2003 is particularly severe:

88 days have a value of discharge under the corresponding volume is

64 days under MAM(10)₅

> 23 days under MAM(10)₁₀

SCALE PARAMETER

istributions of MAM with various durations are adjusted to the two he parallelism observed betweer distributions of different durations means that a single slope can be calculated, independently from their durations. This single slope is determined by the "consolidated' standard deviation: S^c

NB: U_F are the reduced variates of Gauss corresponding to each nonexceedance probability.

FREQUENTIAL MAM(10) DATA BASE

The MAM(10) is the most representative hydrological variable of low flow because lower durations may involve anthropic influences. MAM(10)'s characteristic values of non-exceedance probabilities are calculated according to the formula of FdF model:

 $= \ln(MAM(d)) - \ln[(a \times d - 1) + 1) \times MAM(1)_2$

Characteristic non-exceedance probabilities: -F0.5 : recurrence interval 2 years -F0.2: recurrence interval 5 years -F0.1: recurrence interval 10

PRESAGES* : a tool for low flow forecasting Lang C., Freyermuth A., Gille E., François D.

tationarity and trends hydrological data:

Epinal long-term tation presents the longest time series of discharges in Moselle River catchment. The statistical treatment of the MAM(10) Mean Annual Minimum during 10 consecutive days shows 3 periods : 1953-1964, 1965-1982, 1983-2005. determined by "jumps" of (method CUSUM). The most recent period is not exceptional compared to 1953-1964, but it appears that low flows are weaker then during the 70's

median



 $MAM(d)_{u_{F}}$

 $MAM(1)_2$

z(d)=0.016(d-1)+1

LOCATION PARAMETER

MAM 1 day recurrence interval 2 years: MAM(1)

PARAMETER « a »

slope of the straight line (z(d)=a*(d-1)+1). It establishes the link between rapports of different durations of the MAM observed (MAM(d)_{ut}) and the MAM 1 day recurrence interval 2 years (MAM(1)₂). The parameter « a » represents the theoretical decrease of discharges in

periods of low flow.

MAPS OF MAM(10)'S CHARACTERISTIC FREQUENCIES

A map of each MAM(10)'s characteristic frequency is made for the Rhine-Meuse basin. These maps represent pecific discharges (I/s/km²) for all catchments (colored areas) and discharges (m³/s) at gauging stations (proportional

LOW FLOWS OF RHINE-MEUSE **BASIN RIVERS IN 2003**

This map represents specific lischarges (colored areas) and discharges (proportional symbols) of the MAM(10) at gauging stations in 2003. Return periods of the MAM(10) are epresented by the colors of the oportional symbols. They are alculated according to the FdF model equation.

The low flow in 2003 is particularly critical for most of the Rhine-Meuse rivers. Return periods of the MAM(10) are higher than 5 years and they can even exceed 10 years for a lot of gauging stations. Only catchments with human influences present recurrence intervals equal or lower than 2

3.1. SIMPLE INDICATORS FOR LOW FLOW ASSESSMENT AND TO ESTIMATE SEVERE LOW WATER RISK

I. 1. CURRENT FOLLOW-UP OF THE SITUATION BY SIMPLE INDICATORS aps about the frequency of monthly precipitations plurality; an information to monitor current situation



Follow-up of the Mean Monthly Minimum (3-day)

For each river the device proposes references values based on the Mean Monthly Minimum (3-day). So for each month a data base of following references is available:

MMM (3-day) – Median MMM (3-day) – Non-exceedance probability 0.2

MMM (3-day) – Non-exceedance probability 0.1

Current hydrological situation can be compared every month to these low frequencies.

I. 2. A simple predictor to evaluate the possibility of a risk in drought: SEPAGES* Our main motivation is to develop a simple indicator to evaluate the risk in hydrological drought. This predictor is exclusively founded on the total precipitations of winter and spring (period of recharge).

The frequencies of the total precipitations from January to June are compared with the frequencies of the minimum monthly annual discharge to determine if these two variables are related. The figures show a concomitant increase between them : The most severe low water levels, lower than a 5 years' recurrence, are often related to particularly weak winter and spring precipitations.

Many tries show that among all the frequencies of total precipitations from January to June, the frequency 0.3 (no-exceeding) best explains the severe low water levels. This threshold is thus adopted and its value is calculated for each gauging site (cf. map).

f the total precipitations observed between January and June are lower nan this threshold, the risk that a severe low water level appears is



precipitations. The SEPAGES tool is tested for the year 2003 which has been



FOOTNOTES & REFERENCES

*PRESAGES : French acronym for « PREvision et Simulation pour l'Annonce et la Gestion des Etiages Sévères » UFR SHA – Ile du Saulcy - BP 30306 – 57006 METZ *SEPAGES : French acronym for « SEuil de Précipitations pour l'Annonce et la Gestion des Etiages Sévères » E-mail: clair_lang@yahoo.fr

For low flow forecasting, cumulated precipitation recorded during the recharge period are an interesting indicator for basins having important aguifers. We propose a tool which calculates the frequency of in order to produc nths, an evaluation ations to the ones from January to June) an raws the corresponding map. Public authorities ar

Example of MMM (3-day) follow-up: The River Meuse at Vaucouleurs in 2003





period. Thus this tool only applies to the basins which have big aquifers: for the impermeable basins for example in the crystalline Vosges, the rainfall deficit of the beginning of the year can largely be compensated by abundant estival

particularly severe in France. For this year, this indicator has announced a severe low water level for all the stations. For only 16% of the cases, the low water level observed has not been particularly severe. Let's note that they are generally rivers which benefit from anthropic influences.

<u>nthly basis of groundwater discharge</u> onthly river discharges could in no case be liken to groundwater discharge

ause it is always mixed with overland flow. However, the slope of monthly harge decrease during the low flow period is related to groundwater capacity deed, all the basins in this study present the same hydrological regime but they re more or less moderate. This can be explained by geology and groundwater apacity. Thus, we propose to <u>estimate</u> the groundwater table depletion rate. arting from the decrease of monthly river discharge (see on the right)



lecreasing discharges because on o simplify and to have a



3.3. MONTHLY WATER BALANCE MODEL FOR LONG-TERM FORECASTING



- PE : potentia evapotranspirati excepted) -AE : actual evapotranspira The paramete - A : a runoff

- **B** : a maximum size of the so reservoir (in mm) C: a monthly recession parameter

assisted optimization" (Gille & al.^[3], 2003).

call that "the assisted optimization"

discharge).



« Final optimization » means that all the parameters are now optimized.

Long-term forecasting he hydrological forecast depends wholly on weather forecast. The

particularly long genesis of low water allows long-term forecasting, in he term of several months. As seasonal forecasts don't propose juantified precipitations, the models must be supplied by stochastic

The monthly model functions in continuous in the course of the year. It supplied by observed precipitations and evapotranspiration until April and after then stochastic scenarios are introduced. For each catchment, we dispose of a data base with monthly frequency precipitations and mean evapotranspiration.







f an hydrological drought may occur.

^[3] GILLE E., LANG C., 2003, Problématique d'optimisation des paramètres de calage d'un bilan hydrologique : application aux bassins versants de la Sauer, *Mosella*, Tome XXVIII-N°1-2, p. 157-172

SIMPLE INDICATOR

LONG TERM FORECASTING TOOLS

Contact Claire Lang, Department of Geography, Centre d'Etudes Géographiques de l'Université de Metz Phone: + 33 – 387315986, Fax: + 33 – 387547134

^[2] RUTLEDGE (A.T.), DANIEL (C.C.), 1994, Testing an automated method to estimate ground-water recharge from streamflow records, Ground water, vol. 32, n^o2

BERNIER J., 1963, La prévision statistique des bas débits, Assemblée générale de Berkeley, AISH publication n°63, p. 340-351 ^[4] EDIJATNO E., MICHEL C., 1989, Un modèle pluie-débit journalier à trois paramètres. *La houille blanche* n°2. 1] GALEA G. MERCIER G. et ADLER J.M., 1998, Modèle Débit-durée-Fréquence, concept et usage pour une approche régionale des régimes de basses eaux des bassins hydrographiques de la Loire (France) et Crisu-Alb (Roumanie), Revue des Sciences de l'Eau, Vol. 12, n°1, p. 93-122 ¹⁵ SHARMA T. C., 1996, Simulation of the Kenyan longest dry and wet spells and the largest rain-sums using a Markov model, Journal of hydrology, 178, p. 55-67



3. LOW FLOW PREDICTION AND FORECASTING