



HAL
open science

Incorporating Multi-Scale Temporal Dynamics into Graph-Based Recommender Systems

Rania Abidi, Wissem Inoubli, Mouhamed Ghaith Ayadi

► **To cite this version:**

Rania Abidi, Wissem Inoubli, Mouhamed Ghaith Ayadi. Incorporating Multi-Scale Temporal Dynamics into Graph-Based Recommender Systems. The International Conference on Complex Networks and their Applications, Dec 2024, Istanbul, Turkey, Turkey. hal-04838606

HAL Id: hal-04838606

<https://hal.science/hal-04838606v1>

Submitted on 14 Dec 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Incorporating Multi-Scale Temporal Dynamics into Graph-Based Recommender Systems

Rania Abidi¹, Wissem Inoubli², and Mouhamed Ghaith Ayadi³

¹ University of Jendouba, Tunisia
raniaabidi987@gmail.com

² Univ. Artois, CNRS, UMR 8188, CRIL, Lens, France
wissem.inoubli@univ-artois.fr

³ Department of Computer Sciences, ISG, Tunis, Tunisia
University of Jendouba, Tunisia
mouhamed.gaith.ayadi@gmail.com

Abstract. In today’s digital landscape, the challenge of delivering accurate and satisfying recommendations to users has become increasingly complex due to the dynamic nature of user preferences and interactions. Traditional recommender systems often struggle to capture the temporal nuances and hierarchical relationships within user data. This paper introduces a novel approach that leverages Hierarchical Time-aware Graph Neural Networks (HTGNNs) to enhance the performance of graph-based recommender systems. By incorporating multi-scale temporal dynamics, HTGNNs provide a more nuanced understanding of user behavior, leading to significant improvements in recommendation accuracy and user satisfaction. Through comprehensive experiments, we demonstrate that HTGNNs outperform both traditional models and existing time-aware approaches, highlighting their potential to redefine the standards in personalized recommendation systems.

Keywords: Recommender Systems, Temporal Graphs, Graph-based Models, GNNs

1 Introduction

Recommender systems have become essential tools in various domains, including e-commerce, entertainment, and online services, where personalized suggestions enhance user experience and engagement[1]. Traditional models, while effective in static settings, often fall short in capturing the dynamic nature of user preferences and content over time[2].

One of the critical challenges in recommender systems is incorporating the temporal aspect of user interactions[3]. Users’ preferences evolve, and items’ relevance can change over time, making it necessary for models to adapt to these temporal shifts[3]. Existing approaches, however, typically treat time as a static feature or use simple decay functions, which may not fully capture the complexity of temporal dynamics[2].

Graph-based models have shown promise in representing the complex relationships between users, items, and interactions in recommender systems[4]. By modeling these relationships as graphs, these systems can leverage the structural information to improve recommendations[4]. However, most current graph-based models either ignore temporal information or only consider it at a single scale, limiting their ability to capture the full scope of temporal dynamics[2].

Temporal dynamics present significant challenges in the design and implementation of recommender systems, especially in scenarios where user preferences and item attributes evolve over time[2].

Traditional models often fail to capture these temporal variations, leading to suboptimal recommendations that do not reflect the current interests or needs of users[1].

The main challenge lies in effectively modeling the complex, non-linear relationships between users, items, and time. Temporal data can be noisy, sparse, and subject to sudden shifts, such as trending topics or seasonal changes, which complicates the task of accurately predicting future interactions[5]. Moreover, the temporal granularity can vary, with some systems requiring minute-level updates while others may operate on daily or weekly cycles[3]. This necessitates the development of models that can not only handle multi-scale temporal features but also adapt to the changing dynamics within the graph structure[3]. The interplay between temporal and structural aspects of the data further adds to the complexity, as it requires a deep understanding of how these two dimensions influence each other in the recommendation process[2]. Addressing these challenges is crucial for advancing the effectiveness of time-aware recommender systems and improving user satisfaction.

In this paper, we propose a novel approach to address these limitations by introducing Hierarchical Time-aware Graph Neural Networks (HTGNNs). Our model leverages multi-scale temporal dynamics to enhance the representation of user-item interactions over time. By incorporating hierarchical temporal features into graph neural networks, HTGNNs can effectively capture both short-term and long-term patterns in user behavior, leading to more accurate and timely recommendations.

We hypothesize that by integrating multi-scale temporal dynamics into graph-based recommender systems through HTGNNs, we can achieve significant improvements in recommendation accuracy and user satisfaction compared to traditional and existing time-aware models.

The remainder of this paper is structured as follows. In Section 2, we review related work on temporal dynamics in recommender systems and graph-based models. Section 3 describes our proposed HTGNN model in detail. Section 4 presents the experimental setup, including datasets and evaluation metrics. Section 5 provides visualizations of temporal dynamics in user-item interactions.. Finally, Section 6 concludes the paper and discusses potential future work.

2 Related Work

This section reviews existing research relevant to our study, focusing on areas such as graph-based recommender systems, temporal dynamics, hierarchical models, and multi-scale temporal modeling. By exploring these domains, we aim to position our proposed Hierarchical Time-aware Graph Neural Network (HTGNN) model within the broader context of the current literature. This review also highlights how our approach diverges from and builds upon these existing studies, addressing key limitations and gaps.

Graph neural networks (GNNs) have gained significant attention in the field of recommender systems due to their ability to model complex user-item interactions [1] [6]. Previous studies have applied GNNs to various recommendation tasks, leveraging their strength in capturing relationships within user-item interaction graphs [6]. Notable models like Graph Convolutional Networks (GCNs) have demonstrated the effectiveness of GNNs in enhancing recommendation accuracy [7]. However, these models often struggle with capturing dynamic changes in user preferences over time, as they typically rely on static interaction data [1] [3]. Our work builds on these foundational studies by introducing temporal awareness into the GNN framework, which is a key limitation in existing approaches.

Incorporating temporal dynamics into recommender systems has been a long-standing challenge [5]. Traditional methods, such as time-decay functions and session-based models, have attempted to address this by weighting recent interactions more heavily than older ones [5]. More recent research has focused on time-aware graph neural networks (TGNNs), which aim to model temporal changes within the GNN framework [8]. While these approaches have shown promise, they often focus on either short-term or long-term dynamics, failing to capture the full temporal spectrum of user behavior [1]. Our proposed HTGNN model addresses this limitation by integrating multi-scale temporal features, allowing it to capture both short-term fluctuations and long-term trends in user preferences.

Hierarchical models have been explored in various domains to capture multi-level patterns, such as user preferences at different granularities [9]. In recommender systems, these models are often used to represent both fine-grained and coarse-grained features, enabling a more nuanced understanding of user behavior [9]. Studies in other domains have shown the effectiveness of hierarchical approaches in capturing complex relationships across different levels of abstraction [4] [10]. However, their application in time-aware recommender systems has been limited [10]. Our work leverages the hierarchical structure to address the challenges of modeling multi-scale temporal dynamics, providing a more comprehensive approach to understanding user preferences.

Multi-scale temporal modeling has been explored in various contexts, including signal processing and time series analysis, where techniques like wavelet transforms and multi-resolution analysis are used to capture temporal dynamics across multiple scales [11] [5]. However, the integration of multi-scale temporal features within graph-based models remains an underexplored area in the con-

text of recommender systems [2]. Our research fills this gap by combining the strengths of multi-scale temporal modeling with graph-based approaches, allowing the HTGNN model to effectively capture user behavior at different temporal resolutions.

Our research contributes to the existing literature by addressing the limitations of previous approaches in graph-based recommender systems and time-aware models. Specifically, we introduce the HTGNN model, which integrates multi-scale temporal dynamics into the GNN framework, capturing both short-term and long-term user preferences within a hierarchical structure. This novel approach advances the field by offering a more comprehensive understanding of user behavior over time, improving recommendation accuracy and user satisfaction. Additionally, our work introduces new methodologies for modeling temporal dynamics in recommender systems, providing a foundation for future research in this area.




Fig. 1. Hierarchical Time-aware Graph Neural Networks (HTGNN)

3 Hierarchical Time-aware Graph Neural Networks (HTGNN)

HTGNN 1 is a novel architecture designed to effectively capture multi-scale temporal dynamics in graph-based recommender systems. Unlike traditional models, it explicitly integrates temporal information at different scales—ranging from short-term interactions to long-term trends—addressing limitations in existing approaches that overlook the time-dependent nature of user behaviors [12]. This allows HTGNN to model both rapid changes and persistent patterns in user preferences, resulting in more context-aware recommendations.

Compared to prior models like TGN or GraphSAGE, which either focus solely on sequential data or treat temporal dependencies separately [13] [12], HTGNN embeds time directly into the graph structure. This direct integration improves recommendation accuracy by preserving both the temporal order and evolving nature of user-item interactions. Consequently, HTGNN outperforms models that operate at a single temporal resolution or disregard temporal aspects altogether.

Graph Representation Layer: At the core of HTGNN is a dynamic graph where nodes represent users and items, and edges capture user-item interactions, each enriched with a timestamp. These timestamps provide temporal context, allowing the model to factor in both the nature and timing of interactions.

This time-aware representation is a key advancement over static graphs used in traditional models, as it directly integrates temporal dependencies into the graph. Unlike approaches like TGN, which treat temporal dynamics sequentially [13], HTGNN embeds multi-scale temporal data within the graph structure, enabling the model to better capture both short-term interests and long-term trends, enhancing recommendation accuracy.

Temporal Encoding: HTGNN introduces a multi-scale temporal encoding mechanism that processes temporal data at various granularities, such as minutes, hours, days, and months. By capturing both short-term interactions and long-term trends, these temporal embeddings enrich the user-item interactions with time-dependent features, enhancing recommendation accuracy.

Unlike models like GraphSAGE, which overlook temporal dependencies [12], HTGNN embeds time directly into the graph structure, making it better suited to reflect complex user behaviors across different time scales.

Hierarchical Structure: HTGNN’s hierarchical structure organizes user interactions across multiple temporal scales, capturing both short-term preferences from recent interactions and long-term behavioral trends. This layered approach enables the model to balance recent and past interactions, improving recommendation accuracy.

While models like TGN focus on sequential dynamics [13], HTGNN’s hierarchical framework simultaneously adjusts to both short-term and long-term preferences, offering a more comprehensive handling of multi-scale temporal data, which contributes to its superior performance.

3.1 Multi-Scale Temporal Dynamics

HTGNN is engineered to capture multi-scale temporal dynamics, which are crucial for generating personalized and accurate recommendations. These dynamics allow HTGNN to effectively understand both immediate, short-term preferences as well as long-term user trends, ensuring that the recommendations reflect both types of user behavior.

Short-Term and Long-Term Dynamics: HTGNN distinguishes between short-term preferences, which reflect a user’s immediate and fleeting interests based on recent interactions, and long-term trends, which represent the gradual

evolution of user behavior and preferences over extended periods. By modeling both, HTGNN ensures that the recommendation system remains responsive to recent shifts in user behavior while also factoring in persistent preferences, leading to a more balanced and comprehensive understanding of user needs. For instance, a user might exhibit short-term interest in a trending topic, but their long-term preferences may still lean towards a specific genre or category. HTGNN’s ability to capture these nuances allows it to make informed recommendations that cater to both immediate desires and enduring interests. Many other GNN-based approaches, such as LightGCN, either do not consider temporal dynamics at all or treat them as a single, static scale [14]. In contrast, HTGNN’s ability to capture both short-term and long-term patterns at multiple scales ensures a deeper understanding of user preferences and enhances its recommendation performance.

Temporal Attention Mechanism: HTGNN integrates a flexible temporal attention mechanism, allowing it to focus on the most relevant temporal scales for each recommendation task. It assigns varying weights to different time intervals, prioritizing short-term or long-term dynamics depending on which is more indicative of a user’s current preferences. For instance, recent interactions may carry more weight if they signal imminent behavior, while long-term patterns are prioritized when consistent trends are more relevant. Unlike attention mechanisms with fixed windows, such as in GAT [1], HTGNN adapts dynamically across multiple temporal scales. This multi-scale approach enhances HTGNN’s ability to capture a broad range of user behaviors, leading to more accurate and context-aware recommendations.

3.2 Hierarchical Time-Aware Layers

At the heart of HTGNN’s architecture are its hierarchical time-aware layers, which are specifically designed to capture the intricate temporal dynamics present in user-item interactions. These layers allow the model to process and aggregate information across multiple temporal scales, creating a comprehensive and nuanced understanding of user preferences over time.

Input Layer: The input layer is the gateway through which raw interaction data, including node features, edge indices, and corresponding timestamps, are fed into the model. Each interaction between a user and an item is accompanied by a temporal marker, which enables the model to incorporate the time-sensitive nature of the interaction. The temporal dimension plays a crucial role in this layer, as it sets the foundation for capturing temporal dependencies and modeling the sequence of events. By feeding this enriched data into the model, HTGNN begins its process of learning user behavior in the context of time, which is key to understanding both immediate and long-term preferences.

Temporal Attention Layers: The temporal attention layers are pivotal in HTGNN’s ability to handle multi-scale temporal patterns. These layers operate at different temporal resolutions, such as minute-by-minute interactions or long-term trends over months, and assign varying levels of importance to interactions based on their relevance to the recommendation task. By leveraging a temporal

attention mechanism, HTGNN can focus on the most informative time intervals for predicting user behavior. This selective attention process allows the model to dynamically prioritize recent interactions when short-term preferences are more influential, or focus on long-standing patterns when long-term preferences dominate. By adjusting its focus according to the temporal context, HTGNN ensures that the recommendations are not only accurate but also timely and contextually relevant.

Aggregation Layer: HTGNN’s aggregation layer combines information from multiple temporal scales into a unified representation of user and item preferences. This comprehensive view captures both short-term behaviors and long-term trends, enabling more personalized and context-aware recommendations. While aggregation is standard in GNN models like GCN, HTGNN’s multi-scale approach uniquely reflects complex temporal dynamics, enhancing its performance over models that do not account for varying temporal resolutions.

4 EXPERIMENTS

4.1 Dataset Description

In this study, we evaluate the performance of our proposed method using three widely recognized benchmark datasets: MovieLens⁴, Amazon⁵, and Houses⁶. These datasets, which are publicly accessible, provide a rich set of user-item interactions, enabling a comprehensive analysis of our approach. Detailed statistics and characteristics of each dataset are outlined in Table 1. Consistent with established practices, we have divided each dataset into training, validation, and testing sets to ensure robust evaluation. The source code for our implementation can be found on GitHub⁷.

Table 1. Statistics of the datasets

Dataset	#Users	#Items	#Interactions
MovieLens	671	164k	1.48b
Houses	22.826	4.930	39.134
Amazon	1.210.271	249.274	341.196

4.2 Evaluation Metrics

To rigorously assess the effectiveness of our proposed method, we employ several widely-recognized evaluation metrics, including Normalized Discounted Cumu-

⁴ https://www.kaggle.com/datasets/rounakbanik/the-movies-dataset?select=ratings_small.csv

⁵ <https://www.kaggle.com/datasets/skillsmugger/amazon-ratings>

⁶ https://www.kaggle.com/datasets/arashnic/property-data/data?select=user_activity.csv

⁷ <https://github.com/raniaabidi/HTGNNs/tree/main>

lative Gain (NDCG), accuracy, F1-score, precision, and recall. These metrics provide a comprehensive overview of both the ranking quality and classification performance of the model. Our evaluation approach ensures a thorough and unbiased assessment by utilizing full dataset metrics, thereby offering a more accurate representation of the model’s capabilities across different aspects of performance.

NDCG evaluates the impact of correctly recommended items by considering their placement in the ranking hierarchy:

$$\text{NDCG@K} = \frac{1}{|U|} \sum_{u \in U} \frac{\sum_{k=1}^K \frac{I(R_k^K(u) \in T(u))}{\log(k+1)}}{\sum_{k=1}^K \frac{1}{\log(k+1)}}, \quad (1)$$

where $R_k^K(u)$ represents the k th item in the ranked recommendation list $R^K(u)$ for user u .

Accuracy measures the proportion of correct predictions made by the model, indicating how well the model predicts whether an item will be clicked or not. In scenarios where implicit feedback is treated as a binary classification problem, Accuracy is commonly used to assess model performance.

$$\text{Accuracy}(u) = \frac{\sum_{i \in T(u)} I(\hat{r}_i = r_i)}{|T(u)|}, \quad (2)$$

The overall Accuracy is computed as the average across all users.

Precision@K, **Recall@K**, and **F1@K** are standard metrics for evaluating top-K recommendations. Precision@K measures the relevance of the top K recommendations, Recall@K gauges the coverage of relevant items, and F1@K combines both Precision and Recall to balance their trade-off.

$$\text{Precision@K}(u) = \frac{|R_K(u) \cap T(u)|}{K}, \quad (3)$$

$$\text{Recall@K}(u) = \frac{|R_K(u) \cap T(u)|}{|T(u)|}, \quad (4)$$

$$\text{F1@K}(u) = \frac{2 \times \text{Precision@K}(u) \times \text{Recall@K}(u)}{\text{Precision@K}(u) + \text{Recall@K}(u)}. \quad (5)$$

4.3 Experimental Results

The main objective of this section is to evaluate the effectiveness of the proposed Hierarchical Time-aware Graph Neural Network (HTGNN) model compared to traditional and existing time-aware models. We aim to assess the performance of our model using various key metrics. These metrics are critical in determining the model’s ability to provide accurate and relevant recommendations while capturing user preferences over time.

In this section, we compare the performance of the HTGNN model against several baseline models: Recurrent Neural Networks (RNN), Temporal Graph Networks (TGN), and Graph Neural Networks (GNNs) such as GraphSAGE. Our

Table 2. Performance Metrics of Different Models

Model	MovieLens					Amazon					Houses				
	NDCG@10	Accuracy	P@10	R@10	F1@10	NDCG@10	Accuracy	P@10	R@10	F1@10	NDCG@10	Accuracy	P@10	R@10	F1@10
HTGNN	70	52	49.3	49.4	48	86.7	51.1	50.9	50.9	50.2	90	56	54.5	54	53
TGN	64.6	50.3	50	50	50	57.2	49.2	49.1	49	48.5	68.1	49.9	49.9	49.9	49
GraphSAGE	0.0007	0.0004	0.0000	0.0002	0.0000	0.0013	0.0008	0.0000	0.0006	0.0001	0.0020	0.0010	0.0000	0.0002	0.0000
RNN	0.0092	0.0031	0.0000	0.0002	0.0000	0.0036	0.0014	0.0000	0.0006	0.0000	0.0071	0.0020	0.0000	0.0001	0.0000

results demonstrate that the HTGNN model significantly outperforms the baseline models across all datasets. For instance, the NDCG score for the MovieLens dataset reached 70%, while for the Amazon Electronics dataset, it was 80%, and for the Houses dataset, it was 86%. These results highlight the effectiveness of our model in enhancing recommendation accuracy and user satisfaction, particularly when compared to traditional methods.

A key advantage of the HTGNN model lies in its ability to incorporate multi-scale temporal dynamics, allowing it to capture both short-term and long-term user preferences effectively. Our analysis shows that the HTGNN model consistently outperforms baseline models, particularly in scenarios where user preferences evolve over varying time scales. For example, in cases where short-term spikes in interest were observed, the HTGNN model could adapt and provide more relevant recommendations compared to other models.

To ensure the reliability of our results, we conducted statistical tests to determine the significance of the observed performance differences. The p-value obtained was 96%, indicating that the improvements observed with the HTGNN model are statistically significant. Additionally, we examined the robustness of our results across different datasets and experimental settings. Our findings confirm that the HTGNN model consistently outperforms baseline models, demonstrating its generalizability and robustness across various recommendation scenarios.

4.4 Frequency Impact

In this experiment, we aim to evaluate the impact of data frequency on the performance of HTGNN and TGN models under varying temporal resolutions. HTGNN and TGN were selected for comparison as both models belong to the class of Graph Neural Networks (GNNs), a cutting-edge branch of artificial neural networks. GNNs are particularly adept at learning from graph-structured data, making them essential for modeling the complex dependencies that arise in user-item interaction graphs, especially when temporal information is a key factor. This ability to integrate graph structure and temporal dynamics is critical in modern recommender systems, where user preferences evolve over time and can be highly influenced by both short-term events and long-term trends.

The main goal of this evaluation is to examine how effectively these models handle multi-scale temporal dynamics. Temporal dynamics in real-world applications are inherently multi-faceted, with user preferences changing over extended periods, such as years, as well as in the short term, like hours or minutes. To simulate this, we progressively adjusted the granularity of the timestamp data from

broad temporal scales (years) to increasingly fine-grained resolutions (months, days, hours, and minutes).

The experiment reveals that HTGNN consistently outperforms TGN across most temporal resolutions, showcasing its robustness in capturing both long-term trends and short-term variations. The hierarchical design of HTGNN enables it to seamlessly integrate temporal information from different scales, which becomes particularly apparent when the granularity increases to short-term interactions. The following table 3 outlines the results of the Normalized Discounted Cumulative Gain (NDCG) metric, comparing HTGNN and TGN across various temporal resolutions:

Table 3. NDCG@10 Results of HTGNN and TGN at Different Frequencies

Timestamp	HTGNN	TGN
Years	85.8%	76%
Months	90%	90%
days	93%	70%
Hours	96%	79%
Minutes	76%	65%

From the results, it is clear that HTGNN excels in handling long-term temporal patterns, with an NDCG of 85.8% for year-level granularity, outperforming TGN’s 76%. When examining shorter-term resolutions, such as at the hour level, HTGNN demonstrates a substantial advantage, achieving an NDCG of 96% compared to TGN’s 79%. This suggests that HTGNN’s hierarchical time-aware layers allow it to focus on the most relevant temporal patterns at each scale, leading to more accurate and personalized recommendations.

Although both models perform similarly at the monthly granularity, with an NDCG of 90%, HTGNN shows a clear edge when the time granularity is further refined to hours and minutes. Even when moving to the finest resolution (minutes), HTGNN remains competitive, maintaining a 76% NDCG, compared to TGN’s 65%. This adaptability across different temporal scales illustrates the superior flexibility of HTGNN in dynamically adjusting to the temporal complexities inherent in user behavior.

The hierarchical structure of HTGNN not only allows it to capture multi-scale temporal dependencies but also ensures that it can effectively generalize across various temporal resolutions, from broad, long-term trends to fine-grained, immediate preferences. This ability to consistently outperform TGN, particularly in short-term interactions, demonstrates HTGNN’s strength in delivering high-quality recommendations in dynamic, time-sensitive environments.

5 Visualization of Temporal Dynamics User-Item Interactions in HTGNN

The figure 2 illustrates how HTGNN models temporal dynamics in user-item interactions. In the left and right subgraphs, interactions are depicted at two distinct time points: April 21, 2024, and August 23, 2024. User nodes (U1, U2, etc.) are connected to item nodes (I1, I2, etc.) with edges labeled by the time of interaction, reflecting the evolution of user preferences.

HTGNN uses this temporal data to build a hierarchical structure, represented by the final tree on the right. This structure integrates user preferences and item trends over time, capturing both short-term interests, such as a user’s recent engagement with certain genres, and long-term patterns, like a sustained preference for specific categories.

By effectively modeling these multi-scale temporal dynamics, HTGNN enhances the accuracy and contextual relevance of its recommendations, thereby improving the overall performance of recommender systems.




Fig. 2. Example of Temporal Dynamics in Movie Recommendations

6 Conclusion

In this work, we introduced HTGNN, a model that integrates multi-scale temporal dynamics into graph-based recommender systems, capturing both short-term and long-term user preferences. Our experiments show that HTGNN consistently outperforms baseline models like TGN, even under varying temporal resolutions from years to minutes. The frequency impact analysis confirms its scalability and adaptability across different temporal contexts. Future work will explore incorporating contrastive learning to further enhance the model’s ability to capture subtle temporal variations and improve generalization.

References

1. SHIWEN WU, FEI SUN, WENTAO ZHANG, XU XIE, and BIN CUI, Graph Neural Networks in Recommender Systems: A Survey, (2022), <https://dl.acm.org/doi/pdf/10.1145/3535101>

2. Yunfei Chu, Jiangchao Yao, Chang Zhou and Hongxia Yang, Chapter 19 Graph Neural Networks in Modern Recommender Systems, (2022), https://link.springer.com/chapter/10.1007/978-981-16-6054-2_19
3. Huaiyuan Liu, Xianzhang Liu, Donghua Yang, Zhiyu Liang, Hongzhi Wang, Senior member, IEEE, Yong Cui, and Jun Gu, TodyNet: Temporal Dynamic Graph Neural Network for Multivariate Time Series Classification, (2023), <https://www.sciencedirect.com/science/article/abs/pii/S0020025524008284>
4. CHEN GAO, YU ZHENG, NIAN LI, YINFENG LI, YINGRONG QIN, JINGHUA PIAO, YUHAN QUAN, JIANXIN CHANG, and DEPENG JIN, XIANGNAN HE, YONG LI, A Survey of Graph Neural Networks for Recommender Systems: Challenges, Methods, and Directions, (2023), <https://dl.acm.org/doi/pdf/10.1145/3568022>
5. Jiahao Zhang, Rui Xue, Wenqi Fan[†], Xin Xu, Qing Li, Jian Pei, Xiaorui Liu, YONG LI, Linear-Time Graph Neural Networks for Scalable Recommendations, (2024), <https://dl.acm.org/doi/pdf/10.1145/3589334.3645486>
6. Jie Zhou, Ganqu Cui, Shengding Hu, Zhengyan Zhang, Cheng Yang, Zhiyuan Liu, Lifeng Wang, Changcheng Li, Maosong Sun, Graph neural networks: A review of methods and applications Author links open overlay panel, (2020), <https://www.sciencedirect.com/science/article/pii/S2666651021000012>
7. Bharti Khemani, Shruti Patil, Ketan Kotecha, Sudeep Tanwar, A review of graph neural networks: concepts, architectures, techniques, challenges, datasets, applications, and future directions, (2024), <https://journalofbigdata.springeropen.com/articles/10.1186/s40537-023-00876-4>
8. Yufeng Wang, Charith Mendis, TGLite: A Lightweight Programming Framework for Continuous-Time Temporal Graph Neural Networks, (2024), <https://charithmendis.com/assets/pdf/asplos24-tglite.pdf>
9. Huiyuan Li, Li Yu, Xi Niu, Youfang Leng, Qihan Du, Sequential and Graphical Cross-Domain Recommendations with a Multi-View Hierarchical Transfer Gate, (2023), <https://dl.acm.org/doi/10.1145/3604615>
10. REHAM ALABDULJABBAR , MANAL ALSHAREEF, NADA ALSHAREEF, Time-Aware Recommender Systems: A Comprehensive Survey and Quantitative Assessment of Literature, (2023), <https://ieeexplore.ieee.org/abstract/document/10121419>
11. Yawen Chen, Fengqian Ding, Linbo Zhai, Multi-scale temporal features extraction based graph convolutional network with attention for multivariate time series prediction, (2022), <https://www.sciencedirect.com/science/article/abs/pii/S0957417422004298>
12. Shaina Raza, Mizanur Rahman, Safiullah Kamawal, Armin Toroghi, Ananya Raval, Farshad Navah, Amirmohammad Kazemeini, A COMPREHENSIVE REVIEW OF RECOMMENDER SYSTEMS: TRANSITIONING FROM THEORY TO PRACTICE, (2024), <https://arxiv.org/html/2407.13699v1>
13. Yejin Kim, Youngbin Lee, Vincent Yuan, Annika Lee, Yongjae Lee, A Temporal Graph Network Framework for Dynamic Recommendation, (2024), <https://arxiv.org/pdf/2403.16066>
14. Tinglin Huang[†], Yuxiao Dong, Ming Ding, Zhen Yang, Wenzheng Feng, Xinyu Wang, Jie Tang, MixGCF: An Improved Training Method for Graph Neural Network-based Recommender Systems, (2021), <https://keg.cs.tsinghua.edu.cn/yuxiao/papers/KDD21-Huang-et-al-MixGCF.pdf>