

# A Quasi-Trefftz Method Based on a Flux Reconstruction Local Solver for the Time-Harmonic Maxwell System

Sébastien Pernet<sup>1</sup>, Matthias Rivet<sup>1,2</sup>, Sébastien Tordeux<sup>2</sup>

<sup>1</sup>DTIS, ONERA, Université de Toulouse, 31000, Toulouse, France

<sup>2</sup>EPI Makutu, INRIA, Université de Pau et des Pays de l'Adour, TotalEnergies, CNRS UMR 5142

1st July 2024



## Context of the work

- Increasing need of 3D simulations of time-harmonic electromagnetic waves: **high-frequency**, **heterogeneous** environments, **wide** domains (in terms of wavelengths)...




Figure: FDTD simulation on a Manhattan mesh of  $700 \times 600 \times 300\text{m}$ , Thibault Volpert (DEMR ONERA)

Example of computation challenge:  
field radiated by two antennas in Manhattan

- **Large simulation domain.**
- **Wide range of frequencies** (1-18 GHz).

⇒ Need of **efficient methods** to solve such ambitious cases!

## Plan of the talk

1. 3D Maxwell: limitations and Trefftz method
2. FR for wave propagation problems
3. Quasi-Trefftz numerical analysis

# The 3D Maxwell problem: current limitations and Trefftz method interests

## Current issues: memory and iterative resolution

**Time-harmonic Maxwell equations** for the electromagnetic field  
 $\mathbf{Y} := (\mathbf{E}, \mathbf{H}) \in [\mathbf{H}(\text{curl}, \Omega)]^6$ :

$$i\kappa\mathbf{M}\mathbf{Y} + \sum_{j=1}^3 \frac{\partial \mathbf{F}^j \mathbf{Y}}{\partial x_j} = \mathbf{0} \text{ in } \Omega, \quad (1)$$

with **impedance Boundary Conditions** (BCs)

$$(\mathbf{n}_{\partial\Omega} \times \mathbf{E}) \times \mathbf{n}_{\partial\Omega} + Z_{\partial\Omega} \mathbf{n}_{\partial\Omega} \times \mathbf{H} = \mathbf{g} \text{ on } \partial\Omega. \quad (2)$$

Many classic methods as Finite Differences [Yee 1966], Finite Elements [Nédélec 1980], Discontinuous Galerkin [Fezoui et al. 2005], but limitations for current applications:

- Wide domains lead to **very large linear systems**.
- Traditional direct solvers induce a **prohibitive memory consumption**.
- Usual numerical methods are **not well adapted to iterative resolution**.

## Considered numerical method: the Trefftz approach

1. Belongs to the Discontinuous Galerkin methods, with the Galerkin space  $\mathbb{X} := \prod_{T \in \mathcal{T}_h} \mathbb{X}_T$  made up of **local solutions** (i.e. in each mesh cell  $T \in \mathcal{T}_h$ ) of the Maxwell equations.
2. Use of the **reciprocity formula** verified in each cell

$$\forall T \in \mathcal{T}_h, \int_{\partial T} \gamma_{\times}^T \mathbf{H}^T \cdot \overline{\gamma_t \mathbf{E}'^T} + \gamma_t \mathbf{E}^T \cdot \overline{\gamma_{\times}^T \mathbf{H}'^T} = 0, \quad (3)$$

in addition to the introduction of **numerical traces** [Sirdey 2022]:

Find  $\mathbf{Y} = (\mathbf{E}, \mathbf{H}) \in \mathbb{X}$  such that  $\forall \mathbf{Y}' = (\mathbf{E}', \mathbf{H}') \in \mathbb{X}$ ,

$$\sum_{T \in \mathcal{T}_h} \int_{\partial T} \widehat{\gamma_{\times}^T \mathbf{H}^T} \cdot \overline{\gamma_t \mathbf{E}'^T} + \widehat{\gamma_t \mathbf{E}^T} \cdot \overline{\gamma_{\times}^T \mathbf{H}'^T} = \ell(\mathbf{E}'),$$

where  $\widehat{\cdot}$  stands for *upwind* (or Riemann) **numerical traces** and with

$$\gamma_t \mathbf{u}^T = \mathbf{u}^T - (\mathbf{u}^T \cdot \mathbf{n}_T) \mathbf{n}_T \text{ and } \gamma_{\times}^T \mathbf{u}^T = \mathbf{n}_T \times \mathbf{u}^T.$$

## The Trefftz approach: properties and classic limits

1. The formulation is posed on the **mesh skeleton** and adaptable to an **iterative resolution (contraction property)** [Cessenat, Després 1998].
2. A relevant choice of the numerical traces naturally implies formulation **coercivity**.
3. Basis functions have a **physical meaning**: leads to a **reduced numerical pollution** [Ihlenburg, Babuška 1995].

Limits of the classic Plane Waves (PWs) choice:

- Numerical dependence phenomena: **ill-conditioned basis** [Congreve et al. 2019].
- **No adaptability of the basis** to the local properties: expected singularities, complex interference phenomena...




Figure: Eigenvalues of the mass matrix for 196 PWs.

⇒ Possible algebraic adaptations [Barucq et al. 2021].

⇒ Introduction of **well-conditioned basis** by parameterising the space of local solutions by **polynomial boundary conditions**.

## A Quasi-Trefftz approach

### Definition of the local problem

A local solution  $\mathbf{Y}^T$  in  $T$  is parameterised by a tangential field  $\mathbf{g}^T \in \mathbb{V}$  such that

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (4)$$

$\implies$  Consider a finite-dimensional subspace  $\mathbb{V}_h \subset \mathbb{V}$  and the associated Maxwell solutions [Fure et al. 2020].

Construction of  $\mathbb{V}_h$ :

- Consider a cell  $T \in \mathcal{T}_h$ .
- Define a mesh of  $\mathcal{T}(\partial T)$ .
- Consider a piecewise polynomial  $\mathbf{g}^T$  of degree  $k_{QT}$  on  $\mathcal{T}(\partial T)$ .




Figure: 2D example of the mesh of  $\partial T$  for  $k_{QT} = 1$ .

$\implies$  **Associated Maxwell solutions are unknown:** need of an **auxiliary solver** to compute approximations!

$\implies$  **Other Quasi-Trefftz approaches:** generalised PWs [Imbert-Gérard, Després 2013], polynomial Quasi-Trefftz functions [Imbert-Gérard, Sylvand 2023], Embedded Trefftz DG [Lehrenfeld, Stocker 2023], BEM local solver [Barucq et al. 2017]...



## A Quasi-Trefftz approach

### Definition of the local problem

A local solution  $\mathbf{Y}^T$  in  $T$  is parameterised by a tangential field  $\mathbf{g}^T \in \mathbb{V}$  such that

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (4)$$

$\implies$  Consider a finite-dimensional subspace  $\mathbb{V}_h \subset \mathbb{V}$  and the associated Maxwell solutions [Fure et al. 2020].

Construction of  $\mathbb{V}_h$ :

- Consider a cell  $T \in \mathcal{T}_h$ .
- Define a mesh of  $\mathcal{T}(\partial T)$ .
- Consider a piecewise polynomial  $\mathbf{g}^T$  of degree  $k_{QT}$  on  $\mathcal{T}(\partial T)$ .




Figure: 2D example of the mesh of  $\partial T$  for  $k_{QT} = 1$ .

$\implies$  Associated Maxwell solutions are unknown: need of an auxiliary solver to compute approximations!

$\implies$  Other Quasi-Trefftz approaches: generalised PWs [Imbert-Gérard, Després 2013], polynomial Quasi-Trefftz functions [Imbert-Gérard, Sylvand 2023], Embedded Trefftz DG [Lehrenfeld, Stocker 2023], BEM local solver [Barucq et al. 2017]...

## A Quasi-Trefftz approach

### Definition of the local problem

A local solution  $\mathbf{Y}^T$  in  $T$  is parameterised by a tangential field  $\mathbf{g}^T \in \mathbb{V}$  such that

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (4)$$

$\implies$  Consider a finite-dimensional subspace  $\mathbb{V}_h \subset \mathbb{V}$  and the associated Maxwell solutions [Fure et al. 2020].

Construction of  $\mathbb{V}_h$ :

- Consider a cell  $T \in \mathcal{T}_h$ .
- Define a mesh of  $\mathcal{T}(\partial T)$ .
- Consider a piecewise polynomial  $\mathbf{g}^T$  of degree  $k_{QT}$  on  $\mathcal{T}(\partial T)$ .




Figure: 2D example of the mesh of  $\partial T$  for  $k_{QT} = 1$ .

$\implies$  Associated Maxwell solutions are unknown: need of an auxiliary solver to compute approximations!

$\implies$  Other Quasi-Trefftz approaches: generalised PWs [Imbert-Gérard, Després 2013], polynomial Quasi-Trefftz functions [Imbert-Gérard, Sylvand 2023], Embedded Trefftz DG [Lehrenfeld, Stocker 2023], BEM local solver [Barucq et al. 2017]...

## A Quasi-Trefftz approach

### Definition of the local problem

A local solution  $\mathbf{Y}^T$  in  $T$  is parameterised by a tangential field  $\mathbf{g}^T \in \mathbb{V}$  such that

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (4)$$

$\implies$  Consider a finite-dimensional subspace  $\mathbb{V}_h \subset \mathbb{V}$  and the associated Maxwell solutions [Fure et al. 2020].

Construction of  $\mathbb{V}_h$ :

- Consider a cell  $T \in \mathcal{T}_h$ .
- Define a mesh of  $\mathcal{T}(\partial T)$ .
- Consider a piecewise polynomial  $\mathbf{g}^T$  of degree  $k_{QT}$  on  $\mathcal{T}(\partial T)$ .




Figure: 2D example of the mesh of  $\partial T$  for  $k_{QT} = 1$ .

$\implies$  Associated Maxwell solutions are unknown: need of an auxiliary solver to compute approximations!

$\implies$  Other Quasi-Trefftz approaches: generalised PWs [Imbert-Gérard, Després 2013], polynomial Quasi-Trefftz functions [Imbert-Gérard, Sylvand 2023], Embedded Trefftz DG [Lehrenfeld, Stocker 2023], BEM local solver [Barucq et al. 2017]...

## A Quasi-Trefftz approach

### Definition of the local problem

A local solution  $\mathbf{Y}^T$  in  $T$  is parameterised by a tangential field  $\mathbf{g}^T \in \mathbb{V}$  such that

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (4)$$

$\implies$  Consider a finite-dimensional subspace  $\mathbb{V}_h \subset \mathbb{V}$  and the associated Maxwell solutions [Fure et al. 2020].

Construction of  $\mathbb{V}_h$ :

- Consider a cell  $T \in \mathcal{T}_h$ .
- Define a mesh of  $\mathcal{J}(\partial T)$ .
- Consider a piecewise polynomial  $\mathbf{g}^T$  of degree  $k_{QT}$  on  $\mathcal{J}(\partial T)$ .




Figure: 2D example of the mesh of  $\partial T$  for  $k_{QT} = 1$ .

$\implies$  Associated Maxwell solutions are unknown: need of an auxiliary solver to compute approximations!

$\implies$  Other Quasi-Trefftz approaches: generalised PWs [Imbert-Gérard, Després 2013], polynomial Quasi-Trefftz functions [Imbert-Gérard, Sylvand 2023], Embedded Trefftz DG [Lehrenfeld, Stocker 2023], BEM local solver [Barucq et al. 2017]...

## A Quasi-Trefftz approach

### Definition of the local problem

A local solution  $\mathbf{Y}^T$  in  $T$  is parameterised by a tangential field  $\mathbf{g}^T \in \mathbb{V}$  such that

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (4)$$

$\implies$  Consider a finite-dimensional subspace  $\mathbb{V}_h \subset \mathbb{V}$  and the associated Maxwell solutions [Fure et al. 2020].

Construction of  $\mathbb{V}_h$ :

- Consider a cell  $T \in \mathcal{T}_h$ .
- Define a mesh of  $\mathcal{T}(\partial T)$ .
- Consider a piecewise polynomial  $\mathbf{g}^T$  of degree  $k_{QT}$  on  $\mathcal{T}(\partial T)$ .




Figure: 2D example of the mesh of  $\partial T$  for  $k_{QT} = 1$ .

$\implies$  Associated Maxwell solutions are unknown: need of an auxiliary solver to compute approximations!

$\implies$  Other Quasi-Trefftz approaches: generalised PWs [Imbert-Gérard, Després 2013], polynomial Quasi-Trefftz functions [Imbert-Gérard, Sylvand 2023], Embedded Trefftz DG [Lehrenfeld, Stocker 2023], BEM local solver [Barucq et al. 2017]...

## A Quasi-Trefftz approach

### Definition of the local problem

A local solution  $\mathbf{Y}^T$  in  $T$  is parameterised by a tangential field  $\mathbf{g}^T \in \mathbb{V}$  such that

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (4)$$

$\implies$  Consider a finite-dimensional subspace  $\mathbb{V}_h \subset \mathbb{V}$  and the associated Maxwell solutions [Fure et al. 2020].

Construction of  $\mathbb{V}_h$ :

- Consider a cell  $T \in \mathcal{T}_h$ .
- Define a mesh of  $\mathcal{T}(\partial T)$ .
- Consider a piecewise polynomial  $\mathbf{g}^T$  of degree  $k_{QT}$  on  $\mathcal{T}(\partial T)$ .




Figure: 2D example of the mesh of  $\partial T$  for  $k_{QT} = 1$ .

$\implies$  Associated Maxwell solutions are unknown: need of an auxiliary solver to compute approximations!

$\implies$  Other Quasi-Trefftz approaches: generalised PWs [Imbert-Gérard, Després 2013], polynomial Quasi-Trefftz functions [Imbert-Gérard, Sylvand 2023], Embedded Trefftz DG [Lehrenfeld, Stocker 2023], BEM local solver [Barucq et al. 2017]...

## A Quasi-Trefftz approach

### Definition of the local problem

A local solution  $\mathbf{Y}^T$  in  $T$  is parameterised by a tangential field  $\mathbf{g}^T \in \mathbb{V}$  such that

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (4)$$

$\implies$  Consider a finite-dimensional subspace  $\mathbb{V}_h \subset \mathbb{V}$  and the associated Maxwell solutions [Fure et al. 2020].

Construction of  $\mathbb{V}_h$ :

- Consider a cell  $T \in \mathcal{T}_h$ .
- Define a mesh of  $\mathcal{T}(\partial T)$ .
- Consider a piecewise polynomial  $\mathbf{g}^T$  of degree  $k_{QT}$  on  $\mathcal{T}(\partial T)$ .




Figure: 2D example of the mesh of  $\partial T$  for  $k_{QT} = 1$ .

$\implies$  **Associated Maxwell solutions are unknown:** need of an **auxiliary solver** to compute approximations!

$\implies$  **Other Quasi-Trefftz approaches:** generalised PWs [Imbert-Gérard, Després 2013], polynomial Quasi-Trefftz functions [Imbert-Gérard, Sylvand 2023], Embedded Trefftz DG [Lehrenfeld, Stocker 2023], BEM local solver [Barucq et al. 2017]...

# The Flux Reconstruction method for wave propagation problems



## FR principle

Consider the homogeneous **1D model system** on  $\Omega = [0, L]$ :  
Find  $\mathbf{y} = (u, v) : \Omega \rightarrow \mathbb{C}^2$  such that

$$\begin{cases} i\kappa\mathbf{y} + \frac{d\phi}{dx} = \mathbf{0}, \\ \phi = \mathbf{F}\mathbf{y}, \end{cases} \quad \text{in } \Omega \text{ with } \mathbf{F} = \begin{pmatrix} 0 & -1 \\ -1 & 0 \end{pmatrix}, \quad (5)$$

and the BCs

$$\begin{cases} u(0) - Z_1 v(0) = g_1, \\ u(L) + Z_2 v(L) = g_2. \end{cases} \quad (6)$$



Presentation for a **linear** equation!


$\implies$  Copy this equation at the discrete level on each cell of the mesh [Huynh 2007]:

$$\forall n \in \llbracket 1, N \rrbracket, i\kappa\mathbf{y}_h + \frac{d\tilde{\phi}_h}{dx} = \mathbf{0} \text{ in } [X_{n-1}, X_n]. \quad (7)$$

## FR construction steps and properties

$$\forall n \in \llbracket 1, N \rrbracket, i\kappa \mathbf{y}_h + \frac{d\tilde{\phi}_h}{dx} = \mathbf{0} \text{ in } [X_{n-1}, X_n]. \quad (8)$$


1. Approximation  $\mathbf{y}_h$  as piecewise polynomial of degree  $k_{FR}$ .
2. Natural flux approximation  $\phi_h = \mathbf{F}\mathbf{y}_h$ .
3. Numerical fluxes  $\hat{\phi}_n$  as a mean of  $\phi_n^-$  and  $\phi_n^+$ .
4. Correction polynomials  $P_n^{\rightarrow}$  and  $P_n^{\leftarrow}$  of degree  $k_{FR} + 1$ .
5. Correction  $\tilde{\phi}_{h,n} = \phi_{h,n} + \delta_{n-1}^{\rightarrow} P_n^{\rightarrow} + \delta_n^{\leftarrow} P_n^{\leftarrow}$ .



## FR construction steps and properties

$$\forall n \in \llbracket 1, N \rrbracket, i\kappa \mathbf{y}_h + \frac{d\tilde{\phi}_h}{dx} = \mathbf{0} \text{ in } [X_{n-1}, X_n]. \quad (8)$$


1. Approximation  $\mathbf{y}_h$  as piecewise polynomial of degree  $k_{FR}$ .
2. Natural flux approximation  $\phi_h = \mathbf{F}\mathbf{y}_h$ .
3. Numerical fluxes  $\hat{\phi}_n$  as a mean of  $\phi_n^-$  and  $\phi_n^+$ .
4. Correction polynomials  $P_n^{\rightarrow}$  and  $P_n^{\leftarrow}$  of degree  $k_{FR} + 1$ .
5. Correction  $\tilde{\phi}_{h,n} = \phi_{h,n} + \delta_{n-1}^{\rightarrow} P_n^{\rightarrow} + \delta_n^{\leftarrow} P_n^{\leftarrow}$ .



## FR construction steps and properties

$$\forall n \in \llbracket 1, N \rrbracket, i\kappa \mathbf{y}_h + \frac{d\tilde{\phi}_h}{dx} = \mathbf{0} \text{ in } [X_{n-1}, X_n]. \quad (8)$$



1. Approximation  $\mathbf{y}_h$  as piecewise polynomial of degree  $k_{FR}$ .
2. Natural flux approximation  $\phi_h = \mathbf{F}\mathbf{y}_h$ .
3. Numerical fluxes  $\hat{\phi}_n$  as a mean of  $\phi_n^-$  and  $\phi_n^+$ .
4. Correction polynomials  $P_n^{\rightarrow}$  and  $P_n^{\leftarrow}$  of degree  $k_{FR} + 1$ .
5. Correction  $\tilde{\phi}_{h,n} = \phi_{h,n} + \delta_{n-1}^{\rightarrow} P_n^{\rightarrow} + \delta_n^{\leftarrow} P_n^{\leftarrow}$ .



## FR construction steps and properties

$$\forall n \in \llbracket 1, N \rrbracket, i\kappa \mathbf{y}_h + \frac{d\tilde{\phi}_h}{dx} = \mathbf{0} \text{ in } [X_{n-1}, X_n]. \quad (8)$$



1. Approximation  $\mathbf{y}_h$  as piecewise polynomial of degree  $k_{FR}$ .
2. Natural flux approximation  $\phi_h = \mathbf{F}\mathbf{y}_h$ .
3. Numerical fluxes  $\hat{\phi}_n$  as a mean of  $\phi_n^-$  and  $\phi_n^+$ .
4. Correction polynomials  $P_n^{\rightarrow}$  and  $P_n^{\leftarrow}$  of degree  $k_{FR} + 1$ .
5. Correction  $\tilde{\phi}_{h,n} = \phi_{h,n} + \delta_{n-1}^{\rightarrow} P_n^{\rightarrow} + \delta_n^{\leftarrow} P_n^{\leftarrow}$ .



## FR construction steps and properties

$$\forall n \in \llbracket 1, N \rrbracket, i\kappa \mathbf{y}_h + \frac{d\tilde{\phi}_h}{dx} = \mathbf{0} \text{ in } [X_{n-1}, X_n]. \quad (8)$$


1. Approximation  $\mathbf{y}_h$  as piecewise polynomial of degree  $k_{FR}$ .
2. Natural flux approximation  $\phi_h = \mathbf{F}\mathbf{y}_h$ .
3. Numerical fluxes  $\hat{\phi}_n$  as a mean of  $\phi_n^-$  and  $\phi_n^+$ .
4. Correction polynomials  $P_n^{\rightarrow}$  and  $P_n^{\leftarrow}$  of degree  $k_{FR} + 1$ .
5. Correction  $\tilde{\phi}_{h,n} = \phi_{h,n} + \delta_{n-1}^{\rightarrow} P_n^{\rightarrow} + \delta_n^{\leftarrow} P_n^{\leftarrow}$ .



## FR construction steps and properties

$$\forall n \in \llbracket 1, N \rrbracket, i\kappa \mathbf{y}_h + \frac{d\tilde{\phi}_h}{dx} = \mathbf{0} \text{ in } [X_{n-1}, X_n]. \quad (8)$$

1. Approximation  $\mathbf{y}_h$  as piecewise polynomial of degree  $k_{FR}$ .
2. Natural flux approximation  $\phi_h = \mathbf{F}\mathbf{y}_h$ .
3. Numerical fluxes  $\hat{\phi}_n$  as a mean of  $\phi_n^-$  and  $\phi_n^+$ .
4. Correction polynomials  $P_n^{\rightarrow}$  and  $P_n^{\leftarrow}$  of degree  $k_{FR} + 1$ .
5. Correction  $\tilde{\phi}_{h,n} = \phi_{h,n} + \delta_{n-1}^{\rightarrow} P_n^{\rightarrow} + \delta_n^{\leftarrow} P_n^{\leftarrow}$ .



- **Strong formulation:** no dependence on a quadrature rule.
- Choice of correction polynomials allows to **retrieve usual methods**: classic choice of Radau polynomials (nodal DG).
- Natural **generalisation to 3D** and adaptable to **unstructured meshes**.

## Numerical results




Table:  $h$ -convergence of the FR method in 1D and 3D for different correction polynomials (SD\_CLo (— $\times$ —), SD\_IG (— $\times$ —), FR\_Rad (— $\times$ —) and FR\_G2 (— $\times$ —)).

$\Rightarrow$  **Dependence on the choice** of the correction polynomials: what is the **best choice**?



## Error estimate and optimised correction polynomials

Developed an **explicit a priori error estimate** with incoming BCs, *i.e.*  $Z_1 = Z_2 = 1$  [Rivet et al. 2023]:

$$\|\mathbf{y} - \mathbf{y}_h\|_{L^2(\Omega)}^2 \leq C(\kappa, h, L, P^{\rightarrow}) (|\mathbf{g}_1|^2 + |\mathbf{g}_2|^2) \quad (9)$$

⇒ Choose the correction polynomial  $P^{\rightarrow}$  as [Rivet et al. 2024]

$$P^{\rightarrow} = \operatorname{argmin}_{\tilde{P} \in \mathbb{P}^{adm}} C(\kappa, h, L, \tilde{P}). \quad (10)$$

## Error estimate and optimised correction polynomials

⇒ Direction-wise optimisation in the 3D case: **applicable even for general BCs!**




Table: General 3D simulation for Radau (—✖) and optimised (—+) polynomials.

⇒ Possible to find **better polynomials than the classic ones!**

# **A quasi-Trefftz approach based on a Flux Reconstruction auxiliary solver: numerical analysis**

## Summary of this Quasi-Trefftz approach

Variational formulation posed on  $\mathbb{X} := \prod_{T \in \mathcal{T}_h} \mathbb{X}_T$  made up of **local solutions**.



Functions  $(\mathbf{E}^T, \mathbf{H}^T)$  of  $\mathbb{X}_T$  parameterised by  $\mathbf{g}^T \in \mathbb{V}$  such that:

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (11)$$



**Polynomial approximation** of the trace space:  $\mathbb{V}_h = \text{span}(\mathbf{g}_i^T)$ .  
For all  $i$ , the associated solutions  $(\mathbf{E}_i^T, \mathbf{H}_i^T)$  are taken as basis functions of  $\mathbb{X}_T$ .



FR **auxiliary solver** to compute an approximation of  $(\mathbf{E}_h^T, \mathbf{H}_h^T)$ .

## Summary of this Quasi-Trefftz approach

Variational formulation posed on  $\mathbb{X} := \prod_{T \in \mathcal{T}_h} \mathbb{X}_T$  made up of **local solutions**.



Functions  $(\mathbf{E}^T, \mathbf{H}^T)$  of  $\mathbb{X}_T$  **parameterised** by  $\mathbf{g}^T \in \mathbb{V}$  such that:

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (11)$$



**Polynomial approximation** of the trace space:  $\mathbb{V}_h = \text{span}(\mathbf{g}_i^T)$ .  
For all  $i$ , the associated solutions  $(\mathbf{E}_i^T, \mathbf{H}_i^T)$  are taken as basis functions of  $\mathbb{X}_T$ .



FR **auxiliary solver** to compute an approximation of  $(\mathbf{E}_h^T, \mathbf{H}_h^T)$ .

## Summary of this Quasi-Trefftz approach

Variational formulation posed on  $\mathbb{X} := \prod_{T \in \mathcal{T}_h} \mathbb{X}_T$  made up of **local solutions**.



Functions  $(\mathbf{E}^T, \mathbf{H}^T)$  of  $\mathbb{X}_T$  **parameterised** by  $\mathbf{g}^T \in \mathbb{V}$  such that:

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (11)$$



**Polynomial approximation** of the trace space:  $\mathbb{V}_h = \text{span}(\mathbf{g}_i^T)$ .  
For all  $i$ , the associated solutions  $(\mathbf{E}_i^T, \mathbf{H}_i^T)$  are taken as basis functions of  $\mathbb{X}_T$ .



FR auxiliary solver to compute an approximation of  $(\mathbf{E}_h^T, \mathbf{H}_h^T)$ .

## Summary of this Quasi-Trefftz approach

Variational formulation posed on  $\mathbb{X} := \prod_{T \in \mathcal{T}_h} \mathbb{X}_T$  made up of **local solutions**.



Functions  $(\mathbf{E}^T, \mathbf{H}^T)$  of  $\mathbb{X}_T$  **parameterised** by  $\mathbf{g}^T \in \mathbb{V}$  such that:

$$\gamma_t \mathbf{E}^T + Z_{\partial T} \gamma_{\times}^T \mathbf{H}^T = \mathbf{g}^T \text{ on } \partial T. \quad (11)$$



**Polynomial approximation** of the trace space:  $\mathbb{V}_h = \text{span}(\mathbf{g}_i^T)$ .  
For all  $i$ , the associated solutions  $(\mathbf{E}_i^T, \mathbf{H}_i^T)$  are taken as basis functions of  $\mathbb{X}_T$ .



**FR auxiliary solver** to compute an approximation of  $(\mathbf{E}_h^T, \mathbf{H}_h^T)$ .

## Numerical experiments: basis quality




Figure: Eigenvalues of the mass matrix for 196 PWs (and reduction for  $\epsilon = 10^{-6}$ ) and 192 Quasi-Trefftz basis functions.

**Basis quality**

- ⇒ Possible reduction techniques to restore the condition number.
- ⇒ Avoids spurious numerical modes and ill-conditioning of the mass matrix!



## Numerical experiments: basis quality




Figure: Eigenvalues of the mass matrix for 196 PWs (and reduction for  $\epsilon = 10^{-6}$ ) and 192 Quasi-Trefftz basis functions.

**Basis quality**

- ⇒ Possible **reduction techniques** to restore the condition number.
- ⇒ Avoids **spurious numerical modes** and **ill-conditioning** of the mass matrix!

## Numerical experiments: basis quality




Figure: Eigenvalues of the mass matrix for 196 PWs (and reduction for  $\epsilon = 10^{-6}$ ) and 192 Quasi-Trefftz basis functions.

**Basis quality**

- ⇒ Possible **reduction techniques** to restore the condition number.
- ⇒ **Avoids spurious numerical modes** and **ill-conditioning** of the mass matrix!

## Approximation properties of the basis for a smooth solution: sum of random PWs




Figure: Projection error on the different basis for a sum of random PWs.

⇒ **Saturation phenomenon** due to condition number.

⇒ **Reduction techniques** avoid conditioning issues, but **locked convergence** because of rounding pollution error for an **asked threshold**.

⇒ **Robust approximation** by FR basis.

## Approximation properties of the basis for a smooth solution: sum of random PWs




Figure: Projection error on the different basis for a sum of random PWs.

⇒ **Saturation phenomenon** due to condition number.

⇒ **Reduction techniques** avoid conditioning issues, but **locked convergence** because of rounding pollution error for an **asked threshold**.

⇒ **Robust approximation** by FR basis.

## Approximation properties of the basis for a smooth solution: sum of random PWs




Figure: Projection error on the different basis for a sum of random PWs.

⇒ **Saturation phenomenon** due to condition number.

⇒ **Reduction techniques** avoid conditioning issues, but **locked convergence** because of rounding pollution error for an **asked threshold**.

⇒ **Robust approximation** by FR basis.

## Approximation properties of the basis for a 'non-smooth' solution: sum of random dipoles




Figure: Projection error on the different basis for a sum of random dipoles.

⇒ **Saturation phenomenon** due to condition number: **difficult representation of complex local solutions with PWs.**

⇒ **Reduction techniques** avoid conditioning issues, but **locked convergence** because of rounding pollution error for an **asked threshold.**

⇒ **Robust approximation** by FR basis.

## Approximation properties of the basis for a 'non-smooth' solution: sum of random dipoles




Figure: Projection error on the different basis for a sum of random dipoles.

⇒ **Saturation phenomenon** due to condition number: **difficult representation of complex local solutions with PWs.**

⇒ **Reduction techniques** avoid conditioning issues, but **locked convergence** because of rounding pollution error for an **asked threshold.**

⇒ **Robust approximation** by FR basis.

## Approximation properties of the basis for a 'non-smooth' solution: sum of random dipoles




Figure: Projection error on the different basis for a sum of random dipoles.

⇒ **Saturation phenomenon** due to condition number: **difficult representation of complex local solutions with PWs.**

⇒ **Reduction techniques** avoid conditioning issues, but **locked convergence** because of rounding pollution error for an **asked threshold.**

⇒ **Robust approximation** by FR basis.



## Calibration of the FR auxiliary solver

Trefftz approach rests on the use of **exact solutions** of the Maxwell equations:

**Is using quasi-solutions enough?**  
**How to adapt the FR order to the Trefftz one?**

- Uniform Cartesian mesh  $\mathcal{T}_H(\Omega)$  of the domain  $\Omega$ :  $N$  **macro-cells** per direction.
- Uniform Cartesian mesh  $\mathcal{T}_h(\partial T)$  of  $\partial T$ :  $M$  **micro-faces** per direction.
- Piecewise polynomial BCs of degree  $k_{QT} = 1$ .




Figure: Mesh  $\mathcal{T}_H(\Omega)$  for  $N = 3$ .



Figure: Mesh  $\mathcal{T}_h(\partial T)$  for  $M = 2$  and  $k_{QT} = 1$ .

$\implies$  No theoretical *a priori* error estimates in  $L^2(\Omega)$ -norm: **numerical convergence in mesh and number of basis functions** [Fure et al. 2020].

## Calibration of the FR auxiliary solver

Trefftz approach rests on the use of **exact solutions** of the Maxwell equations:

**Is using quasi-solutions enough?**  
**How to adapt the FR order to the Trefftz one?**

- Uniform Cartesian mesh  $\mathcal{T}_H(\Omega)$  of the domain  $\Omega$ :  $N$  **macro-cells** per direction.
- Uniform Cartesian mesh  $\mathcal{T}_h(\partial T)$  of  $\partial T$ :  $M$  **micro-faces** per direction.
- Piecewise polynomial BCs of degree  $k_{QT} = 1$ .




Figure: Mesh  $\mathcal{T}_H(\Omega)$  for  $N = 3$ .




Figure: Mesh  $\mathcal{T}_h(\partial T)$  for  $M = 2$  and  $k_{QT} = 1$ .

⇒ No theoretical *a priori* error estimates in  $L^2(\Omega)$ -norm: **numerical convergence in mesh and number of basis functions** [Fure et al. 2020].

## Calibration of the FR auxiliary solver

Trefftz approach rests on the use of **exact solutions** of the Maxwell equations:

**Is using quasi-solutions enough?**  
**How to adapt the FR order to the Trefftz one?**

- Uniform Cartesian mesh  $\mathcal{T}_H(\Omega)$  of the domain  $\Omega$ :  $N$  **macro-cells** per direction.
- Uniform Cartesian mesh  $\mathcal{T}_h(\partial T)$  of  $\partial T$ :  $M$  **micro-faces** per direction.
- Piecewise polynomial BCs of degree  $k_{QT} = 1$ .




Figure: Mesh  $\mathcal{T}_H(\Omega)$  for  $N = 3$ .




Figure: Mesh  $\mathcal{T}_h(\partial T)$  for  $M = 2$  and  $k_{QT} = 1$ .

⇒ No theoretical *a priori* error estimates in  $L^2(\Omega)$ -norm: **numerical convergence in mesh and number of basis functions** [Fure et al. 2020].

## Calibration of the FR auxiliary solver

Trefftz approach rests on the use of **exact solutions** of the Maxwell equations:

**Is using quasi-solutions enough?**  
**How to adapt the FR order to the Trefftz one?**

- Uniform Cartesian mesh  $\mathcal{T}_H(\Omega)$  of the domain  $\Omega$ :  $N$  **macro-cells** per direction.
- Uniform Cartesian mesh  $\mathcal{T}_h(\partial T)$  of  $\partial T$ :  $M$  **micro-faces** per direction.
- Piecewise polynomial BCs of degree  $k_{QT} = 1$ .




Figure: Mesh  $\mathcal{T}_H(\Omega)$  for  $N = 3$ .




Figure: Mesh  $\mathcal{T}_h(\partial T)$  for  $M = 2$  and  $k_{QT} = 1$ .

⇒ No theoretical *a priori* error estimates in  $L^2(\Omega)$ -norm: **numerical convergence in mesh and number of basis functions** [Fure et al. 2020].

## Calibration of the FR auxiliary solver

Trefftz approach rests on the use of **exact solutions** of the Maxwell equations:

**Is using quasi-solutions enough?**  
**How to adapt the FR order to the Trefftz one?**

- Uniform Cartesian mesh  $\mathcal{T}_H(\Omega)$  of the domain  $\Omega$ :  $N$  **macro-cells** per direction.
- Uniform Cartesian mesh  $\mathcal{T}_h(\partial T)$  of  $\partial T$ :  $M$  **micro-faces** per direction.
- Piecewise polynomial BCs of degree  $k_{QT} = 1$ .




Figure: Mesh  $\mathcal{T}_H(\Omega)$  for  $N = 3$ .





Figure: Mesh  $\mathcal{T}_h(\partial T)$  for  $M = 2$  and  $k_{QT} = 1$ .

$\implies$  No theoretical *a priori* error estimates in  $L^2(\Omega)$ -norm: **numerical convergence in mesh and number of basis functions** [Fure et al. 2020].

## Calibration of the FR auxiliary solver

Is using quasi-solutions enough?  
How to adapt the FR order to the Trefftz one?

⇒ Mesh-convergence: refinement of the macro-mesh  $\mathcal{T}_H(\Omega)$ .




- Need of  $k_{FR} \geq k_{QT} + 2$  for quasi-optimal orders, but **no interest in over-resolving!**

## Numerical experiments: convergence in the number of basis functions

Is using quasi-solutions enough?  
How to adapt the FR order to the Trefftz one?

⇒ **Local basis enrichment** through refinement of the micro-mesh  $\mathcal{T}_h(\partial T)$ .



- Need of  $k_{FR} \geq k_{QT}$  to be **sufficiently 'quasi-solution'**.
- Improvement for  $k_{FR} \geq k_{QT} + 1$ , but **limited interest in over-resolving!**

## Conclusion and perspectives

- Classic numerical schemes are **not well adapted to wide domain simulations**, contrary to the **Trefftz method**.
- The classic choice of **Plane Waves** leads to limitations: we introduce a **Quasi-Trefftz approach**, in which a FR solver computes approximate Maxwell solutions associated to polynomial BCs in each cell.
- Good numerical **independence properties** of the basis functions.
- **Robust approximation** properties of the basis, even for complex local solutions.
- Numerically,  $k_{FR} \geq k_{QT} + 2$  for **quasi-optimality**, but **no need to over-resolve!**

### Perspectives:

- **Theoretical well-posedness conditions and a priori error estimates** in progress.
- Adaptable for (piecewise constant) **heterogeneous** configurations.
- Possible **hybrid approach** by mixing with PW basis.
- Development of **optimised transmission conditions** to reduce the number of iterations for convergence.



# Bibliography



[Sirdey 2022] M. Sirdey. 'Méthode itérative de Trefftz pour la simulation d'ondes électromagnétiques en trois dimensions', PHD, Université de Pau et des Pays de l'Adour, 2022.



[Yee 1966] Kane Yee. Numerical solution of initial boundary value problems involving maxwell's equations in isotropic media. IEEE Transactions on Antennas and Propagation, 14(3):302–307, 1966.



[Nédélec 1980] J. C. Nedelec, 'Mixed finite elements in 3', Numer. Math., vol. 35, no. 3, pp. 315–341, 1980.



[Fezoui et al. 2005] L. Fezoui, S. Lanteri, S. Lohrengel, and S. Piperno, 'Convergence and stability of a discontinuous Galerkin time-domain method for the 3D heterogeneous Maxwell equations on unstructured meshes', ESAIM: Mathematical Modelling and Numerical Analysis - Modélisation Mathématique et Analyse Numérique, vol. 39, no. 6, pp. 1149–1176, 2005.



[Cessenat, Després 1998] O. Cessenat, B. Després. 'Application of an Ultra Weak Variational Formulation of Elliptic PDEs to the Two-Dimensional Helmholtz Problem', SIAM Journal on Numerical Analysis, vol. 35, pp. 255-299, 1998.



[Ihlenburg, Babuška 1995] F. Ihlenburg, I. Babuška. 'Finite element solution of the Helmholtz equation with high wave number Part I : The h-version of the FEM', Computers Mathematics with Applications, vol. 30, pp. 9-37, 1995.



[Congreve et al. 2019] S. Congreve, J. Gedicke, I. Perugia. 'Numerical Investigation of the Conditioning for Plane Wave Discontinuous Galerkin Methods', in Numerical Mathematics and Advanced Applications ENUMATH 2017, pp. 493-500, 2019, Springer, Cham.



[Barucq et al. 2021] H. Barucq, A. Bendali, J. Diaz, and S. Tordeux, 'Local strategies for improving the conditioning of the plane-wave Ultra-Weak Variational Formulation', Journal of Computational Physics, vol. 441, p. 110449, 2021.



[Fure et al. 2020] H. Fure, S. Pernet, M. Sirdey, S. Tordeux, 'A discontinuous Galerkin Trefftz type method for solving the two dimensional Maxwell equations', SN Partial Differential Equations and Applications, vol. 1, pp. 1-25, 2020.



[Imbert-Gérard, Després 2013] L.-M. Imbert-Gérard, B. Després. 'A generalized plane wave numerical method for smooth non constant coefficients'. IMA Journal of Numerical Analysis 34, 2024.



[Imbert-Gérard, Sylvand 2023] L.-M. Imbert-Gérard, G. Sylvand. 'Three types of quasi-Trefftz functions for the 3D convected Helmholtz equation: construction and approximation properties'. arXiv preprint, 2023.



[Lehrenfeld, Stocker 2023] C. Lehrenfeld and P. Stocker, 'Embedded Trefftz discontinuous Galerkin methods', International Journal for Numerical Methods in Engineering, vol. 124, no. 17, pp. 3637-3661, 2023.



[Barucq et al. 2017] H. Barucq, A. Bendali, M. Fares, V. Mattesi and S. Tordeux, 'A symmetric Trefftz-DG formulation based on a local boundary element method for the solution of the Helmholtz equation'. Journal of Computational Physics, Vol. 330, pp. 1069-92, 2017.



[Huynh 2007] H.T. Huynh, 'A Flux Reconstruction Approach to High-Order Schemes Including Discontinuous Galerkin Methods'. AIAA Paper 2007-4079, pp. 1-42, 2007.



[Rivet et al. 2023] M. Rivet, S. Pernet, S. Tordeux, 'Flux reconstruction method for time-harmonic linear propagation problems: 1D a priori error analysis'. HAL preprint, 2023.



[Rivet et al. 2024] M. Rivet, S. Pernet, S. Tordeux, 'Optimised Correction Polynomial Functions for the Flux Reconstruction Method in Time-Harmonic Electromagnetism'. HAL preprint, 2024.