

High order contact detection between fibres

Emile Hohnadel, Octave Crespel, Thibaut Métivet, Florence Bertails-Descoubes

▶ To cite this version:

Emile Hohnadel, Octave Crespel, Thibaut Métivet, Florence Bertails-Descoubes. High order contact detection between fibres. RNL 2024 - 27e Rencontre du Non-Linéaire, Mar 2024, Paris, France. pp.1-1, 2024. hal-04885297

HAL Id: hal-04885297 https://hal.science/hal-04885297v1

Submitted on 14 Jan 2025 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

High order contact detection between fibres

Emile Hohnadel Octave Crespel Thibaut Métivet Florence Bertails-Descoubes

Univ. Grenoble Alpes, Inria, CNRS, Grenoble INP, LJK, Grenoble, France

emile.hohnadel@inria.fr

1. Motivation and challenges

Our objective is to correctly evaluate contact forces in a fibrous assembly by studying the effects of detection methods and curvature at contact. We compare a low order model, Discrete Elastic Rods [3], and a high order one, **Super-Helix** [2], to simulate inextensible Kirchhoff rods. The contact response is computed using the non-regular solver **so-bogus** [4]. In the Computer Graphics community, low order proxy (typically segments for lines), are generally used during the contact detection step.

We show that using a low order proxy is a source of spurious jumps in the force response, with the example of the curved three point test, and propose an alternative algorithm to compute the closest point between a pair of curves, which we apply in the simulation of the combing of hair wisps.



Figure: Geometrically discontinuous contact detection linked to segment proxies

2. Curved three point test



At contact, the curvature of the fibre is **constant** and equals its natural curvature κ_0 .

Figure: Normalised force \overline{F} as a function of normalised indentation $\overline{\delta}$ for the curved three point test. Comparison of the analytic curve (in black) with the simulation results. Only our method (in red) completely removes the jumps.

3. Role of curvature at contact

Jumps appear in the curved three point test with segment proxy as can be seen in the figure on the left. To study the **amplitude of the** jumps, the force is normalised with an analytic solution. The jumps are bigger with **DER** [3] but remain present with **SH** [2] as can be seen in the plots below. The curvier the fibre, the bigger the jumps.





4. Exact contact detection



Figure: Schema of the Branch and Bound approach used in our method [1] to find the **closest points** between two curves in 3D. The upper branch underlines the **early stop** of the method for distant curves. The bounding volumes

Figure: Combing of a wavy 2025 hair wisp with natural curvature $\kappa_0 = 0.6$ cm⁻¹.

5. Hair wisp combing



Figure: Plot of the force of the wavy wisp on the comb during its passage with two contact detection methods. We observe a shift between the forces obtained with the segment proxy (in black) and our exact method (in yellow). Our method integrate less noise, hence increasing the accuracy of force prediction.

are obtained with the **Taylor-Lagrange inequality**. They rely on an **upper bound of the second derivative** of the curve.

Bibliography

- O. Crespel, E. Hohnadel, T. Metivet, F. Bertails-Descoubes. *Contact detection between fibres: high order makes a difference*, submitted.
- F. Bertails, B. Audoly, M.-P. Cani, B. Querleux, F. Leroy, J.-L. Lévêque. Super-Helices for Predicting the Dynamics of Natural *Hair*, ACM Trans. Graph., 25 (2006).
- M. Bergou, M. Wardetzky, S. Robinson, B. Audoly, E. Grinspun. *Discrete Elastic Rods*, ACM Trans. Graph., 27 (2008) 63:1-63:12
- G. Daviet, F. Bertails-Descoubes, L. Boissieux. A hybrid iterative solver for robustly capturing coulomb friction in hair dynamics, ACM Trans. Graph., 139 (2011).

